














BBT - ABySS [5]





FILFmin**@**f HLA predictions from shotgun sequence data

René L Warren, Sarah Yeo, Justin Chu, Robert Holt, İnanç Birol



The Human Leukocyte Antigen (HLA) is a gene locus that encodes cell-surface receptors that present epitopes to T cells, and is the foundation of immune system regulation in humans

Due to the necessity of recognizing diverse molecular signatures, there is extreme diversity in the genes that encode HLA proteins, and determining the specific gene variants of an individual is of considerable importance in medicine and research. HLAminer [1, 2] is the first reported and highly cited HLA prediction software using next-generation shotgun (NGS) genome and transcriptome sequence data. The flexible pipeline enables predictions from direct read alignments to a set of known references or, for best results, uses targeted de novo assembly [3] of sequence reads. We present improvements since publication, including the utilization of BioBloom Tools [4] for efficient read partitioning Since January 2016, HLAminer has had over 5000 world-wide downloads

100

50


100

HLA Groups (%)

Knowing HLA: key to successful graft ★ Standard typing methods: \$, laborious, time ★ Potent vaccines ought to consider HLA

Strategy Human NGS datasets: HLA reference sequences genomic or coding sequences Targets





Computational predictions of HLA from shotgun data by targeted assembly (left) or read alignment (right). For targeted assembly with TASR [3], NGS reads having their first fifteen (optional) 5' bases matching one of HLA CDS (RNA-Seq) or genomic (WGS/exon capture) sequences are recruited and assembled de novo. Resulting sequence contigs are aligned against a database sequence of all predicted HLA CDS (RNA-Seq) or genomic sequences (WGS/exon capture), tracking best HLA hits

Allele assignments from shotgun datasets (HLAminer) are informed by contig length, depth of coverage and similarity to reference sequences, when applicable. The probability of each prediction being correct is estimated by determining the probability of that prediction being observed by chance

Updates

- o Concise HLA allele summary
- Reports top 2 predictions [highest-scoring by HLA group/gene]
- o 'P' designated allele when HLA has same antigen binding
- o Predictions from Pacific Biosciences (PacBio) reads
- o Predictions from direct alignment of single-end reads

HLA-typed CRC patients RNA-Seq data (~5M read pairs) HLA Alleles (%) 75 50 25

Targeted Assembly Appraisal

100

75

50

25

100

48 56 64 72 80 88 96 **TASR** 30 30i 40 40i 50 50i TASR k-mer length Ambiguity Sensitivity Specificity

Benchmarks	BBT-ABySS*	BBT-SSAKE	TASR
time (mm:ss)	1:36 +/- 19s	6:32 +/- 34s	10:56 +/- 67s
memory (MB)	32.3 +/- 4.0	41.2 +/- 1.5	58.2 +/- 4.8
Skine	* 3 samples yielded no contigs/failed (k=30, 56, 64)		

Acknowledgements

- 1. Warren RL, et al. 2012. Genome Med 4:95
- http://www.bcgsc.ca/platform/bioinfo/software/hlaminer
- Warren and Holt. 2011. PLoS ONE 6:e19816
- Chu J. et al. 2014. Bioinformatics 30:3402
- Simpson JT, et al. 2009. Genome Res 19:1117
- Warren RL, et al. 2007. Bioinformatics 23:500
- 7. Brown SD, et al. 2014. Genome Res 24:743

8. Hundal J, et al. 2016. Genome Med 8:11



René is a scientist with extensive experience in computational biology In his career, he has been at the forefront of innovation, pioneering a numbe bioinformatics "firsts". Among those, **SSAKE**, the first algorithm for short r bloinformatics litsis. Afficing urber, 53AACE, the litsis algorithm for short reacting genome assembly. Applications of the software extend beyond genome assembly. The innovative technology was applied to profiling T-cell metagenomes, targeted de novo genome sequence assembly (TASR), HLA typing (HLAminer and NMDP Be The Match), genome scaffolding with long reads (LIMKS), proteome assembly (PASS) and was key to the discovery of Fusobacterium in colon cancer, a finding designated as one of the top 10 medical breakthroughs of 2011 by Time magazine

rwarren@bcgsc.ca



Applications

Neo-antigens predicted by tumor genome meta-analysis correlate with patient survival [7]: Candidates epitopes identified based on HLAminer derived HLA types of patients from The Cancer Genome Atlas

pVAC-Seq: A genome-guided in silico approach to identifying tumor neoantigens [8]: Pipeline with HLAminer used in melanoma patients trials, to identify neo-epitopes for use in personalized vaccines

