

Rufus Unattend Feature Options

Inventory of every `UNATTEND_*` flag Rufus can set (`reference/rufus/src/rufus.h` , generated in `reference/rufus/src/wue.c:CreateUnattendXml`), what this repo already does that overlaps, and which of the rest are worth adding later. Written up after implementing `-LocalAccountName` (which ports Rufus's `UNATTEND_SET_USER` , see below) so the rest of the comparison doesn't get lost.

Already covered by this repo

Rufus flag	What it does	This repo's equivalent
<code>UNATTEND_SECUREBOOT_TPM_MINRAM</code>	<code>reg add</code> bypass for Secure Boot/TPM/RAM checks during Setup	<code>-BypassMode Unattend</code> (<code>Add-AnswerFileBypassCommands</code>) — also offers <code>Hive</code> and <code>Both</code> , which Rufus doesn't
<code>UNATTEND_NO_ONLINE_ACCOUNT</code>	Skip MSA/online-account requirement (<code>BypassNRO</code>)	<code>Enable-LocalAccountOOBE</code>
<code>UNATTEND_SET_USER</code>	Create a local account so OOBE doesn't require an MSA	<code>-LocalAccountName</code> (<code>Add-AnswerFileLocalAccount</code>) — see "Different from Rufus" below
<code>UNATTEND_DISABLE_BITLOCKER</code> (partial)	<code>PreventDeviceEncryption</code>	<code>Disable-BitLockerAutoEncryption</code> — Rufus also sets <code>TCGSecurityActivationDisabled</code> , which we don't yet (see below)
<code>UNATTEND_QOL_ENHANCEMENTS</code> (partial)	Remove OneDrive/Outlook/Teams, disable Copilot	<code>Remove-OneDriveSetup</code> , <code>Disable-OneDriveSync</code> , <code>Disable-TeamsInstall</code> , <code>Disable-DevHomeOutlookInstall</code> , <code>Disable-Copilot</code> — Rufus bundles a few more QoL tweaks we don't have (see below)

Different from Rufus: `-LocalAccountName` password handling

Rufus's `UNATTEND_SET_USER` sets a blank password (via the magic Base64-encoded UTF-16 string `"Password"` , which Windows interprets as "no password"), then runs `net user "<name>" /logonpasswordchg:yes` as a first-logon command to force a password change, plus `net accounts /maxpwage:unlimited` to stop the forced change from also resetting the expiry policy.

`-LocalAccountName` instead sets the account's password to the same value as its name, in plain text (`<PlainText>true</PlainText>`), by explicit choice — no password generation, storage, or first-logon command handling needed. Trade-off: the password is exactly the (public) account name, which is fine for a disposable/dev/VM image but should never be used for anything reachable by an untrusted network or user.

Not implemented — candidates for later

Ranked roughly by effort-to-value.

1. `UNATTEND_DUPLICATE_LOCALE` — match the build PC's regional settings

Copies the *building* machine's timezone, keyboard layout (`InputLocale`), system locale, user locale, and UI-language-fallback into the target image's `oobeSystem` pass, instead of shipping generic `en-US` defaults. Straightforward: same namespace-aware-XML pattern as `Add-AnswerFileLocalAccount` , values read from `Get-TimeZoneInformation / Get-Culture / registry ( reference/rufus/src/wue.c:335-343,462-478 )` . Low effort, likely useful if you build images for yourself rather than for redistribution.

2. More `UNATTEND_QOL_ENHANCEMENTS` first-logon tweaks

Rufus's QoL bundle does a few things we don't have equivalents for yet (`reference/rufus/src/wue.c:398-446`):

- Disable Fast Startup (`HiberbootEnabled=0`)
- Disable News and Interests widgets (`AllowNewsAndInterests=0` , `EnableFeeds=0`)
- Hide Edge's first-run dialog (`HideFirstRunExperience=1`)
- A few more Start-menu pins by default

Each is a one-line `Set-RegistryValue` call in the existing `Disable-*` style; could fold into existing functions (e.g. `Disable-Copilot` already touches similar taskbar/search keys) or a new `Enable-QualityOfLifeTweaks` grouping function. Low effort per item.

3. `UNATTEND_NO_DATA_COLLECTION` — skip OOB privacy/EULA screens

`HideEULAPage` , `ProtectYourPC=3` (declines diagnostic data during OOB), and (for fully silent/offline installs) `HideWirelessSetupInOOBE` (`reference/rufus/src/wue.c:319-334`). Also namespace-aware-XML, same shape as the local-account block. Medium value — mostly matters if you want OOB to require zero clicks.

4. `TCGSecurityActivationDisabled` for `Disable-BitLockerAutoEncryption`

Rufus's BitLocker-disable also sets `Microsoft-Windows-EnhancedStorage-Adm's` `TCGSecurityActivationDisabled=1` (`reference/rufus/src/wue.c:487-491`) in addition to `PreventDeviceEncryption` , which is all `Disable-BitLockerAutoEncryption` currently sets. Trivial one-line registry addition (or a matching `oobeSystem` component if we want it via answer file instead of hive edit).

5. `UNATTEND_APPLY_SKUSIPOLICY` — reapply `SkuSiPolicy.p7b` post-install

Narrow fix for a specific Secure Boot certificate-revocation edge case (`reference/rufus/src/wue.c:392-397` , see <https://support.microsoft.com/kb/5042562>). Low priority unless you hit the specific `0xc0000428` boot signature error this addresses.

Not applicable to this project

These are about Rufus's own USB-installer mechanics — partitioning a *target* disk during Setup, offlining other drives, or building Windows-To-Go media — none of which apply here, since this project bakes changes into `install.wim` / `boot.wim` for an ISO rather than driving Setup's disk-partitioning behavior:

- `UNATTEND_OFFLINE_INTERNAL_DRIVES` (`SanPolicy=4`)
- `UNATTEND_FORCE_S_MODE`
- `UNATTEND_SILENT_INSTALL` (disk creation/partitioning steps)
- `UNATTEND_USE_MS2023_BOOTLOADERS` / `UNATTEND_WINDOWS_TO_GO`