

Object Explorer | Dashboard | Properties | SQL | Statistics | Dependents | Processes | airport_DB/emilakshabayev@s*

Foreign Tables | Functions | Materialized Views | Operators | Procedures | Sequences | Tables (10) | Columns (14)

- airline
- airport
- baggage
- baggage_check
- boarding_pass
- booking
- booking_flight
- flights
- Columns (14)
 - flight_id
 - flight_no
 - scheduled_departure
 - scheduled_arrival
 - departure_airport_id
 - arrival_airport_id
 - departing_gate
 - arriving_gate
 - airline_id
 - status
 - actual_departure
 - actual_arrival
 - created_at
 - update_at
- Constraints
- Indexes
- RLS Policies
- Rules
- Triggers
- passengers

Query | Query History

```
--1
1 create or replace procedure add_flight(
2   p_airline_id int,
3   p_departure_airport_id int,
4   p_arrival_airport_id int,
5   p_scheduled_departure timestamp,
6   p_scheduled_arrival timestamp,
7   p_status text
8 )
9
10 language plpgsql
11 as $$
12 begin
13   insert into flights (
14     airline_id,
15     departure_airport_id,
16     arrival_airport_id,
17     scheduled_departure,
18     scheduled_arrival,
19     status
20   )
21   values (
22     p_airline_id,
23     p_departure_airport_id,
24     p_arrival_airport_id,
```

Execute script

Data Output | Messages | Notifications

CREATE PROCEDURE

Query returned successfully in 238 msec.

Total rows: Query complete 00:00:00.238 LF Ln 30, Col 4

Object Explorer | Dashboard | Properties | SQL | Statistics | Dependents | Processes | airport_DB/emilakshabayev@s*

Foreign Tables | Functions | Materialized Views | Operators | Procedures | Sequences | Tables (10) | Columns (14)

- airline
- airport
- baggage
- baggage_check
- boarding_pass
- booking
- booking_flight
- flights
- Columns (14)
 - flight_id
 - flight_no
 - scheduled_departure
 - scheduled_arrival
 - departure_airport_id
 - arrival_airport_id
 - departing_gate
 - arriving_gate
 - airline_id
 - status
 - actual_departure
 - actual_arrival
 - created_at
 - update_at
- Constraints
- Indexes
- RLS Policies
- Rules
- Triggers
- passengers

Query | Query History

```
--2
32
33 create or replace procedure update_flight_status(
34   p_flight_id int,
35   p_status text
36 )
37 language plpgsql
38 as $$
39 begin
40   update flights
41   set status = p_status
42   where flight_id = p_flight_id;
43 end;
44 $$;
```

Data Output | Messages | Notifications

CREATE PROCEDURE

Query returned successfully in 34 msec.

Total rows: Query complete 00:00:00.034

✓ Query returned successfully in 34 msec. ✕ LF Ln 44, Col 4

Object Explorer

- Foreign Tables
- Functions
- Materialized Views
- Operators
- Procedures
- Sequences
- Tables (10)
 - airline
 - airport
 - baggage
 - baggage_check
 - boarding_pass
 - booking
 - booking_flight
 - flights
- Columns (14)
 - flight_id
 - flight_no
 - scheduled_departure
 - scheduled_arrival
 - departure_airport_id
 - arrival_airport_id
 - departing_gate
 - arriving_gate
 - airline_id
 - status
 - actual_departure
 - actual_arrival
 - created_at
 - update_at
- Constraints
- Indexes
- RLS Policies
- Rules
- Triggers
- passengers

airport_DB/emilakshabayev@s

Query

```
48 create or replace procedure list_flights_fromairport(  
49     p_airport_id int  
50 )  
51 language plpgsql  
52 as $$  
53 begin  
54     select  
55         flight_id,  
56         departure_airport_id,  
57         arrival_airport_id,  
58         scheduled_departure,  
59         status  
60     from flights  
61     where departure_airport_id = p_airport_id  
62     order by scheduled_departure;  
63 end;  
64 $$;
```

Data Output Messages Notifications

CREATE PROCEDURE

Query returned successfully in 38 msec.

Total rows: Query complete 00:00:00.038

Query returned successfully in 38 msec. X

LF Ln 65, Col 1

Object Explorer

- Foreign Tables
- Functions
- Materialized Views
- Operators
- Procedures
- Sequences
- Tables (10)
 - airline
 - airport
 - baggage
 - baggage_check
 - boarding_pass
 - booking
 - booking_flight
 - flights
- Columns (14)
 - flight_id
 - flight_no
 - scheduled_departure
 - scheduled_arrival
 - departure_airport_id
 - arrival_airport_id
 - departing_gate
 - arriving_gate
 - airline_id
 - status
 - actual_departure
 - actual_arrival
 - created_at
 - update_at
- Constraints
- Indexes
- RLS Policies
- Rules
- Triggers
- passengers

airport_DB/emilakshabayev@s

Query

```
67  
68 create or replace function avg_delay_forairport(  
69     p_airport_id int  
70 )  
71 returns interval  
72 language plpgsql  
73 as $$  
74 declare  
75     v_avg_delay interval;  
76 begin  
77     select avg(actual_arrival - scheduled_arrival)  
78     into v_avg_delay  
79     from flights  
80     where arrival_airport_id = p_airport_id  
81     and actual_arrival is not null  
82     and scheduled_arrival is not null;  
83  
84     return v_avg_delay;  
85 end;  
86 $$;
```

Data Output Messages Notifications

CREATE FUNCTION

Query returned successfully in 31 msec.

Total rows: Query complete 00:00:00.031

Query returned successfully in 31 msec. X

LF Ln 86, Col 4

Object Explorer | Dashboard | Properties | SQL | Statistics | Dependents | Processes | airport_DB/emilakshabayev@s*

airport_DB/emilakshabayev@s

Query | Query History

```
--5
create or replace procedure list_passengers_for_flight(
  p_flight_id int
)
language plpgsql
as $$
begin
  select
    p.passenger_id,
    p.first_name,
    p.last_name,
    b.booking_id,
    b.price
  from passengers p
  join booking b
    on p.passenger_id = b.passenger_id
  where b.flight_id = p_flight_id
  order by p.last_name;
end;
$$;
```

Data Output | Messages | Notifications

CREATE PROCEDURE

Query returned successfully in 73 msec.

Total rows: Query complete 00:00:00.073

LF Ln 100, Col 16

Columns (14): flight_id, flight_no, scheduled_departure, scheduled_arrival, departure_airport_id, arrival_airport_id, departing_gate, arriving_gate, airline_id, status, actual_departure, actual_arrival, created_at, update_at

Object Explorer | Dashboard | Properties | SQL | Statistics | Dependents | Processes | airport_DB/emilakshabayev@s*

airport_DB/emilakshabayev@s

Query | Query History

```
--6
create or replace procedure most_frequent_passenger()
language plpgsql
as $$
begin
  select
    p.passenger_id,
    p.first_name,
    p.last_name,
    count(*) as flights_count
  from passengers p
  join booking b
    on p.passenger_id = b.passenger_id
  group by p.passenger_id, p.first_name, last_name
  order by flights_count desc
  limit 1;
end;
$$;
```

Data Output | Messages | Notifications

CREATE PROCEDURE

Query returned successfully in 41 msec.

Total rows: Query complete 00:00:00.041

LF Ln 127, Col 14

Columns (14): flight_id, flight_no, scheduled_departure, scheduled_arrival, departure_airport_id, arrival_airport_id, departing_gate, arriving_gate, airline_id, status, actual_departure, actual_arrival, created_at, update_at

Object Explorer | Dashboard | Properties | SQL | Statistics | Dependents | Processes | airport_DB/emilakshabayev@s*

airpot_DB/emilakshabayev@s

Query | Query History

```
130 --7
131 create or replace procedure list_long_delays()
132 language plpgsql
133 as $$
134 begin
135     select
136         flight_id,
137         departure_airport_id,
138         arrival_airport_id,
139         scheduled_departure,
140         scheduled_arrival,
141         actual_departure,
142         actual_arrival,
143         actual_arrival - scheduled_arrival as delay
144     from flights
145     where actual_arrival is not null
146           and scheduled_arrival is not null
147           and actual_arrival - scheduled_arrival > interval '24 hours'
148     order by delay desc;
149 end;
150 $$;
```

Data Output | Messages | Notifications

CREATE PROCEDURE

Query returned successfully in 39 msec.

Total rows: Query complete 00:00:00.039

LF Ln 150, Col 4

Columns (14): flight_id, flight_no, scheduled_departure, scheduled_arrival, departure_airport_id, arrival_airport_id, departing_gate, arriving_gate, airline_id, status, actual_departure, actual_arrival, created_at, update_at

Object Explorer | Dashboard | Properties | SQL | Statistics | Dependents | Processes | airport_DB/emilakshabayev@s*

airpot_DB/emilakshabayev@s

Query | Query History

```
153 --8
154 create or replace function flights_count_by_airline()
155 returns table (
156     airline_id int,
157     flights_count bigint
158 )
159 language plpgsql
160 as $$
161 begin
162     return query
163     select
164         f.airline_id,
165         count(*) as flights_count
166     from flights f
167     group by f.airline_id
168     order by flights_count desc;
169 end;
170 $$;
```

Data Output | Messages | Notifications

CREATE FUNCTION

Query returned successfully in 29 msec.

Total rows: Query complete 00:00:00.029

LF Ln 171, Col 1

Columns (14): flight_id, flight_no, scheduled_departure, scheduled_arrival, departure_airport_id, arrival_airport_id, departing_gate, arriving_gate, airline_id, status, actual_departure, actual_arrival, created_at, update_at

Object Explorer

- baggage
- baggage_check
- boarding_pass
- booking
 - Columns (8)
 - booking_id
 - passenger_id
 - booking_platform
 - created_at
 - update_at
 - status
 - price
 - ticket_discount
 - Constraints
 - Indexes
 - RLS Policies
 - Rules
 - Triggers
 - booking_flight
 - Columns (5)
 - booking_flight_id
 - booking_id
 - flight_id
 - created_at
 - update_at
 - Constraints
 - Indexes
 - RLS Policies
 - Rules
 - Triggers
 - flights
 - Columns (14)
 - flight_id
 - flight_no
 - scheduled_departure
 - scheduled_arrival
 - departure_airport_id
 - Constraints
 - Indexes
 - RLS Policies
 - Rules
 - Triggers

airport_DB/emilakshabayev@s

Query

```
--9
create or replace procedure avg_ticket_price_flights(
  p_flight_id int
)
language plpgsql
as $$
begin
  select
    bf.flight_id,
    avg(b.price) as avg_price
  from booking b
  join booking_flight bf
  on b.booking_id = bf.booking_id
  where bf.flight_id = p_flight_id
  group by bf.flight_id;
end;
$$;
```

Data Output Messages Notifications

CREATE PROCEDURE

Query returned successfully in 41 msec.

Total rows: Query complete 00:00:00.041

Query returned successfully in 41 msec. X

LF Ln 189, Col 4

Object Explorer

- baggage
- baggage_check
- boarding_pass
- booking
 - Columns (8)
 - booking_id
 - passenger_id
 - booking_platform
 - created_at
 - update_at
 - status
 - price
 - ticket_discount
 - Constraints
 - Indexes
 - RLS Policies
 - Rules
 - Triggers
 - booking_flight
 - Columns (5)
 - booking_flight_id
 - booking_id
 - flight_id
 - created_at
 - update_at
 - Constraints
 - Indexes
 - RLS Policies
 - Rules
 - Triggers
 - flights
 - Columns (14)
 - flight_id
 - flight_no
 - scheduled_departure
 - scheduled_arrival
 - departure_airport_id
 - Constraints
 - Indexes
 - RLS Policies
 - Rules
 - Triggers

airport_DB/emilakshabayev@s

Query

```
--10
create or replace procedure most_expensive_flight()
language plpgsql
as $$
begin
  select
    f.flight_id,
    f.departure_airport_id,
    f.arrival_airport_id,
    b.price
  from booking b
  join booking_flight bf
  on b.booking_id = bf.booking_id
  where bf.flight_id = p_flight_id
  order by b.price desc
  limit 1;
end;
$$;
```

Data Output Messages Notifications

CREATE PROCEDURE

Query returned successfully in 37 msec.

Total rows: Query complete 00:00:00.037

Query returned successfully in 37 msec. X

LF Ln 208, Col 4