

Head for joystick controller, Harmony XB4, Ø22 mm 2 direction stay put

ZD4PA127

Main

Range of Product	Harmony XB4	
Product or Component Type	Head for joystick controller	
Device short name	ZB4	
Bezel material	Black metal	
Mounting diameter	0.9 in (22 mm)	
Sale per indivisible quantity	1	
Shape of signaling unit head	Round	
Type of operator	stay put	
Operator profile	54 mm long operating shaft	
Operator direction information	2 directions	

Complementary

Net Weight	0.049 lb(US) (0.022 kg)	
Resistance to high pressure washer	1015.3 psi (7000000 Pa) 131 °F (55 °C) 0.1 m	
Operator position information	3 positions	
Mechanical durability	1000000 cycles	
Device presentation	Basic element	

Environment

Protective treatment	тн	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
Electrical shock protection class	Class I IEC 60536	
IP degree of protection	IP66 IEC 60529	
NEMA degree of protection	NEMA 13 NEMA 4X	
IK degree of protection	IK03 conforming to IEC 50102	
Standards	UL 508 IEC 60947-5-5 IEC 60947-5-4 IEC 60947-1 JIS C8201-5-1 IEC 60947-5-1 CSA C22.2 No 14 JIS C8201-1	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Product Certifications	CSA LROS (Lloyds register of shipping) BV UL Listed DNV		
Vibration resistance	resistance 5 gn (f= 2500 Hz) conforming to IEC 60068-2-6		
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27		

Ordering and shipping details

GTIN 3389110823516

Packing Units

_		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.34 in (3.400 cm)	
Package 1 Width	2.13 in (5.400 cm)	
Package 1 Length	3.66 in (9.300 cm)	
Package 1 Weight	2.081 oz (59.000 g)	
Unit Type of Package 2	S02	
Number of Units in Package 2	40	
Package 2 Height	5.91 in (15 cm)	
Package 2 Width	11.81 in (30 cm)	
Package 2 Length	15.75 in (40 cm)	
Package 2 Weight	5.776 lb(US) (2.620 kg)	
Unit Type of Package 3	P06	
Number of Units in Package 3	640	
Package 3 Height	29.53 in (75.000 cm)	
Package 3 Width	31.50 in (80.000 cm)	
Package 3 Length	23.62 in (60.000 cm)	
Package 3 Weight	110.055 lb(US) (49.920 kg)	

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	3f5be3ea-91d8-44be-909b-d6ac0a6fe845
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.