# 2023-11-14

```
* {
font-family: 'Single Day', cursive;
}
```

```
<button type="button" class="btn btn-outline-danger mt-3" onclick="js:begin">
```

부트스트랩에서 버튼을 가져올수있고 margin-top을 넣을수있다.

```
@keyframes fadeIn {
    from {opacity: 0;}
    to {opacity: 1;}
}
@keyframes fadeOut {
    from {opacity: 1;}
    to {opacity: 0;}
}
@-webkit-keyframes fadeIn {
    from {opacity: 0;}
    to {opacity: 1;}
 }
 @-webkit-keyframes fadeOut {
     from {opacity: 1;}
     to {opacity: 0;}
 }
```

```
function begin(){
    main.style.webkitAnimation = "fadeOut 1s";
    main.style.animation = "fadeOut 1s";
    setTimeout(() => {
        qna.style.webkitAnimation = "fadeOut 1s";
        qna.style.animation = "fadeOut 1s";
        //qna.style.webkitAnimation = "fadeIn 1s";
        //qna.style.animation = "fadeIn 1s";
        setTimeout(() => {
            main.style.display="none";
            qna.style.display="block";
        }, 400); //0.4초 시간 정함
```

```
        }, 400);
    }
```

페이지에 애니메이션을 넣을수있다.

animation.css에 대소문자 구별을 잘 해야한다.