

ACME COMPONENTS (FICTIONAL SAMPLE)

Tantalum Chip Capacitor - Case A (EIA 3216)

Part Number: ACM-T10UF16V-A 10 uF, 16V

NOTE: Synthetic sample for tool testing only - not a real product.

This datasheet is intentionally ambiguous (see below) to demonstrate the review queue - it is not a documentation defect.

Dimensions (millimeters)

Symbol	Description	Min	Nom	Max
L (D)	Body length	3.05	3.20	3.35
W (E)	Body width	1.45	1.60	1.80
H (A)	Body height (seated)	1.40	1.50	1.60

Construction & Handling

- Termination: two metallized end electrodes (chip, no formed leads).
- Polarity: YES - this is a polarity-sensitive device. Reverse voltage may damage the part. Orientation marking varies by date code; see manufacturer date-code orientation guide (not included in this excerpt).
- Top surface: flat (suitable for vacuum nozzle pickup).
- Weight: approx. 0.09 g per piece.
- Packaging: 8 mm carrier tape, 4 mm pocket pitch, 7-inch reel.

Mechanical Drawing (side view)



A (height) = 1.80 mm max per Rev.A drawing

D = 3.20 mm (length)

Drawing note: Rev.A mechanical drawing lists H max = 1.80 mm; the Rev.B table above lists H max = 1.60 mm. Discrepancy unresolved - confirm before tooling.