

SAFETY DATA SHEET

(GHS, Appendix 4)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : DADDY

Product code : ITM0487706

1.2. Relevant identified uses of the substance or mixture and uses advised against

Industrial-grade fragrance compound

1.3. Details of the supplier of the safety data sheet

Registered company name : Argeville (Thailand)

Address : 333/11 UNIT TIP 8-11 MOO 9, SOI PROJECT TIP 8, BANGPLA SUB-DISTRICT, BANGPLEE DISTRICT 10540
SAMUTPRAKARN PROVINCE Thailand

Telephone : (+66)226338456 Fax : (+66)22633847

Mail legislation@argeville.com

1.4. Emergency telephone number : .

(+33)4.93.65.38.38

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS compliant.

Skin irritation, Category 3 (Skin Irrit. 3, H316).

Eye irritation, Category 2A (Eye Irrit. 2A, H319).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Acute hazard, Category 2 (Aquatic Acute 2, H401).

Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

GHS compliant.

Hazard pictograms :



GHS09



GHS07

Signal Word :

WARNING

Product identifiers (list of classified components) :

CAS 122-40-7 ALPHA-AMYL CINNAMALDEHYDE

CAS 127-51-5 ALPHA-ISO-METHYL IONONE

CAS 91-64-5 COUMARIN

Hazard statements :

H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

DADDY - ITM0487706

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements - Prevention :

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/ ...

Precautionary statements - Response :

P302 + P352 IF ON SKIN: Wash with plenty of water/...

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P391 Collect spillage.

Precautionary statements - Disposal :

P501 Dispose of contents/container in accordance with local regulation.

2.3. Other hazards

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	Classification GHS	Note	%
CAS: 140-11-4 EC: 205-399-7 BENZYL ACETATE	Wng Acute Tox. 5, H303 Aquatic Acute 2, H401 Aquatic Chronic 3, H412	[1]	2.5 <= x % < 10
CAS: 98-55-5 EC: 202-680-6 REACH: 01-2119553062-49-0000 ALPHA-TERPINEOL	GHS07 Wng Flam. Liq. 4, H227 Acute Tox. 5, H303 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 2, H401		2.5 <= x % < 10
CAS: 101-84-8 EC: 202-981-2 DIPHENYL ETHER	GHS07, GHS09 Wng Acute Tox. 5, H303 Skin Irrit. 3, H316 Eye Irrit. 2, H319 Aquatic Chronic 3, H412 Aquatic Acute 1, H400 M Acute = 1	[1]	2.5 <= x % < 10
CAS: 122-40-7 EC: 204-541-5 ALPHA-AMYL CINNAMALDEHYDE	GHS07, GHS09 Wng Acute Tox. 5, H303 Skin Irrit. 3, H316 Skin Sens. 1B, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411		2.5 <= x % < 10
CAS: 60-12-8 EC: 200-456-2 REACH: 01-2119963921-31-0000 PHENETHYL ALCOHOL	GHS07 Wng Acute Tox. 4, H302 Acute Tox. 5, H313 Skin Irrit. 3, H316 Eye Irrit. 2, H319		2.5 <= x % < 10

DADDY - ITM0487706

CAS: 121-33-5 EC: 204-465-2 REACH: 01-2119516040-60-0000 VANILLIN	GHS07 Wng Acute Tox. 5, H303 Acute Tox. 5, H313 Eye Irrit. 2, H319 Aquatic Acute 3, H402	[1]	1 ≤ x % < 2.5
CAS: 127-51-5 EC: 204-846-3 ALPHA-ISO-METHYLIONONE	GHS07, GHS09 Wng Skin Irrit. 3, H316 Skin Sens. 1B, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411		1 ≤ x % < 2.5
CAS: 586-81-2 EC: 209-584-3 GAMMA-TERPINEOL	GHS07 Wng Acute Tox. 5, H303 Eye Irrit. 2, H319 Aquatic Acute 3, H402 Skin Irrit. 2, H315		1 ≤ x % < 2.5
CAS: 91-64-5 EC: 202-086-7 REACH: 01-2119943756-26-0000 COUMARIN	GHS07, GHS06 Dgr Acute Tox. 3, H301 Skin Sens. 1B, H317 Aquatic Acute 3, H402		1 ≤ x % < 2.5
CAS: 25265-71-8 EC: 246-770-3 REACH: 01-2119456811-38-0000 DIPROPYLENE GLYCOL (ISOMER UNSPECIFIED)		[1]	1 ≤ x % < 2.5
CAS: 5413-60-5 EC: 226-501-6 TRICYCLODECENYL ACETATE	Wng Acute Tox. 5, H303 Skin Irrit. 3, H316 Aquatic Acute 3, H402		1 ≤ x % < 2.5
CAS: 87-20-7 EC: 201-730-4 ISOAMYL SALICYLATE	GHS07, GHS09 Wng Acute Tox. 4, H302 Aquatic Acute 2, H401 Aquatic Chronic 2, H411		1 ≤ x % < 2.5
CAS: 2437-25-4 EC: 219-440-1 DODECANENITRILE	GHS07, GHS09 Wng Acute Tox. 5, H303 Skin Irrit. 2, H315 Aquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 10		1 ≤ x % < 2.5
CAS: 63500-71-0 EC: 405-040-6 REACH: 01-0000015458-64-0000 TETRAHYDRO-2-ISOBUTYL-4-METHYLPYRAN-4-OL, MIXED ISOMERS (CIS AND TRANS)	GHS07 Wng Eye Irrit. 2, H319		1 ≤ x % < 2.5
CAS: 5989-27-5	GHS02, GHS07, GHS08, GHS09	[1]	0 ≤ x % < 1

DADDY - ITM0487706

EC: 227-813-5 D-LIMONENE	Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 3, H412 Aquatic Acute 1, H400 M Acute = 1		
CAS: 112-44-7 EC: 203-972-6 REACH: 01-2119529242-47-0000 UNDECANAL	GHS07, GHS09 Wng Skin Irrit. 2, H315 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1		0 <= x % < 1
CAS: 99-85-4 EC: 202-794-6 P-MENTHA-1,4-DIENE	GHS02, GHS08, GHS09 Dgr Flam. Liq. 3, H226 Acute Tox. 5, H303 Asp. Tox. 1, H304 Repr. 2, H361 Aquatic Acute 2, H401 Aquatic Chronic 2, H411	[2]	0 <= x % < 1

Information on ingredients :

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

DADDY - ITM0487706

Recommended equipment and procedures :

- For personal protection, see section 8.
- Observe precautions stated on label and also industrial safety regulations.
- Avoid skin and eye contact with this mixture.
- Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

- No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

- No data available.

Storage

- Keep the container tightly closed in a dry, well-ventilated place.
- The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

- Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

- No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
101-84-8	7	1	14	2	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
140-11-4	10 ppm			A4	
101-84-8	1 ppm	2 ppm			

- South Africa / DME (Department of Minerals and Energy, 2006) :

- South Africa / DOL RL (Department of Labour, Recommended limits, 1995) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
101-84-8	1 ppm 7 mg/m3				

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

CAS	VME :	VME :	Excess	Notes
101-84-8		1 ppm 7.1 mg/m3		1(I)
25265-71-8		100 E mg/m3		2(II)
5989-27-5		5 ppm 28 mg/m3		4(II)

- Australia (NOHSC: 3008, 1995) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
101-84-8	1 ppm 7 mg/m3	2 ppm 14 mg/m3		H	

- Belgium (Royal decree of 11/05/2021) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
-----	-------	--------	-----------	--------------	------------

DADDY - ITM0487706

140-11-4	10 ppm 62 mg/ m3					
101-84-8	1 ppm 7 mg/ m3	2 ppm 14 mg/ m3				
- Canada / Alberta (Occupational health and safety code, 2009) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
140-11-4	10 ppm 61 mg/ m3					
101-84-8	1 ppm 7 mg/ m3	2 ppm 14 mg/ m3				
- Canada / British Colombia (2009) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
140-11-4	10 ppm					
101-84-8	1 ppm	2 ppm				
- Canada / Ontario (Control of exposure to biological or chemical agents, regulation 491/2009) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
140-11-4	10 ppm	-	-	-	-	
- Canada / Quebec (Regulations on occupational health and safety) :						
- China (GBZ 2.1, 2007) :						
CAS	TWA :	STEL :	Anm :	TWA :	STEL :	
101-84-8	7 mg/m3	14 mg/m3				
- Denmark (2020) :						
Stof	TWA	VSTEL	Loftvaerdi	Anm		
140-11-4	10 ppm 61 mg/ m3					
101-84-8	1 ppm 7 mg/ m3			E		
- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :						
CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
101-84-8	1	7	2	14	-	-
- Finland (HTP-värden 2018) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
101-84-8	1 ppm 7 mg/ m3	2 ppm 14 mg/ m3				
5989-27-5	25 ppm 140 mg/m3	50 ppm 280 mg/m3				
- Spain (Instituto Nacional de Seguridad e Higiene en el Trabajo (INSHT), 2019) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
140-11-4	10 ppm 62 mg/ m3					
101-84-8	1 ppm 7.1 mg/ m3	2 ppm 14.2 mg/m3		VLI		
5989-27-5	30 ppm 168 mg/m3			Sen. via dermica		
- Greece (90/1999) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	

DADDY - ITM0487706

101-84-8		1 ppm 7 mg/ m3			
- Ireland (Code of practice for the Chemical Agents Regulations, 2021) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
140-11-4	10 ppm				
101-84-8	1 ppm 7 mg/ m3				
- Latvia (Regulation No. 325/2007) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
140-11-4	5 mg/m3				
- Lithuania (HN 23 :2001) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
140-11-4	5 mg/m3				
- Malaysia :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
140-11-4	10 ppm	-	-	-	-
101-84-8	1 ppm	-	-	-	-
- Mexico :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
101-84-8	1 ppm	2 ppm	-	-	-
- Norway (Veiledning om administrative normer for forurensning i arbeidsatmosfære, 2019) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
101-84-8	1 ppm 7 mg/ m3	2 ppm 14 mg/ m3		E	
5989-27-5	25 ppm 140 mg/m3			A	
- New Zealand (Workplace Exposure standards, 11/2020, edition 12-1) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
101-84-8	1 ppm 7 mg/ m3	2 ppm 14 mg/ m3			
- Poland (Dz. U. z 2018 r. poz. 917, 1000 i 1076) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
101-84-8	7 mg/m3	14 mg/m3			
- Czech Republic (Regulation No. 361/2007) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
101-84-8	5 mg/m3	10 mg/m3			
- Slovakia (Regulation 300/2007, 471/2011 23/11/2011) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
101-84-8	1 ppm 7.1 mg/ m3				
- Slovenia (Uradni List, 04/06/2015) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
101-84-8		1 ppm 7.1 mg/ m3			
- Switzerland (Suva 2021) :					

DADDY - ITM0487706

CAS	VME	VLE	Valeur plafond	Notations	
101-84-8	1 ppm 7 mg/ m3	2 ppm 14 mg/ m3			
25265-71-8	140 ppm	280 ppm			
5989-27-5	7 ppm 40 mg/ m3	14 ppm 80 mg/ m3			
- Sweden (AFS 2018 :1) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
101-84-8	1 ppm 7 mg/ m3	2 ppm 14 mg/ m3			
5989-27-5	25 ppm	50 ppm	-	-	-
- Romania (Hotarâre 1218/2006) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
140-11-4	8 ppm 50 mg/ m3	13 ppm 80 mg/ m3			
101-84-8	0.7 ppm 5 mg/ m3	1.4 ppm 10 mg/m3			
- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
101-84-8	1 ppm 7 mg/ m3	2 ppm 14 mg/ m3			
- USA / NIOSH REL (National Institute for Occupational Safety and Health, Recommended exposure limits) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
101-84-8	1 ppm	-	-	-	-
- USA / NIOSH IDLH (National Institute for Occupational Safety and Health, Immediately Dangerous to Life or Health Concentrations) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
101-84-8	1 ppm 7 mg/ m3				
- USA / OSHA PEL (Occupational Safety and Health Administration, Permissible Exposure Limits) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
101-84-8	1 ppm 7 mg/ m3				
- USA / AIHA WEEL (American Industrial Hygiene Association, Workplace Environmental Exposure Limit, 2010) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
121-33-5	10 mg/m3				
- Netherlands / MAC-waarde (10 december 2014) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
101-84-8	1 ppm 7 mg/ m3	2 ppm 14 mg/ m3			

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

- Butyl Rubber (Isobutylene-isoprene copolymer)

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

No data available.

Physical state

Physical state :

Fluid liquid.

Colour

Unspecified

Odour

Odour threshold :

Not stated.

Melting point

DADDY - ITM0487706

Melting point/melting range :	Not specified.
Freezing point	
Freezing point / Freezing range :	Not stated.
Boiling point or initial boiling point and boiling range	
Boiling point/boiling range :	Not specified.
Flammability	
Flammability (solid, gas) :	Not stated.
Lower and upper explosion limit	
Explosive properties, lower explosivity limit (%) :	Not stated.
Explosive properties, upper explosivity limit (%) :	Not stated.
Flash point	
Flash Point Interval :	> 93°C
	Method for determining the flash point: ASTM D 93-15 (Standard Test Methods for Flash Point by Pensky-Martens Closed Cup Tester).
Auto-ignition temperature	
Self-ignition temperature :	Not specified.
Decomposition temperature	
Decomposition point/decomposition range :	Not specified.
pH	
pH :	Not relevant.
pH (aqueous solution) :	Not stated.
Kinematic viscosity	
Viscosity :	Not stated.
Solubility	
Water solubility :	Insoluble.
Fat solubility :	Not stated.
Partition coefficient n-octanol/water (log value)	
Partition coefficient: n-octanol/water :	Not stated.
Vapour pressure	
Vapour pressure (50°C) :	Not stated.
Density and/or relative density	
Density :	1,088-1,108@20°C
	Method for determining the density : NF ISO 279:1999 (T75-111)
Relative vapour density	
Vapour density :	Not stated.

9.2. Other information

DADDY - ITM0487706

Index of refraction :

1,454-1,464@20°C

Method of determining the refractive index :

NF ISO 280:1999 (T75-112)

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

May cause reversible damage to the skin; namely the formation of erythema and eschar following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

May cause an allergic reaction by skin contact.

11.1.1. Substances

Acute toxicity :

P-MENTHA-1,4-DIENE (CAS: 99-85-4)

Oral route :

LD50 = 3650 mg/kg bodyweight/day

DODECANENITRILE (CAS: 2437-25-4)

Oral route :

LD50 = 3400 mg/kg bodyweight/day

ISOAMYL SALICYLATE (CAS: 87-20-7)

Oral route :

LD50 = 1406 mg/kg bodyweight/day

TRICYCLODECENYL ACETATE (CAS: 5413-60-5)

DADDY - ITM0487706

Oral route :	LD50 = 3050 mg/kg bodyweight/day
COUMARIN (CAS: 91-64-5)	
Oral route :	LD50 = 290 mg/kg bodyweight/day
VANILLIN (CAS: 121-33-5)	
Oral route :	LD50 = 3300 mg/kg bodyweight/day
Dermal route :	LD50 = 2600 mg/kg bodyweight/day
PHENETHYL ALCOHOL (CAS: 60-12-8)	
Oral route :	LD50 = 1610 mg/kg bodyweight/day
ALPHA-AMYL CINNAMALDEHYDE (CAS: 122-40-7)	
Oral route :	LD50 = 3730 mg/kg bodyweight/day
DIPHENYL ETHER (CAS: 101-84-8)	
Oral route :	LD50 = 2830 mg/kg bodyweight/day
ALPHA-TERPINEOL (CAS: 98-55-5)	
Oral route :	LD50 = 4300 mg/kg bodyweight/day
BENZYL ACETATE (CAS: 140-11-4)	
Oral route :	LD50 = 2490 mg/kg bodyweight/day

11.1.2 Complex substance

Skin corrosion/skin irritation :

Irritation : Causes mild skin irritation.

11.2. Information on other hazards

Monograph(s) from the IARC (International Agency for Research on Cancer) :

- CAS 108-88-3 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.
- CAS 64-17-5 : IARC Group 1 : The agent is carcinogenic to humans.
- CAS 128-37-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.
- CAS 123-35-3 : IARC Group 2B : The agent is possibly carcinogenic to humans.
- CAS 5989-27-5 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.
- CAS 91-64-5 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.
- CAS 140-11-4 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.2 Complex substance

No aquatic toxicity data available for the substances.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

The appropriate waste management of the mixture and/or its container must be determined in accordance with local regulations.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2023 - IMDG 2020 [40-20] - ICAO/IATA 2023 [64]).

14.1. UN number

3082

14.2. UN proper shipping name

UN3082=ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(dodecanenitrile)

14.3. Transport hazard class(es)



- Classification :

9

14.4. Packing group

III

14.5. Environmental hazards



- Environmentally hazardous material :

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	9	M6	III	9	90	5 L	274 335	E1	3	-

DADDY - ITM0487706

							375 601			
	Not subject to this regulation if Q ≤ 5 1 / 5 kg (ADR 3.3.1 - DS 375)									
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage, Handling	Segregation	
	9	-	III	5 L	F-A. S-F	274 335 969	E1	Category A		
	Not subject to this regulation if Q ≤ 5 1 / 5 kg (IMDG 3.3.1 - 2.10.2.7)									
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	9	-	III	964	450 L	964	450 L	A97 A158 A197 A215	E1	
	9	-	III	Y964	30 kg G	-	-	A97 A158 A197 A215	E1	
	Not subject to this regulation if Q ≤ 5 1 / 5 kg (IATA 4.4.4 - DS A197)									

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

Marine pollutant (IMDG 3.1.2.9):(dodecanenitrile)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The following regulations have been used:

- Globally Harmonized System of Classification and Labelling of Chemicals (GHS), review no. 8 (2019)

Container information:

No data available.

Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H226	Flammable liquid and vapour.
H227	Combustible liquid.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H360	May damage fertility or the unborn child .
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

CMR: Carcinogenic, mutagenic or reprotoxic.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

GHS07 : Exclamation mark

GHS09 : Environment

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.