

NB-359: Liquid phase H₂ and O₂ of RhCrO_x,Al:SrTiO₃ (EA-358, 0.5 mg/mL), 365 nm, 50 mW/cm², 10 °C (reproduction NB-351)

Date: 2025-11-24

Tags: O₂ Test Calibration NB Firing
O₂ sensor H₂ SrTiO₃ troubleshooting
Unisense RhCrO₃:Al:SrTiO₃ H₂ Sensor
temperature In situ H₂/O₂ reactor Trace
range robust oxygen sensor
photocatalysis Unisense normal range

Category: SrTiO₃


Status: Done

Created by: Nadzeya Brezhneva

Objectives

Reproduction of NB-351: simultaneous detection of H₂ and O₂ evolution in liquid phase for irradiated suspension of Rh_xCrO_y:Al:SrTiO₃ suspension (EA-358, 0.5 mg/mL), 365 nm LED, 50 mW/cm², 10 °C (changing temperature relatively to reference conditions).

Reaction scheme



ChemDraw file linked: [NB-351-SrTiO3-photocatalytic H2O splitting.cdxml](#)

Literature/reference experiments

Literature	/
Reproduction	SrTiO₃ - NB-351: Liquid phase H₂ and O₂ of RhCrO_x,Al:SrTiO₃ (EA-358, 0.5 mg/mL), 365 nm, 50 mW/cm², 10 °C
Similar experiments	SrTiO₃ - NB-316: Liquid phase H₂ and O₂ of RhCrO_x,Al:SrTiO₃ (EA-358, 0.5 mg/mL), 365 nm, 50 mW/cm², 20 °C

Reagents

Name	CAS Number / Experiment Number	Inventory number	Amount [mmol]	Equivalents	Mass _{theo} [mg]	Mass _{exp} [mg]	Molar mass [g/mol]	Density (g/ml)	Volume [ml]	Pressure [bar]	Concentration [mM]
milli-Q H ₂ O	/	/	/	/	/	/	/	0.998	25 + 25 (for calibration)	/	/
Al:SrTiO ₃ RhCrO _x (EA-358)	SrTiO₃ - EA-358: Modification of Al:SrTiO₃ (EA-354) via deposition of Rh, Cr oxide co-catalyst, 350°C, 1h, Upscaling (3.33x)	/	/	/	12.50	12.58	/	/	/	/	/
Hydrogen	1333-74-0	/	/	/	/	/	/	/	1 balloon (ca. 2 L)	ca. 1	/

Excel sheet for reagent calculation

/

Irradiation Parameters

Power measurement was performed using [Power Meter - 843-R-USB + 919P-020-12](#) in [Equipment - Advanced power measurment setup V1.0 I](#)

Power measurement was performed in experiment [Prep work - NB-314: Measuring power output of UHP-365 nm #4 with 18A-4 in advanced irradiation setup](#)

	Name
Used Set-up	Equipment - Advanced irradiation setup V1.0 I
Irradiation setup number	Equipment - Irradiation setup 4 (CEEC II, E002)

	Light Source Name	Power Source Name	Wavelength [nm]	Power Setting [mW]	Analog Setting [0.00 - 10.00]
First light source	Light Source - UHP LED 365 nm-4	Power Sources - BLS-18000-1 4	365	56	0.19

Used beam combiner [Name or None]	/
Irradiation distance [cm]	6.5
Thermostat temperature [°C]	10
Stirring speed [rpm]	500
Irradiation start: 1. Firesting [relative to start log] 2. Unisense	1. 600 s 2. 17:47:57
Irradiation stop: 1. Firesting [relative to start log] 2. Unisense	1. 1520 s 2. 18:03:17

O₂/H₂ sensor equipment

	Equipment	Used protocol
Used Firesting	Equipment - Firesting Fiber-Optic Oxygen Meter 2 Channel (Firesting 2)	Protocol - Operation of Firesting Fiber-Optic Oxygen Meter 2 Channel Software
Used O ₂ sensor	Equipment - Robust probe for liquid O ₂ measurment	Protocol - In-situ hydrogen and oxygen measurment in H ₂ /O ₂ reactor
Used H ₂ sensor	Equipment - H ₂ UniAmp Sensor - Normal range - 2.1 x 80 mm needle	Protocol - In-situ hydrogen and oxygen measurment in H ₂ /O ₂ reactor

Procedure/observations

Date	Time	Step	Observations	Pictures/Files
24.11.2025		The experiment was done according to Protocol - In-situ hydrogen and oxygen measurment in H₂/O₂ reactor Important steps and deviations are listed below	/	/
	12:01-13:11	Conditioning of H ₂ sensor	NB-359-Logger1 1.6 mV at the end of polarization procedure	NB-359.ulong NB-359-Logger1-pre-polarization.csv NB-359-Logger1-pre-polarization.bmp
	13:30	Assembling the setup for calibration (25 mL of water was added using graduated cylinder), (LAUDA set to 10 °C) done according to Protocol - Liquid phase calibration of H₂ UniAmp sensor with H ₂ bubbling.	/	/
	13:40-53	Keeping the system under stirring to reach 10 °C (T control by PT1000).	/	/
	13:53	Start of O ₂ logging.	NB-359-Ch2-1	2025-11-24_135359_NB-359-Ch2-1.txt 2025-11-24_135359_NB-359-Ch2-1.png
	13:56	Degassing was started.	/	20251124_135652-degassing of water.jpg

	14:19	Start of H2 logging.	NB-359-Logger2 offset -2 mV	NB-359.ulog NB-359-Logger2-calibration.csv NB-359-Logger2-calibration step.bmp NB-359-Logger2-2point calibration.bmp
	14:20	Moving cannula to gas phase above the liquid level.	/	/
	14:23	Introducing H2 sensor into the reactor under Ar flow.	/	/
	14:24	0 ppm was taken.	offset -1 mV	/
	14:32	Removing the previous 0 point, taking new 0 ppm.	/	/
	14:32	Degassing was stopped.	/	/
	14:33	H2 bubbling of the reactor was started.	Drop in H2 value at 14:41, but afterwards increased and could reach steady state.	20251124_143502-H2 bubbling.jpg
	14:47	1.000.000 ppm point was taken.	618 mV	20251124_144653-H2 table.jpg 2
	14:52	The previous point was deleted, new 1.000.000 ppm point was taken and calibration was saved	662 mV (stable for several minutes), slope: 0.771, 856 uM 14:54 - decrease in H2 signal, followed by stopping the logging.	/
	14:54	Stop of H2 logging.	/	/
	14:57	Stop of O2 logging.	/	/
	15:00	Deassembling the setup, drying the reactor with acetone and compressed air .	/	/
		Sample preparation		
	15:25	Weighing EA-358 photocatalyst in a 50 mL vial.	Creamy solid.	/
	15:30	Addition of 25 mL H2O to the vial via graduated cylinder.	/	/
	15:32-35	The suspension was vortexed for 3 min (Equipment - VWR® VV3, Vortex Mixer , stage 4/6), covered with Al foil before further use.	/	20251124_153508-suspension after vortex.jpg
		Continue in Protocol - In-situ hydrogen and oxygen measurment in H2/O2 reactor from step 6		

	15:40	The suspension was transferred to the reactor using glass pipette (preliminary the vial was manually shaken ca. 15 s) .	/	/
	15:45	Assembling the setup.	Currently, stopper instead of H ₂ sensor, PT100, PT1000 and O ₂ robust probe are inside the reactor immersed in the liquid phase	/
	15:48-58	Keeping suspension at 10 °C, T control by PT1000.	/	/
	15:58	Start of O2 logging.	NB-359-Ch2-2	2025-11-24_155825_NB-359-Ch2-2.txt 2025-11-24_155825_NB-359-Ch2-2.png
	16:00	The degassing was started	/	20251124_160032-degassing of the suspension.jpg
	16:29	Cannula was transferred to gas phase, above the suspension.	/	/
	16:31	H ₂ sensor was added in Ar counterflow.	/	/
	16:33	The degassing was stopped by removing the cannula and closing the valve.	/	/
	16:35	Stop of O2 logging.	/	/
	16:35	Start of O2 logging.	NB-359-Ch2-3	2025-11-24_163521_NB-359-Ch2-3.txt 2025-11-24_163521_NB-359-Ch2-3.png
	16:35	Start of H2 logging.	NB-359-Logger3 High H2 signal after introducing sensor to the reactor.	NB-359.uog NB-359-Logger3.csv NB-359-Logger3.bmp
	16:36	Stop of H2 and O2 loggings.	Removing the sensor from the reactor, introducing once again, checking cable management.	/
	16:42	Start degassing once again.	NB-351-Ch2-4	2025-11-24_164417_NB-359-Ch2-4.txt 2025-11-24_164417_NB-359-Ch2-4.png
	16:44	Moving cannula to gas phase above the liquid level.	/	/

	16:56	Introducing H2 sensor under Ar flow.	Immediately after immersing the sensor in the suspension - signal OK, but afterwards again the signal value was high (maybe problems with the position of the cable)	/
	16:56	Removing cannula, closing the valve.	/	/
	ca. 17:07	Stop of O2 logging.	/	/
	17:07	Start of O2 logging.	NB-351-Ch2-5	2025-11-24_170748_NB-359-Ch2-5.txt 2025-11-24_170748_NB-359-Ch2-5.png
	17:08	Start of H2 logging.	NB-351-Logger4	NB-359.uolog NB-359-Logger4.csv NB-359-Logger4.bmp
	17:13	Stop of O2 logging.	H2 logging showed not stable signal of the sensor after immersion in the suspension	/
	17:20	Stop of H2 logging.	/	/
	17:22-36	Degassing of the suspension (cannula above the suspension).	/	/
	17:37	Start of O2 logging	NB-351-Ch2-6	2025-11-24_173757_NB-359-Ch2-6.txt 2025-11-24_173757_NB-359-Ch2-6.png
	17:37	Start of H2 logging.	NB-351-Logger5	NB-359.uolog NB-359-Logger5-during irradiation.csv NB-359-Logger5-during irradiation.bmp
	17:37-47	Equilibration time.	/	/
	17:47	The irradiation was started	/	/
	18:03	The irradiation was stopped.	/	/
	18:03-13	Equilibration time.	/	/
	18:13	Stop of O2 and H2 logging.	/	/

	ca. 18:20	Deassembling the setup, cleaning the reactor.	Tips of the sensors and reactor were covered with attached photocatalyst particles. Tip: After preliminary cleaning with sticks, wipes, the residual particles attached to the walls of the reactor could be removed by sonication - fill the reactor with water and place it in ultrasonic bath for ca. 20 s (Eco mode).	20251124_181412-after irradiation.jpg
--	-----------	---	--	---

Analysis

Used calibration for Firesting: [20250611-BOLA-fitting-liquid-phase-trace-oxygen-sensor-H2-O2 reactor.ini](#)

Used calibration for UniSense: NB-359-Logger2

for feasibility, loggings used for calibration and in photocatalytic tests are highlighted with green.

Date	Time	Sample name	Analysis method	Analytical device	Solvent	Raw Data	Python script	Processed Data	Comparative Data	Interpretation
18.11.2025	12:01	NB-359-Logger1	electrochemical H2 detection	Equipment - H2 UniAmp Sensor - Normal range - 2.1 x 80 mm needle	water	NB-359.ulog NB-359-Logger1-pre-polarization.csv	/	NB-359-Logger1-pre-polarization.bmp	/	Pre-polarization of H2 sensor.
	14:19	NB-359-Logger2	electrochemical H2 detection	Equipment - H2 UniAmp Sensor - Normal range - 2.1 x 80 mm needle	water	NB-359.ulog NB-359-Logger2-calibration.csv	/	NB-359-Logger2-calibration step.bmp NB-359-Logger2-2point calibration.bmp	/	Calibration of H2 sensor, at 10^{-6} ppm signal 662 mV, slope 0.771
	16:35	NB-359-Logger3	electrochemical H2 detection	Equipment - H2 UniAmp Sensor - Normal range - 2.1 x 80 mm needle	water	NB-359.ulog NB-359-Logger3.csv	/	NB-359-Logger3.bmp	/	High signal after introducing H2 snsor to the suspension --> needs to be eliminated.
	17:08	NB-359-Logger4	electrochemical H2 detection	Equipment - H2 UniAmp Sensor - Normal range - 2.1 x 80 mm needle	water	NB-359.ulog NB-359-Logger4.csv	/	NB-359-Logger4.bmp	/	Not stable signal after immersing the sensor in the suspension.
	17:37	NB-359-Logger5	electrochemical H2 detection	Equipment - H2 UniAmp Sensor - Normal range - 2.1 x 80 mm needle	water	NB-359.ulog NB-359-Logger5-during irradiation.csv	NB-359-O2 and H2 curve.py	NB-359-Logger5-during irradiation.bmp	SrTiO3 - NB-351: Liquid phase H2 and O2 of RhCrOx,Al:SrTiO3 (EA-358, 0.5 mg/mL), 365 nm, 50 mW/cm2, 10 °C	H2 evolution during irradiation.
	13:53	NB-359-Ch2-1	Optical O2 detection	Equipment - Firesting Fiber-Optic Oxygen Meter 2 Channel	water	2025-11-24_135359_NB-359-Ch2-1.txt	/	2025-11-24_135359_NB-359-Ch2-1.png	/	Degassing of water followed by calibration of H2 sensor.

15:58	NB-359-Ch2-2	Optical O2 detection	Equipment - Firesting Fiber-Optic Oxygen Meter 2 Channel	water	2025-11-24_155825_NB-359-Ch2-2.txt	/	2025-11-24_155825_NB-359-Ch2-2.png	/	Degassing of the suspension (eliminating problems)
16:35	NB-359-Ch2-3	Optical O2 detection	Equipment - Firesting Fiber-Optic Oxygen Meter 2 Channel	water	2025-11-24_163521_NB-359-Ch2-3.txt	/	2025-11-24_163521_NB-359-Ch2-3.png	/	Degassing of the suspension (eliminating problems).
16:44	NB-359-Ch2-4	Optical O2 detection	Equipment - Firesting Fiber-Optic Oxygen Meter 2 Channel	water	2025-11-24_164417_NB-359-Ch2-4.txt	/	2025-11-24_164417_NB-359-Ch2-4.png	/	Degassing of the suspension (eliminating problems).
17:07	NB-359-Ch2-5	Optical O2 detection	Equipment - Firesting Fiber-Optic Oxygen Meter 2 Channel	water	2025-11-24_170748_NB-359-Ch2-5.txt	/	2025-11-24_170748_NB-359-Ch2-5.png	/	Degassing of the suspension (successful).
17:37	NB-359-Ch2-6	Optical O2 detection	Equipment - Firesting Fiber-Optic Oxygen Meter 2 Channel	water	2025-11-24_173757_NB-359-Ch2-6.txt	NB-359-O2 and H2 curve.py	2025-11-24_173757_NB-359-Ch2-6.png	SrTiO3 - NB-351: Liquid phase H2 and O2 of RhCrOx,Al:SrTiO3 (EA-358, 0.5 mg/mL), 365 nm, 50 mW/cm2, 10 °C	O2 evolution during irradiation.

Results

Reproduction of NB-351: simultaneous H₂ and O₂ measurements of irradiated suspension of EA-358 (0.5 mg/mL) in O₂/H₂ photoreactor under 365 nm irradiation (50 mW/cm², 10 °C, 15 min) were performed.

Linked experiments

SrTiO3 - NB-316: Liquid phase H2 and O2 of RhCrOx,Al:SrTiO3 (EA-358, 0.5 mg/mL), 365 nm, 50 mW/cm2, 20 °C

SrTiO3 - NB-318: Liquid phase H2 and O2 of RhCrOx,Al:SrTiO3 (EA-358, 0.5 mg/mL), 365 nm, 100 mW/cm2, 20 °C

SrTiO3 - NB-322: Liquid phase H2 and O2 of RhCrOx,Al:SrTiO3 (EA-358, 0.5 mg/mL), 365 nm, 100 mW/cm2, 20 °C (reproduction NB-318)

SrTiO3 - NB-325: Liquid phase H2 and O2 of RhCrOx,Al:SrTiO3 (EA-358, 0.5 mg/mL), 365 nm, 20 mW/cm2, 20 °C

SrTiO3 - NB-330: Liquid phase H2 and O2 of RhCrOx,Al:SrTiO3 (EA-358, 0.5 mg/mL), 365 nm, 50 mW/cm2, 30 °C

SrTiO3 - NB-334: Liquid phase H2 and O2 of RhCrOx,Al:SrTiO3 (EA-358, 0.5 mg/mL), 365 nm, 50 mW/cm2, 30 °C (reproduction NB-330)

SrTiO3 - NB-351: Liquid phase H2 and O2 of RhCrOx,Al:SrTiO3 (EA-358, 0.5 mg/mL), 365 nm, 50 mW/cm2, 10 °C

Linked resources

Equipment - [VWR® VV3, Vortex Mixer](#)

Equipment - [Firesting Fiber-Optic Oxygen Meter 2 Channel \(Firesting 2\)](#)

Equipment - [Advanced power measurment chamber V1.0 I](#)

Equipment - [Irradiation setup 4 \(CEEC II, E002\)](#)

Light Source - [UHP LED 365 nm-4](#)

Power Sources - [BLS-18000-1 4](#)


Protocol - [Getting hydrogen from hydrogen bottle in CEEC II E014](#)

Protocol - [In-situ hydrogen and oxygen measurment in H2/O2 reactor](#)

Attached files

NB-359-O2 and H2 curves.png

sha256: 7e261d593699416169fbad539298cffd286a3db90a0be9c6ec1fe6e5ab5517eb



NB-359-O2 and H2 curve.py

sha256: 66dcb1b52bb66f538631e27b8ccf59ff8b5b91eb5be6747348f1fb475bd580fa

20251124_135652-degassing of water.jpg

sha256: 3cc21cac997d068387758e92ccfe9953bca80d350274621a0edca66e371b4650



20251124_143502-H2 bubbling.jpg

sha256: b55e35a793b26c5ba1a80051282fd8bc2e14ea0611b99a8000164b7f15701ae6



20251124_144653-H2 table.jpg

sha256: eaf4360e979e207abf033e78af1c4167ff71932072a61f40d481bc2f4cc3d625



20251124_153508-suspension after vortex.jpg

sha256: bdec8dd6de54b880751ed87c464fb4d59504a47cd7d0ca10d4a695fa76256840



20251124_174915-after start of irradiation.jpg

sha256: b92e63f758b1f8ad614621d7114ca3f6df8429a0836a02a6279bc40c2591e991



20251124_181412-after irradiation.jpg

sha256: 1da7435737491a2eb4f807f29cdc9594609cdfa1805860bbdde400f7c0f378ea



20251124_160032-degassing of the suspension.jpg

sha256: 7343c6a40cf71d37d27d1eca146f8a41c2cee3dcb2c13c3530a390e924fbf155




NB-359-Logger5-during irradiation.csv

sha256: 557d94b5b91a525aadf76490c5a9f8a105476466d00e1e069fdb4031199a56aa

NB-359-Logger5-during irradiation.bmp

sha256: e2ee14d8b727e50beebf717b1047ce202d45f74d196b23aba2da3810aaf5c0c1



NB-359-Logger4.csv

sha256: e5acf9b787c055f3b892a1ccf9c5183cf2f2d1e70ebd58aa0de83ec5d869007d

NB-359-Logger4.bmp

sha256: 3de4d1c8f1af7e4b90494cee150301397264f91c8a4fb8ca066fbccc6b27af0e



NB-359-Logger3.bmp

sha256: d146b759cfe6cc6927ae60e5a11680b52e6daf7b20ff7059c3075f6b51b30ba0



NB-359-Logger3.csv


sha256: 02b7bddbfc61c6401de524eb3622f5dbf7830a35ce26dd4c5eaf097a1c8dbce1

NB-359-Logger2-calibration.csv

sha256: c1655be6b573094bd2b7083fe18de5eb29ac02f55d88d9d3dafd925a2e928970


NB-359-Logger2-calibration step.bmp

sha256: 37c0417e59a3c77f180fb54f6c70c293630fd7f13e589beac23dd2d47f40c1ca




NB-359-Logger2-2point calibration.bmp

sha256: c73820970678eab6b5e07203967ba66bf34b4d32bc9a3b267191276c7e49ecd9



NB-359-Logger1-pre-polarization.bmp

sha256: 1d8934d5b3026bccea86450b678967fd7d0f4776436f0e93a160fbd33c3a579b



NB-359-Logger1-pre-polarization.csv

sha256: 56255759b57906e58903f38a6b47310f0dcd59202d125d07506dfb5acc8fc776

NB-359.ulog


sha256: a227575fd84534abff88076fcefb183617facec2acd158bb62f68fb50c885df2

2025-11-24_173757_NB-359-Ch2-6.txt

sha256: ccde8b55cf427ffef3d5d01b44e1aaf3bbc03b8ca96f8f6369adb47a5291465

2025-11-24_173757_NB-359-Ch2-6.png

sha256: 47f65f19d7c48b68e338f7b5283fd821adb2078cc13b4f314ba9a7b2919fc2dc




2025-11-24_170748_NB-359-Ch2-5.txt

sha256: 00e17dcc1ef55c9815e77d57e33ea47d4e96602a06cb219c77e98c2b45f8cfde

2025-11-24_170748_NB-359-Ch2-5.png

sha256: f943eed204d5b6e487774112e99fdce07a0cd912f852b71d2ef1bc3c01af8667




2025-11-24_164417_NB-359-Ch2-4.txt

sha256: 17fb3ebefbfe39b8cef35f89d0fecc6447253ebef4f01a6f85440c16528164c49

2025-11-24_164417_NB-359-Ch2-4.png

sha256: 30508dd9b08a478de6f18bcda5365b2a7b69f3c788976deea5a021cd68738c68



2025-11-24_163521_NB-359-Ch2-3.txt

sha256: ada0b59c76c8d3cd85b487fec6c83382dc33680484a93f401bcd58dcbbba4b6ef

2025-11-24_163521_NB-359-Ch2-3.png

sha256: 6722824f818b370c2b8145938a50500d77bc784944b1620e53aa64cc1c59d180



2025-11-24_155825_NB-359-Ch2-2.txt

sha256: 786d69f5772d64e4f368c16aa1331c0bf26d7608f9089dd20d73e105f699e705

2025-11-24_155825_NB-359-Ch2-2.png

sha256: 09b1a918c5281db9b761c2d3c2ab08dd8db10f6adf951d86b391cb2d284665bd



2025-11-24_135359_NB-359-Ch2-1.png

sha256: 24c1bf0fe900013778e7764ee926eabef4638750129c3834d7a8c2c44b1a1701



2025-11-24_135359_NB-359-Ch2-1.txt

sha256: b3e44755d48e7c4939811ce1294e0890f27f51dba826ddec707ab120d4ed68dd



Unique eLabID: 20251124-e766d8e233c80c1dd94ef9cee1ef586c4da76ace
Link: <https://elab.water-splitting.org/experiments.php?mode=view&id=3542>