

Power Meter

Newport 843-R-USB

<https://www.newport.com/p/843-R-USB>

Thermopile Sensor

Newport 919P-020-12

<https://www.newport.com/p/919P-020-12>

Sensor Specifications

Detector Type General Purpose	Spectral Range 0.19 to 11 µm	Maximum Measurable Power 4 W (standalone), 20 W (with a heat sink)
Sensor Size Ø12 mm	Maximum Power Density 23 kW/cm ²	Maximum Energy Density <100 ns, 0.3 J/cm ² 0.5 ms, 2 J/cm ² 2 ms, 2 J/cm ² 10 ms, 2 J/cm ²
Noise Equivalent Power 0.5 mW	Power Range 10 mW - 4 W (standalone), 20 W (with a heat sink)	Noise Equivalent Energy 20 mJ
Cooling Sensor Body	Connector Type DB15	Rise Time 0.8 s
Linearity ±1 %	Calibration Uncertainty ±3 %	Repeatability ±0.5 %
Beam Size Dependence ±0.7 %	Detector Active Area 1.13 cm ²	Operating Temperature Range 15°C to 35°C, <70% RH, non-condensing
Storage Temperature Range 0°C to 50°C, <90% RH	Cable Length 1.5 m	Dimensions 38 x 38 x 14 mm
Repeatability ±0.5 %	Weight 0.2 kg	RoHS Compliant

Attached file

919P-Detector-Datasheet.pdf

sha256: 6164c446cacb9d8e814ee4f5b5f3f5d49f3576fd6c7b9dc33b443be97aacf49a



Unique eLabID: 20221112-bb7cc43fb3838a8dbad27f2cf41f2979315beb2e

Link: <https://elab.water-splitting.org/database.php?mode=view&id=51>