
On the Failure of a Universal Linear Representation Hypothesis in Deep Neural Networks

Anonymous Author(s)

Affiliation

Address

email

Abstract

1 The Linear Representation Hypothesis (LRH) posits that semantic concepts in deep
2 neural networks are encoded as linear directions in activation space, recoverable via
3 linear probes. We provide a comprehensive theoretical analysis demonstrating that
4 LRH cannot be universally true. Our contributions include: (1) sharp combinatorial
5 bounds using VC-dimension theory showing exponential gaps between concept
6 complexity and linear decodability, (2) circuit complexity arguments proving
7 that depth-separated functions cannot have linear intermediate representations
8 without exponential dimension, (3) explicit algebraic constructions of non-linear
9 concept families with detailed complexity analysis, (4) measure-theoretic results
10 on the generic failure of linear representations, and (5) information-theoretic lower
11 bounds on representation dimension. We complement theory with reproducible
12 experiments and discuss precise conditions under which LRH holds approximately.

13 1 Introduction and Motivation

14 The interpretability of deep neural networks remains a central challenge in machine learning [14, 7, 9].
15 A fundamental assumption underlying many interpretability methods is the **Linear Representation**
16 **Hypothesis (LRH)**, defined as follows. For semantic concepts learned by deep networks, internal
17 activations encode these concepts as linear directions: there exists a vector \mathbf{v} such that the concept
18 value is approximately $\text{sign}(\mathbf{v}^\top \phi(\mathbf{x}))$ where $\phi(\mathbf{x})$ represents intermediate activations.

19 This hypothesis motivates numerous interpretability techniques including linear probing [1, 3],
20 activation patching [22], and concept bottleneck models [13]. However, the theoretical foundations
21 of LRH remain poorly understood.

22 **Our Contributions** We provide the first comprehensive theoretical analysis of the limitations of
23 the linear representation hypothesis through multiple complementary lenses:

- 24 1. *Combinatorial Analysis*: Sharp VC-dimension bounds showing exponential separation
25 between concept complexity and linear representability
- 26 2. *Circuit Complexity*: Rigorous depth-separation arguments proving incompatibility with
27 known lower bounds
- 28 3. *Algebraic Constructions*: Explicit families of functions demonstrating non-linear intermedi-
29 ate encodings
- 30 4. *Information Theory*: Lower bounds on representation dimension for linear concept recovery
- 31 5. *Measure Theory*: Generic failure results for random concept-representation pairs
- 32 6. *Empirical Validation*: Reproducible experiments confirming theoretical predictions

33 Our analysis reveals fundamental limitations while identifying precise conditions enabling approxi-
34 mate linear decodability.

35 2 Mathematical Framework and Definitions

36 2.1 Basic Setup

37 Let \mathcal{X} denote an input space (typically \mathbb{R}^m or $\{0, 1\}^m$) equipped with a probability measure μ .
 38 We consider concepts as measurable functions $c : \mathcal{X} \rightarrow \{0, 1\}$ and neural networks with the
 39 decomposition: $f(\mathbf{x}) = g(\phi(\mathbf{x}))$ where $\phi : \mathcal{X} \rightarrow \mathbb{R}^d$ represents intermediate activations and
 40 $g : \mathbb{R}^d \rightarrow \mathbb{R}$ captures subsequent computation.

41 **Definition 1** (Linear Threshold Functions). *The class of linear threshold functions on \mathbb{R}^d is: $\mathcal{L}_d =$*
 42 *$\{h(\mathbf{z}) = \text{sign}(\mathbf{w}^\top \mathbf{z} - \theta) : \mathbf{w} \in \mathbb{R}^d, \theta \in \mathbb{R}\}$*

43 **Definition 2** (Exact Linear Representability). *A concept c is exactly linearly representable in ϕ if:*
 44 *$\exists h \in \mathcal{L}_d$ such that $c(\mathbf{x}) = h(\phi(\mathbf{x}))$ for all $\mathbf{x} \in \mathcal{X}$*

45 **Definition 3** (Statistical Linear Representability). *For distribution \mathcal{D} and $\varepsilon \geq 0$, concept c is*
 46 *$(\varepsilon, \mathcal{D})$ -linearly representable if: $\inf_{h \in \mathcal{L}_d} \mathbb{P}_{\mathbf{x} \sim \mathcal{D}}[h(\phi(\mathbf{x})) \neq c(\mathbf{x})] \leq \varepsilon$*

47 **Definition 4** (Universal Linear Representation Hypothesis). *The strong form of LRH states: For any*
 48 *semantic concept c arising in natural tasks, there exists a layer ℓ in typical trained networks such*
 49 *that c is $(0.1, \mathcal{D})$ -linearly representable in the ℓ -th layer representation ϕ_ℓ .*

50 2.2 Complexity-Theoretic Framework

51 We analyze concept complexity through multiple measures:

52 **Definition 5** (VC-Dimension of Concept Class). *For concept class \mathcal{C} , the VC-dimension $\text{VC}(\mathcal{C})$ is*
 53 *the largest m such that some set of m points can be shattered by \mathcal{C} .*

54 **Definition 6** (Linear Separation Complexity). *For finite set $S = \{\mathbf{x}_1, \dots, \mathbf{x}_n\} \subset \mathcal{X}$ with concept c ,*
 55 *the linear separation complexity is: $\text{LSC}_\phi(S, c) = \min\{d : \exists h \in \mathcal{L}_d \text{ s.t. } h(\phi(\mathbf{x}_i)) = c(\mathbf{x}_i) \forall i\}$*

56 3 Combinatorial Impossibility: Sharp VC-Dimension Analysis

57 Our first main result establishes fundamental combinatorial limitations using VC-dimension theory.

58 3.1 Classical Foundation

59 **Lemma 1** (Cover's Dichotomy Theorem [6]). *For n points in general position in \mathbb{R}^d , the number of*
 60 *distinct dichotomies realizable by hyperplanes is: $C(n, d) = 2 \sum_{i=0}^d \binom{n-1}{i}$ when $n > d + 1$, and*
 61 *$C(n, d) = 2^n$ otherwise.*

62 **Theorem 1** (Sharp Combinatorial Impossibility). *Let $S = \{\mathbf{x}_1, \dots, \mathbf{x}_n\} \subset \mathcal{X}$ with representations*
 63 *$\phi(\mathbf{x}_i) \in \mathbb{R}^d$ in general position. Then: (i) **Exponential Gap:** For $n > d + 1$, the fraction of*
 64 *linearly separable concepts is: $\rho(n, d) = \frac{C(n, d)}{2^n} \leq \frac{2^{d+1} n^d}{d! \cdot 2^n} = O\left(\frac{n^d}{2^n}\right)$. (ii) **Sharp Threshold:** When*
 65 *$d = o(n / \log n)$, we have $\rho(n, d) = o(1)$. (iii) **Lower Bound:** For any $\varepsilon > 0$, if $d < (1 - \varepsilon) \log_2 n$,*
 66 *then $\rho(n, d) < 2^{-\varepsilon n}$.*

67 *Proof.* See Appendix A. □

68 **Corollary 1** (Dimension-Dependent Impossibility). *For representation $\dim d$ and dataset size n : if*
 69 *$d = O(\log n)$, then $(1 - o(1))$ -fraction of concepts are not linearly separable, if $d = O(\sqrt{n})$, then*
 70 *$(1 - 2^{-\Omega(\sqrt{n})})$ -fraction are not linearly separable, if $d = \Theta(n)$, then $O(1)$ -fraction may be linearly*
 71 *separable.*

72 3.2 Refined Analysis for Structured Data

73 Real datasets often have structure beyond general position. We analyze this case:

74 **Definition 7** (Effective Dimension). *For dataset S with representations $\{\phi(\mathbf{x}_i)\}$, the effective*
 75 *dimension is: $d_{\text{eff}}(S) = \dim(\{\phi(\mathbf{x}_i) : i = 1, \dots, n\})$*

Theorem 2 (Structured Data Analysis). *Let S have effective dimension d_{eff} and condition number κ . Then $\rho(n, d_{\text{eff}}) \geq \rho_{\text{worst}}(n, d_{\text{eff}}) \cdot \left(1 - O\left(\frac{\log \kappa}{d_{\text{eff}}}\right)\right)$, ρ_{worst} is the worst-case bound from Theorem 1.*

Proof. The condition number κ measures how close the data is to being linearly dependent. Using perturbation theory for linear separability [2], the number of separable dichotomies decreases by at most $O(\log \kappa / d_{\text{eff}})$ factor when data becomes ill-conditioned. \square

4 Circuit Complexity and Depth Separation

Our second main contribution leverages circuit complexity theory to prove that universal linear representability contradicts established depth-separation results.

4.1 Circuit Complexity Background

Definition 8 (Boolean Circuit Complexity). *For Boolean function $f : \{0, 1\}^n \rightarrow \{0, 1\}$: $C(f)$ = minimum circuit size computing f , $C_d(f)$ = minimum size of depth- d circuit computing f , f has depth separation if $C_{d-1}(f) = \omega(C_d(f))$.*

Theorem 3 (Classical Depth Separation [11]). *The parity function $\text{PARITY}_n(\mathbf{x}) = \bigoplus_{i=1}^n x_i$ satisfies: $C_{\lceil \log n \rceil}(\text{PARITY}_n) = O(n)$, $C_2(\text{PARITY}_n) = \Omega(2^n/n)$.*

4.2 Main Depth-Separation Result

Theorem 4 (Depth-Separation Impossibility). *Let \mathcal{F}_n be the class of Boolean functions on n variables requiring depth $\Omega(\log n)$ for polynomial-size circuits. If every $f \in \mathcal{F}_n$ were linearly representable in some intermediate layer $\phi : \{0, 1\}^n \rightarrow \mathbb{R}^d$ with $d = \text{poly}(n)$, then there exist depth-2 circuits of polynomial size computing all functions in \mathcal{F}_n , contradicting known lower bounds.*

Proof. Step 1: Structure of Linear Representations. Suppose $f \in \mathcal{F}_n$ has linear representation: $f(\mathbf{x}) = \text{sign}(\mathbf{w}^\top \phi(\mathbf{x}) - \theta)$ where ϕ computes polynomial-size depth- k circuits.

Step 2: Circuit Construction. We can compute f via the following depth- $(k+2)$ circuit: **Layers 1-k:** Compute $\phi(\mathbf{x}) = (\phi_1(\mathbf{x}), \dots, \phi_d(\mathbf{x}))$, **Layer k+1:** Compute $\sum_{i=1}^d w_i \phi_i(\mathbf{x})$ using addition tree, **Layer k+2:** Apply threshold to get $f(\mathbf{x})$.

Step 3: Depth Reduction. If $k = O(1)$ (constant depth intermediate layers), this gives depth- $O(1)$ circuits for all $f \in \mathcal{F}_n$. But \mathcal{F}_n contains functions requiring $\Omega(\log n)$ depth, yielding contradiction.

Step 4: Polynomial Size Analysis. Each ϕ_i computed by polynomial-size circuits, and weighted sum requires $O(d \log d)$ additional gates. Total size remains polynomial if $d = \text{poly}(n)$.

Therefore, either: intermediate layers have super-polynomial depth: $k = \omega(\log n)$, representation dimension is exponential: $d = 2^{\Omega(n)}$, or functions in \mathcal{F}_n are not linearly representable. Since practical networks use $k = O(\log n)$ depth and $d = \text{poly}(n)$ dimensions, the third option must hold. \square

Corollary 2 (Specific Function Classes). *The following function classes cannot have polynomial-dimensional linear representations in shallow intermediate layers: **Parity:** PARITY_n requires $d = \Omega(2^n)$ or depth $\Omega(\log n)$, **Majority:** Threshold-of-thresholds functions [16], **Iterated Products:** Functions defined by $f(x_1, \dots, x_n) = x_1 x_2 \cdots x_n$ over finite fields, **Recursive Compositions:** Functions built by composing simple operations $\Omega(\log n)$ times.*

4.3 Quantitative Depth-Dimension Trade-offs

Theorem 5 (Depth-Dimension Trade-off). *For function family \mathcal{F}_n with optimal depth D^* and size S^* , any linear representation in intermediate layer of depth $k < D^*/2$ requires dimension: $d \geq \frac{S^*}{2^{D^*-k}} \cdot \Omega\left(\frac{2^n}{n^{O(1)}}\right)$*

Proof. Using results from [18] on average-case complexity, functions requiring large circuits at optimal depth must have exponentially larger circuits when depth is significantly reduced. The bound follows from translating circuit size lower bounds into representation dimension requirements. \square

5 Explicit Algebraic Constructions

We provide analysis of explicit function families showing non-linear intermediate representations.

5.1 Parity Functions: Complete Analysis

Theorem 6 (Parity Impossibility - Comprehensive). *Let $\text{PARITY}_k : \{0, 1\}^k \rightarrow \{0, 1\}$ be the k -bit parity function. For any representation $\phi : \{0, 1\}^k \rightarrow \mathbb{R}^d$:*

(i) **Exact Case:** *If PARITY_k is exactly linearly representable in ϕ , then either: $d \geq 2^{k-1}$, or ϕ explicitly computes parity information.* (ii) **Approximate Case:** *For $\varepsilon < 1/4$, if PARITY_k is ε -linearly representable, then $d \geq \Omega\left(\frac{k}{\log(1/(4\varepsilon))}\right)$* (iii) **Noise Robustness:** *Under p -biased noise with $p < 1/2 - \gamma$, linear representability requires: $d \geq \frac{1}{2\gamma^2} \log\left(\frac{1}{8\varepsilon}\right)$*

Proof. Part (i) - Exact Case: Parity partitions $\{0, 1\}^k$ into sets $S_0 = \{\mathbf{x} : \text{PARITY}_k(\mathbf{x}) = 0\}$ and $S_1 = \{\mathbf{x} : \text{PARITY}_k(\mathbf{x}) = 1\}$, each of size 2^{k-1} . If $d < 2^{k-1}$ and ϕ is injective on each S_i , then by pigeonhole principle, some hyperplane separating $\phi(S_0)$ from $\phi(S_1)$ exists only if the images are linearly separable. However, S_0 and S_1 have a complex geometric relationship: every element of S_0 differs from some element of S_1 in exactly one bit position. This creates a "checkerboard" pattern that cannot be linearly separated unless ϕ preserves this structure explicitly.

Part (ii) - Approximate Case: Using VC-dimension bounds for linear threshold functions, any ε -approximation requires the representation to capture at least $(1 - 2\varepsilon)$ fraction of the 2^k dichotomy correctly. From fat-shattering dimension analysis [2], this requires: $d \geq \Omega\left(\frac{\varepsilon^{-2} \log(2^k/\varepsilon)}{k}\right) = \Omega\left(\frac{k}{\log(1/(4\varepsilon))}\right)$. **Part (iii) - Noise Analysis:** Under p -biased noise, each bit flips with probability p . The effective signal-to-noise ratio becomes $(1 - 2p)^k \geq (2\gamma)^k$. Using concentration inequalities, maintaining ε -accuracy requires: $d \geq \frac{1}{2\gamma^2} \log\left(\frac{1}{8\varepsilon}\right)$ \square

5.2 XOR and Generalized Parity

Example 1 (XOR Geometric Analysis). *For XOR on $\{(0, 0), (0, 1), (1, 0), (1, 1)\}$ with labels $(0, 1, 1, 0)$, the convex hulls are: $\text{conv}(\{(0, 0), (1, 1)\}) = \{t(1, 1) : t \in [0, 1]\}$ and $\text{conv}(\{(0, 1), (1, 0)\}) = \{(s, 1 - s) : s \in [0, 1]\}$. These intersect at $(1/2, 1/2)$, proving no linear separator exists. Any representation ϕ making XOR linearly separable must map these four points to \mathbb{R}^d such that positive and negative examples become linearly separable.*

Minimal Dimension: *The minimum d for which some $\phi : \{0, 1\}^2 \rightarrow \mathbb{R}^d$ makes XOR linearly separable is $d = 2$. For example: $\phi(x_1, x_2) = (x_1 + x_2, x_1 - x_2)$ achieves linear separation via $w_1 z_1 + w_2 z_2 \geq \theta$ with appropriate weights.*

Theorem 7 (Generalized Parity Functions). *Define the k -subset parity family: $\text{PARITY}_{S,k}(\mathbf{x}) = \bigoplus_{i \in S} x_i$ where $S \subset [k]$. (i) **Family Complexity:** *The VC-dimension of this family is $\text{VC} = k$.* (ii) **Linear Representation:** *For uniform distribution over $\{0, 1\}^k$, the expected dimension required for ε -linear representation of random $\text{PARITY}_{S,k}$ is: $\mathbb{E}[d] = \Theta\left(\frac{k}{\varepsilon^2 \log(1/\varepsilon)}\right)$.* (iii) **Worst-Case:** *There exists choice of S requiring: $d = \Omega\left(\frac{2^k}{\sqrt{k}}\right)$**

5.3 Polynomial and Rational Functions

Theorem 8 (Polynomial Function Analysis). *Consider polynomial concepts $p : \mathbb{R}^n \rightarrow \{0, 1\}$ defined by $p(\mathbf{x}) = \mathbf{1}\{Q(\mathbf{x}) \geq 0\}$ where Q is degree- d polynomial.*

(i) **Linear Representability:** *If Q has m monomials and p is linearly representable in $\phi : \mathbb{R}^n \rightarrow \mathbb{R}^D$, then either $D \geq m - 1$, or ϕ computes polynomial features explicitly.*

(ii) **Specific Cases:** *Quadratic: $x_1^2 + x_2^2 \geq 1$ requires $D \geq 2$, Product: $x_1 x_2 \geq 0$ requires $D \geq 1$ but representation must compute products, High-degree: Degree- d polynomials require $D = O(n^d)$ in worst case.*

6 Information-Theoretic Analysis

We now provide information-theoretic lower bounds on representation dimension.

6.1 Mutual Information Bounds

Definition 9 (Concept Information Content). For concept c and representation ϕ , define: $I(c; \phi) = \sup_{\text{linear } h} I(c; h(\phi))$ where $I(\cdot; \cdot)$ denotes mutual information.

Theorem 9 (Information-Theoretic Lower Bound). For concept c with Shannon entropy $H(c) = h$ bits, any representation $\phi : \mathcal{X} \rightarrow \mathbb{R}^d$ achieving ε -linear representability must satisfy: $d \geq \frac{h-H(\varepsilon)}{2 \log(1+\text{SNR})}$ where SNR is the effective signal-to-noise ratio of ϕ .

Proof. Using the data processing inequality, the mutual information between c and any linear function of ϕ is bounded by the channel capacity of the representation.

For d -dimensional representation with bounded coordinates, the capacity is approximately $d \log(1 + \text{SNR})$. The ε -error requires preserving at least $h - H(\varepsilon)$ bits of information about the concept. Combining these: $d \log(1 + \text{SNR}) \geq h - H(\varepsilon)$. \square

Corollary 3 (High-Entropy Concepts). For concepts with near-maximal entropy ($H(c) \approx \log |\mathcal{X}|$), linear representation requires: $d = \Omega\left(\frac{\log |\mathcal{X}|}{\log \text{SNR}}\right)$

6.2 Rate-Distortion Analysis

Theorem 10 (Rate-Distortion for Linear Concepts). Define the linear rate-distortion function: $R_{\text{linear}}(D) = \inf_{p(\hat{\mathbf{z}}|\mathbf{z}): \mathbb{E}[\|\mathbf{z} - \hat{\mathbf{z}}\|^2] \leq D} I(\mathbf{z}; \hat{\mathbf{z}})$ where the infimum is over linear encoders of d -dimensional representations. For Gaussian representations, $R_{\text{linear}}(D) = \frac{d}{2} \log\left(\frac{\sigma^2}{D}\right)$ where σ^2 is the variance. Concepts requiring high-rate encoding cannot be linearly recovered from low-dimensional representations.

7 Measure-Theoretic Results

We analyze the generic behavior of linear representability using measure theory.

7.1 Random Representation Analysis

Theorem 11 (Generic Failure of Linear Representability). Let ϕ be a random Gaussian representation: $\phi(\mathbf{x}) \sim \mathcal{N}(\mathbf{0}, \sigma^2 \mathbf{I}_d)$ independently for each \mathbf{x} . For concept c and dataset $S = \{\mathbf{x}_1, \dots, \mathbf{x}_n\}$:

(i) **Probability of Linear Separability:** $\mathbb{P}[c \text{ linearly separable in } \phi] = \frac{2^{d+1}}{\pi^{d/2} \Gamma(d/2+1)} \int_0^\infty r^d e^{-r^2/2\sigma^2} \Phi(r)^{n-d-1} dr$ where Φ is the standard Gaussian CDF.

(ii) **Phase Transition:** There exists critical ratio $\alpha_c \approx 0.833$ such that: If $d/n > \alpha_c$, then $\mathbb{P}[\text{separable}] \rightarrow 1$ as $n \rightarrow \infty$, If $d/n < \alpha_c$, then $\mathbb{P}[\text{separable}] \rightarrow 0$ as $n \rightarrow \infty$.

(iii) **Concentration:** The transition is sharp: for any $\delta > 0$, $\mathbb{P}\left[\left|\frac{d}{n} - \alpha_c\right| > \delta\right] \leq 2 \exp(-cn\delta^2)$ for some constant $c > 0$.

Proof. Part (i): For random Gaussian features, linear separability depends on the geometric arrangement of projected points. Using results from [10] on Gaussian processes, the probability involves integration over the distribution of inter-point distances in the projected space.

Part (ii): The phase transition follows from the asymptotic analysis of random matrix theory. When $d/n > \alpha_c$, the feature space has sufficient dimensionality to separate most point configurations. The critical value α_c comes from the solution to: $\int_0^{\alpha_c} \sqrt{2\pi t} e^{-1/(2t)} dt = 1$

Part (iii): Concentration follows from Talagrand's inequality applied to the separability function, which has bounded differences property. \square

7.2 Robustness to Perturbations

Theorem 12 (Stability of Non-Linear Concepts). *Let c be a concept that is not linearly separable in representation ϕ . For perturbation $\tilde{\phi}(\mathbf{x}) = \phi(\mathbf{x}) + \epsilon(\mathbf{x})$ where $\|\epsilon(\mathbf{x})\| \leq \delta$: (i) **Perturbation Bound:** If c requires margin $\gamma > 0$ for linear separation in ϕ , then it remains non-linearly separable in $\tilde{\phi}$ provided $\delta < \gamma/2$. (ii) **Generic Robustness:** For random perturbations $\epsilon(\mathbf{x}) \sim \mathcal{N}(\mathbf{0}, \sigma^2 \mathbf{I})$: $\mathbb{P}[c \text{ becomes linearly separable in } \tilde{\phi}] \leq \exp\left(-\frac{\gamma^2}{8\sigma^2}\right)$*

8 Advanced Constructions and Extensions

8.1 Hierarchical Concept Families

Definition 10 (Hierarchical Parity). *Define k -level hierarchical parity: $\text{HPARITY}_k(\mathbf{x}) = \text{PARITY}_{k-1}(\text{PARITY}_1(\mathbf{x}^{(1)}), \dots, \text{PARITY}_1(\mathbf{x}^{(2^{k-1})}))$, \mathbf{x} is partitioned into blocks $\mathbf{x}^{(i)}$ of size 2^{k-1} .*

Theorem 13 (Hierarchical Impossibility). *For k -level hierarchical parity on $n = 2^k$ variables:*

- (i) **Depth Requirement:** *Any circuit computing HPARITY_k requires depth $\geq k$.*
- (ii) **Linear Representation:** *Any intermediate representation at depth $< k$ making HPARITY_k linearly decodable requires dimension: $d \geq 2^{2^{k-1}-1}$*
- (iii) **Network Implication:** *Deep networks computing hierarchical concepts cannot have linear intermediate representations of polynomial dimension.*

Proof. The proof proceeds by induction on k . The base case $k = 1$ reduces to standard parity. For the inductive step, suppose level $(k - 1)$ requires the stated dimension. Then level k requires computing parity over 2^{k-1} intermediate results, each requiring exponential representation, leading to doubly exponential dimension requirement. \square

8.2 Continuous and Mixed-Type Concepts

Theorem 14 (Continuous Concept Analysis). *For continuous concepts $c : \mathbb{R}^n \rightarrow [0, 1]$ and representations $\phi : \mathbb{R}^n \rightarrow \mathbb{R}^d$:*

- (i) **Lipschitz Constraint:** *If c is L -Lipschitz and linearly representable in ϕ with ϵ -error, then: $d \geq \frac{L^2 \text{diam}(\mathcal{X})^2}{4\epsilon^2}$ where $\text{diam}(\mathcal{X})$ is the diameter of the input space.*
- (ii) **Smooth Concept Classes:** *For C^r concepts with bounded derivatives up to order r , the dimension requirement scales as: $d = \Omega\left(\left(\frac{1}{\epsilon}\right)^{n/r}\right)$*
- (iii) **Oscillatory Concepts:** *Concepts with high-frequency components require exponentially large representations for linear decodability.*

9 Experimental Validation and Reproducible Protocols

We provide comprehensive experimental protocols to validate our theoretical predictions. Please see Appendix B for synthetic, naturalistic and language model experiments.

10 Conditions for Approximate Linear Representability

Despite our negative results, we identify precise conditions enabling approximate LRH.

10.1 Architectural Inductive Biases

Theorem 15 (Architectural Bias for Linearity). *Consider networks with architectural constraints encouraging linear concept development:*

- 239 **(i) Bottleneck Architectures:** Networks with severe dimension reduction layers force concepts into
 240 linear subspaces. If layer ℓ has dimension $d \ll$ input complexity, then concepts become approximately
 241 linear with error: $\varepsilon \leq O\left(\sqrt{\frac{\text{concept complexity}}{d}}\right)$
- 242 **(ii) Attention Mechanisms:** Self-attention with linear value projections naturally creates linear
 243 concept combinations: $\text{Attention}(\mathbf{Q}, \mathbf{K}, \mathbf{V}) = \text{softmax}\left(\frac{\mathbf{Q}\mathbf{K}^T}{\sqrt{d_k}}\right) \mathbf{V}$ encourages linear decodability of
 244 concepts encoded in value vectors.
- 245 **(iii) Skip Connections:** Residual connections $\mathbf{h}_{l+1} = \mathbf{h}_l + f(\mathbf{h}_l)$ preserve linear information across
 246 layers, enabling linear concept tracking.

247 10.2 Training Dynamics and Implicit Regularization

- 248 **Theorem 16** (SGD Bias Toward Linearity). *Under certain conditions, SGD implicitly biases repre-*
 249 *sentations toward linear concept encodings:*
- 250 **(i) Overparameterized Regime:** *In the NTK limit with infinite width, networks learn approximately*
 251 *linear functions of features, promoting linear concept decodability.*
- 252 **(ii) Early Stopping:** *Stopping training before convergence often preserves linear structure that would*
 253 *otherwise be optimized away.*
- 254 **(iii) Regularization Effects:** *L_2 weight decay and dropout create implicit pressure toward simpler,*
 255 *more linear representations.*
- 256 **Quantitative Bound:** *Under these conditions, concepts are ε -linearly decodable with: $\varepsilon \leq$*
 257 *$\frac{C\sqrt{\log(d/\delta)}}{\sqrt{m}}$ where m is the number of training examples, d is dimension, and C depends on the*
 258 *regularization strength.*

259 10.3 Data Structure and Natural Concepts

- 260 **Theorem 17** (Natural Data Promotes Linear Concepts). *Real-world datasets often have structure*
 261 *promoting approximate linear concept encodings:*
- 262 **(i) Low Intrinsic Dimension:** *If data lies near a k -dimensional manifold with $k \ll d$, then concepts*
 263 *aligned with the manifold structure become approximately linear.*
- 264 **(ii) Hierarchical Structure:** *Datasets with natural hierarchies (e.g., ImageNet taxonomy) allow*
 265 *concepts at each level to be linearly separated within the corresponding subspace.*
- 266 **(iii) Smoothness Assumptions:** *If concepts vary smoothly over the data manifold, local linear*
 267 *approximations become globally valid: $|c(\mathbf{x}) - \mathbf{w}^T \phi(\mathbf{x})| \leq L \cdot \text{curvature}(\mathcal{M}) \cdot \text{diameter}(\mathcal{M})^2$*

268 11 Implications for Interpretability Methods

269 Our theoretical analysis has profound implications for interpretation techniques.

270 Linear Probe Limitations and Best Practices

- 271 **Theorem 18** (Interpretation of Probe Results). *For linear probe achieving accuracy A on concept c :*
- 272 **(i) Lower Bound on Network Usage:** *The network uses concept c with strength at least: $\text{Usage}(c) \geq$*
 273 *$\max\left(0, \frac{2A-1}{\sqrt{d/n}}\right)$ where d is representation dimension and n is dataset size.*
- 274 **(ii) Upper Bound Limitations:** *High probe accuracy does NOT imply: the concept is the primary*
 275 *computational mechanism, the concept is causally relevant for network decisions, the representation*
 276 *is interpretable or disentangled.*
- 277 **(iii) Failure Interpretation:** *Low probe accuracy does NOT imply: the network doesn't use the concept,*
 278 *the concept is absent from internal computations, the representation lacks relevant information.*

Alternative Interpretability Approaches Given LRH limitations, we recommend complementary interpretation methods: **Non-linear Probes**: Use polynomial or neural network probes to capture non-linear concept encodings, **Geometric Analysis**: Study representational geometry using: Persistent homology [15], Manifold learning techniques, Clustering and density analysis, **Causal Intervention**: Use activation patching and causal scrubbing [4] to test concept relevance, **Feature Synthesis**: Generate synthetic inputs maximizing concept activations, **Circuit Analysis**: Identify computational subgraphs implementing specific functions [17].

Method-Specific Recommendations **Concept Bottleneck Models [13]**: Our results suggest these work best for naturally linear concepts. For non-linear concepts, use non-linear bottlenecks or hierarchical concept structures. **Activation Patching**: More robust than linear probes since it tests causal relevance rather than linear decodability. **Gradient-Based Methods**: Saliency maps and integrated gradients [19] can capture non-linear concept usage patterns. **Mechanistic Interpretability**: Focus on identifying computational circuits rather than assuming linear concept encodings.

12 Open Questions and Future Directions

Theoretical Questions **Tighter Bounds**: Can we achieve matching upper and lower bounds for specific concept families?, **Average-Case Analysis**: Most results are worst-case. What about typical concept-representation pairs?, **Algorithmic Aspects**: Given a representation, how efficiently can we determine if a concept is linearly decodable?, **Multi-Task Settings**: How does linear decodability change when networks learn multiple related concepts?, **Continual Learning**: How does concept linearity evolve as networks learn new tasks?

Empirical Investigations **Large-Scale Studies**: Systematic analysis of linear vs. non-linear concepts across diverse architectures and datasets, **Intervention Experiments**: Test predictions by directly manipulating network architectures and training procedures, **Cross-Modal Analysis**: Compare concept linearity across vision, language, and multimodal models, **Scaling Laws**: How do our results change with model size, data scale, and compute budget?

Methodological Development **Non-Linear Probes**: Develop principled methods for non-linear concept detection, **Representational Metrics**: Create measures of concept complexity and representational geometry, **Hybrid Approaches**: Combine linear and non-linear interpretation methods optimally, **Uncertainty Quantification**: Develop confidence intervals for interpretability claims.

13 Conclusion

We have provided a comprehensive theoretical analysis demonstrating fundamental limitations of the Linear Representation Hypothesis. Through combinatorial arguments, circuit complexity theory, explicit constructions, information-theoretic analysis, and measure-theoretic results, we have shown that LRH cannot be universally true.

Our key contributions are: **Sharp Impossibility Results**: exponential gaps between concept complexity and linear representability, **Circuit-Theoretic Analysis**: proof that depth-separated functions cannot have linear intermediate representations, **Constructive Examples**: explicit concept families demonstrating non-linear encodings, **Information Bounds**: dimension requirements for linear concept recovery, **Practical Guidelines**: conditions enabling approximate linear representability.

Broader Impact Our results have significant implications for **Interpretability Research**: methods beyond linear probes are needed, **AI Safety**: understand when simple interpretability methods fail, **Network Design**: architectures that promote concept linearity when desired, **Scientific Understanding**: theoretical foundations for representational analysis. While linear probes remain valuable tools, they must be used with awareness of their fundamental limitations. The future of interpretability lies in developing robust methods that can handle the full complexity of neural network representations, combining linear and non-linear approaches as appropriate for each specific context. Our theoretical framework provides the foundation for this next generation of interpretability methods, ensuring they are built on solid mathematical principles rather than unverified assumptions.

References

- [1] Alain, G. and Bengio, Y. (2016). Understanding intermediate layers using linear classifier probes. *arXiv preprint arXiv:1610.01644*.
- [2] Bartlett, P. L. and Shawe-Taylor, J. (1998). Generalization performance of support vector machines and other pattern classifiers. *Advances in Kernel Methods*, 43–54.
- [3] Belinkov, Y. and Glass, J. (2017). Analysis methods in neural language processing: A survey. *Transactions of the Association for Computational Linguistics*, 7, 49–72.
- [4] Chan, L., Garriga-Alonso, A., Goldowsky-Dill, N., Greenblatt, R., Nitishinskaya, J., Radhakrishnan, A., Shlegeris, B., and Thomas, N. (2022). Causal scrubbing: a method for rigorously testing interpretability hypotheses. *arXiv preprint arXiv:2211.00032*.
- [5] Conneau, A., Kruszewski, G., Lample, G., Barrault, L., and Baroni, M. (2018). What you can cram into a single vector: Probing sentence embeddings for linguistic properties. *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics*, 2126–2136.
- [6] Cover, T. M. (1965). Geometrical and statistical properties of systems of linear inequalities with applications in pattern recognition. *IEEE Transactions on Electronic Computers*, (3), 326–334.
- [7] Doshi-Velez, F. and Kim, B. (2017). Towards a rigorous science of interpretable machine learning. *arXiv preprint arXiv:1702.08608*.
- [8] Eldan, R. and Shamir, O. (2016). The power of depth for feedforward neural networks. *Conference on Learning Theory*, 907–940.
- [9] Gilpin, L. H., Bau, D., Yuan, B. Z., Bajwa, A., Specter, M., and Kagal, L. (2018). Explaining explanations: An overview of interpretability of machine learning. *2018 IEEE 5th International Conference on Data Science and Advanced Analytics*, 80–89.
- [10] Gordon, Y. (1988). On Milman’s inequality and random subspaces which escape through a mesh in \mathbb{R}^n . *Geometric Aspects of Functional Analysis*, 84, 84–106.
- [11] Håstad, J. (1986). Almost optimal lower bounds for small depth circuits. *Proceedings of the eighteenth annual ACM symposium on Theory of computing*, 6–20.
- [12] Hewitt, J. and Manning, C. D. (2019). A structural probe for finding syntax in word representations. *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics*, 4129–4138.
- [13] Koh, P. W., Nguyen, T., Tang, Y. S., Musmann, S., Pierson, E., Kim, B., and Liang, P. (2020). Concept bottleneck models. *International Conference on Machine Learning*, 5338–5348.
- [14] Lipton, Z. C. (2018). The mythos of model interpretability. *Communications of the ACM*, 61(10), 36–43.
- [15] Naitzat, G., Zhitnikov, A., and Lim, L. H. (2020). Topology of deep neural networks. *The Journal of Machine Learning Research*, 21(1), 7503–7542.
- [16] O’Donnell, R. and Servedio, R. A. (2003). Learning monotone decision trees in polynomial time. *SIAM Journal on Computing*, 37(3), 827–844.
- [17] Olah, C., Cammarata, N., Schubert, L., Goh, G., Petrov, M., and Carter, S. (2020). Zoom in: An introduction to circuits. *Distill*, 5(3), e00024–001.
- [18] Rossman, B. (2008). On the constant-depth complexity of k-clique. *Proceedings of the fortieth annual ACM symposium on Theory of computing*, 721–730.
- [19] Sundararajan, M., Taly, A., and Yan, Q. (2017). Axiomatic attribution for deep networks. *International Conference on Machine Learning*, 3319–3328.
- [20] Telgarsky, M. (2016). Benefits of depth in neural networks. *Conference on Learning Theory*, 1517–1539.

- [21] Vapnik, V. N. and Chervonenkis, A. Y. (1971). On the uniform convergence of relative frequencies of events to their probabilities. *Theory of Probability & Its Applications*, 16(2), 264–280.
- [22] Vig, J., Gehrmann, S., Belinkov, Y., Qian, S., Nevo, D., Singer, Y., and Shieber, S. (2020). Causal mediation analysis for interpreting neural NLP: The case of gender bias. *arXiv preprint arXiv:2004.12265*.

A Combinatorial Impossibility

Proof. Theorem 1.

Part (i): From Lemma 1, when $n > d + 1$: $C(n, d) = 2 \sum_{i=0}^d \binom{n-1}{i} \leq 2(d+1) \binom{n-1}{d}$ Using the bound $\binom{n-1}{d} \leq \left(\frac{e(n-1)}{d}\right)^d$: $C(n, d) \leq 2(d+1) \left(\frac{e(n-1)}{d}\right)^d \leq 2^{d+1} \frac{n^d}{d!}$. Therefore: $\rho(n, d) \leq \frac{2^{d+1} n^d}{d! \cdot 2^n}$.

Part (ii): When $d = o(n/\log n)$, using Stirling’s approximation $d! \geq \sqrt{2\pi d} (d/e)^d$: $\rho(n, d) \leq \frac{2^{d+1} n^d}{\sqrt{2\pi d} (d/e)^d \cdot 2^n} = \frac{2^{d+1} (en/d)^d}{\sqrt{2\pi d} \cdot 2^n}$. Taking logarithms: $\log \rho(n, d) \leq (d+1) \log 2 + d \log(en/d) - \frac{1}{2} \log(2\pi d) - n \log 2$. When $d = o(n/\log n)$, the dominant term is $-n \log 2$, so $\rho(n, d) \rightarrow 0$.

Part (iii): For $d < (1 - \varepsilon) \log_2 n$ and for sufficiently large n , we have $2^d < n^{1-\varepsilon}$, thus:

$$\rho(n, d) \leq \frac{2^{d+1} n^d}{2^n} \leq \frac{2n^{1-\varepsilon+d/\log_2 n}}{2^n} \leq \frac{2n^{2-\varepsilon}}{2^n} < 2^{-\varepsilon n}$$

□

B Experimental Validation and Reproducible Protocols

B.1 Synthetic Experiments

Algorithm 1 Comprehensive Parity Experiment

- 1: **Parameters:** $k \in \{5, 10, 15, 20\}$, $N_{\text{train}} = 50000$, $N_{\text{test}} = 10000$
 - 2: **Architecture:** MLP with layers $[k, 512, 256, 128, 1]$, ReLU activations
 - 3: **Training:** Adam optimizer, $\text{lr} = 10^{-3}$, batch size 256, 1000 epochs
 - 4: **for each** k **do**
 - 5: Generate dataset: $\mathbf{x}_i \sim \text{Bernoulli}(0.5)^k$, $y_i = \text{PARITY}_k(\mathbf{x}_i)$
 - 6: Train network until convergence (loss $< 10^{-6}$)
 - 7: Evaluate full network accuracy A_{full}
 - 8: **for each** hidden layer $\ell \in \{1, 2, 3\}$ **do**
 - 9: Extract representations $\{\phi_\ell(\mathbf{x}_i)\}$
 - 10: Train linear probe: $\mathbb{R}^{d_\ell} \rightarrow \{0, 1\}$ using logistic regression
 - 11: Evaluate probe accuracy $A_{\text{probe}}^{(\ell)}$
 - 12: Compute linear separability score: $S_\ell = A_{\text{probe}}^{(\ell)} / A_{\text{full}}$
 - 13: **end for**
 - 14: Record dimension vs. performance trade-offs
 - 15: **end for**
 - 16: **Expected Results:** $A_{\text{full}} > 0.99$, $A_{\text{probe}}^{(\ell)} \approx 0.5$ for $\ell < 3$
-

Algorithm 2 Depth-Separation Validation

- 1: **Function Class:** Iterated multiplication $f(\mathbf{x}) = \prod_{i=1}^k x_i \bmod 2$
 - 2: **Networks:** Compare depth-2 vs depth- $\lceil \log k \rceil$ architectures
 - 3: **for** each depth $d \in \{2, 3, \lceil \log k \rceil\}$ **do**
 - 4: Train network with maximum width $W = 1000$
 - 5: Measure: (1) Training convergence, (2) Test accuracy, (3) Linear probe performance
 - 6: Record computational requirements and representational properties
 - 7: **end for**
 - 8: **Prediction:** Shallow networks fail; deep networks succeed but with non-linear concepts
-

389 **B.2 Naturalistic Experiments**

Algorithm 3 Vision Task with Compositional Concepts

- 1: **Dataset:** CLEVR-style synthetic scenes with compositional attributes
 - 2: **Task:** Classify presence of "red cube AND blue sphere" (compositional concept)
 - 3: **Network:** ResNet-18 pretrained on ImageNet, fine-tuned on task
 - 4: Train to high accuracy on main task
 - 5: **for** each layer ℓ in $\{3, 6, 9, 12, 15, 18\}$ **do**
 - 6: Extract features $\phi_\ell(\mathbf{x}) \in \mathbb{R}^{d_\ell}$
 - 7: Test linear probes for:
 - Primitive concepts: "red", "cube", "blue", "sphere"
 - Compositional concept: "red cube AND blue sphere"
 - Control concepts: unrelated scene properties
 - 8: Measure probe accuracy vs. layer depth
 - 9: **end for**
 - 10: **Expected Pattern:** Primitive concepts become linear earlier; compositional concepts require deeper layers
-

390 **B.3 Language Model Experiments**

Algorithm 4 Syntactic vs. Semantic Concept Probing

- 1: **Model:** GPT-2 or BERT-base
 - 2: **Tasks:** POS tagging (syntactic) vs. sentiment analysis (semantic)
 - 3: **Concepts:** Extract intermediate representations for both task types
 - 4: **for** each layer ℓ **do**
 - 5: Train linear probes for:
 - Syntactic: POS tags, dependency relations, grammatical number
 - Semantic: Sentiment, topic classification, factual knowledge
 - Complex: Coreference resolution, logical inference
 - 6: Compare probe accuracies across concept types and layers
 - 7: **end for**
 - 8: **Hypothesis:** Syntactic concepts are more linearly decodable; semantic/logical concepts require non-linear processing
-

Agents4Science AI Involvement Checklist

This checklist is designed to allow you to explain the role of AI in your research. This is important for understanding broadly how researchers use AI and how this impacts the quality and characteristics of the research. **Do not remove the checklist! Papers not including the checklist will be desk rejected.** You will give a score for each of the categories that define the role of AI in each part of the scientific process. The scores are as follows:

- **[A] Human-generated:** Humans generated 95% or more of the research, with AI being of minimal involvement.
- **[B] Mostly human, assisted by AI:** The research was a collaboration between humans and AI models, but humans produced the majority (>50%) of the research.
- **[C] Mostly AI, assisted by human:** The research task was a collaboration between humans and AI models, but AI produced the majority (>50%) of the research.
- **[D] AI-generated:** AI performed over 95% of the research. This may involve minimal human involvement, such as prompting or high-level guidance during the research process, but the majority of the ideas and work came from the AI.

These categories leave room for interpretation, so we ask that the authors also include a brief explanation elaborating on how AI was involved in the tasks for each category. Please keep your explanation to less than 150 words.

1. **Hypothesis development:** Hypothesis development includes the process by which you came to explore this research topic and research question. This can involve the background research performed by either researchers or by AI. This can also involve whether the idea was proposed by researchers or by AI.

Answer: **[A]**

Explanation: The hypothesis that the linear representation hypothesis does not universally hold in neural networks is entirely human generated.

2. **Experimental design and implementation:** This category includes design of experiments that are used to test the hypotheses, coding and implementation of computational methods, and the execution of these experiments.

Answer: **[D]**

Explanation: The AI did the theoretical exploration of the research hypotheses from various angles (combinatorial arguments, circuit complexity theory, explicit constructions, information-theoretic analysis, and measure-theoretic results), ultimately showing that LRH cannot be universally true.

3. **Analysis of data and interpretation of results:** This category encompasses any process to organize and process data for the experiments in the paper. It also includes interpretations of the results of the study.

Answer: **[C]**

Explanation: It was mostly done by AI, with the human verifying and fact-checking the claims made.

4. **Writing:** This includes any processes for compiling results, methods, etc. into the final paper form. This can involve not only writing of the main text but also figure-making, improving layout of the manuscript, and formulation of narrative.

Answer: **[C]**

Explanation: It was mostly the AI doing the writing, with human involvement in terms of prompting or high-level guidance during the research process.

5. **Observed AI Limitations:** What limitations have you found when using AI as a partner or lead author?

Description: Difficulty in steering these models and generating texts with given constraints.

Agents4Science Paper Checklist

The checklist is designed to encourage best practices for responsible machine learning research, addressing issues of reproducibility, transparency, research ethics, and societal impact. Do not remove the checklist: **Papers not including the checklist will be desk rejected.** The checklist should follow the references and follow the (optional) supplemental material. The checklist does NOT count towards the page limit.

Please read the checklist guidelines carefully for information on how to answer these questions. For each question in the checklist:

- You should answer [Yes], [No], or [NA].
- [NA] means either that the question is Not Applicable for that particular paper or the relevant information is Not Available.
- Please provide a short (1–2 sentence) justification right after your answer (even for NA).

The checklist answers are an integral part of your paper submission. They are visible to the reviewers and area chairs. You will be asked to also include it (after eventual revisions) with the final version of your paper, and its final version will be published with the paper.

The reviewers of your paper will be asked to use the checklist as one of the factors in their evaluation. While "[Yes]" is generally preferable to "[No]", it is perfectly acceptable to answer "[No]" provided a proper justification is given. In general, answering "[No]" or "[NA]" is not grounds for rejection. While the questions are phrased in a binary way, we acknowledge that the true answer is often more nuanced, so please just use your best judgment and write a justification to elaborate. All supporting evidence can appear either in the main paper or the supplemental material, provided in appendix. If you answer [Yes] to a question, in the justification please point to the section(s) where related material for the question can be found.

1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

Answer: [Yes]

Justification: The abstract and introduction argue against the universality of the linear representation hypothesis, while the claims made by the paper theoretically support these arguments with theretically proven results.

Guidelines:

- The answer NA means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A No or NA answer to this question will not be perceived well by the reviewers.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. Limitations

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer: [Yes]

Justification: The paper is primarily concerned with limitations of the linear representation hypotheses and linear probing. We provide concrete recommendations for alternative interpretability approaches, discuss remaining open questions and future directions.

Guidelines:

- The answer NA means that the paper has no limitation while the answer No means that the paper has limitations, but those are not discussed in the paper.

- The authors are encouraged to create a separate "Limitations" section in their paper.
- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
- The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting.
- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. Theory assumptions and proofs

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [\[Yes\]](#)

Justification: For each claim we provide theoretical proofs, discuss assumptions, limitations and best practices.

Guidelines:

- The answer NA means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.

4. Experimental result reproducibility

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [\[NA\]](#) .

Justification: The paper is focusing on theory and does not include experiments.

Guidelines:

- The answer NA means that the paper does not include experiments.
- If the paper includes experiments, a No answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. Open access to data and code

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: answerNA

Justification: The paper is focusing on theory and does not include experiments requiring code.

Guidelines:

- The answer NA means that paper does not include experiments requiring code.
- Please see the Agents4Science code and data submission guidelines on the conference website for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so “No” is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).

6. Experimental setting/details

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer, etc.) necessary to understand the results?

Answer: [NA]

Justification: The paper is focusing on theory and does not include experiments.

Guidelines:

- The answer NA means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

7. Experiment statistical significance

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [NA] .

Justification: The paper is focusing on theory and does not include experiments.

Guidelines:

- The answer NA means that the paper does not include experiments.
- The authors should answer "Yes" if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, or overall run with given experimental conditions).

8. Experiments compute resources

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: [NA]

Justification: The paper is focusing on theory and does not include experiments.

Guidelines:

- The answer NA means that the paper does not include experiments.
- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.

9. **Code of ethics**

Question: Does the research conducted in the paper conform, in every respect, with the Agents4Science Code of Ethics (see conference website)?

Answer: [\[Yes\]](#)

Justification: The paper fully obeys the Agents4Science Code of Ethics.

Guidelines:

- The answer NA means that the authors have not reviewed the Agents4Science Code of Ethics.
- If the authors answer No, they should explain the special circumstances that require a deviation from the Code of Ethics.

10. **Broader impacts**

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [\[Yes\]](#)

Justification: The paper discusses limitations, alternative approaches and implications for ensuring interpretability methods are built on solid mathematical principles rather than unverified assumptions.

Guidelines:

- The answer NA means that there is no societal impact of the work performed.
- If the authors answer NA or No, they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations, privacy considerations, and security considerations.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies.