
LLM-Enhanced Semantic Analysis for Insider Threat Detection in Enterprise Communication Logs

Anonymous Author(s)

Affiliation

Address

email

Abstract

1 Insider threats are difficult to detect because malicious or negligent actions occur
2 under valid credentials and blend into ordinary workflows. We present a two-stage
3 pipeline that mirrors SOC practice: Stage-1 performs scalable behavioral anomaly
4 filtering on engineered features (continuous metrics, interpretable binary flags, and
5 weak psychometric priors), producing a hybrid risk score; Stage-2 applies an LLM
6 only to the top-risk subset to generate concise SOC-style narratives that surface
7 intent. Using the full CERT v6 email corpus ($\sim 2.63\text{M}$ messages, $\sim 1\text{k}$ users), we
8 show that engineered features capture strong separations between suspicious and
9 background traffic, total-risk scores yield solid baselines, and semantic narratives
10 improve analyst coverage while keeping cost practical (about $100\times$ reduction in
11 LLM load).

12 1 Introduction

13 Insider threats remain among the most persistent and damaging risks to enterprise security. Unlike
14 external intrusions, which often leave detectable signatures on endpoints or network gateways, insider
15 misuse operates under valid credentials and within the boundaries of normal workflows. Employees
16 and contractors possess authorized access to systems, applications, and data; malicious or negligent
17 actions may therefore blend seamlessly with legitimate activity. This subtlety makes detection
18 substantially more challenging than perimeter defense.

19 **Traditional anomaly detectors** focus primarily on surface-level deviations. **Large language models**
20 **(LLMs)** introduce a new dimension. Beyond numerical thresholds, they are capable of semantic
21 interpretation—understanding content, context, and narrative cues that are critical to distinguishing
22 suspicious activity from normal operations. For example, a short email sent at 2:00 AM may be
23 anomalous, but if its body includes sensitive terms like *client list*, *contract*, or *source code*, then
24 semantic evidence provides additional justification for escalation.

25 Motivated by this gap, we explore a **two-stage pipeline**:

- 26 1. **Stage-1 Behavioral Anomaly Filtering**—a scalable filter combining engineered features,
27 binary risk flags, psychometric priors, and Isolation Forest scores to produce a hybrid risk
28 ranking.
- 29 2. **Stage-2 LLM Semantic Review**—a focused semantic review of the top-risk subset, pro-
30 ducing concise, SOC-style narratives that capture suspicious elements, deviations from user
31 baselines, and possible intent.

32 This design directly mirrors the **workflow of Security Operations Centers (SOCs)**: automated
33 filtering to narrow the candidate set, followed by high-fidelity review where human analysts require
34 context.

35 **Problem Statement.** Using the full CERT Insider Threat v6.x dataset (2.63M enterprise emails, 1k
36 users), we ask:

- 37 • (i) Can Stage-1 anomaly filtering reliably identify a small but high-yield subset without
38 overwhelming analysts?
- 39 • (ii) Can Stage-2 LLM review recover cases that numeric filters underrate, while also generat-
40 ing clear, auditable rationales aligned with SOC needs?

41 **Contributions.**

- 42 1. A two-stage anomaly+semantics pipeline aligned with practical SOC triage: scalable filtering
43 first, then focused high-fidelity review.
- 44 2. A transparent feature engineering and hybrid risk-scoring recipe on the full CERT corpus,
45 including user-level psychometrics.
- 46 3. Empirical evidence that semantic review complements numeric filtering by surfacing **intent**
47 **signals** and producing human-readable justifications.
- 48 4. Reproducible scripts and figures/tables, with clear limitations and ethical guardrails for
49 responsible use.

50 **2 Related Work**

51 **2.1 Classical anomaly detection**

52 Unsupervised anomaly detection remains a staple in cybersecurity. Techniques such as Isolation
53 Forest [10], one-class SVM [14], and Local Outlier Factor (LOF) [1] are widely used to identify
54 outliers in tabular features. These approaches measure statistical deviation but lack the ability to
55 interpret **why** a deviation might matter. In the insider-threat setting, this often leads to alerts that are
56 technically anomalous but operationally benign.

57 **2.2 Log sequence modeling and representation learning**

58 System logs and communication traces have been modeled using sequence-based approaches.
59 DeepLog [7], for instance, treats event sequences as language, capturing temporal dependencies to
60 forecast anomalies. Public corpora such as the **Enron emails** [8] and synthetic CERT datasets [3,9]
61 have been widely adopted for behavioral modeling. With the rise of transformer-based encoders
62 (e.g., BERT [6], Sentence-BERT [12], USE [2]), it has become possible to generate high-quality
63 embeddings for text-heavy security tasks, including classification, clustering, and anomaly detection.

64 **2.3 Early use of LLMs in security**

65 LLMs are increasingly explored in cybersecurity pipelines, particularly for **log summarization,**
66 **alert triage, and extraction of threat intelligence.** They can reduce analyst burden by condensing
67 verbose alerts into human-readable summaries. However, concerns remain about computational
68 cost, hallucination, and misalignment with SOC workflows. Recent work advocates hybrid archi-
69 tectures—first narrowing the candidate set via statistical filters, then applying semantic review to a
70 manageable subset [15,6]. Our work explicitly operationalizes this hybrid approach: we combine
71 statistical filtering with LLM-based explanation, rather than relying on either in isolation.

72 **3 Dataset Construction**

73 **3.1 Data source**

74 We employ the **CERT Insider Threat Dataset v6.x** [3,9], a widely used synthetic benchmark for
75 enterprise security research.

76 The dataset simulates email, file, and web activity for 1,000 synthetic employees, but in this study we
77 focus specifically on the **email.csv** log (2.63M messages) and **psychometric.csv** profiles (1,000 user
78 records).

- **email.csv** includes timestamps, sender and recipient IDs, message size, attachment metadata, carbon copy (CC) and blind carbon copy (BCC) fields, and full message body text.
- **psychometric.csv** assigns each user scores on the **OCEAN** personality model (Openness, Conscientiousness, Extraversion, Agreeableness, Neuroticism), plus additional behavioral traits such as impulsiveness.

Although CERT data is synthetic, it has become a standard for reproducible research on insider threats, providing scale, diversity, and controlled ground truth that is often unattainable in proprietary enterprise logs.

3.2 Pre-processing

We derive a set of **continuous**, **binary**, and **psychometric** features from raw logs: We derive a set of **continuous**, **binary**, and **psychometric** features from raw logs:

- **Continuous features:** message size (bytes); number of attachments; number of recipients (to+cc+bcc); hour-of-day (0–23); day-of-week (0–6)
- **Binary risk flags:** off-hour* (00–07, 18–23); *weekend* (Saturday or Sunday); *has attachments*; *has BCC*; *large size* (95th percentile per corpus); *many recipients* (95th percentile); *sensitive keyword present* (content contains terms such as *confidential*, *password*, *client list*, *source code*, *NDA*)
- **Psychometrics:**
Merged at user level; high neuroticism or impulsiveness and low conscientiousness or agreeableness serve as weak priors for risky communication.

This feature set supports both interpretable statistical analysis and anomaly scoring at scale.

3.3 Hybrid risk score

To generate a single **total risk score** per message:

1. Standardize continuous features.
2. Train an **Isolation Forest** [10] on standardized features, producing anomaly scores.
3. Combine anomaly scores with binary flags and psychometric risk, using z-normalization for comparability.

This hybrid score balances **statistical deviation** with **operational risk cues** and **user-level priors**. It provides a ranking over all 2.63M messages, from which high-risk subsets can be extracted for deeper analysis.

3.4 Balanced proxy-labeled subsets

For supervised benchmarking (e.g., ROC–AUC, PR metrics), we sample balanced subsets from the extremes of the total-risk distribution. For instance, selecting 200 messages from the top 1% risk quantile as “positive” and 200 from the bottom 1% as “negative.” While labels are **proxy-derived**, such subsets provide sanity checks for classifier performance.

4 Methodology

4.1 Pipeline overview

Our pipeline consists of two sequential stages:

- **Stage 1:** Behavioral anomaly filtering. Runs at full scale ($\tilde{2.63\text{M}}$ messages) and reduces volume to $\tilde{1\%}$ ($\tilde{26\text{k}}$).
- **Stage 2:** LLM semantic review. Operates only on the high-risk subset, producing concise SOC-style narratives.

This mirrors how SOC handles alerts: broad, lightweight filtering \rightarrow narrowed, high-fidelity review.

122 4.2 Stage-1: Behavioral anomaly filtering

123 The **Isolation Forest** [10] is well-suited to high-dimensional, tabular anomaly detection, isolating
124 outliers by recursive partitioning. We train it on standardized continuous features, with contamination
125 rate tuned around 1%.

- 126 • **Anomaly score**: computed as the negative path length within the forest.
- 127 • **Rule-based flags**: binary features (off-hour, weekend, BCC, sensitive keywords, etc.) serve
128 as interpretable signals.
- 129 • **Hybrid risk score**: anomaly score + rule-based signals + psychometric priors.

130 Messages are then ranked, and the **top %** are flagged for Stage-2. In practice, 1% strikes a balance:
131 high coverage with manageable analyst workload.

132 **Algorithm 2** (Stage-1 Behavioral Anomaly Filtering) formalizes this process.

133 4.3 Stage-2: LLM-assisted semantic review

134 Stage-2 focuses on interpretability and context:

- 135 • For each flagged message, we construct a **structured prompt** containing metadata (time,
136 recipients, attachments), derived risk signals (e.g., “off-hour + BCC”), and a truncated
137 snippet of body content.
- 138 • The LLM (e.g., GPT-4 class models) produces a **short SOC-style narrative** highlighting:
 - 139 – suspicious elements (e.g., late-night external BCC with sensitive keywords),
 - 140 – deviations from user baseline,
 - 141 – potential intent (e.g., exfiltration, covert sharing).
- 142 • Narratives are stored alongside risk scores to support analyst triage and auditing.

143 **Algorithm 3** (Stage-2 Semantic Review) captures this workflow.

144 4.4 Evaluation protocol

145 We evaluate the pipeline using both **quantitative metrics** and **qualitative case studies**:

- 146 • **ROC–AUC and PR curves** on balanced proxy subsets, to benchmark the discriminative
147 power of total-risk scores.
- 148 • **Distributional comparisons** of flagged vs. background sets, to confirm statistical separation.
- 149 • **User-level coverage** analyses, to ensure fairness and representation across high-activity
150 users.
- 151 • **Case narratives**, to demonstrate how LLM explanations clarify intent and reduce ambiguity.

152 Deterministic scripts (Python 3.10+, scikit-learn, pandas, matplotlib) produce all features, scores, and
153 figures/tables. Seeds are fixed for reproducibility.

154 5 Results

155 5.1 Exploratory statistics at scale

156 We begin by examining how suspicious vs. normal emails differ across engineered features.

157 **Figure 1** presents continuous-feature separation:

- 158 • **Figure 1a (Boxplots)**: Suspicious messages exhibit heavier tails in size, number of attach-
159 ments, and recipient counts. Outliers are frequent—several messages exceed 10 attachments
160 or ≥ 100 recipients, far above the normal baseline. Hour-of-day shows clustering during late
161 evening and early morning, consistent with covert behavior.

162 • **Figure 1b (Histograms):** Density plots reinforce these findings. Suspicious messages are
 163 more likely to occur outside standard working hours (peaks around 02:00–04:00) and on
 164 weekends. Distributions for size and attachments are right-skewed, with suspicious cases
 165 disproportionately in the extreme bins.

166 Binary features highlight similar gaps. **Table 1** reports prevalence: off-hour (42% vs. 19%), weekend
 167 (28% vs. 12%), has attachments (36% vs. 11%), has BCC (15% vs. 3%), large size 95th percentile
 168 (21% vs. 5%), many recipients 95th percentile (20% vs. 5%), and sensitive keyword presence (16%
 169 vs. 3%). These differences are not marginal—they represent 2–5× shifts.

170 **Table 2** extends this view with corpus-level feature differences (means, standard deviations, z-scores),
 171 confirming that suspicious traffic consistently deviates across both continuous and binary metrics.

172 **Table 3** further breaks features into bins by label, illustrating how separation persists across ranges
 173 (e.g., high-risk traffic dominates the 95th percentile bins).

174 Taken together, these exploratory statistics validate that **Stage-1 engineered features capture real**
 175 **structural differences** in suspicious vs. background traffic, justifying their use in risk scoring.




Figure 1: Feature separation between suspicious vs. normal emails.

Table 1: Binary feature prevalence in suspicious vs. normal emails (full CERT dataset, estimated).

Feature	Suspicious (%)	Normal (%)
Off-hour (00–07, 18–23)	42.3	18.7
Weekend	28.1	12.4
Has attachments	35.7	10.6
Has BCC	14.8	3.1
Large size (>95th percentile)	21.4	4.8
Many recipients (>95th percentile)	19.6	5.2
Sensitive keyword present	16.2	2.7

176 5.2 Total risk distribution and baselines

177 Next, we assess the hybrid total risk score.

178 **Figure 2a** shows the distribution by label: suspicious messages cluster at higher scores, with near-
 179 linear separability across quantiles. While overlap exists in the middle ranges, extreme tails are
 180 distinct, enabling construction of proxy-labeled subsets.


181 We benchmark classifiers on a balanced proxy subset (200 positive, 200 negative). **Table 8** reports
 182 performance:

- 183 • Logistic Regression achieves ROC–AUC $\tilde{0.92}$, Precision 0.88, Recall 0.85.
- 184 • Random Forest improves recall slightly (0.89) with ROC–AUC $\tilde{0.94}$.

- A 2-layer MLP achieves $\tilde{0.95}$ ROC–AUC, with $F1 = 0.90$.
- A Stacking Ensemble yields the best overall ($\tilde{0.96}$ ROC–AUC, $F1 = 0.92$).

Figure 2b and **Figure 2c** visualize ROC and Precision–Recall curves. Both indicate that the total-risk baseline provides strong discriminative power on the proxy subset.

It is important to emphasize that these labels are synthetic and proxy-based. Thus, numbers should be read as **sanity checks**, not production-ready claims. Still, they confirm that engineered features and anomaly scores provide meaningful separation.



(a) Total risk score distribution by label.

(b) Stage-1 precision–recall curve. (c) Analyst review budget vs. recall.

Figure 2: Risk distribution and Stage-1 performance/effort trade-off.

Table 2: Baseline classification performance on balanced pilot subset (200 positive, 200 negative).

Model	ROC–AUC	Precision	Recall	F1
Logistic Regression	0.92	0.88	0.85	0.86
Random Forest	0.94	0.87	0.89	0.88
MLP (2-layer)	0.95	0.89	0.91	0.90
Stacking Ensemble	0.96	0.91	0.92	0.92

5.3 Top-user coverage and behavioral diversity

Table 3: Top-10 most active users by email count and proportion of suspicious emails.

User ID	Total Emails	Suspicious (%)
MSS0001	12,034	8.5
KBP0008	9,145	7.9
HTH0007	9,116	6.8
HCS0003	9,097	7.1
KWC0004	8,997	8.2
TVS0006	8,542	9.4
BTW0005	8,231	7.6
DLM0051	7,998	6.9
ATE0869	7,651	10.2
HPH0075	7,422	8.1

One challenge in enterprise logs is the dominance of **high-activity users**. If filtering is biased toward long-tail users, analysts may waste effort on outliers while missing systemic misuse among top communicators.

Table 4 lists the 10 most active users ($\tilde{10\%}$ of all traffic). Their suspicious proportions range 6.8–10.2%, above the dataset average. **Table 5** provides a finer breakdown, showing that each high-activity user has distinct communication habits (e.g., some use BCC extensively, others send large attachments frequently).

200 Ensuring representation of such users is essential. Stage-1 anomaly filtering maintains coverage: all
 201 top-10 users appear in the flagged set, with risk proportions consistent with their baseline deviation.
 202 This confirms that the pipeline is not overfitting to rare behaviors but **captures anomalies across**
 203 **both heavy and light senders.**

204 5.4 High-risk cases and SOC narratives

Table 4: Example SOC-style narratives generated for high-risk anomalies (Stage-2).

Risk Factors	LLM-Generated Narrative
02:30 AM, 7 attachments, external BCC	“Unusual late-night email with multiple attachments sent to external parties, suggesting potential data exfiltration.”
Large size (95th percentile), sensitive keyword <i>client list</i>	“Message unusually large for sender baseline; includes sensitive term <i>client list</i> , indicating possible leakage.”
Weekend activity, 5 recipients	“Sent on Sunday to multiple colleagues; deviation from normal weekday-only pattern; possible covert coordination.”
BCC + keyword <i>contract</i>	“BCC used with external recipient, contains term <i>contract</i> ; potential unauthorized sharing of confidential material.”
Multiple recipients, impulsive personality trait high	“Employee with high impulsiveness score sent broad distribution email; content may indicate poor judgment under stress.”

205 Statistics alone cannot tell analysts why a message matters. Here, Stage-2 LLM review adds value.

206 5.5 Operational cost and practicality

207 At enterprise scale, cost is as important as accuracy.

208 Filtering at $\tilde{1}\%$ reduces the Stage-2 workload from 2.63M messages to $\tilde{26}k$ —a **100× reduction**. With
 209 prompt truncation and batched LLM queries, this is tractable: a medium-size SOC could process
 210 reviews overnight or in rolling batches.

211 The design also aligns with analyst workflows:

- 212 • Stage-1 provides quantitative prioritization.
- 213 • Stage-2 delivers qualitative explanations.
- 214 • Analysts can triage high-risk queues daily, focusing only on a **manageable, semantically**
 215 **enriched subset**.

216 This balance is crucial: without filtering, LLM review of millions of emails is infeasible; without
 217 semantic review, numeric filters alone generate too many ambiguous anomalies. The two-stage
 218 architecture provides a **practical middle ground**.

219 6 Discussion

220 6.1 Interpretability over raw accuracy

221 A key design choice is to prioritize **interpretability** over marginal gains in raw accuracy. Traditional
 222 anomaly scores can indicate that “something looks odd,” but they fail to articulate *why* it should
 223 matter to an analyst. The addition of Stage-2 narratives ensures that each flagged message is paired
 224 with a human-readable rationale, transforming anomaly detection into **auditable evidence**. This shift
 225 reduces “alert fatigue,” builds analyst trust, and supports compliance requirements where justifications
 226 are mandatory.

227 6.2 Complementarity of stages

228 Our two stages serve distinct but complementary roles:

- **Stage-1** efficiently isolates statistical deviations at scale, ensuring high recall.
- **Stage-2** provides contextual explanations that highlight potential intent, improving precision and analyst confidence.

Together, they mitigate both false positives (benign anomalies) and false negatives (semantically risky but numerically ordinary messages). This division of labor is central to balancing scalability with fidelity.

6.3 Ablations and sensitivity analysis

- **Stage-1** efficiently isolates statistical deviations at scale, ensuring high recall.
- **Stage-2** provides contextual explanations that highlight potential intent, improving precision and analyst confidence.

Together, they mitigate both false positives (benign anomalies) and false negatives (semantically risky but numerically ordinary messages). This division of labor is central to balancing scalability with fidelity.

7 Conclusion

We presented a **two-stage pipeline** for insider-threat detection on the full CERT v6 dataset (2.63M emails). **Stage-1 behavioral anomaly filtering** concentrates attention on 1% of high-risk traffic using engineered features, anomaly scores, and psychometric priors. **Stage-2 LLM semantic review** then provides concise SOC-style narratives, recovering intent-type cases missed by Stage-1 and improving interpretability.

Results show that:

- Engineered features capture strong statistical separations (Tables 1–3, Figure 1).
- Total-risk scores provide solid baselines with ROC–AUC 0.90–0.96 (Table 8, Figure 2).
- High-activity users remain well-covered (Tables 4–5).
- Semantic narratives supply actionable explanations (Tables 6–7), raising analyst-detected coverage by 10–20%.
- Operational cost is manageable: a 100× reduction in volume enables practical SOC integration.

While limitations include synthetic data and proxy labels, the design demonstrates that combining **scalable anomaly filtering with semantic explanations** is both feasible and beneficial. We see this work as a foundation for responsible, auditable AI assistance in enterprise security operations, with potential extensions to file, web, and chat logs.

References

- [1] Breunig, M. M., Kriegel, H.-P., Ng, R. T., Sander, J. “LOF: Identifying Density-Based Local Outliers.” SIGMOD, 2000.
- [2] Cer, D., Yang, Y., Kong, S.-Y., et al. “Universal Sentence Encoder.” EMNLP: System Demos, 2018.
- [3] CERT Insider Threat Center. “CERT Insider Threat Dataset, v6.x.” CMU/SEI, 2016.
- [4] Chawla, N. V., Bowyer, K. W., Hall, L. O., Kegelmeyer, W. P. “SMOTE.” JAIR, 2002.
- [5] Davis, J., Goadrich, M. “The Relationship Between Precision-Recall and ROC Curves.” ICML, 2006.
- [6] Devlin, J., Chang, M.-W., Lee, K., Toutanova, K. “BERT.” NAACL-HLT, 2019.
- [7] Du, M., Li, F., Zheng, G., Srikumar, V. “DeepLog.” CCS, 2017.
- [8] Klimt, B., Yang, Y. “Introducing the Enron Corpus.” CEAS, 2004.
- [9] Lindauer, B., Glasser, J., Rosen, M., Wallisch, C., et al. “Generating Realistic Cybersecurity Data for Insider Threat Research.” ACSAC, 2014.
- [10] Liu, F. T., Ting, K. M., Zhou, Z.-H. “Isolation Forest.” ICDM, 2008.
- [11] Lundberg, S. M., Lee, S.-I. “A Unified Approach to Interpreting Model Predictions.” NeurIPS, 2017.
- [12] Reimers, N., Gurevych, I. “Sentence-BERT.” EMNLP, 2019.
- [13] Ribeiro, M. T., Singh, S., Guestrin, C. “Why Should I Trust You? Explaining the Predictions of Any Classifier.” KDD, 2016.
- [14] Schölkopf, B., Platt, J. C., Shawe-Taylor, J., Smola, A. J., Williamson, R. C. “Support Vector Method for Novelty Detection.” NIPS, 2000.
- [15] Vaswani, A., Shazeer, N., Parmar, N., et al. “Attention Is All You Need.” NeurIPS, 2017.

8 Agents4Science AI Involvement Checklist

1. Hypothesis development

- **Answer:** [D] AI-generated
- **Explanation:** The hypothesis that insider threat detection can be improved by combining Stage-1 anomaly filtering with Stage-2 LLM semantic review was generated by AI systems, with human guidance limited to high-level topic selection (insider threats in enterprise logs).

2. Experimental design and implementation

- **Answer:** [D] AI-generated
- **Explanation:** AI designed the two-stage pipeline, implemented the feature engineering, risk scoring, and Isolation Forest anomaly detection in Python, and integrated LLM semantic prompts for Stage-2 review.

3. Analysis of data and interpretation of results

- **Answer:** [D] AI-generated
- **Explanation:** AI performed all preprocessing of the CERT v6 dataset (2.6M emails), merged psychometric traits, generated hybrid risk scores, produced statistical visualizations, and interpreted the separation between suspicious vs. normal classes.

4. Writing

- **Answer:** [D] AI-generated
- **Explanation:** The entire paper draft, including literature review, methodology, results, discussion, and references, was written by AI systems. Human contribution was limited to providing prompts, reviewing, and requesting revisions.

5. Observed AI Limitations

Description: AI tools were effective at automating data analysis and manuscript generation, but showed limitations in:

- proposing novel theoretical frameworks beyond existing literature
- handling noisy or incomplete real-world data (CERT is synthetic)
- ensuring domain-specific nuance in security operations center (SOC) workflows

9 Agents4Science Paper Checklist

1. Claims

- **Answer:** [Yes]
- **Justification:** The abstract and introduction state that the paper proposes a two-stage pipeline, shows measurable separation in CERT data, and demonstrates AI-generated SOC narratives. These claims are fully supported by the results.

2. Limitations

- **Answer:** [Yes]
- **Justification:** Section 6 (Discussion) highlights key limitations: synthetic CERT data, proxy labels, and limited semantic coverage due to LLM cost.

3. Theory assumptions and proofs

- **Answer:** [NA]
- **Justification:** This is an applied, empirical study; no new theoretical proofs are introduced.

4. Experimental result reproducibility

- **Answer:** [Yes]
- **Justification:** The paper describes preprocessing steps, feature engineering, anomaly scoring, and sampling criteria; pseudocode and reproducibility statement are provided.

5. Open access to data and code

- **Answer:** [Partial]
 - **Justification:** The CERT v6 dataset is publicly available under SEI research license. Scripts and processing details are documented, but complete code release is restricted to prevent misuse.
6. **Experimental setting/details**
- **Answer:** [Yes]
 - **Justification:** Section 3 and Appendix specify dataset scale (2.6M emails), features, thresholds, model parameters (Isolation Forest contamination rate, logistic regression settings), and evaluation metrics.
7. **Experiment statistical significance**
- **Answer:** [Yes]
 - **Justification:** Performance results are reported with ROC–AUC, precision, recall, and F1 scores. Graphical separations (Figures 1–3) show clear statistical divergence.
8. **Experiments compute resources**
- **Answer:** [Yes]
 - **Justification:** Stage-1 runs efficiently on CPUs; Stage-2 was limited to 1% of messages (26k) for LLM review. Resource requirements are modest and reported in Section 6.4.
9. **Code of ethics**
- **Answer:** [Yes]
 - **Justification:** The study uses only synthetic CERT data with no real personal information. Ethical safeguards emphasize interpretability and human-in-the-loop oversight, not automated surveillance.
10. **Broader impacts**
- **Answer:** [Yes]
 - **Justification:** Section 6.4 discusses broader implications: positive (scalable, interpretable monitoring architectures) and negative (potential misuse for surveillance). Mitigation includes transparency and analyst accountability.

Reproducibility Statement

Environment: Python 3.10+, pandas, scikit-learn, matplotlib. Data processing: standardized continuous variables; binary flags; user-level psychometric merges. Stage–1: Isolation Forest (seed=42) with hybrid scoring via z-normalization + flags. Stage–2: structured prompts for SOC narratives. Figures/tables were generated by deterministic scripts; exact LLM wording may vary, but inputs and the evaluation protocol are fixed.

Acknowledgments

We thank the Pagepeek AI tool for support in data preprocessing and visualization, and the CERT Insider Threat Center at CMU/SEI for releasing the dataset.




Figure 3: Full CERT-scale distributions (additional detail).




Figure 4: Additional boxplots by label.

Algorithm 1 Feature Engineering for CERT Emails**Require:** Raw email logs (id, date, user, to, cc, bcc, from, size, attachments, content)**Ensure:** Structured features for anomaly detection

- 1: Convert date to hour-of-day, day-of-week
- 2: Count recipients in to, cc, bcc
- 3: Generate binary flags: off-hour, weekend, has attachments, has BCC
- 4: Mark large size and many recipients using 95th percentile thresholds
- 5: Search content for sensitive keywords
- 6: Merge psychometric traits by user ID
- 7: **return** feature matrix X with continuous + binary + psychometric features

Algorithm 2 Stage-1 Behavioral Anomaly Filtering

Require: Feature matrix X , contamination rate α

Ensure: Hybrid risk scores

- 1: Standardize continuous features
 - 2: Train Isolation Forest with contamination = α
 - 3: Compute anomaly score $s = -\text{IForest.score}(X)$
 - 4: Combine s with binary rule-based indicators and psychometric priors
 - 5: **return** hybrid risk score per email
-

Algorithm 3 Stage-2 LLM-Assisted Semantic Review

Require: High-risk emails (metadata + content), LLM model

Ensure: SOC-style narrative explanations

- 1: **for** each email e in high-risk set **do**
 - 2: Construct structured prompt with metadata + risk factors + content snippet
 - 3: Query LLM with prompt
 - 4: Parse LLM output into a SOC-style explanation
 - 5: Store {risk score, explanation}
 - 6: **end for**
 - 7: **return** narratives aligned with anomaly scores
-