알고리즘 3분반, 32170578, 김산

소스코드

E_DIST.java

```
public class E_DIST {
   int m, n;
   int cost[][];
   char edit[][];
   String str1, str2;
    E_DIST(String _str1,String _str2) {
        str1 = _str1;
        str2 = \_str2;
        m = _str1.length();
        n = _str2.length();
        cost = new int [m+1][n+1];  // Minimum Cost
        edit = new char [m+1][n+1];
                                       // Edit Order
   }
   private int minEdit(int del, int chg, int ins,int i, int j) {
        if(del < chg && del < ins) {</pre>
            edit[i][j] = 'D';
            return del;
        } else if(chg < ins && chg < del) {</pre>
            edit[i][j] = 'C';
            return chg;
        } else {
            edit[i][j] = 'I';
            return ins;
        }
   }
   public int editDistDP() {
        for (int i = 0; i <= m; i++) {
            for (int j = 0; j <= n; j++) {
                if (i == 0) {
                    cost[i][j] = j;
                    edit[i][j] = 'I';
                }
                else if(j == 0) {
                    cost[i][j] = i;
                    edit[i][j] = 'D';
                else if (str1.charAt(i - 1) == str2.charAt(j - 1)) {
                    cost[i][j] = cost[i - 1][j - 1];
                    edit[i][j] = 'C';
                }
                else
```

```
cost[i][j] = minEdit(cost[i-1][j] + 1,
                                     cost[i-1][j-1] + 2,
                                     cost[i][j - 1] + 1,
                                     i,j);
        }
    }
    edit[0][0] = '-';
    return cost[m][n];
public char[] optOrder() {
    int i = m;
    int j = n;
    int count = 0;
    char c_tmp = edit[i][j];
    char temp[] = new char[m+n];
    while(i != 0 || j != 0) {
        if (edit[i][j] == 'I'){
            c_{tmp} = 'I';
            j--;
        } else if (edit[i][j] == 'D') {
            c_{tmp} = 'D';
            i--;
        } else {
            c_{tmp} = 'c';
            i--;
            j--;
        temp[count++] = c_tmp;
    }
    char order[] = new char[count];
    for(int k = 0; k < count; k++) {
        order[k] = temp[count - k - 1];
    }
    return order;
}
public String[] orderApply(char order[]) {
    int i = 0, j = 0;
    String[] orderApply = new String[order.length];
    for (int k = 0; k < order.length; k++) {
        String tmp = "";
        switch (order[k]) {
            case 'I':
                j++;
                break;
            case 'D':
                i++;
                break;
            case 'C':
                i++;
                j++;
                break;
        tmp = str2.substring(0,j) + str1.substring(i,str1.length());
        orderApply[k] = tmp;
    return orderApply;
```

```
}
```

E_DIST_TEST.java(Main함수)

```
import java.util.Scanner;
public class E_DIST_TEST {
   public static void main(String[] args) {
       Scanner sc = new Scanner(System.in);
       System.out.print("String 1 : ");
       String str1 = sc.nextLine();
       System.out.print("String 2 : ");
       String str2 = sc.nextLine();
       sc.close();
       /*2개의 문자열 입력을 받아 최적 경로를 구하기 위한 객체를 생성합니다. */
       E_DIST E = new E_DIST(str1,str2);
       System.out.println("Min cost : " + E.editDistDP());
       /*비용 배열을 출력합니다.*/
       System.out.println("----Cost Table----");
       for (int i = 0; i < E.cost.length; i++) {
           for (int j = 0; j < E.cost[i].length; <math>j++) {
               System.out.print(E.cost[i][j] + " ");
           System.out.println();
       }
       System.out.println("----");
       /*편집 배열을 출력합니다.*/
       System.out.println("----Edit Table----");
       for (int i = 0; i < E.edit.length; <math>i++) {
           for (int j = 0; j < E.edit[i].length; <math>j++) {
               System.out.print(E.edit[i][j] + " ");
           System.out.println();
       System.out.println("----");
       /*최적의 편집 순서열을 구합니다*/
       char order[] = E.optOrder();
       System.out.print("Edit Order : ");
       for (int i = 0; i < order.length - 1; i++) {
           System.out.print(order[i] + "->");
       System.out.println(order[order.length-1]);
       /*최적의 편집 순서열을 적용하여 문자열 편집 순서를 나타냅니다.*/
       String s_order[] = E.orderApply(order);
       System.out.print("Edit Order : ");
       for (int i = 0; i < s_order.length - 1; i++) {
           System.out.print(s_order[i] + "->");
       System.out.println(s_order[s_order.length-1]);
   }
}
```

Case 1

String 1	String 2
aabab	babb

```
String 1 : aabab
String 2 : babb
Min cost : 3
-----Cost Table-----
01234
12123
23234
3 2 3 2 3
4 3 2 3 4
5 4 3 2 3
 ----Edit Table----
- I I I I
DICII
DICII
DCICC
DDCII
DCDCC
Edit Order : D->D->C->C->I->C
Edit Order : abab->bab->bab->bab->babb->babb
```

Case 2

String 1	String 2
san	sun

```
String 1 : san
String 2 : sun
Min cost : 2
----Cost Table----
0 1 2 3
1 0 1 2
2 1 2 3
3 2 3 2
----Edit Table----
- I I I
D C I I
D D I C
-----
Edit Order : C->D->I->C
Edit Order : san->sun->sun
```

Case 3

String 1	String 2
sunday	saturday

```
String 1 : sunday
String 2 : saturday
Min cost: 4
-----Cost Table---
012345678
101234567
212323456
323434567
4 3 4 5 4 5 4 5 6
5 4 3 4 5 6 5 4 5
654567654
 ----Edit Table---
- | | | | | | | | | | |
DCIIIIII
DDIICIIII
DDIIDIIII
DDIIDICII
DDCIIIDCI
DDDIIIDDC
Edit Order : C->I->I->C->D->I->C->C->C
Edit Order : sunday->saunday->satunday->satunday->satuday->saturday->saturday->saturday->saturday-
```

Case 4

String 1	String 2
food	money

```
String 1 : food
String 2 : money
Min cost : 7
----Cost Table----
012345
123456
2 3 2 3 4 5
3 4 3 4 5 6
454567
-----Edit Table-----
- I I I I I
DIIIII
DICIII
DICIII
DIDIII
Edit Order : D->D->I->C->D->I->I
Edit Order : ood->od->mod->mod->mo->mon->mone->money
```

Case 5

String 1	String 2
voldemort	dumbledore