

class14: RNA-seq Analysis Mini-Project

Anna Waters (PID: A16271985)

```
library(DESeq2)
```

```
Loading required package: S4Vectors
```

```
Loading required package: stats4
```

```
Loading required package: BiocGenerics
```

```
Attaching package: 'BiocGenerics'
```

```
The following objects are masked from 'package:stats':
```

```
IQR, mad, sd, var, xtabs
```

```
The following objects are masked from 'package:base':
```

```
anyDuplicated, aperm, append, as.data.frame, basename, cbind,  
colnames, dirname, do.call, duplicated, eval, evalq, Filter, Find,  
get, grep, grepl, intersect, is.unsorted, lapply, Map, mapply,  
match, mget, order, paste, pmax, pmax.int, pmin, pmin.int,  
Position, rank, rbind, Reduce, rownames, sapply, setdiff, sort,  
table, tapply, union, unique, unsplit, which.max, which.min
```

```
Attaching package: 'S4Vectors'
```

The following object is masked from 'package:utils':

findMatches

The following objects are masked from 'package:base':

expand.grid, I, unname

Loading required package: IRanges

Loading required package: GenomicRanges

Loading required package: GenomeInfoDb

Loading required package: SummarizedExperiment

Loading required package: MatrixGenerics

Loading required package: matrixStats

Attaching package: 'MatrixGenerics'

The following objects are masked from 'package:matrixStats':

colAlls, colAnyNAs, colAnys, colAvgsPerRowSet, colCollapse,
colCounts, colCummaxs, colCummins, colCumprods, colCumsums,
colDiffs, colIQRDiffs, colIQRs, colLogSumExps, colMadDiffs,
colMads, colMaxs, colMeans2, colMedians, colMins, colOrderStats,
colProds, colQuantiles, colRanges, colRanks, colSdDiffs, colSds,
colSums2, colTabulates, colVarDiffs, colVars, colWeightedMads,
colWeightedMeans, colWeightedMedians, colWeightedSds,
colWeightedVars, rowAlls, rowAnyNAs, rowAnys, rowAvgsPerColSet,
rowCollapse, rowCounts, rowCummaxs, rowCummins, rowCumprods,
rowCumsums, rowDiffs, rowIQRDiffs, rowIQRs, rowLogSumExps,
rowMadDiffs, rowMads, rowMaxs, rowMeans2, rowMedians, rowMins,
rowOrderStats, rowProds, rowQuantiles, rowRanges, rowRanks,
rowSdDiffs, rowSds, rowSums2, rowTabulates, rowVarDiffs, rowVars,
rowWeightedMads, rowWeightedMeans, rowWeightedMedians,
rowWeightedSds, rowWeightedVars

Loading required package: Biobase

Welcome to Bioconductor

Vignettes contain introductory material; view with
'browseVignettes()'. To cite Bioconductor, see
'citation("Biobase")', and for packages 'citation("pkgname")'.

Attaching package: 'Biobase'

The following object is masked from 'package:MatrixGenerics':

rowMedians

The following objects are masked from 'package:matrixStats':

anyMissing, rowMedians

Data Import

```
metaFile <- "GSE37704_metadata.csv"
countFile <- "GSE37704_featurecounts.csv"
```

```
# Import metadata and take a peak
colData = read.csv(metaFile)
head(colData)
```

	id	condition
1	SRR493366	control_sirna
2	SRR493367	control_sirna
3	SRR493368	control_sirna
4	SRR493369	hoxa1_kd
5	SRR493370	hoxa1_kd
6	SRR493371	hoxa1_kd

```
# Import countdata
countData = read.csv(countFile, row.names=1)
head(countData)
```

	length	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370
ENSG00000186092	918	0	0	0	0	0
ENSG00000279928	718	0	0	0	0	0
ENSG00000279457	1982	23	28	29	29	28
ENSG00000278566	939	0	0	0	0	0
ENSG00000273547	939	0	0	0	0	0
ENSG00000187634	3214	124	123	205	207	212

	SRR493371
ENSG00000186092	0
ENSG00000279928	0
ENSG00000279457	46
ENSG00000278566	0
ENSG00000273547	0
ENSG00000187634	258

Data Exploration

The first column doesn't align with the meta data so I need to remove it.

Q. Complete the code below to remove the troublesome first column from count-Data

```
countData <- as.matrix(countData[,2:7]) #taking only the columns 2:7
head(countData)
```

	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
ENSG00000186092	0	0	0	0	0	0
ENSG00000279928	0	0	0	0	0	0
ENSG00000279457	23	28	29	29	28	46
ENSG00000278566	0	0	0	0	0	0
ENSG00000273547	0	0	0	0	0	0
ENSG00000187634	124	123	205	207	212	258

```
all(colData$id == colnames(countData))
```

```
[1] TRUE
```

This looks better but there are lots of zero entries in there so let's get rid of them as we have no data for these.

Q. Complete the code below to filter countData to exclude genes (i.e. rows) where we have 0 read count across all samples (i.e. columns).

Using `rowSums()`, I can sum across the rows and see if the sum is greater than 1.

```
# Filter count data where the sum is above zero
inds <- rowSums(countData) > 0

# filtering so anything without a zero is still taken
nozero_countData <- countData[inds,]

head(nozero_countData)
```

	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
ENSG00000279457	23	28	29	29	28	46
ENSG00000187634	124	123	205	207	212	258
ENSG00000188976	1637	1831	2383	1226	1326	1504
ENSG00000187961	120	153	180	236	255	357
ENSG00000187583	24	48	65	44	48	64
ENSG00000187642	4	9	16	14	16	16

No more entries with zeros, now I can run DESeq2

##DESeq2 set up and analysis

```
library(DESeq2)
```

Use `DESeqDataSetFromMatrix()` to create the deseq object

```
# need countData and colData
#the design is what the compare by/ how they are different which is in the colData (contr
dds <- DESeqDataSetFromMatrix(countData=nozero_countData,
                              colData=colData,
                              design=~condition)
```

Warning in `DESeqDataSet(se, design = design, ignoreRank)`: some variables in design formula are characters, converting to factors

```
dds <- DESeq(dds)
```

estimating size factors

estimating dispersions

gene-wise dispersion estimates

mean-dispersion relationship

final dispersion estimates

fitting model and testing

Look at the DESeq object

```
dds
```

```
class: DESeqDataSet
dim: 15975 6
metadata(1): version
assays(4): counts mu H cooks
rownames(15975): ENSG00000279457 ENSG00000187634 ... ENSG00000276345
               ENSG00000271254
rowData names(22): baseMean baseVar ... deviance maxCooks
colnames(6): SRR493366 SRR493367 ... SRR493370 SRR493371
colData names(3): id condition sizeFactor
```

Next, get results for the HoxA1 knockdown versus control siRNA (remember that these were labeled as “hoxa1_kd” and “control_sirna” in our original colData metaFile input to DESeq, you can check this above and by running resultsNames(dds) command).

##Results Extraction

```
res <- results(dds, contrast=c("condition", "hoxa1_kd", "control_sirna"))
head(res)
```

log2 fold change (MLE): condition hoxa1_kd vs control_sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 6 rows and 6 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>

```

ENSG00000279457 29.9136 0.1792571 0.3248216 0.551863 5.81042e-01
ENSG00000187634 183.2296 0.4264571 0.1402658 3.040350 2.36304e-03
ENSG00000188976 1651.1881 -0.6927205 0.0548465 -12.630158 1.43990e-36
ENSG00000187961 209.6379 0.7297556 0.1318599 5.534326 3.12428e-08
ENSG00000187583 47.2551 0.0405765 0.2718928 0.149237 8.81366e-01
ENSG00000187642 11.9798 0.5428105 0.5215598 1.040744 2.97994e-01
      padj
<numeric>
ENSG00000279457 6.86555e-01
ENSG00000187634 5.15718e-03
ENSG00000188976 1.76549e-35
ENSG00000187961 1.13413e-07
ENSG00000187583 9.19031e-01
ENSG00000187642 4.03379e-01

```

```
resultsNames(dds)
```

```
[1] "Intercept" "condition_hoxa1_kd_vs_control_sirna"
```

Q. Call the `summary()` function on your results to get a sense of how many genes are up or down-regulated at the default 0.1 p-value cutoff.

```
summary(res)
```

```

out of 15975 with nonzero total read count
adjusted p-value < 0.1
LFC > 0 (up)      : 4349, 27%
LFC < 0 (down)    : 4396, 28%
outliers [1]      : 0, 0%
low counts [2]    : 1237, 7.7%
(mean count < 0)
[1] see 'cooksCutoff' argument of ?results
[2] see 'independentFiltering' argument of ?results


```

There are 4349 genes up-regulated and 4396 genes down regulated with the basic cutoff.

##Volcano Plot

Now we will make a volcano plot, a commonly produced visualization from this type of data that we introduced last day. Basically it's a plot of log2 fold change vs -log adjusted p-value.

```
plot( res$log2FoldChange, -log(res$padj) )
```



Q. Improve this plot by completing the below code, which adds color and axis labels

By adding a logical that looks at the pvalue adjusted, I can color the points blue for points that are significant and have high fold change.

```
# Make a color vector for all genes
mycols <- rep("gray", nrow(res) )

# Color red the genes with absolute fold change above 2
mycols[ abs(res$log2FoldChange) > 2 ] <- "red"


# Color blue those with adjusted p-value less than 0.01
# and absolute fold change more than 2

# added the logical for padj < 0.01
inds <- (res$padj < 0.01) & (abs(res$log2FoldChange) > 2 )
mycols[ inds ] <- "blue"

# added col = mycols to change the point colors
```



```
plot( res$log2FoldChange, -log(res$padj), col=mycols, xlab="Log2(FoldChange)", ylab="-Log(
```



Adding Gene Annotations

Since we mapped and counted against the Ensembl annotation, our results only have information about Ensembl gene IDs. However, our pathway analysis downstream will use KEGG pathways, and genes in KEGG pathways are annotated with Entrez gene IDs. So let's add them as we did the last day.

Q. Use the `mapIDs()` function multiple times to add SYMBOL, ENTREZID and GENENAME annotation to our results by completing the code below.

```
library("AnnotationDbi")
library("org.Hs.eg.db")
```

```
columns(org.Hs.eg.db)
```

[1]	"ACCNUM"	"ALIAS"	"ENSEMBL"	"ENSEMBLPROT"	"ENSEMBLTRANS"
[6]	"ENTREZID"	"ENZYME"	"EVIDENCE"	"EVIDENCEALL"	"GENENAME"
[11]	"GENETYPE"	"GO"	"GOALL"	"IPI"	"MAP"
[16]	"OMIM"	"ONTOLOGY"	"ONTOLOGYALL"	"PATH"	"PFAM"
[21]	"PMID"	"PROSITE"	"REFSEQ"	"SYMBOL"	"UCSCKG"
[26]	"UNIPROT"				

```
# set keys to the rownames which are the ensembl id & make the column = to the type I want
res$symbol = mapIds(org.Hs.eg.db,
  keys=rownames(res),
  keytype="ENSEMBL",
  column="SYMBOL",
  multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
# set keys to the rownames which are the ensembl id & make the column = to the type I want
res$entrez = mapIds(org.Hs.eg.db,
  keys=rownames(res),
  keytype="ENSEMBL",
  column="ENTREZID",
  multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
# set keys to the rownames which are the ensembl id & make the column = to the type I want
res$name = mapIds(org.Hs.eg.db,
  keys=row.names(res),
  keytype="ENSEMBL",
  column="GENENAME",
  multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
head(res, 10)
```

log2 fold change (MLE): condition hoxa1_kd vs control_sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 10 rows and 9 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.913579	0.1792571	0.3248216	0.551863	5.81042e-01
ENSG00000187634	183.229650	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.188076	-0.6927205	0.0548465	-12.630158	1.43990e-36
ENSG00000187961	209.637938	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.255123	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.979750	0.5428105	0.5215598	1.040744	2.97994e-01
ENSG00000188290	108.922128	2.0570638	0.1969053	10.446970	1.51282e-25
ENSG00000187608	350.716868	0.2573837	0.1027266	2.505522	1.22271e-02
ENSG00000188157	9128.439422	0.3899088	0.0467163	8.346304	7.04321e-17
ENSG00000237330	0.158192	0.7859552	4.0804729	0.192614	8.47261e-01
	padj	symbol	entrez	name	
	<numeric>	<character>	<character>	<character>	
ENSG00000279457	6.86555e-01	NA	NA	NA	
ENSG00000187634	5.15718e-03	SAMD11	148398	sterile alpha motif ..	
ENSG00000188976	1.76549e-35	NOC2L	26155	NOC2 like nucleolar ..	
ENSG00000187961	1.13413e-07	KLHL17	339451	kelch like family me..	
ENSG00000187583	9.19031e-01	PLEKHN1	84069	pleckstrin homology ..	
ENSG00000187642	4.03379e-01	PERM1	84808	PPARGC1 and ESRR ind..	
ENSG00000188290	1.30538e-24	HES4	57801	hes family bHLH tran..	
ENSG00000187608	2.37452e-02	ISG15	9636	ISG15 ubiquitin like..	
ENSG00000188157	4.21963e-16	AGRN	375790	agrin	
ENSG00000237330	NA	RNF223	401934	ring finger protein ..	

Q. Finally for this section let's reorder these results by adjusted p-value and save them to a CSV file in your current project directory.

```
res <- res[order(res$pvalue),]  
write.csv(res, file = "deseq_results.csv")
```

Pathway Analysis

KEGG Pathway Analysis

```
library(pathview)
```

```
#####
Pathview is an open source software package distributed under GNU General
Public License version 3 (GPLv3). Details of GPLv3 is available at
http://www.gnu.org/licenses/gpl-3.0.html. Particullary, users are required to
formally cite the original Pathview paper (not just mention it) in publications
or products. For details, do citation("pathview") within R.
```

The pathview downloads and uses KEGG data. Non-academic uses may require a KEGG license agreement (details at <http://www.kegg.jp/kegg/legal.html>).

```
#####
```

```
library(gage)
```

```
library(gageData)
```

```
data(kegg.sets.hs)
data(sigmet.idx.hs)
```

```
# Focus on signaling and metabolic pathways only
kegg.sets.hs = kegg.sets.hs[sigmet.idx.hs]
```

```
# Examine the first 3 pathways
head(kegg.sets.hs, 3)
```

```
$`hsa00232 Caffeine metabolism`
```

```
[1] "10" "1544" "1548" "1549" "1553" "7498" "9"
```

```
$`hsa00983 Drug metabolism - other enzymes`
```

```
[1] "10" "1066" "10720" "10941" "151531" "1548" "1549" "1551"
[9] "1553" "1576" "1577" "1806" "1807" "1890" "221223" "2990"
[17] "3251" "3614" "3615" "3704" "51733" "54490" "54575" "54576"
[25] "54577" "54578" "54579" "54600" "54657" "54658" "54659" "54963"
[33] "574537" "64816" "7083" "7084" "7172" "7363" "7364" "7365"
[41] "7366" "7367" "7371" "7372" "7378" "7498" "79799" "83549"
[49] "8824" "8833" "9" "978"
```

```
$`hsa00230 Purine metabolism`
```

```
[1] "100" "10201" "10606" "10621" "10622" "10623" "107" "10714"
```

[9]	"108"	"10846"	"109"	"111"	"11128"	"11164"	"112"	"113"
[17]	"114"	"115"	"122481"	"122622"	"124583"	"132"	"158"	"159"
[25]	"1633"	"171568"	"1716"	"196883"	"203"	"204"	"205"	"221823"
[33]	"2272"	"22978"	"23649"	"246721"	"25885"	"2618"	"26289"	"270"
[41]	"271"	"27115"	"272"	"2766"	"2977"	"2982"	"2983"	"2984"
[49]	"2986"	"2987"	"29922"	"3000"	"30833"	"30834"	"318"	"3251"
[57]	"353"	"3614"	"3615"	"3704"	"377841"	"471"	"4830"	"4831"
[65]	"4832"	"4833"	"4860"	"4881"	"4882"	"4907"	"50484"	"50940"
[73]	"51082"	"51251"	"51292"	"5136"	"5137"	"5138"	"5139"	"5140"
[81]	"5141"	"5142"	"5143"	"5144"	"5145"	"5146"	"5147"	"5148"
[89]	"5149"	"5150"	"5151"	"5152"	"5153"	"5158"	"5167"	"5169"
[97]	"51728"	"5198"	"5236"	"5313"	"5315"	"53343"	"54107"	"5422"
[105]	"5424"	"5425"	"5426"	"5427"	"5430"	"5431"	"5432"	"5433"
[113]	"5434"	"5435"	"5436"	"5437"	"5438"	"5439"	"5440"	"5441"
[121]	"5471"	"548644"	"55276"	"5557"	"5558"	"55703"	"55811"	"55821"
[129]	"5631"	"5634"	"56655"	"56953"	"56985"	"57804"	"58497"	"6240"
[137]	"6241"	"64425"	"646625"	"654364"	"661"	"7498"	"8382"	"84172"
[145]	"84265"	"84284"	"84618"	"8622"	"8654"	"87178"	"8833"	"9060"
[153]	"9061"	"93034"	"953"	"9533"	"954"	"955"	"956"	"957"
[161]	"9583"	"9615"						

The main `gage()` function requires a named vector of fold changes, where the names of the values are the Entrez gene IDs.

```
foldchanges <- res$log2FoldChange
names(foldchanges) = res$entrez
head(foldchanges)
```

```
      1266      54855      1465      51232      2034      2317
-2.422719  3.201955 -2.313738 -2.059631 -1.888019 -1.649792
```

Now, let's run the `gage` pathway analysis.

```
# Get the results
keggres <- gage(foldchanges, gsets=kegg.sets.hs)
```

Because for KEGG and other pathways gene are not always regulated together, I swicthed the `same.dir` to `false` for a better understanding of the pathway.

```
keggres_noco <- gage(foldchanges, gsets=kegg.sets.hs, same.dir = F)
```

Now lets look at the object returned from `gage()`.

```
attributes(keggres)
```

```
$names
```

```
[1] "greater" "less"    "stats"
```

Lets look at the first few down (less) pathway results:

```
# Look at the first few down (less) pathways
head(keggres$less)
```

	p.geomean	stat.mean	p.val
hsa04110 Cell cycle	8.995727e-06	-4.378644	8.995727e-06
hsa03030 DNA replication	9.424076e-05	-3.951803	9.424076e-05
hsa03013 RNA transport	1.375901e-03	-3.028500	1.375901e-03
hsa03440 Homologous recombination	3.066756e-03	-2.852899	3.066756e-03
hsa04114 Oocyte meiosis	3.784520e-03	-2.698128	3.784520e-03
hsa00010 Glycolysis / Gluconeogenesis	8.961413e-03	-2.405398	8.961413e-03

	q.val	set.size	exp1
hsa04110 Cell cycle	0.001448312	121	8.995727e-06
hsa03030 DNA replication	0.007586381	36	9.424076e-05
hsa03013 RNA transport	0.073840037	144	1.375901e-03
hsa03440 Homologous recombination	0.121861535	28	3.066756e-03
hsa04114 Oocyte meiosis	0.121861535	102	3.784520e-03
hsa00010 Glycolysis / Gluconeogenesis	0.212222694	53	8.961413e-03


Now, let's try out the `pathview()` function from the `pathview` package to make a pathway plot with our RNA-Seq expression results shown in color. To begin with lets manually supply a `pathway.id` (namely the first part of the "hsa04110 Cell cycle") that we could see from the print out above.

```
pathview(gene.data=foldchanges, pathway.id="hsa04110")
```

```
'select()' returned 1:1 mapping between keys and columns
```

```
Info: Working in directory /Users/anna/Documents/BIMM 143/class14
```

```
Info: Writing image file hsa04110.pathview.png
```



```
# A different PDF based output of the same data
pathview(gene.data=foldchanges, pathway.id="hsa04110", kegg.native=FALSE)
```

'select()' returned 1:1 mapping between keys and columns

Warning: reconcile groups sharing member nodes!

```
[,1] [,2]
[1,] "9"  "300"
[2,] "9"  "306"
```

Info: Working in directory /Users/anna/Documents/BIMM 143/class14

Info: Writing image file hsa04110.pathview.pdf

Now, let's process our results a bit more to automagically pull out the top 5 upregulated pathways, then further process that just to get the pathway IDs needed by the pathview() function. We'll use these KEGG pathway IDs for pathview plotting below.

```
## Focus on top 5 upregulated pathways here for demo purposes only
keggrespathways <- rownames(keggres$greater)[1:5]

# Extract the 8 character long IDs part of each string
keggresids <- substr(keggrespathways, start=1, stop=8)
keggresids
```

```
[1] "hsa04640" "hsa04630" "hsa00140" "hsa04142" "hsa04330"
```

Finally, let's pass these IDs in keggresids to the pathview() function to draw plots for all the top 5 pathways.

```
pathview(gene.data=foldchanges, pathway.id=keggresids, species="hsa")
```

```
'select()' returned 1:1 mapping between keys and columns
```

```
Info: Working in directory /Users/anna/Documents/BIMM 143/class14
```

```
Info: Writing image file hsa04640.pathview.png
```

```
'select()' returned 1:1 mapping between keys and columns
```

```
Info: Working in directory /Users/anna/Documents/BIMM 143/class14
```

```
Info: Writing image file hsa04630.pathview.png
```

```
'select()' returned 1:1 mapping between keys and columns
```

```
Info: Working in directory /Users/anna/Documents/BIMM 143/class14
```

```
Info: Writing image file hsa00140.pathview.png
```

```
'select()' returned 1:1 mapping between keys and columns
```


Info: Working in directory /Users/anna/Documents/BIMM 143/class14


Info: Writing image file hsa04142.pathview.png


Info: some node width is different from others, and hence adjusted!

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/anna/Documents/BIMM 143/class14

Info: Writing image file hsa04330.pathview.png





Q. Can you do the same procedure as above to plot the pathview figures for the top 5 down-regulated pathways?

```
## Focus on top 5 downregulated pathways here -> use the less column
keggrespathways_down <- rownames(keggres$less)[1:5]

# Extract the 8 character long IDs part of each string
keggresids_down <- substr(keggrespathways_down, start=1, stop=8)
keggresids_down
```

```
[1] "hsa04110" "hsa03030" "hsa03013" "hsa03440" "hsa04114"
```

```
pathview(gene.data=foldchanges, pathway.id=keggresids_down, species="hsa")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/anna/Documents/BIMM 143/class14

Info: Writing image file hsa04110.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/anna/Documents/BIMM 143/class14

Info: Writing image file hsa03030.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/anna/Documents/BIMM 143/class14

Info: Writing image file hsa03013.pathview.png


'select()' returned 1:1 mapping between keys and columns


Info: Working in directory /Users/anna/Documents/BIMM 143/class14


Info: Writing image file hsa03440.pathview.png

Info: Writing image file hsa04114.pathview.png









\$greater

	p.geomean	stat.mean	p.val
G0:0007156 homophilic cell adhesion	8.519724e-05	3.824205	8.519724e-05
G0:0002009 morphogenesis of an epithelium	1.396681e-04	3.653886	1.396681e-04
G0:0048729 tissue morphogenesis	1.432451e-04	3.643242	1.432451e-04
G0:0007610 behavior	1.925222e-04	3.565432	1.925222e-04
G0:0060562 epithelial tube morphogenesis	5.932837e-04	3.261376	5.932837e-04
G0:0035295 tube development	5.953254e-04	3.253665	5.953254e-04

	q.val	set.size	exp1
G0:0007156 homophilic cell adhesion	0.1951953	113	8.519724e-05
G0:0002009 morphogenesis of an epithelium	0.1951953	339	1.396681e-04
G0:0048729 tissue morphogenesis	0.1951953	424	1.432451e-04
G0:0007610 behavior	0.1967577	426	1.925222e-04
G0:0060562 epithelial tube morphogenesis	0.3565320	257	5.932837e-04
G0:0035295 tube development	0.3565320	391	5.953254e-04

\$less

	p.geomean	stat.mean	p.val
G0:0048285 organelle fission	1.536227e-15	-8.063910	1.536227e-15
G0:0000280 nuclear division	4.286961e-15	-7.939217	4.286961e-15
G0:0007067 mitosis	4.286961e-15	-7.939217	4.286961e-15
G0:0000087 M phase of mitotic cell cycle	1.169934e-14	-7.797496	1.169934e-14
G0:0007059 chromosome segregation	2.028624e-11	-6.878340	2.028624e-11
G0:0000236 mitotic prometaphase	1.729553e-10	-6.695966	1.729553e-10

	q.val	set.size	exp1
G0:0048285 organelle fission	5.841698e-12	376	1.536227e-15
G0:0000280 nuclear division	5.841698e-12	352	4.286961e-15
G0:0007067 mitosis	5.841698e-12	352	4.286961e-15
G0:0000087 M phase of mitotic cell cycle	1.195672e-11	362	1.169934e-14
G0:0007059 chromosome segregation	1.658603e-08	142	2.028624e-11
G0:0000236 mitotic prometaphase	1.178402e-07	84	1.729553e-10

\$stats

	stat.mean	exp1
G0:0007156 homophilic cell adhesion	3.824205	3.824205
G0:0002009 morphogenesis of an epithelium	3.653886	3.653886
G0:0048729 tissue morphogenesis	3.643242	3.643242
G0:0007610 behavior	3.565432	3.565432
G0:0060562 epithelial tube morphogenesis	3.261376	3.261376
G0:0035295 tube development	3.253665	3.253665

Reactome Analysis

Let's now conduct over-representation enrichment analysis and pathway-topology analysis with Reactome using the previous list of significant genes generated from our differential expression results above.

First, Using R, output the list of significant genes at the 0.05 level as a plain text file:

```
sig_genes <- res[res$padj <= 0.05 & !is.na(res$padj), "symbol"]  
print(paste("Total number of significant genes:", length(sig_genes)))
```

```
[1] "Total number of significant genes: 8147"
```

```
write.table(sig_genes, file="significant_genes.txt", row.names=FALSE, col.names=FALSE, quo
```