

-

Tutorial

R Tutorial (R-Tutorial.html)

ggplot2

ggplot2 Short Tutorial (ggplot2-Tutorial-With-R.html)

ggplot2 Tutorial 1 - Intro (Complete-Ggplot2-Tutorial-Part1-With-R-Code.html)

ggplot2 Tutorial 2 - Theme (Complete-Ggplot2-Tutorial-Part2-Customizing-Theme-With-R-Code.html)

ggplot2 Tutorial 3 - Masterlist (Top50-Ggplot2-Visualizations-MasterList-R-Code.html)

ggplot2 Quickref (ggplot2-cheatsheet.html)

Foundations

Linear Regression (Linear-Regression.html)

Statistical Tests (Statistical-Tests-in-R.html)

Missing Value Treatment (Missing-Value-Treatment-With-R.html)

Outlier Analysis (Outlier-Treatment-With-R.html)

Feature Selection (Variable-Selection-and-Importance-With-R.html)

Model Selection (Model-Selection-in-R.html)

Logistic Regression (Logistic-Regression-With-R.html)

Advanced Linear Regression (Environments.html)

Advanced Regression Models

Advanced Regression Models (adv-regression-models.html)

Time Series

Time Series Analysis (Time-Series-Analysis-With-R.html)

Time Series Forecasting (Time-Series-Forecasting-With-R.html)

More Time Series Forecasting ([Time-Series-Forecasting-With-R-part2.html](#))

High Performance Computing

Parallel computing ([Parallel-Computing-With-R.html](#))

Strategies to Speedup R code ([Strategies-To-Improve-And-Speedup-R-Code.html](#))

Useful Techniques

Association Mining ([Association-Mining-With-R.html](#))

Multi Dimensional Scaling ([Multi-Dimensional-Scaling-With-R.html](#))

Optimization ([Profiling.html](#))

InformationValue package ([Information-Value-With-R.html](#))

Stay up-to-date. Subscribe!

(https://docs.google.com/forms/d/1xkMYkLNFU9U39Dd8S_2JC0p8B5t6_Yq6zUQjanQQJpY/viewform)

Chat! (<https://docs.google.com/forms/d/13GrkCFcNa-TOIIIQghsz2SIEbc-YqY9eJX02B19I5Ow/viewform>)

Contents

Simple Moving Average

Exponential Smoothing

ARIMA

How To Forecast ARIMA Models With Long Seasonality (Greater Than 350 Periods)?

Some Useful External Regressors For Arima() and auto.arima()

How To Model Time Series With Complex Seasonality Pattern?

How To Find Confidence Intervals For My Forecasts?

More Useful Functions Related To Time Series

Time Series Forecasting

This is a follow-up to the introduction to time series analysis (Time-Series-Analysis-With-R), but focused more on forecasting rather than analysis.

Simple Moving Average

Simple moving average can be calculated using `ma()` from forecast

```
sm <- ma(ts, order=12) # 12 month moving average  
lines(sm, col="red") # plot
```

Exponential Smoothing

Simple, Double and Triple exponential smoothing can be performed using the `HoltWinters()` function. There are multiple implementations of the Holt Winters method – `hw()` {forecast} and `ets()`.

```
library(forecast)

# Simple exponential smoothing: Level Only
model <- hw(trainingData, initial = "optimal", h=(forecastPeriodLen), beta=NULL, gamma=NULL) # h is the no. periods to forecast

# Double Exponential smoothing: Level and Trend components
model <- hw(trainingData, initial = "optimal", h=(forecastPeriodLen), gamma=NULL)

# Holt Winters: Level, Trend and Seasonality
model <- hw(trainingData, initial = "optimal", h=(forecastPeriodLen))
plot(model)
accuracy(model) # calculate accuracy measures
```

ARIMA

The forecast package offers `auto.arima()` function to fit ARIMA models. It can also be manually fit using `Arima()`. A caveat with ARIMA models in R is that it does not have the functionality to fit long seasonality of more than 350 periods eg: 365 days for daily data or 24 hours for 15 sec data.

```
# Fit and forecast with auto.arima()
autoArimaFit <- auto.arima(tsData)
plot(forecast(autoArimaFit, h=20))

# Fit and forecast with Arima()
arimaFit <- Arima(tsData, order=c(3,1,0))
plot(forecast(arimaFit, h=20))
```

How To Forecast ARIMA Models With Long Seasonality (Greater Than 350 Periods)?

Upon plotting your Arima() forecast, you find a more or less flat forecast, it could be because of long seasonality. In such case, you can feed in the seasonality as an external regressor through the 'xreg' argument.

```
Fit <- Arima(tsData,order=c(3,1,0)) # fit Arima model
Fit <- auto.arima(tsData, seasonal=FALSE, xreg=fourier(tsData,4)) # fit auto.arima model
plot(forecast(Fit,h=20))
pred <- predict (Fit, newxreg=newXregVar) # alternate way to forecast
plot(forecast(fit, h=h, xreg=fourierf(tsData,4,h))) # h is number of forecasts
```

If you are using a numeric vector as an external regressor (xreg), make sure you change it to a data.frame() before feeding it as an xreg parameter to auto.arima(). You can also use multiple external regressors by binding them together as a data.frame().

Some Useful External Regressors For Arima() and auto.arima()



Any dataframe with as many rows as length of ts data can be used as 'xreg' argument. A couple of common 'xreg's that are used to model seasonal effects are below.

```
Xreg1 <- seasonaldummy(tsData) # creates dummy binary variable for each period in a season.
Xreg2 <- model.matrix(~ as.factor(weekday) + 0)) # weekday could be a monthday, hour-of-day, holiday indicator etc ..
```

How To Model Time Series With Complex Seasonality Pattern?

Use the `tbats()` in forecast package. Time series with multiple-seasonality can be modelled with this method. Since this is a computationally intensive procedure, the in-built parallel processing facility may be leveraged.

```
tbatsFit <- tbats(tsData, use.parallel=TRUE, num.cores = 2) # fit tbats model
plot(forecast(fit)) # plot
components <- tbats.components(tbatsFit)
plot(components)
```

How To Find Confidence Intervals For My Forecasts?

The `predict()` function has the facility. By providing the argument 'prediction.interval=TRUE' and 'level = n', the prediction intervals for a given confidence is calculated. Below is a general format of the code.

```
model <- HoltWinters(TS) predict(model, 50, prediction.interval = TRUE, level= 0.99) #
prediction.interval = TRUE
```

More Useful Functions Related To Time Series

Functions	Description
<code>accuracy()</code>	accuracy measures of forecast

Functions	Description
BoxCox, invBoxCox()	Box-Cox transformation
decompose()	Decompose time series data into components
dm.test()	Diebold-Mariano test compares the forecast accuracy
monthdays()	number of days in seasonal series
na.interp()	interpolate missing values
seasadj()	Remove the seasonal components from a time series
seasonaldummy()	create matrix of seasonal indicator variables
seasonplot()	Plot seasonal effects

© 2016-17 Selva Prabhakaran. Powered by jekyll (<http://jekyllrb.com/>), knitr (<http://yihui.name/knitr/>), and pandoc (<http://johnmacfarlane.net/pandoc/>). This work is licensed under the Creative Commons License. (<http://creativecommons.org/licenses/by-nc/3.0/>)