

Contents - With restarted GMRES

- Jacobi
- BLKJacobi
- GS
- SOR
- GMRES-100
- PGMRES-100
- Plotting commands

```
function A1q3()

close all
clc

sigma = -10;
tau = -20;
n = 2^10;
h = 1/(n+1);

beta = sigma*h/2;
gamma = tau*h/2;
fprintf('\n =====')
fprintf('\n      Solving the Convection-Diffusion equation with\n')
fprintf('      beta = %2.4f, gamma = %2.4f and n = %3i\n',beta,gamma,n)
fprintf('      =====\n')
% Creating discretised Convection Diffusion matrix
A = ConvectionDiffusion(beta,gamma,n);

% Defin exact solution and RHS functions
u = @(x,y) sin(pi*x).*cos(pi*y);
f = @(x,y,sigma,tau) 2*pi^2*u(x,y)+sigma*pi*cos(pi*x).*cos(pi*y) ...
    -tau*pi*sin(pi*x).*sin(pi*y);

% Creating domain
x = linspace(0,1,n+2);
[X,Y] = meshgrid(x,x);

% Defining RHS vector
F = f(X,Y,sigma,tau);
% Applying Dirichlet boundary conditions
F(:,1) = sparse(n+2,1);
F(:,end) = sparse(n+2,1);
F = h^2*F(:);

% Defining exact solution
```

```

uE = u(X,Y);
uE = uE(:);

% Calculating error
tic
uA = A\F;
Dtime = toc;
fprintf('\n      Time using backslash = %4.4f',Dtime)
fprintf('\n      solution norm = %1.4e \n\n\n',norm(uE-uA,inf));

% Setting up initial guess
x = sparse((n+2)^2,1);

% Defining iterative parameters
max_iter = 2000;
tol = 1e-6;

=====
Solving the Convection-Diffusion equation with
      beta = -0.0049, gamma = -0.0098 and n = 1024
=====

Time using backslash = 12.1265
solution norm = 1.5935e-06

```

Jacobi

```
[~,rJ,iterJ] = Jacobi(max_iter,tol,x,A,F);
```

```

-----
|      Jacobi      |
-----

Residual after error 2000 iterations = 3.4810e-02
Time to run Jacobi = 51.6430

```

BLKJacobi

```
[~,rBLK,iterBLK] = BLKJacobi(max_iter,tol,x,A,F);
```

```

-----
|   BLK Jacobi   |
-----
Residual after error 2000 interations = 3.4290e-02
Time to run Jacobi = 125.7144

```

GS

```
[~,rGS,iterGS] = GS(max_iter,tol,x,A,F);
```

```

-----
| Gauss-Siedel  |
-----
Residual after error 2000 interations = 3.4316e-02
Time to run GS = 82.9518

```

SOR

```

fprintf('-----\n');
fprintf('|       SOR       |\n');
fprintf('-----\n');
ii = 0;
rSOR = cell(9,1);
iterSOR = sparse(9,1);
test = zeros(9,1);
omega = zeros(9,1);
for i = 1.1:.1:1.9
    ii = ii + 1;
    [~,rSORR,iterSOR(ii)] = SOR(max_iter,tol,x,A,F,i);
    rSOR{ii} = rSORR;
    test(ii) = rSORR(end);
    omega(ii) = i;
end
[~,index]=min(test);

```

```

-----
|       SOR       |
-----
Omega = 1.1
Residual after error 2000 interations = 3.4113e-02
Time to run SOR = 92.3514

```

```

Omega = 1.2
Residual after error 2000 iterations = 3.3869e-02
Time to run SOR = 103.5740

Omega = 1.3
Residual after error 2000 iterations = 3.3570e-02
Time to run SOR = 107.5515

Omega = 1.4
Residual after error 2000 iterations = 3.3190e-02
Time to run SOR = 106.1925

Omega = 1.5
Residual after error 2000 iterations = 3.2686e-02
Time to run SOR = 116.8397

Omega = 1.6
Residual after error 2000 iterations = 3.1975e-02
Time to run SOR = 105.1813

Omega = 1.7
Residual after error 2000 iterations = 3.0874e-02
Time to run SOR = 106.0727

Omega = 1.8
Residual after error 2000 iterations = 2.8888e-02
Time to run SOR = 105.2235

Omega = 1.9
Residual after error 2000 iterations = 2.3957e-02
Time to run SOR = 103.5844

```

GMRES-100

```

tic
[~,~,~,iterGM,rGM] = gmres(A,F,[100],tol,max_iter);
time = toc;
% Produces results
fprintf('          ----- \n');
fprintf('          |  GMRES-100  |  \n');
fprintf('          ----- \n');
fprintf('          Residual error after %4.0f %4.0f inner and outter iterations = %1.4e \n...',
,iterGM(1),iterGM(end),rGM(end))

```

```
fprintf('      Time to run CG = %2.4f\n\n',time)
```

```

-----
|  GMRES-100  |
-----
Residual error after 79 37 inner and outter iterations = 3.5575e-08
Time to run CG = 10156.5268

```

PGMRES-100

```

tic
setup.type = 'nofill';
[L,U] = ilu(A,setup);
[~,~,~,iterPGM,rPGM] = gmres(A,F,[100],tol,max_iter,L,U);
time = toc;
% Produces results
fprintf('          ----- \n');
fprintf('          |  PGMRES-100  | \n');
fprintf('          ----- \n');
fprintf('      Residual error after %4.0f %4.0f inner and outter iterations = %1.4e \n...',
,iterPGM(1),iterPGM(end),rPGM(end))
fprintf('      Time to run CG = %2.4f\n\n',time)

rSOR = rSOR{index};
m_iter = max([iterJ,iterBLK,iterGS,iterSOR(index),sum(iterGM),sum(iterPGM)]);
m_res = max([rJ(1),rBLK(1),rGS(1),rSOR(1),rGM(1),rPGM(1)]);

```

```

-----
|  PGMRES-100  |
-----
Residual error after 20 59 inner and outter iterations = 6.0384e-08
Time to run CG = 2749.8409

```

Plotting commands

```


semilogy(rJ,'c'); hold on
semilogy(rBLK,'k'); hold on
semilogy(rGS,'r--');hold on
semilogy(rSOR,'b-.');hold on
semilogy(rGM,'g');hold on
semilogy(rPGM,'c--');hold on

```

```

axis([0 m_iter tol m_res]);
legend('Jacobi','block Jacobi','GS',['SOR-omega=',num2str(omega(index))]\...
,'GMRES','GMRES-ilu','Location','Best')
xlabel('Iterations','fontsize',14);
ylabel('Residual error','fontsize',14);

```



```

function [A] = ConvectionDiffusion(beta,gamma,n)

    e = ones(n,1);

    % Creating sparse diagonal matrices
    I = spdiags(e,0,n,n);
    I1 =spdiags(e,1,n,n);
    I2 = spdiags(e,-1,n,n);

    % Creating 1D Convection-Diffusion matrices
    Abeta = 2*I +(beta-1)*I1 - (beta+1)*I2;
    Agamma = 2*I +(gamma-1)*I1 - (gamma+1)*I2;

    % applying boundary conditions
    AbetaBC = [1 sparse(1,n+1);[-(beta+1); sparse(n-1,1)] ...
        Abeta [sparse(n-1,1); beta-1];sparse(1,n+1) 1];
    AgammaBC = [2 -2 sparse(1,n);[-(gamma+1); sparse(n-1,1)]...

```

```

        Agamma [sparse(n-1,1); gamma-1];sparse(1,n) -2 2 ];

% Creating 2D Convection-Diffusion matrix
A = kron(AbetaBC,speye(n+2))+kron(speye(n+2),AgammaBC);

end

function [x,rJ,i] = Jacobi(max_iter,tol,x,A,b)
% Jacobi method
tic
% Creating vector of diagonals of A
D = spdiags(A,0);
b_norm = norm(b);
r = b;

% Carrying out Jacobi
for i = 1:max_iter

    % updating x
    x = x + r./D;
    r = b-A*x;
    rJ(i) = norm(r);

    if (rJ(i)/b_norm) < tol
        break
    end
end
time = toc;
% Produces results
fprintf('----- \n');
fprintf('|      Jacobi      | \n');
fprintf('----- \n');
fprintf('      Residual after error %4.0f iterations = %1.4e \n'...
,i,rJ(i))
fprintf('      Time to run Jacobi = %2.4f\n\n',time)
end

function [x,rJ,i] = BLKJacobi(max_iter,tol,x,A,b)
% Jacobi method
tic
% Creating Block Jacobi
BLKjac = spdiags([spdiags(A,-1),spdiags(A,0),spdiags(A,1)]...
,[-1:1],(n+2)^2,(n+2)^2);
b_norm = norm(b);

```

```

r = b;
% Factoring BLKjac so can use backwards and forwards substitution at
% each step
[LowT,UpT,Piv] = lu(BLKjac,'vector');
% Carrying out BLKJacobi
for i = 1:max_iter

    % updating x
    x = x + UpT\ (LowT\ (r(Piv,:)));

    r = b-A*x;
    rJ(i) = norm(r);

    if (rJ(i)/b_norm) < tol
        break
    end
end
time = toc;
% Produces results
fprintf('
----- \n');
fprintf('      BLK Jacobi      \n');
fprintf('----- \n');
fprintf('      Residual after error %4.0f iterations = %1.4e \n'...
,i,rJ(i))
fprintf('      Time to run Jacobi = %2.4f\n\n',time)
end

function [x,rGS,i] = GS(max_iter,tol,x,A,b)
tic
% Creating lower triangular
E = tril(A);
b_norm = norm(b);
r = b;

% Carrying out GS
for i = 1:max_iter

    % updating x
    x = x + E\r;
    r = b-A*x;
    rGS(i) = norm(r);

    if (rGS(i)/b_norm) < tol
        break
    end
end
end

```



```

time = toc;
% Produces results
fprintf('          ----- \n');
fprintf('          | Gauss-Siedel | \n');
fprintf('          ----- \n');
fprintf('      Residual after error %4.0f iterations = %1.4e \n'...
        ,i,rGS(i))
fprintf('      Time to run GS = %2.4f\n\n',time)
end

```

```

function [x,rSOR,i] = SOR(max_iter,tol,x,A,b,omega)
tic
% Creating lower triangular
E = tril(A);
[N,~] = size(A);
% Creating sparse diagonal matrix
D = spdiags(spdiags(A,0),0,N,N);

% Calculating the matrix which we need to solve at each step
S = ((1/omega-1)*D+E);
b_norm = norm(b);
r = b;

% Carring out SOR
for i = 1:max_iter

    % updating x
    x = x + S\r;
    r = b-A*x;
    rSOR(i) = norm(r);

    if (rSOR(i)/b_norm) < tol
        break
    end
end
time = toc;
% Produces results
fprintf('      Omega = %1.1f \n',omega)
fprintf('      Residual after error %4.0f iterations = %1.4e \n'...
        ,i,rSOR(i))
fprintf('      Time to run SOR = %2.4f\n\n',time)
end

```

end