Report Reproducibly with

Slides CC BY-SA RStudio

Navigate to the **05-Report** folder.

Open **05-Report-Exercises.Rmd**

R Markdown

R Markdown

Plain text file with 3 types of content:



CC BY-SA RStudio

How it works



CC BY-SA RStudio

Logistics

1 Knitr runs the document in a fresh R session, which means you need to load the libraries that the document uses *in the*

CC BY-SA RStudio

Logistics

1 Knitr runs the document in a fresh R session, which means you need to load the libraries that the document uses *in the*

2 Objects made in one code chunk will be available to code in later code

CC BY-SA RStudio

knitr is multi-lingual!

- ☑ SAS
- ☑ python
- ☑ more

CC BY-SA RStudio

engine

python

To embed non R code, change the chunk label from r to the language to

```
Some python code,
```{python}
x = 'hello, python world!'
print(x)
print(x.split(' '))
```
```

Some python code:

```
x = 'hello, python world!'
print(x)
print(x.split(' '))
```

```
## hello, python world!
## ['hello,', 'python', 'world!']
```

CC BY-SA RStudio

Reticulate

Python in R Markdown

(Optional) Build Python env to use.

Add **knitr::knit_engines$set(python = reticulate::eng_python)** to the setup chunk to set up the reticulate Python engine (not required for knitr >= 1.18).

Suggest the Python environment to use, in your setup chunk.

Begin Python chunks with **```{python}**. Chunk options like **echo**, **include**, etc. all work as expected.

Use the **py** object to access objects created in Python chunks from R chunks.

Python chunks all execute within a **single** Python session so you have access to all objects created in previous chunks.

Use the **r** object to access objects created in R chunks from Python chunks.

Output displays below chunk, including matplotlib plots.

python.Rmd

Knit Insert Run

```{r setup, include = FALSE}
library(reticulate)
virtualenv_create("fmri-proj")
py_install("seaborn", envname = "fmri-proj")
use_virtualenv("fmri-proj")
```

```{python, echo = FALSE}
import seaborn as sns
fmri = sns.load_dataset("fmri")
```

```{r}
f1 <- subset(py$fmri, region == "parietal")
```

```{python}
import matplotlib as mpl
sns.lmplot("timepoint","signal", data=r.f1)
mpl.pyplot.show()
```

R Console

21:4 (Top Level) R Markdown

A package for using R and Python together.





bookdown.org/yihui/rmarkdown/

ONLINE, FREE

CC BY-SA RStudio

Markdown

R-Notebook.Rmd

Preview Insert

```
---
title: "R Notebook"
output: html_notebook
---

Text written in **markdown**

```{r}
# code written in R
(x <- rnorm(7))
```

[1] -1.2 1.0 -0.5 0.9 -0.6 -1.1 -1.5

Text written in _markdown_

```{r}
# code written in R
```
```

16:20 Chunk 2 R Markdown

Text in markdown

Headers

Use # to create headers.
Multiple #'s create lower level

```
# Header 1
## Header 2
### Header 3
#### Header 4
##### Header 5
###### Header 6
```



CC BY-SA RStudio

Text

Add two spaces at the end of a line to start a

Text is rendered as plain text.
Surround text with _, **, or ` to

```
Text
_italics_
**bold**
`code`
```

Text
italics
bold
`code`

CC BY-SA RStudio

Lists

Use asterisks to make bullet points.
Use numbers to make numbered

```
Bullets

* bullet 1
* bullet 2

Numbered list

1. item 1
2. item 2
```

Bullets

- bullet 1
- bullet 2

Numbered list

1. item 1
2. item 2

CC BY-SA RStudio

Hyperlinks

Use brackets to denote a link. Place the URL in

```
This is a
[link](www.git.com).
```

This is a link.

CC BY-SA RStudio

Images

Use a link preceded by an ! to insert an image.

The link text should be a URL (if the image is hosted

```
![](images/1.png)
The RStudio logo.
```



The RStudio logo.

CC BY-SA RStudio

Equations

Write equations with latex math commands and surround them in

```
According to
Einstein,
$E=mc^{2}$
```

According to Einstein, $E = mc^2$

CC BY-SA RStudio

Equation blocks

Use two $'s to make centered equation

```
According to
Einstein,

$$E=mc^{2}$$
```

According to Einstein,

$$E = mc^2$$

CC BY-SA RStudio

Markdown

Dictionary of formatting cues.



on back of RMarkdown cheat sheet

IDE Reference

Go to **Help > Markdown Quick Reference**



Code

R-Notebook.Rmd

Preview Insert

```
---
title: "R Notebook"
output: html_notebook
---

Text written in **markdown**

```{r}
# code written in R
(x <- rnorm(7))
```

[1] -1.2 1.0 -0.5 0.9 -0.6 -1.1 -1.5

Text written in _markdown_

```{r}
# code written in R
```
```

16:20 Chunk 2 R Markdown

Code chunks surrounded by ```

Code chunks

Insert a chunk of R code with

```
```{r}
# some code
```
```

When you render the report, R Markdown will run the code and include its results. R Markdown will also remove the ```{r} and ```.

CC BY-SA RStudio

Code chunks

Insert a chunk of R code with

```
```{r}
# some code
```
```

⌘ + Opt + i (Mac

Ctrl + Alt + i (PC)

CC BY-SA RStudio

chunk options

By default, R Markdown includes both the code and its results

```
Here's some code
```{r}
dim(iris)
```
```

Here's some code

```
dim(iris)
```

```
## [1] 150   5
```

CC BY-SA RStudio

echo

Add options in the brackets after r.
echo = FALSE hides the code.

```
Here's some code
```{r echo=FALSE}
dim(iris)
```
```

Here's some code

```
## [1] 150   5
```

Very useful for plots

CC BY-SA RStudio

eval

eval = FALSE prevents the code from being run. As a result, no results will be displayed

```
Here's some code
```{r eval=FALSE}
dim(iris)
```
```

Here's some code

```
dim(iris)
```

CC BY-SA RStudio

include

include = FALSE runs the code, but prevents both the code and the results from appearing (e.g. to

```
Here's some code
```{r include=FALSE}
dim(iris)
```
```

Here's some code

CC BY-SA RStudio

fig.height, fig.width

Specify the dimension of plots (in inches) with fig.width and fig.height. Separate multiple arguments with commas.

```
Here’s a plot
```{r echo=FALSE, fig.width=3, fig.height=5}
hist(iris[[2]])
```
```



CC BY-SA RStudio

Pop Quiz

Do you notice the **TODOs** in 05-RMarkdown-Exercises.Rmd?

Do you notice the long **setup** chunk**?**

CC BY-SA RStudio

Inline code

Place code in a sentence with **`r <code>`**. R Markdown will replace the code with its

```
Today is
`r Sys.Date()`.
```

Today is 2015-04-16.

CC BY-SA RStudio

Inline code

Code whose results are inserted into the

```
Today is `r Sys.Date()`.
```

Surround with `r `

Code to run. Only the result will be included.

CC BY-SA RStudio

Your Turn 1

In **05-RMarkdown-Exercises.Rmd**:

1. Replace every Garrett with your name
2. Replace every TODO with inline R code
3. Check that the setup chunk is not included with the output
4. Ensure that only the output of the plot chunk is shown (not the code)
5. Knit the document

05:00

CC BY-SA RStudio

YAML

R-Notebook.Rmd

Preview Insert

```
---
title: "R Notebook"
output: html_notebook
---

Text written in **markdown**

```{r}
# code written in R
(x <- rnorm(7))
```

[1] -1.2 1.0 -0.5 0.9 -0.6 -1.1 -1.5

Text written in _markdown_

```{r}
# code written in R
```
```

16:20 Chunk 2 R Markdown

A YAML header surrounded

YAML

A section of key:value pairs
separated by dashed lines — — —

```
---
title: "Untitled"
author: "RStudio"
date: "February 4, 2015"
output: html_document
---
Text of document
```



CC BY-SA RStudio

output

The output: field sets the format of the final report

on back



output value	creates
html_document	html
pdf_document	pdf (requires Tex)
word_document	Microsoft Word (.docx)
odt_document	OpenDocument Text
rtf_document	Rich Text Format
md_document	Markdown
github_document	Github compatible markdown
ioslides_presentation	ioslides HTML slides
slidy_presentation	slidy HTML slides
beamer_presentation	Beamer pdf slides (requires Tex)

More at rmarkdown.rstudio.com/formats.html

CC BY-SA RStudio

Parameters

Your Turn 2

Open **05-RMarkdown-Parameters.Rmd**.

Click the dropdown menu next to Knit and use **Knit with Parameters** to render the document.

What happens if you type in a different name?

02:00

CC BY-SA RStudio

Parameters

A list of values that you can call in R code chunks

```
---
title: "Untitled"
output: html_document
params:
  filename: "data.csv"
  symbol: "FB"
---
```

params list

elements and values

colon

New line. Indented two spaces

CC BY-SA RStudio

Using Parameters

Call parameter values as elements of the params list, **params$num**

```
---
params:
  num: 42
---
The value of the
parameter is
`r params$num`, e.g.

```{r}
params$num
```
```

The value of the parameter is 42, e.g.

```
params$num
```

```
## [1] 42
```

CC BY-SA RStudio

render() + for

```
names <- c("Alice", "Bob", "Cathy")

for (name in names) {
  render("05-RMarkdown-Parameters.Rmd",
         params = list(data = name))
}
```

CC BY-SA RStudio

THIN PAPER
LIGHT TRACING CLOTH

Demo

CC BY-SA RStudio

Report Reproducibly with

Slides CC BY-SA RStudio

Thank you

CC BY-SA RStudio



Please take the class survey
rstd.io/class-survey

Editable course material at
rstd.io/remaster-the-tidyverse

Ask your questions
community.rstudio.com

CC BY-SA RStudio