



APPFORUM2014

Helping the developer community build
next-generation, multi-platform apps.



SCHAUMBURG, ILLINOIS | SEPTEMBER 8-10

CREATING MULTIPLE RHODES APPS THAT ARE ALL THE SAME... BUT DIFFERENT



“WAH WATUSI”
The Orlons
1962 Peaked @ #2

Jon Tara | Chief Code-Wrangler, Watusiware Corporation

APPFORUM2014



MOTOROLA SOLUTIONS

WATUSIWARE CORPORATION



THEY'RE ALL THE SAME...

... BUT THEY'RE DIFFERENT



We often need to create multiple apps that are very similar... but different.

How can we do that without reinventing the wheel each time?






ABOUT ME



MY FIRST COMPUTER

IBM 1620, Circa 1971


- 20K BCD Digit Core Memory
- 5000 instructions/sec MAX (simple branch)



AND THEN THESE...



TO DO THIS...





THE PROBLEM

THEY'RE ALL THE SAME...

... BUT THEY'RE DIFFERENT



We often need to create multiple apps that are very similar... but different.

How can we do that without reinventing the wheel each time?



THEY'RE ALL THE SAME...


... OR ARE THEY?



NBC LA
News



NBC New York
News



NBC Chicago
News



NBC 6 South
Florida
News



Do they all have a “troubleshooter”?
Do they all have a regular sportsfishing segment?

THEY'RE ALL THE SAME...

... BUT THEY'RE DIFFERENT...



BOO, NO PANDAS! ☹️



SanDiegoZoo
Travel

Downloaded ▾



Cincinnati Zoo
Entertainment

Free ▾



Smithsonian's
National Zoo
Travel

\$1.99 ▾



Detroit Zoo App
Travel

+\$1.99 ▾

YAY, PANDAS! 😊

THREE RUBY MANTRAS



WE'LL KEEP COMING BACK TO THIS...

- Don't Repeat Yourself
 - "Every piece of knowledge must have a single, unambiguous, authoritative representation within a system." – Dave Thomas
- Convention Over Configuration
- Configuration Over Code

APP GENERATORS

ONE WAY TO DO IT




AN APPLICATION THAT CREATES
APPLICATIONS



Taylor Swift
Music



Madonna
Music



**The Rolling
Stones Official...**
Music



**Katy Perry Mobile
App**
Music



Dean Koontz
Books



APP GENERATORS



lim·i·ta·tion

/ˌlɪməˈtāʃən/ 

noun

1. a limiting rule or circumstance; a restriction.
"severe **limitations** on water use"

- Typically meant for a specific category of application
- Formulaic
- Can be inflexible
- May lack “escape hatches”
- Still can take a lot of work to create content

COPY THE APP AND GO FROM THERE...

THE NAÏVE' CHOICE



- Fast out of the gate – you start with a working app!
- But how to manage updates? Do you incorporate them into derived app?
- Drift, drift, and more drift
- Need a way to keep app features in sync

CREATE SOME LIBRARIES

EXTRACT COMMON CODE TO LIBRARIES



- Avoids duplication of effort
- Can package functionality in nice, neat units
- Interfaces and specifications, and versions, oh my!
- Maintaining compatibility can take a significant effort
- We can easily descend into “Dependency Hell”

CREATE ME SOME GIT BRANCHES



THERE'S A BRANCH FOR THAT!

- Gives you some tools for maintaining multiple similar apps
 - branch, merge
- And of course gives us other great benefits
- But we're using version control already anyway, right?
- Impractical for more than a small number of apps
- Walking away from a branch for some time can have serious consequences



CENTER FOR ENERGY AND ENVIRONMENT

CENTER FOR ENERGY AND ENVIRONMENT




DOES...

- Program Design and Delivery
- Research
- Engagement and Education
- Energy Policy
- Lending Center
- Engineering Services



WORKING WITH...

- Homeowners
- Businesses and Non-Profits
- Rental Property Owners
- Government




<http://mncee.org>

CEE MOBILE APPS

6 1/2 APPS FOR PERFORMING ENERGY AUDITS



- Home Energy Retrofit Index (HERI)
- Residential (MiScore-R 2012 and 2014)
- Commercial
- Green Iowa
- Electricities of North Carolina
- Min (common features only)



CEE MOBILE APPS



Carrier 3:15 PM

SUMMARY

1525 Reeves Ct [Two HVAC & DHW]

House Information

Year Built *	2002
House Type *	Single Family
Number of Bedrooms *	5
Approximate floor area *	3000-4000
Occupants Age 19+ *	2
Occupants Age < 19 *	0

Attic Insulation

No SqFt - Unconditioned Attic

Attic Cavity R Value *	R-16.0
Access type *	Walk Up
Access door condition *	Fair

Insulation thickness is very uneven, with very thin or no insulation in several places.

Carrier 3:19 PM

SUMMARY

1525 Reeves Ct [Two HVAC & DHW]

How can we contact the customer for audit service follow up? No

Can we contact the customer later for follow up? No

House Information

Year Built *	2002
House Type *	Single Family
Number of Bedrooms *	5
Approximate floor area *	3000-4000
Occupants Age 19+ *	2
Occupants Age < 19 *	0

Carrier 3:21 PM 100%

SUMMARY

1525 Reeves Ct [Two HVAC & DHW]

Audit Information

Image Gallery

Location

Contacts

Services

House Information

Year Built *	2002
House Type *	Single Family
Number of Bedrooms *	5
Approximate floor area *	3000-4000
Occupants Age 19+ *	2
Occupants Age < 19 *	0

Attic Insulation

No SqFt - Unconditioned Attic

Attic Cavity R Value *	R-16.0
Access type *	Walk Up
Access door condition *	Fair

Insulation thickness is very uneven, with very thin or no insulation in several places.

Wall Insulation

Wall Cavity R value *	R-14.3
-----------------------	--------

Could not verify if insulation is full depth.

Foundation

Foundation type *	Vented Crawlspace
Floor R-Value *	R-7.8

Windows

Number of single pane *	5
Number of double pane *	12

Heating Systems

1) 50% - 1st Floor

Fuel Type *	Natural Gas
System Type *	Furnace (Forced Air)
Year installed *	1995
Thermostat type *	Mechanical
Regular maintenance *	No
Filter maintenance *	Yes
System condition *	Fair


2) 50% - 2nd Floor

Fuel Type *	Electric
System Type *	Heat Pump (Air Source)
Year installed *	1995
Thermostat type *	Programmable

CEE MOBILE APPS

miScore-R (2012, 2013)

- Home Energy Audits
- Creates Energy Label
- Scoring: DOE Berkeley Lab



Lawrence Berkeley
National Laboratory



U.S. DEPARTMENT OF
ENERGY


CEE MOBILE APPS

miScore-C

- Commercial Building Audits
- Creates Energy Label
- Scoring: DOE Pacific Northwest National Laboratory
- Most complex data collection



Proudly Operated by **Battelle** Since 1965





Watusiware Corporation



Agile Mobilesoft, LLC

cee

Center for Energy
and Environment



GREEN IOWA
AMERICORPS



ELECTRICITIES
of NORTH CAROLINA, INC.
The energy behind public power



U.S. DEPARTMENT OF
ENERGY



Pacific Northwest
NATIONAL LABORATORY

Proudly Operated by Battelle Since 1965

U.S. DEPARTMENT OF
ENERGY



TOOLS



RVM

RVM



RVM is a command-line tool which allows you to easily install, manage, and work with multiple ruby environments from interpreters to sets of gems

- Allows you to maintain and easily switch between multiple Ruby versions
- And “gemsets” – sets of Gems you can easily switch
- Unfortunately, OSX and Linux only – Windows: try pik
- For windows, rvm can be installed if you can tolerate Cygwin
- Motorola has helpful documentation for using rvm
- Do not do a “root” installation – install in user directory
- Allows us to maintain separate Ruby/RubyGem environments for Prepare and Rhodes build

<http://rvm.io>



iTerm 2

iTerm 2



iTerm 2 is a terminal emulator for Mac OS X that does amazing things

- **Tabs**
- **Split Panes**
- **Search**
- **Auto-complete**
- **Paste History**
- **Scrollback buffer**

<http://iterm2.com>



Zsh



Zsh is a shell designed for interactive use, although it is also a powerful scripting language

- **Command completion**
- **Pattern-matching/globbing on alien steroids**
- **Themeable prompts**
- **Loadable modules**
- **Spelling correction**
- **Shares command history among running shells**
- **Global aliases**
- **All this – and more**

<http://www.slideshare.net/jaguardesignstudio/why-zsh-is-cooler-than-your-shell-16194692>

<http://www.zsh.org>



oh-my-zsh

oh-my-zsh



oh-my-zsh is an open source, community-driven framework for managing your Zsh configuration

- 150+ plugins
- 600+ contributors
- 100+ themes

My installed plugins:

```
plugins=(autojump brew gem rake-fast git node npm osx rvm sublime)
```

<http://ohmyz.sh>

<https://github.com/robbyrussell/oh-my-zsh>



RAKE

Ruby's “make”

RAKE




THANKS TO JIM WEIRICH – 1956-2014

Rake (inventor)

Builder (contributor)

RubyGems (collaborator)

**Thank you, Jim.
We'll miss you deeply.**



RAKE



- The standard Ruby build tool
- Use it to help build anything not just Ruby
- However, we will use it in a very stupid way



{{MUSTACHE}}

Mustache



- **Logic-less templates for many languages. (We care about Ruby)**
- **Meant for HTML, but works with any kind of text file**
- **Simple, high-readable syntax**
- **Doesn't look a thing like ERB (this is good!)**
- **Simple text insertion, helpers, partials**

We will process almost EVERY source file through Mustache!

- **HTML**
- **ERB**
- **RB**
- **JS**
- **Etc.**

Mustache Example: simple text substitution



Conducting an “audit”? Or making a “visit”?

```
:imported_on => {  
  :field_label => '{{audit.name}} Imported on',  
  :description => 'If this {{audit.name}} was imported, this is the  
time stamp of the import' },  
:exported_on => {  
  :field_label => '{{audit.name}} Exported on',  
  :description => 'If this {{audit.name}} has been exported, this is  
the time stamp of the export'},
```

Mustache Example:build.yml



7 Apps. One build.yml...

#--- The name of the application is the string literal attached to the icon on the smartphone and can include spaces
#--- This is the string which gets displayed in the title bar area on Android.

```
name: "{{app.name}}"
```

Whoa! Watch out!

#--- **Make sure this corresponds with the application_version in rhoconfig.txt**

```
version:
```

```
"{{app.major_version}}.{{app.minor_version}}.{{app.build_number}}"
```



Mustache Example:

rhoconfig.txt

Not to worry...

```
cee_application_version_prior = 'none'  
cee_application_version_first_start = ''  
cee_application_version =  
'{{app.major_version}}.{{app.minor_version}}.{{app.build_number}}'  
cee_application_build_date = '{{build.time.date_str}}'  
cee_application_build_type = '{{build.type}}'
```

(Yes, we pollute rhoconfig.txt with our own keys. It's a convenient place for run-time configuration data. Don't do this at home. Rhom would be a better place....)

Mustache Example: build.yml



```
ios-common: &ios-common
  entitlements:      ""
  configuration:     Release
  BundleURLScheme:  "{{build.reverse_domain_identifier}}.{{build.product}}"
  BundleIdentifier:  "{{build.reverse_domain_identifier}}.{{build.product}}"
  sdk:
    "iphone{{build.ios.target.sdk.type}}{{build.ios.target.sdk.version}}"
iphone-simulator: &iphone-simulator
  <<: *ios-common
  emulatortarget:  "{{build.ios.target.device}}"
  emulator:        "{{build.ios.target.sdk.version}}"
iphone-hardware: &iphone-hardware
  <<: *ios-common
  codesignidentity:  "{{build.ios.development.code_sign_identity}}"
  provisionprofile:  "{{build.ios.development.provisioning_profile}}"
iphone-adhoc: &iphone-adhoc
  <<: *ios-common
  codesignidentity:  "{{build.ios.adhoc.code_sign_identity}}"
  provisionprofile:  "{{build.ios.adhoc.provisioning_profile}}"
```

Mustache Example

INCLUDE IF TRUE



```
def choose_options
  options = camera_options
  {{^photo.choose_photo_obeyes_resolution_preference}}
    options.delete :desired_width
    options.delete :desired_height
  {{/photo.choose_photo_obeyes_resolution_preference}}
  options
end
```



deep_merge

deep_merge



A RubyGem for efficiently and flexibly merging deeply-nested hashes and lists

- **Warning:** This is NOT ActiveSupport deep_merge! (It's much more.) Watch out for conflict. (workaround on website)
- Recursively merges hashes
- Top level must be a hash
- Below top level can be hash, list, simple data types (string, number, etc.)
- You can optionally “drop out” complete hashes and lists (-- prefix)

```
require 'deep_merge'

x = {:x => [3,4,5]}
y = {:x => [1,2,3]}

y.deep_merge!(x)

# results: y = {:x => [1,2,3,4,5]}
```

github.com/danielsdeleo/deep_merge

deep_merge

EXAMPLE



```
require 'deep_merge'
x = {:x => [3,4,5]}
y = {:x => [1,2,3]}
y.deep_merge!(x)
# results: y = {:x => [1,2,3,4,5]}
```

deep_merge

WHAT WILL WE USE THIS FOR?

- We can merge data loaded from multiple YAML configuration files
- Product configuration data overrides framework configuration data
- We'll reference these merged structures from template tags in our Rhodes source files.



Can we use deep_merge in Rhodes, too?



Yes! It's a small pure-Ruby Gem. Just extract the library (four files) from the Gem.



uglify

Uglifier



A Ruby wrapper for the UglifyJS JavaScript compressor

- Popular Javascript compressor
- Safe
- UglifyJS is written in Javascript, but runs on desktop. You do not need to install a desktop JS environment – everything is built-in to the Gem
- Make sure to disable Rhodes' built-in JS compression in build.yml

```
obfuscate:
```

```
  js: no
```

```
  css: no
```

```
minify:
```

```
  js: no
```

```
  css: no
```

Uglifier: Prepare log



```
app/Skylight/skylight_edit
app/Wall/wall_edit
app/Window/envelope_window_edit
app/Floor/floor_edit
app/Fixture/fixture_edit
app/Plant/plant_edit
app/AirHandler/air_handler_edit
app/ZoneEquipment/zone_equipment_edit
app/WaterHeater/water_heater_edit
app/Operation/operation_edit
```

Minifying 71 Javascript files, 1090143 bytes (be patient...)

Minified to 399329 bytes

Uglifier: COMPRESSED OUTPUT



Some fine gobbledygook...

```
function jqmIscrollviewRemoveLayerXYProps(e){delete e.layerX,delete
e.layerY}function non_edit_key(e){var t={};return t[0]="Num
Lock",t[9]="Tab",t[13]="Enter",t[16]="Shift",t[17]="Ctrl",t[18]="Alt",t[20]=
"Caps Lock",t[27]="Esc",t[33]="Page Up",t[34]="Page
Down",t[35]="End",t[36]="Home",t[45]="Insert",t[91]="Windows",t[112]="F1",t[
113]="F2",t[114]="F3",t[115]="F4",t[116]="F5",t[117]="F6",t[118]="F7",t[119]
="F8",t[120]="F9",t[121]="F10",t[122]="F11",t[123]="F12",t.hasOwnProperty(e)
}function file_system_name_check(e){var t=e.val(),i=e.val();return
i=i.replace(/[\\0\\f\\r\\t\\v\\\\\\: \\* \\? \\\" \\< \\> \\| \\ \\_ \\_]/g,"-
"),t!=i?(e.val(i),!1):!0}function file_system_name_error(e,t){var
i=e.closest(".ui-page"),n=i.find(".name-check-popup"),o=n.find(".field-
name"),a=(n.find(".original-name"),n.find(".disallowed-
characters")),s=n.find(".repaired-name");o.text(t),a.text('/ \\ : * ? " < >
| . _'),s.text(e.val()),n.jqmData("associated-
element",e),n.popup("open")}function
```


Uglifier: BUNDLE EXCLUSION



When compressing, exclude source files from the app bundle in build.yml

```
excludedirs:
  all:
    - "**/*.orig.*"          # A convenience - developer might copy file with .orig
    - "**/unused"            # Another developer convenience - handy sometimes to st
    - "**/reference"         # similar to unused, just semantics. Reference material
    - "**/*.vendor.*"        # We might want to keep an original vendor file for ref
    - "**/*.bak"
    - "**/*.sw[on]"          # Java swap file - created by Eclipse
    - "**/*.s[ac]ss"         # Sass source files
    - "public/js/jqmobile-patch.js"
    - "public/bourbon"      # .scss already excluded, but let's exclude the director
    {{#build.minify_js}}
    - "**/*.js"              # We use a .min-js extension as a kludge around non-neg
    - "/app/public/jquery"  # Just empty directory if minifying JS, so exclude
    {{/build.minify_js}}
    {{#audit.exclude_framework_classes}}
    - "app/{{.}}"           # Things in the framework that we explicitly want to ex
    {{/audit.exclude_framework_classes}}
  iphone:
```



colorize

colorize



A small RubyGem for adding color to your console output

- Make your console output purty, just like Rhodes command-line build
- Change string color
- Change string background
- Change string effect
- Needs ANSI console

```
puts "This is blue".colorize(:blue)
puts "This is light blue".colorize(:light_blue)
puts "This is also blue".colorize(:color => :blue)
puts "This is light blue with red background".colorize(
  :color => :light_blue, :background => :red)
puts "This is blue text on red".blue.on_red
```

<https://github.com/fazibear/colorize>

Colorize

SAMPLE OUTPUT



```
framework/app/partials [dir]
framework/app/partials/_menu.erb -> build/ios/miscore-c/development/simulator/7.1/app/partials/_menu.erb
framework/app/partials/_menu_item.erb -> build/ios/miscore-c/development/simulator/7.1/app/partials/_menu_item
framework/app/preloader.rb -> build/ios/miscore-c/development/simulator/7.1/app/preloader.rb
^ File has data in framework and product, showing merged data:
---
build:
  product: miscore-c
  type: development
  time:
    date_str: 09/05/2014
    time_str: '19:34:33'
    stamp: 1409970873
  minify_js: false
  js_debug: true
  js_debug_debug: true
```



SASS

Syntactically Awesome Style Sheets

SASS



A CSS Preprocessor with SuperPowers

- CSS can be painful to write. Sass eases the pain

<http://sass-lang.com>



BOURBON

BOURBON



A SIMPLE AND LIGHTWEIGHT MIXIN LIBRARY FOR SASS

- Writes vendor-prefixing for you
- Many other utility functions
- A solution to the flex-box mess

<http://bourbon.io>

BOURBON

EXAMPLE



```
// Bourbon mixin with Sass  
  
section {  
  @include linear-gradient(to top, red, orange);  
}
```

```
/* Compiled CSS */  
  
section {  
  background-color: red;  
  background-image: -webkit-linear-gradient(bottom, red, orange);  
  background-image: linear-gradient(to top, red, orange);  
}
```



PREPARE

PREPARE



A rakefile task for creating app source directories from a base framework, a product-specific overlay, and configuration data

- Combine, transform, modify source files
- Follows conventions to do this in specific ways
- Emulates an overlay filesystem
- Every source file is potentially a Mustache template
- Uses YAML files to provide data to Mustache
- Compiles SASS files to CSS and optionally combines/minifies
- Optionally combines/minifies Javascript files

Prepare



Live Demo

PREPARE


PROJECT DIRECTORY STRUCTURE

- ▼ CeeMobileApps
 - ▶ docs
 - ▶ framework
 - ▶ git-hooks
 - ▶ herx
 - ▶ miaudit-ecnc
 - ▶ miaudit-gia
 - ▶ min
 - ▶ miscore-c
 - ▶ miscore-r-2012
 - ▶ miscore-r-2013
 - ▶ prepare
 - ▶ script
 - ▶ tool




PREPARE

BUILD DIRECTORY STRUCTURE



PREPARE

BUILD DIRECTORY STRUCTURE



PREPARE

UP-FRONT SUMMARY



```
➜ CeeMobileApps rake prepare:development[miaudit-ecnc]
```

```
Environment variables...
```

```
--- {}
```

```
*** gather_build_data @product = 'miaudit-ecnc'
```

```
Preparing product miaudit-ecnc for development using iOS simulator 7.1 SDK for simulator deployment...
```

```
102 Product files
```

```
651 Framework files
```

```
Excluding bin from target directory clean
```

```
Excluding project from target directory clean
```


PREPARE



1. COPY PRODUCT FILES

Copying product files to build target...

```
miaudit-ecnc/README-prepare-sanity-check.txt -> build/ios/miaudit-ecnc/development/s
miaudit-ecnc/app [dir]
miaudit-ecnc/app/Appliance [dir]
miaudit-ecnc/app/Appliance/appliance.rb -> build/ios/miaudit-ecnc/development/simula
miaudit-ecnc/app/Appliance/appliance_controller.rb -> build/ios/miaudit-ecnc/develop
miaudit-ecnc/app/Appliance/appliance_edit.js -> build/ios/miaudit-ecnc/development/s
miaudit-ecnc/app/Appliance/edit.erb -> build/ios/miaudit-ecnc/development/simulator/
miaudit-ecnc/app/Attic [dir]
miaudit-ecnc/app/Attic/attic.rb -> build/ios/miaudit-ecnc/development/simulator/7.1/
miaudit-ecnc/app/Attic/attic_controller.rb -> build/ios/miaudit-ecnc/development/sim
miaudit-ecnc/app/Attic/attic_edit.js -> build/ios/miaudit-ecnc/development/simulator
miaudit-ecnc/app/Attic/edit.erb -> build/ios/miaudit-ecnc/development/simulator/7.1/
miaudit-ecnc/app/Attic/edit_list.erb -> build/ios/miaudit-ecnc/development/simulator
```



```
miaudit-ecnc/public/samples/import-sample-visits.csv -> build/ios/miaudit-ecnc/development/simulators
```

```
Copying framework files to build target...
```

```
framework/README [no-copy]
```

```
framework/README-prepare-sanity-check.txt [overridden]
```

```
framework/README-prepare-sanity-check2.txt -> build/ios/miaudit-ecnc/development/simulators
```

```
^ File has data in framework, showing merged data:
```

```
---
```

```
build:
```

```
  product: miaudit-ecnc
```

```
  type: development
```

```
  time:
```

```
    date_str: 09/08/2014
```

```
    time_str: '01:39:37'
```

```
    stamp: 1410165577
```

```
  minify_js: false
```

PREPARE



OVERRIDDEN FILES

```
framework/app/Location/_address_app_inputs.erb [overridden]
framework/app/Location/device_location.rb -> build/ios/miaudit-ecnc/development/simu
framework/app/Location/edit.erb -> build/ios/miaudit-ecnc/development/simulator/7.1/
framework/app/Location/location.rb -> build/ios/miaudit-ecnc/development/simulator/7
framework/app/Location/location_controller.rb -> build/ios/miaudit-ecnc/development/
framework/app/Location/location_edit.js -> build/ios/miaudit-ecnc/development/simula
framework/app/Location/location_help.html -> build/ios/miaudit-ecnc/development/simu
framework/app/Location/schema.rb [overridden]
framework/app/Location/summary_field_markup.rb -> build/ios/miaudit-ecnc/development

framework/app/Message [dir]
framework/app/Message/message.rb -> build/ios/miaudit-ecnc/development/simulator/7.1
framework/app/Message/message_controller.rb -> build/ios/miaudit-ecnc/development/si

framework/app/Photo [dir]
framework/app/Photo/edit.erb -> build/ios/miaudit-ecnc/development/simulator/7.1/app
framework/app/Photo/edit_list.erb -> build/ios/miaudit-ecnc/development/simulator/7.
```

PREPARE



3. COMPILE SASS, COMBINE, MINIFY

```
framework/unused/rhoconfig.jgtjr.production.txt [no-copy]
framework/unused/rhoconfig.rrj.development.txt [no-copy]
framework/unused/rhoconfig.rrj.production.txt [no-copy]
framework/xcode.rb -> build/ios/miaudit-ecnc/development/simulator/7.1/xcode.rb

Compiling Sass files to CSS...
build/ios/miaudit-ecnc/development/simulator/7.1/public/css/main.scss -> build/ios/miaudit-ecnc/development/simulator/7.1/public/css/main_x.scss
build/ios/miaudit-ecnc/development/simulator/7.1/public/css/main_x.scss -> build/ios/miaudit-ecnc/development/simulator/7.1/public/css/main_x.min.css
build/ios/miaudit-ecnc/development/simulator/7.1/public/css/layout_2_column.scss -> build/ios/miaudit-ecnc/development/simulator/7.1/public/css/layout_2_column.min.css
build/ios/miaudit-ecnc/development/simulator/7.1/public/css/tail.scss -> build/ios/miaudit-ecnc/development/simulator/7.1/public/css/tail.min.css
build/ios/miaudit-ecnc/development/simulator/7.1/public/css/dictionary_standalone.scss -> build/ios/miaudit-ecnc/development/simulator/7.1/public/css/dictionary_standalone.min.css

build.minify_js = false, skipping Javascript concatenation/minification

© → CeeMobileApps
```

© → CeeMobileApps



```
build/ios/miaudit-ecnc/development/simulator/7.1/public/css/dictionary_standalone.css
```

Concatenating Javascript files...

```
public/js/console
```

```
public/jquery/jquery-1.8.3
```

```
public/js/jquery-timeout
```

```
public/js/jquery.caret
```

```
public/js/jquery.haversine.0.2-ccc
```

```
public/js/jquery.mobile.custom
```

```
public/js/jquery.mobile.transition-handler-simple
```

```
public/js/jquery.mobile.simultaneous-transitions-replace-simple
```

```
public/jqmobile/jquery.mobile-1.2.1.ccc
```

```
public/js/iscroll
```

```
public/js/jquery.mobile.iscrollview
```

```
public/js/sketch
```



```
app/Location/location_edit_county  
app/House/house_edit  
app/Attic/attic_edit  
app/Wall/wall_edit  
app/Foundation/foundation_edit  
app/Heating/heating_edit  
app/Cooling/cooling_edit  
app/Duct/duct_edit  
app/HotWater/hot_water_edit  
app/Appliance/appliance_edit  
app/EcmChecklist/ecm_checklist_edit
```

Minifying 73 Javascript files, 1152463 bytes (be patient...)

Minified to 419458 bytes

PREPARE



MERGING YML DATA

- Data from YML files is merged using `deep_merge`
 - `Developers.yml`
 - Built-ins
 - Framework
 - Product
 - Developer
- Developer merged only if prepare for development
- Within each of framework and product, additional YML files (**caution: of dubious value!**)
 - Per-directory
 - Per file e.g. `building.rb`

PREPARE

DEFAULT ROOT DATA (RUBY)



```
@default_root_data = {  
  'build' => {  
    'product' => @product,  
    'type' => @build_type,  
    'time' => {  
      'date_str' => now.strftime('%m/%d/%Y'),  
      'time_str' => now.strftime('%H:%M:%S'),  
      'stamp' => now.to_time.to_i # Seconds since start of epoch  
    },  
    # All Javascript gets minified and aggregated into one main.js file  
    # (slow to prepare, not for debugging, but best runtime performance)  
    # If you want to build for development with minification, override  
    # build.minify_js in your root developer-specific nn.prepare.yml  
    'minify_js' => @build_type != 'development',  
    'js_debug' => false, # Developer should override in nn.prepare.yml  
  }  
}
```




```
'minify_js' => @build_type != 'development',
'js_debug' => false,           # Developer should override in nn.prepare.yml
'js_kybd_debug' => false,      # Developer should override if wanted
'js_calc_debug' => false,
'git_commit_hash' => @git_commit_hash, # SHA1 of this commit
'git_commit_short_hash' => @git_commit_short_hash,
'git_local_branch' => @git_local_branch,
'git_remote_branch' => @git_remote_branch,
'git_dirty' => @git_dirty, # true if git had uncommitted changes
'reverse_domain_identifier' => @developer_reverse_domain, # should this
'developer' => {
  'initials' => @developer_initials
},
'rvm' => {
  #'ruby_version' => '1.9.3-p547', # version of Ruby to build with
```



```
,
  'rvm' => {
    # 'ruby_version' => '1.9.3-p547',      # version of Ruby to build with
    # 'ruby_gemset'  => 'rhodes_4.1.0'     # gemset to use when building
    'ruby_version' => '2.1.2',             # version of Ruby to build with
    'ruby_gemset'  => 'rhodes_5.0.2'      # gemset to use when building
  },
  'ios' => {
    'xcode' => {
      'version' => '5.1.1'
    },
    'target' => {
      'device' => 'ipad',
      'environment' => @ios_target_environment,
      'sdk' => {
        'type' => @ios_target_sdk_type
      }
    }
  }
}
```

PREPARE

FRAMEWORK ROOT YML



```
prepare.yml
1 ---
2 app:
3   framework_version: "1.0.3"
4   title: unconfigured
5   long_title: unconfigured
6   description: unconfigured
7   app_mode: long
8   current_upgrade_fields: hide
9   survey_mode: disabled
10  unanswered_selector_indicator: "?"
11
12 photo:
13   choose_photo_obeyes_resolution_preference: true
14
15 database:
16   # We will automatically create an index for these properties
17   # Note: if you don't want to auto-index any properties, use
18   # alternative YML syntax auto_index_properties: []
19   auto_index_properties:
20     - audit_id
21   # Set to true to create a compound index for calc records
22   # [:audit_id, :model_name, :record_id, :field_name]
23   # Note that audit_id index is omitted for calc models in this case
```

PREPARE

FRAMEWORK ROOT YML



```
prepare.yml x
22 # [:audit_id, :model_name, :record_id, :field_name]
23 # Note that audit_id index is omitted for calc models in this case,
24 # as it is redundant. SQLite will just use the compound index if the
25 # audit_id index is omitted.
26 create_calc_compound_index: true
27
28 js:
29   epsilon: 0.0001 # Javascript does not define floating-point Epsilon. We'll
30
31 debug:
32   js:
33     detached_node_canary: false
34   css:
35     photo_page: false
36     sketch_page: false
37   rhodes_server:
38     use_fixed_port: false
39     port: 8080
40   weinre:
41     enable: false
42     host: localhost
43     port: 8081
44
```

PREPARE

FRAMEWORK ROOT YML



```
prepare.yml
43   port: 8081
44
45  audit:
46    name: Visit
47    name_plural: Visits
48    date_field_name: id_date
49    # Note: each product should define audit.child_classes, the ordered list of
50
51  dictionary:
52    include_survey_properties: false
53    include_value_list_values: true
54    # If the application has a primary API, then it should be set here
55    api_value_key: "api_val"
56
57  development:
58    debug:
59      logging:
60        # minimum level to log
61        # 0-trace, 1-info(app level), 2-warnings, 3-errors, 4-fatal errors
62        min_severity: 1
63        cee_log_preference: "info"
64        memory: false
65        memory_period: 20000 # If we do log memory, we will log every memory
```

PREPARE

FRAMEWORK ROOT YML



```
prepare.yml
94
95 license:
96   # Ordered list of roles from most features/permissions to least
97   allowable_roles:
98     - Developer
99     - CEE Administrator
100    - Evaluator
101    - Administrator
102    - Auditor/Admin
103    - Auditor
104    - Auditor (Restricted)
105
106 assets:
107   js:
108     core:
109       - public/js/console
110       - public/jquery/jquery-1.8.3
111       - public/js/jquery-timeout
112       - public/js/jquery.caret
113       - public/js/jquery.haversine.0.2-cee
114       #- public/js/imagesloaded.pkgd
115       - public/js/jquery.mobile.custom
116       - public/js/jquery.mobile.transition.handler.simple
```



```
prepare.yml
104 - Auditor (Restricted)
105
106 assets:
107   js:
108     core:
109       - public/js/console
110       - public/jquery/jquery-1.8.3
111       - public/js/jquery-timeout
112       - public/js/jquery.caret
113       - public/js/jquery.haversine.0.2-ccc
114       #- public/js/imagesloaded.pkgd
115       - public/js/jquery.mobile.custom
116       - public/js/jquery.mobile.transition-handler-simple
117       - public/js/jquery.mobile.simultaneous-transitions-replace-simple
118       - public/jqmobile/jquery.mobile-1.2.1.ccc
119       - public/js/iscroll
120       - public/js/jquery.mobile.iscrollview
121       - public/js/sketch
122     # "framework" here is a bit of misnomer
123     # These files might be defined in either the product directory or framework
124     # The "framework" name is just to distinguish from files that might be sp
125     # a particular product.
```

PREPARE

FRAMEWORK ROOT YML



```
145 - app/Addit/new_scheduled_county
146 - app/layout-calculators
147 - app/Settings/registration
148 - app/Settings/preferences
149 - app/Settings/advanced
150 - app/Settings/delete_options
151 - app/Settings/dropbox_access
152 - app/Settings/dropbox_authorize
153 - app/Settings/password_prompt
154 - app/Settings/startup_name
155 - app/Export/export_programs
156 - app/Import/restore
157 - app/Import/program_folders
158 - app/Import/import_programs
159 - app/Import/restore
160 - app/Import/user_folders
161 - app/Import/users
162 - app/Import/visits
163 - app/ProgressView/progress
164 product: [] # Define any product-specific JS in the app's YML. These will
165 # Note that you can still override any JS listed above in js.framework by p
166 # a file with the same name in the app. assets.js.app is for any assets ADI
167 # in the app.
168 ...
169
```


PREPARE

PRODUCT ROOT YML



```
prepare.yml
1  ---
2  app:
3    major_version: "1"
4    minor_version: "0"
5    build_number: "63"
6    name: miAudit-ECNC
7    title: miAudit-ECNC
8    single_letter_identifier: E
9    long_title: ElectriCities North Carolina Energy Audit
10   description: Mobile application for ElectriCities North Carolina energy aud
11   app_mode: short
12   survey_mode: disabled
13   analysis_api:
14     class_name: "NoAnalysisIncluded"
15     result_class_name: "NoAnalysisIncluded"
16   dropbox:
17     app_key: [REDACTED]
18     app_secre [REDACTED]
19
20   development:
21     app:
22     password:
```

PREPARE

FRAMEWORK ROOT DATA (LOG)



Framework root data:

app:

framework_version: 1.0.3
title: unconfigured
long_title: unconfigured
description: unconfigured
app_mode: long
current_upgrade_fields: hide
survey_mode: disabled
unanswered_selector_indicator: "?"

photo:

choose_photo_obeyes_resolution_preference: true

database:

auto_index_properties:
- audit_id
create_calc_compound_index: true

js:

epsilon: 0.0001

PREPARE

DEVELOPER FRAMEWORK ROOT DATA (LOG)



```
Developer framework root data:
```

```
---
```

```
build:
```

```
  minify_js: false
```

```
  js_debug: true
```

```
  js_kybd_debug: true
```

```
  js_calc_debug: false
```

```
  ios:
```

```
    target:
```

```
      device: iphone
```

```
debug:
```

```
  js:
```

```
    detached_node_canary: true
```

```
  css:
```

```
    photo_page: false
```

```
    sketch_page: false
```

```
  rhodes_server:
```

```
    use_fixed_port: true
```

```
photo:
```

PREPARE

PRODUCT ROOT DATA (LOG)



Product root data:

```
app:
  major_version: '1'
  minor_version: '0'
  build_number: '63'
  name: miAudit-ECNC
  title: miAudit-ECNC
  single_letter_identifier: E
  long_title: ElectriCities North Carolina Energy Audit
  description: Mobile application for ElectriCities North Carolina energy audit
  app_mode: short
  survey_mode: disabled
  analysis_api:
    class_name: NoAnalysisIncluded
    result_class_name: NoAnalysisIncluded
  dropbox:
```

PREPARE

PRODUCT ROOT DATA (LOG)



```
audit:
  name: Audit
  name_plural: Audits
  child_classes:
    - Photo
    - Location
    - Contact
    - Service
    - House
    - Attic
    - Wall
    - Foundation
    - Window
    - Heating
    - Cooling
    - Duct
    - Thermostat
```

PREPARE



MERGED ROOT DATA (LOG)

Merged root data:

build:

product: miaudit-ecnc

type: development

time:

date_str: 09/08/2014

time_str: '01:39:37'

stamp: 1410165577

minify_js: false

js_debug: true

js_kybd_debug: true

js_calc_debug: false

git_commit_hash: 5494c9b1b2f8267a06c7f55cb63368d951356670

git_commit_short_hash: 5494c9b

git_local_branch: dev

PREPARE



JAVASCRIPT SWEEPING

```
Discovered Audit child class JS files in framework (available in 'assets.js.audit_ch
app/Photo/photo_edit
app/Photo/photo_edit_list
app/Photo/signature_capture
app/Photo/sketch_edit
app/Location/location_edit
app/Contact/contact_edit
app/Thermostat/thermostat_edit
app/CalcAreaHeightVolume/calc_area_height_volume_edit
app/CalcArea/calc_area_edit
app/CalcInsulation/calc_insulation_edit
app/CalcInsulationAvg/calc_insulation_avg_edit
app/CalcYear/calc_year_edit
app/Recommendation/recommendation_edit
app/Report/report_edit
```



```
app/Report/report_edit
```

```
Discovered Audit child class JS files in product (available in 'assets.js.audit_child
```

```
app/Location/location_edit_county
```

```
app/House/house_edit
```

```
app/Attic/attic_edit
```

```
app/Wall/wall_edit
```

```
app/Foundation/foundation_edit
```

```
app/Heating/heating_edit
```

```
app/Cooling/cooling_edit
```

```
app/Duct/duct_edit
```

```
app/HotWater/hot_water_edit
```

```
app/Appliance/appliance_edit
```

```
app/EcmChecklist/ecm_checklist_edit
```

```
Root data:
```

```
---
```




```
87
88 {{^build.minify_js}}
89 <!-- Core JS files -->
90 {{#script_tags}} {{assets.js.core}} {{/script_tags}}
91
92 <!-- framework JS files (can be overridden in product) -->
93 {{#script_tags}} {{assets.js.framework}} {{/script_tags}}
94
95 <!-- Any additional product-specific JS files -->
96 {{#script_tags}} {{assets.js.product}} {{/script_tags}}
97
98 <!-- framework audit child JS files -->
99 {{#script_tags}} {{assets.js.audit_children.framework}} {{/script_tags}}
100
101 <!-- product audit child JS files -->
102 {{#script_tags}} {{assets.js.audit_children.product}} {{/script_tags}}
103 {{/build.minify_js}}
104
105 {{#build.minify_js}}
106 <script src='/public/js/main.min-js?{{build.time.stamp}}'></script>
107 {{/build.minify_js}}
108
```

PREPARE


GIT AND OTHER ENVIRONMENT DATA



```
^ Directory has data in framework, showing merged data:
---
build:
  product: miaudit-ecnc
  type: development
  time:
    date_str: 09/08/2014
    time_str: '01:39:37'
    stamp: 1410165577
  minify_js: false
  js_debug: true
  js_kybd_debug: true
  js_calc_debug: false
  git_commit_hash: 5494c9b1b2f8267a06c7f55cb63368d951356670
  git_commit_short_hash: 5494c9b
  git_local_branch: dev
  git_remote_branch: github/dev
```

PREPARE


VERSION INFO




PREPARE

VERSION INFO



Carrier 12:13 AM 

 Version Info

Version Summary

Title	miAudit-ECNC
Product	miaudit-ecnc
Build Type	Development
Description	ElectriCities North Carolina Energy Audit
Version	1.0.65
Framework	1.0.3
Build Date	09/10/2014
SHA	21360be(DIRTY)
Local Branch	dev
Remote Branch	github/dev
Prepared By	JT
Prepared On	09/10/2014 at 00:08:57 (1410325737)

Installation Summary

THANK YOU



“THE WATUSI”
The Vibrations
1961 Peaked @ #25

jon@watusiware.com

[linkedin/in/jontara](https://www.linkedin.com/in/jontara)



MOTOROLA SOLUTIONS

WATUSIWARE CORPORATION

