

Untitled

Amy Pitts

3/17/2022

Data import

This dataset has 569 rows and 32 columns. The outcome variable of interest is **Diagnosis** which takes on values benign or malignant cases. There are 357 benign cases and 212 malignant cases as seen below in Table 1. One variable is **id** and the rest 30 variables are the mean, sd and largest values of the following criteria.

- radius (mean of distances from center to points on the perimeter)
- texture (standard deviation of gray-scale values)
- perimeter
- area
- smoothness (local variation in radius lengths)
- compactness ($\text{perimeter}^2 / \text{area} - 1.0$)
- concavity (severity of concave portions of the contour)
- concave points (number of concave portions of the contour)
- symmetry
- fractal dimension ("coastline approximation" - 1)

Using this dataset models will be compared and compared on their ability to predict cancer diagnosis.

Characteristic	Benign, N = 357	Malignant, N = 212	p-value
radius_mean	12.147 (1.781)	17.463 (3.204)	<0.001
texture_mean	17.915 (3.995)	21.605 (3.779)	<0.001
perimeter_mean	78.075 (11.807)	115.365 (21.855)	<0.001
area_mean	462.790 (134.287)	978.376 (367.938)	<0.001
smoothness_mean	0.092 (0.013)	0.103 (0.013)	<0.001
compactness_mean	0.080 (0.034)	0.145 (0.054)	<0.001
concavity_mean	0.046 (0.043)	0.161 (0.075)	<0.001
concave.points_mean	0.026 (0.016)	0.088 (0.034)	<0.001
symmetry_mean	0.174 (0.025)	0.193 (0.028)	<0.001
fractal_dimension_mean	0.063 (0.007)	0.063 (0.008)	0.5
radius_se	0.284 (0.113)	0.609 (0.345)	<0.001
texture_se	1.220 (0.589)	1.211 (0.483)	0.6
perimeter_se	2.000 (0.771)	4.324 (2.569)	<0.001
area_se	21.135 (8.843)	72.672 (61.355)	<0.001
smoothness_se	0.007 (0.003)	0.007 (0.003)	0.2
compactness_se	0.021 (0.016)	0.032 (0.018)	<0.001
concavity_se	0.026 (0.033)	0.042 (0.022)	<0.001
concave.points_se	0.010 (0.006)	0.015 (0.006)	<0.001
symmetry_se	0.021 (0.007)	0.020 (0.010)	0.028
fractal_dimension_se	0.004 (0.003)	0.004 (0.002)	<0.001
radius_worst	13.380 (1.981)	21.135 (4.284)	<0.001
texture_worst	23.515 (5.494)	29.318 (5.435)	<0.001
perimeter_worst	87.006 (13.527)	141.370 (29.457)	<0.001

Characteristic	Benign, N = 357	Malignant, N = 212	p-value
area_worst	558.899 (163.601)	1,422.286 (597.968)	<0.001
smoothness_worst	0.125 (0.020)	0.145 (0.022)	<0.001
compactness_worst	0.183 (0.092)	0.375 (0.170)	<0.001
concavity_worst	0.166 (0.140)	0.451 (0.182)	<0.001
concave.points_worst	0.074 (0.036)	0.182 (0.046)	<0.001
symmetry_worst	0.270 (0.042)	0.323 (0.075)	<0.001
fractal_dimension_worst	0.079 (0.014)	0.092 (0.022)	<0.001

Build a logistic model to classify the images into malignant/benign

Before building the model we need to first write down the likelihood function, its gradient and Hessian matrix. The likelihood function for our data which has a single binary response and 30 numerical explanatory variables is

$$\pi_i = P(Y_i = 1 | x_{i,1}, \dots, x_{i,30}) = \frac{e^{\beta_0 + \beta_1 x_{i,1} + \dots + \beta_{30} x_{i,30}}}{1 + e^{\beta_0 + \beta_1 x_{i,1} + \dots + \beta_{30} x_{i,30}}} = \frac{e^{\beta_0 + \sum_{j=1}^{30} \beta_j x_{i,j}}}{1 + e^{\beta_0 + \sum_{j=1}^{30} \beta_j x_{i,j}}}$$

Where \mathbf{X}_i represents the i observation of all 30 of our predictor variables. For the data give we have the likelihood is given by

$$L(\mathbf{X}|\beta) = \prod_{i=1}^n [\pi_i^{y_i} (1 - \pi_i)^{1-y_i}]$$

Finding the log-likelihood we have

$$l(\mathbf{X}|\vec{\beta}) = \sum_{i=1}^n \left[y_i \left(\beta_0 + \sum_{j=1}^{30} \beta_j x_{i,j} \right) - \log \left(1 + \exp \left(\beta_0 + \sum_{j=1}^{30} \beta_j x_{i,j} \right) \right) \right]$$

The gradient can then can be solved for. Observe

$$\nabla l(\mathbf{X}|\vec{\beta}) = \begin{bmatrix} \sum_{i=1}^n y_i - \pi_i & \sum_{i=1}^n x_{i,1}(y_i - \pi_i) & \dots & \sum_{i=1}^n x_{i,30}(y_i - \pi_i) \end{bmatrix}^T_{(1 \times 31)}$$

Finally, with the gradient we can derive our hessian. Note that due to the 30 predictor variables the hessian will be a 31 by 31 matrix.

$$\begin{aligned} \nabla^2 l(\mathbf{X}|\vec{\beta}) &= - \sum_{i=1}^n \begin{pmatrix} 1 \\ X \end{pmatrix} (1 - X) \pi_i (1 - \pi_i) \\ &= - (1 \quad X) \text{diag}(\pi_i (1 - \pi_i)) \begin{pmatrix} 1 \\ X \end{pmatrix} \end{aligned}$$

Where $X = (x_{i,1}, \dots, x_{i,30})$. Note that this matrix will always be negative definite at all parameters making this a well behaved problem.

Develop a Newton-Raphson algorithm to estimate your model

Modifications:

- I include half stepping in the Newton-Raphson method.
- Assent direction

Data Preprocess

```
dat <- bc %>% select(-id) %>%  
  rename(y = diagnosis) %>%  
  mutate(y = ifelse(y=="B", 0, 1))
```

Functions

```
loglike_func <- function(dat, betavec){  
  # setting up an intercept  
  dat_temp = dat %>%  
    rename(intercept = y) %>%  
    mutate(intercept = rep(1, nrow(dat) ))  
  dat_x = unname(as.matrix(dat_temp)) # creating the x matrix  
  
  # finding the pi values  
  u = dat_x%*%betavec  
  pi <- exp(u) / (1+exp(u))  
  
  # loglikelihood  
  loglik <- sum(dat$y*u - log(1 + exp(u)))  
  
  #gradient  
  grad <- t(dat_x)%*%(dat$y - pi)  
  
  # Hessian  
  mat_temp = matrix(0, nrow = dim(dat)[1], ncol = dim(dat)[1])  
  diag(mat_temp)= pi*(1-pi)  
  hess = -t(dat_x)%*% mat_temp %*%(dat_x)  
  
  return(list(loglik = loglik, grad = grad, hess = hess))  
}  
#loglike_func(dat, betavec = c( rep(0.03, 31))) # test!
```

```
NewtonRaphson <- function(dat, start, tol = 1e-11, maxiter = 200){  
  i = 0  
  cur = start  
  stuff = loglike_func(dat, cur)  
  res <- c(i=0, "loglik" = stuff$loglik, cur, "step" = 1)  
  prevloglik <- -Inf # To make sure it iterates  
  while(i < maxiter && abs(stuff$loglik - prevloglik) > tol) {  
    step = 1  
    i <- i + 1  
    prevloglik <- stuff$loglik  
  
    # ascent direct check  
    eigen_vals = eigen(stuff$hess)
```

```

if(max(eigen_vals$values) <= 0 ){ # we don't want neg def
  hess = stuff$hess
} else{ # if it is neg def then need to adjust
  hess = stuff$hess - (max(eigen_vals$values) + 0.1)*diag(nrow(stuff$hess))
}
prev <- cur
cur <- prev - rep(step, length(prev))*(solve(stuff$hess) %*% stuff$grad)
stuff <- loglike_func(dat, cur) # log-lik, gradient, Hessian

# doing half stepping
while(stuff$loglik < prevloglik){
  stuff <- loglike_func(dat, prev)
  step <- step / 2 # this is where half stepping happens
  cur <- prev - rep(step, length(prev))*(solve(stuff$hess) %*% stuff$grad)
  stuff <- loglike_func(dat, cur)
}
# Add current values to results matrix
res <- rbind(res, c(i, stuff$loglik, cur, step))
}

colnames(res) <- c("intercept", names(dat[, -1]), "i", "loglik", "step")
return(res)
}

#Running the algorithm with random starting values
betavec = c(rep(0.01, 31))
ans <- NewtonRaphson(dat, betavec)

```

Results:

```

##           i           step      loglik
## 1    0.0100000 1.000000e+00    0.010000
## 2   -8.7417254 3.814697e-06   -1.179555
## 3    77.5461663 3.125000e-02  488.328508
## 4   -37.2945192 2.441406e-04 -109.021004
## 5    -0.5525171 3.125000e-02  110.172111
## 6     7.9084537 1.250000e-01  -73.777844
## 7     0.6217574 2.500000e-01   43.286394
## 8     2.8144108 1.000000e+00   49.370660
## 9     6.1210033 1.000000e+00   69.073972
## 10    9.3973114 1.000000e+00  108.752603
## 11   12.7591621 1.000000e+00  165.900414
## 12   18.5983341 1.000000e+00  232.811890
## 13   28.2379507 1.000000e+00  315.879945
## 14   40.9114174 1.000000e+00  410.630445
## 15   61.8581625 1.000000e+00  529.187768
## 16  131.6888689 1.000000e+00  757.177885
## 17  147.4077605 1.250000e-01  807.047155
## 18  149.4996063 1.562500e-02  813.889267
## 19  150.5536412 7.812500e-03  817.351665
## 20  151.0826931 3.906250e-03  819.093312
## 21  151.3477290 1.953125e-03  819.966761
## 22  151.4803745 9.765625e-04  820.404145
## 23  151.5467293 4.882812e-04  820.623002
## 24  151.5633219 1.220703e-04  820.677736

```

```

## 25 151.5716188 6.103516e-05 820.705106
## 26 151.5757673 3.051758e-05 820.718792
## 27 151.5758970 9.536743e-07 820.719220
## 28 151.5759132 1.192093e-07 820.719273
## 29 151.5759172 2.980232e-08 820.719286
## 30 151.5759193 1.490116e-08 820.719293
## 31 151.5759203 7.450581e-09 820.719297
## 32 151.5759205 1.862645e-09 820.719297
## 33 151.5759206 4.656613e-10 820.719298
## 34 151.5759206 2.328306e-10 820.719298
## 35 151.5759206 1.164153e-10 820.719298
## 36 151.5759206 5.820766e-11 820.719298
## 37 151.5759206 2.910383e-11 820.719298
## 38 151.5759206 1.455192e-11 820.719298
## 39 151.5759206 7.275958e-12 820.719298
## 40 151.5759206 3.637979e-12 820.719298
## 41 151.5759206 1.818989e-12 820.719298

```

Variables Name	Beta Coef
intercept	40.000
radius_mean	-11.183
texture_mean	-30.139
perimeter_mean	-44.734
area_mean	0.553
smoothness_mean	0.618
compactness_mean	0.378
concavity_mean	607.372
concave.points_mean	-428.700
symmetry_mean	170.327
fractal_dimension_mean	307.008
radius_se	-154.434
texture_se	254.243
perimeter_se	-15.974
area_se	-5.739
smoothness_se	-6.772
compactness_se	1.201
concavity_se	-110.513
concave.points_se	810.326
symmetry_se	-655.396
fractal_dimension_se	3058.293
radius_worst	-716.255
texture_worst	-8714.163
perimeter_worst	16.337
area_worst	1.128
smoothness_worst	0.452
compactness_worst	-0.118
concavity_worst	-206.369
concave.points_worst	-70.968
symmetry_worst	81.319
fractal_dimension_worst	-50.233

Comparing to glm model

Data Cleaning

Model Implementation

```
glm_fit <- glm(y~., data=dat)
summary(glm_fit)
```

```
##
## Call:
## glm(formula = y ~ ., data = dat)
##
## Deviance Residuals:
##      Min       1Q   Median       3Q      Max
## -0.60241  -0.16209  -0.02705   0.12982   0.82295
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    -2.0218117   0.4280072  -4.724 2.96e-06 ***
## radius_mean    -0.2177721   0.1735089  -1.255 0.209985
## texture_mean     0.0045455   0.0079439   0.572 0.567426
## perimeter_mean   0.0237399   0.0250985   0.946 0.344641
## area_mean        0.0003178   0.0005253   0.605 0.545391
## smoothness_mean  0.0846891   2.0172759   0.042 0.966529
## compactness_mean -4.2220353   1.3336803  -3.166 0.001635 **
## concavity_mean   1.3979973   1.0458611   1.337 0.181887
## concave.points_mean 2.1418330   1.9791819   1.082 0.279657
## symmetry_mean     0.1027092   0.7427382   0.138 0.890067
## fractal_dimension_mean 0.0332616   5.5722693   0.006 0.995240
## radius_se        0.4349559   0.3104682   1.401 0.161800
## texture_se       -0.0067585   0.0368439  -0.183 0.854525
## perimeter_se     -0.0225203   0.0411183  -0.548 0.584129
## area_se          -0.0009232   0.0013978  -0.660 0.509235
## smoothness_se    15.8543207   6.6248737   2.393 0.017046 *
## compactness_se    0.0649034   2.1694829   0.030 0.976145
## concavity_se     -3.5654680   1.3007522  -2.741 0.006327 **
## concave.points_se 10.5679513   5.4520354   1.938 0.053103 .
## symmetry_se       1.6973407   2.7276006   0.622 0.534019
## fractal_dimension_se -7.1464402  11.6764096  -0.612 0.540769
## radius_worst      0.1951831   0.0579677   3.367 0.000814 ***
## texture_worst     0.0071594   0.0069489   1.030 0.303339
## perimeter_worst   -0.0024351   0.0059360  -0.410 0.681807
## area_worst        -0.0010112   0.0003197  -3.163 0.001648 **
## smoothness_worst  0.5428569   1.4346393   0.378 0.705288
## compactness_worst 0.0671583   0.3830830   0.175 0.860902
## concavity_worst   0.3811912   0.2686173   1.419 0.156453
## concave.points_worst 0.4643099   0.9142253   0.508 0.611751
## symmetry_worst     0.5567875   0.4943014   1.126 0.260493
## fractal_dimension_worst 4.3034831   2.3832134   1.806 0.071517 .
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## (Dispersion parameter for gaussian family taken to be 0.05579479)
##
```

```
##      Null deviance: 133.012  on 568  degrees of freedom
## Residual deviance:  30.018  on 538  degrees of freedom
## AIC: 4.6991
##
## Number of Fisher Scoring iterations: 2
```