

Lie detection protocol

Louis Ossant

15 August 2024

1 Introduction

In this document, we identify the EEG channels and experimental methods used to detect deception in subjects. Many previous studies have utilized EEG channels without offering detailed explanations. For this project, our goal is to understand the neural mechanisms underlying deception in social contexts and develop our own process for creating a lie detector database. Subsequently, we will employ data processing methods to identify the features that will ultimately enable us to classify the data effectively.

2 EEG Channels

Few documents have been published on this subject, and most of them do not explain why specific EEG channels are used ([2], [4], [3], [1], [5], [8], [10], [7]).

2.1 Visualization of deception with fMRI

In various studies, researchers have gained a better understanding of the brain mechanisms involved in deception in strategic interactions. The initial study conducted in 2015 [9] identified key brain regions associated with deception. Other research has highlighted additional brain areas involved in deceptive behavior. These key brain regions include the right temporoparietal junction, the left temporoparietal junction, the retrosplenial cortex, the left precuneus, and the right superior temporal sulcus. This information was extracted using functional magnetic resonance imaging (fMRI). See Figure 1 for activated brain areas during deception.

2.2 Selecting the EEG Channels

We will use all EEG channels in our experiment. Referring to the EEG model shown in Fig: 10-20 EEG model for experimentation, we identify the appropriate sensors for our experiment.

The EEG signal is recorded to capture information from specific brain regions, including the following:




Figure 1: Deception visualization with fMRI




Figure 2: EEG 10-20 Model for experimentation

- Right TPJ
- Left TPJ
- Retrosplenial cortex
- Left precuneus
- Right STS

Thanks to the identification of these area on MRI, we will be able to use them during the "DataProcessing" stage to focus our research on specific zones or channels.

3 Experimentation

3.1 Experimentation for the fMRI

In the study [11] [9] a particular experimentation has been used. This experimentation is the Sender Receiver game.

The sender-receiver game is a complex game designed to detect truth and two types of lies: simple deception and sophisticated deception(see Figure 3). Four possible results are obtained: sophisticated deception, truth, simple deception, and not classifiable. In our study, we focus on simple deception. That's why we develop a simplified lie detection game with two possible result like we can see Figure 4.




Figure 3: Sender-Receiver Game




Figure 4: Lie Detection Game

3.2 Description of the Experiment

Participants are presented with two distinct sets of images alternately on the screen. Each image is displayed for 7 seconds. Within this timeframe, participants must decide whether to tell the truth or deceive by selecting one of two corresponding buttons. These buttons may or may not align with the content of the displayed image, we can see Figure 5 the Experimentation graph. The interface for this game is shown in Figure 6.

To help with decision-making and reduce interference from other brain activities, participants are guided to use specific keys on the keyboard to make their selections. This method is intended to decrease unnecessary cognitive processes and simplify the neural activity related to decision-making, recognizing that this activity primarily occurs in the cortex.

Afterward, the computer compares these brain signals with what it knows to be the correct answers. This helps us spot any differences between what the participants' brains are doing and what they should be doing, making our lie detection more accurate and allowing us to build a database of brain activity.

3.3 Result

At the end of my internship, we have recorded the data of 3 different subjects. for a total of 568 epochs (279 lie and 289 true).




Figure 5: Experimentation graph



Figure 6: Lie Detector Game

4 Data Processing

4.1 Preprocessor




Figure 7: Preprocessing raw data

Our Preprocessing chain is built as follows:

- Bandpass filter from 0.5 Hz to 45Hz
- Remove bads channels
- Artifact Subspace Reconstruction (ASR)

The figure below 7 shows our data before and after this processing chain. The left-hand side of the figure shows the frequency representation of the signal and the right-hand side the time representation.

4.2 ERN

4.2.1 Analysis

We use an ERN representation of our EEG data to obtain a clear depiction of the related epochs and to see if we can find any similarities. We will present the expected results found in the thesis below and then compare them with our own findings.

As discussed in [6], the following image of ERN was found (8). We have attempted to reproduce this with our data to observe whether the same phenomenon can be detected.

On the following images (9,10,11,12): red represents the related epochs, and blue represents the average true epochs across the channels.

4.2.2 Conclusion

We can identify similarities between the research findings and the extraction of our data from our experiments. This suggests that the research avenue is promising, and it would be beneficial to identify the corresponding features. Ultimately, this will enable us to perform classification effectively.




Figure 8: ERN representation example




Figure 9: ERN representation subject 1 run 1




Figure 10: ERN representation subject 1 run 2




Figure 11: ERN representation subject 1 run 3




Figure 12: ERN representation subject 1 run 4

5 Others analysis

The analysis of ERN appears to be the most promising approach because we have already explored more advanced techniques, such as source localization. This method extracts over 8,000 sources, and we computed our features based on this data. We then ranked these features by their importance, as shown in the following figure. However, this approach proved to be non-viable.




Figure 13: Importances of the frequencial features




Figure 14: Importances of the temporal features

The maximum importance value for the frequency-based features is 0.028, which is not considered significant. Similarly, the maximum importance value for the time-based features is 0.0200.

Even when considering the top features, we are unable to identify any particularly activated regions using this method.

References

- [1] Valhid Abootalebi, Mohammad Hassan Moradi, and Mohammad Ali Khalilzadeh. A new approach for eeg feature extraction in p300-based lie detection, April 2009.
- [2] Musa Aslan, Muhammet Baykara, and Talha Burak. Liewaves: dataset for lie detection based on eeg signals and wavelets, February 2024.

- [3] Junfeng Gao, Zhao Wang, Yong Yang, Wenjia Zhang, Chunyi Tao, Jinan Guan, and Nini Rao. A novel approach for lie detection based on f-score and extreme learning machine, June 2013.
- [4] Viresh Gupta, Mohit Agarwal, Manik Arora, Tammoy Chakraborty, Richa Singh, and Mayank Vatsa. Bag-of-lies: A multimodal dataset for deception detection, July 2020.
- [5] Ki-Won Jang, Deok-Yong Kim, Sungkun Cho, and Jang-Han Lee. Effects of the combination of p3-based gkt and reality monitoring on deceptive classification, January 2013.
- [6] Guoxiang Zhao Antao Chen Lijun Wang, Yan Gu. Error-related negativity and error awareness in a go/no-go task, March 2020.
- [7] Navjot Saini, Saurabh Bhardwaj, and Ravinder Agarwal. Classification of eeg signals using hybrid combination of features for lie detection, February 2019.
- [8] Artha Ivonita Simbolon, Arjon Turnip, Jeperson Hutahaeon, Yessica Siagian, and Novica Irawati. An experiment of lie detection based eeg-p300 classified by svm algorithm, October 2015.
- [9] Kirsten G. Volz, Kai Vogeley, Marc Tittgemeyer, D. Yves von Cramon, and Matthias Sutter. The neural basis of deception in strategic interactions, February 2015.
- [10] EA Yumatov, VYu Potapov, NA Karatygin, EN Dudnik, and SS Pertsov. Experimental approach to the recognition of truthful and false mental responses based on the wavelet transform of the electroencephalogram, July 2019.
- [11] Maya Zheltyakova, Maxim Kireev, Alexander Korotkov, and Svyatoslav Medvedev. Neural mechanisms of deception in a social context: an fmri replication study, July 2020.