Coding Guidelines

- ▾ **Variable Instantiation**
    - ▾ using namespace std should only be used in a local scope or not at all
        - ▪

            ```cpp
            void function(){
                std::cout << "data" << std::endl;
                std::string var = "data";
                std::shared_ptr<int> int_var = std::make_shared<int>(5);
            }
            ```

        - ▪

            ```cpp
            void function(){
                using namespace std;

                cout << "data" << endl;
                string var = "data";
                shared_ptr<int> int_var = make_shared<int>(5);
            }
            ```

    - ▪ global variables should not be mutable, rather they should be immutable CONST variables typed in all capitals

- ▼ variables should be passed down to functions such that a variable's lifetime that is created by scope is controlled by that scope unless that scope is returning a smart pointer

  - ▼

    ```cpp
    void doOtherThing(int* a)
    {
        //do things with 'a'
        //complete things
        //but "doOtherThing" cannot deallocate 'a' because it does not own it
        //so just return
        return;
    }

    void doSomething()
    {
        int* a = new int(5);
        doOtherThing(a); //borrow 'a' to doOtherThing
        delete a; // I'm done with 'a' so since I created it in my scope, I will delete it
    }
    ```

  - ▼ The only exception to this rule would be if doOtherThing was returning a pointer, in that case it should be wrapped in a smart pointer so that we don't have to guess who will delete the pointer

    - ▪

      ```cpp
      std::shared_ptr<int> doOtherThing()
      {
          //create and return smart shared pointer
          return std::make_shared<int>(5);
      }

      void doSomething()
      {
          std::shared_ptr<int> user = doOtherThing(); //create
          return;//user will automatically delete itself
      }
      ```

- **Comment Style**
  - H/HPP Files
    - Header
      - ▪
        ```
        /**
         * @file fileName.h fileName.cpp
         * @class className
         * @author Author Name
         * @brief Description of Class
         */
        ```
   - Functions follow a camelCase convention
      - ▪
        ```
        /**
         * @brief Function Description
         * @param paramName Description of paramater
         * @return returnType
         */
        ```
    - Variables follow a snake_case convention

```
/**
 * @brief variable description
 */
```

Function Implementation

CPP Files

- Avoid Long if, else if, else branching

- Avoid deeply nested if's

- Avoid spagetti recursion

- Avoid making a single function longer than 200-300 lines of code; consider making portions into their own sub functions

- Test a function to make sure it works by using your own tests and since we don't need full unit test coverage, test at least one function in your class with the provided google test library. An example template for tests has already been set up in the tests.cpp files

- Indentation should be standard for readibility, so avoid one lining code, wrap everything in curly braces even if it is a simple if statement

Git Contributions

- making git contributions

```
              create a branch ──────────────────────┐                    ┌─────────┐
                   │                                 │                    │   End   │
                  No                                 │                   Yes
                   │                                 ▼                    │
  ┌───────┐     ┌─────────┐  Yes   ┌──────────────┐  No   ┌──────────────┐
  │ Start │────▶│ have a  │───────▶│ clone to local│◀─────│ remote tests │
  └───────┘     │ branch? │        └──────────────┘       │   passed?    │
                └─────────┘                                └──────────────┘
                                         │                        ▲
                                      ┌──────────────┐     ┌──────────────────┐
                                 No   │ add/edit/debug│     │ merge branch with dev │
                                  │   │   feature     │     └──────────────────┘
                                  │   └──────────────┘              ▲
                                  │          │                      │
                                  │    ┌──────────────┐  Yes         │
                                  └───▶│ local tests  │─────────────┘
                                       │   passed?    │
                                       └──────────────┘
```

- repo lifetime

How it works

(stable auto-maintained) ── documentation branch ──▶

(stable) ── master branch ──▶   QA tests passed

(unstable/tested) ── develop branch ──

create your branch   local tests passed

(unstable/untested)

feature/bug-fixes

- CONTRIBUTING.md

  https://github.com/waveyboym/COS-2...

▼ **Documentation**

- documentation is automatically generated by a github action whenever changes are made to the src directory on the main branch. The docs are found in the documentation branch

Errors

- if you decide to use exceptions, contain them to your package or class only

Github issues

- please make use of github issues when you encounter certain code that you are unable to fix. Labels are available when creating your issue and please also assign issues to members who are supposed to work on that portion of code

Github pull requests

- please assign labels and assignees who worked on the code in the pr when creating and merging pr's with a branch