

SPI-230G

230 Watts Mini AT/ PS2 Power Supply



Product Specifications

Features

High efficiency
Low noise and ripple
Output over voltage protection
Short circuit protection on all outputs
Resettable power shut down
Approved by UL 1950, CSA 22.2 Level 3, TUV
EN60950 CB Internal 12 VDC fan provided
Complies with FCC part 15 subpart J class B 115
VAC operation and VDE VFG 243 class B 230
VAC operation
100% burn-in under high ambient temperature
(50°C)
MTBF above 50,000 hours
100% Hi-Pot & ATE tested

Input Characteristics

Voltage: 90-132 VAC or 180-264 VAC switchable
Frequency: 48 Hz to 63 Hz

Specification

Temperature range: Operating 0°C ~ 50°C; Non-operating: -20°C ~ 80°C
Temperature coefficient: 0.01%/°C
Transient response: Output voltage returns in less than 1 ms max. following a 25% load change
Hold up time: 16ms minimum at full load & nominal input voltage
Dielectric withstand: Input/output 1800 VAC for 1 second input to frame ground 1800 VAC for 1 second
Humidity: 5~95% RH
Efficiency: 65% Min., 70% typical, at full load
Power good signal: On delay 100 ms to 500 ms, off delay 1ms
Overload protection: 150% Max
Over voltage protection: +5V output: 6V±0.5V

Output Charteristics

Output Voltage	Minimum Load	Maximum Load	Load Reg.	Line Reg.	Ripple & Noise
+5V	3.0 A	23 A	± 5%	± 1%	50 mV P-P
+12V	0.2 A	9.0 A	± 5%	± 1%	120 mV P-P
-5V	0.0A	0.5 A	± 10%	± 2%	150 mV P-P
-12V	0.0A	0.5 A	± 10%	± 2%	150 mV P-P

Dimensions (WxHxL): 150 x 86 x 140 (mm)/ 5.9" x 3.4" x 5.5"