NTF3055-100, NVF3055-100

Power MOSFET 3.0 Amps, 60 Volts

N−Channel SOT−223

Designed for low voltage, high speed switching applications in power supplies, converters and power motor controls and bridge circuits.

Features

- NVF Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q101 Qualified and PPAP Capable
- These Devices are Pb−Free and are RoHS Compliant

Applications

- Power Supplies
- Converters
- Power Motor Controls
- Bridge Circuits

MAXIMUM RATINGS (T_C = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Drain−to−Source Voltage	V_{DSS}	60	Vdc
Drain−to−Gate Voltage (R_{GS} = 10 MΩ)	V_{DGR}	60	Vdc
Gate−to−Source Voltage − Continuous − Non−repetitive ($t_p \le 10$ ms)	V_{GS}	± 20 ± 30	Vdc Vpk
Drain Current − Continuous @ T_A = 25°C − Continuous @ T_A = 100°C − Single Pulse ($t_p \le 10$ μs)	I_D I_D I_{DM}	3.0 1.4 9.0	Adc Apk
Total Power Dissipation @ T_A = 25°C (Note 1) Total Power Dissipation @ T_A = 25°C (Note 2) Derate above 25°C	P_D	2.1 1.3 0.014	W W W/°C
Operating and Storage Temperature Range	T_J, T_{stg}	−55 to 175	°C
Single Pulse Drain−to−Source Avalanche Energy − Starting T_J = 25°C (V_{DD} = 25 Vdc, V_{GS} = 10 Vdc, I_L(pk) = 7.0 Apk, L = 3.0 mH, V_{DS} = 60 Vdc)	E_{AS}	74	mJ
Thermal Resistance − Junction−to−Ambient (Note 1) − Junction−to−Ambient (Note 2)	$R_{\theta JA}$ $R_{\theta JA}$	72.3 114	°C/W
Maximum Lead Temperature for Soldering Purposes, 1/8″ from case for 10 seconds	T_L	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. When surface mounted to an FR4 board using 1″ pad size, 1 oz. (Cu. Area 1.127 sq in).
2. When surface mounted to an FR4 board using minimum recommended pad size, 2−2.4 oz. (Cu. Area 0.272 sq in).

ON Semiconductor®

www.onsemi.com

3.0 A, 60 V
$R_{DS(on)}$ = 110 mΩ

N−Channel





SOT−223
CASE 318E
STYLE 3

MARKING DIAGRAM & PIN ASSIGNMENT



A = Assembly Location
WW = Work Week
3055 = Specific Device Code
▪ = Pb−Free Package
(Note: Microdot may be in either location)

ORDERING INFORMATION

Device	Package	Shipping†
NTF3055−100T1G	SOT−223 (Pb−Free)	1000 / Tape & Reel
NTF3055−100T3G	SOT−223 (Pb−Free)	4000 / Tape & Reel
NVF3055−100T1G	SOT−223 (Pb−Free)	1000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2016

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Drain−to−Source Breakdown Voltage (Note 3) (V_{GS} = 0 Vdc, I_D = 250 μAdc) Temperature Coefficient (Positive)	$V_{(BR)DSS}$	60 –	68 66	– –	Vdc mV/°C
Zero Gate Voltage Drain Current (V_{DS} = 60 Vdc, V_{GS} = 0 Vdc) (V_{DS} = 60 Vdc, V_{GS} = 0 Vdc, T_J = 150°C)	I_{DSS}	 – –	 – –	 1.0 10	μAdc
Gate−Body Leakage Current (V_{GS} = ± 20 Vdc, V_{DS} = 0 Vdc)	I_{GSS}	–	–	± 100	nAdc
ON CHARACTERISTICS (Note 3)					
Gate Threshold Voltage (Note 3) (V_{DS} = V_{GS}, I_D = 250 μAdc) Threshold Temperature Coefficient (Negative)	$V_{GS(th)}$	2.0 –	3.0 6.6	4.0 –	Vdc mV/°C
Static Drain−to−Source On−Resistance (Note 3) (V_{GS} = 10 Vdc, I_D = 1.5 Adc)	$R_{DS(on)}$	–	88	110	mΩ
Static Drain−to−Source On−Resistance (Note 3) (V_{GS} = 10 Vdc, I_D = 3.0 Adc) (V_{GS} = 10 Vdc, I_D = 1.5 Adc, T_J = 150°C)	$V_{DS(on)}$	–	0.27 0.24	0.40 –	Vdc
Forward Transconductance (Note 3) (V_{DS} = 8.0 Vdc, I_D = 1.7 Adc)	g_{fs}	–	3.2	–	Mhos
DYNAMIC CHARACTERISTICS					
Input Capacitance	(V_{DS} = 25 Vdc, V_{GS} = 0 V, f = 1.0 MHz)	C_{iss}	–	324	455	pF
Output Capacitance		C_{oss}	–	35	50	
Transfer Capacitance		C_{rss}	–	110	155	
SWITCHING CHARACTERISTICS (Note 4)					
Turn−On Delay Time	(V_{DD} = 30 Vdc, I_D = 3.0 Adc, V_{GS} = 10 Vdc, R_G = 9.1 Ω) (Note 3)	$t_{d(on)}$	–	9.4	20	ns
Rise Time		t_r	–	14	30	
Turn−Off Delay Time		$t_{d(off)}$	–	21	45	
Fall Time		t_f	–	13	30	
Gate Charge	(V_{DS} = 48 Vdc, I_D = 3.0 Adc, V_{GS} = 10 Vdc) (Note 3)	Q_T	–	10.6	22	nC
		Q_1	–	1.9	–	
		Q_2	–	4.2	–	
SOURCE−DRAIN DIODE CHARACTERISTICS					
Forward On−Voltage	(I_S = 3.0 Adc, V_{GS} = 0 Vdc) (I_S = 3.0 Adc, V_{GS} = 0 Vdc, T_J = 150°C) (Note 3)	V_{SD}	 –	 0.89	 1.0	Vdc
			–	0.74	–	
Reverse Recovery Time	(I_S = 3.0 Adc, V_{GS} = 0 Vdc, dI_S/dt = 100 A/μs) (Note 3)	t_{rr}	–	30	–	ns
		t_a	–	22	–	
		t_b	–	8.6	–	
Reverse Recovery Stored Charge		Q_{RR}	–	0.04	–	μC

3. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.
4. Switching characteristics are independent of operating junction temperatures.



Figure 1. On−Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On−Resistance versus Gate−to−Source Voltage



Figure 4. On−Resistance versus Drain Current and Gate Voltage



Figure 5. On−Resistance Variation with Temperature



Figure 6. Drain−to−Source Leakage Current versus Voltage



Figure 7. Capacitance Variation



Figure 8. Gate−to−Source and Drain−to−Source Voltage versus Total Charge



Figure 9. Resistive Switching Time Variation versus Gate Resistance



Figure 10. Diode Forward Voltage versus Current



Figure 11. Maximum Rated Forward Biased Safe Operating Area



Figure 12. Maximum Avalanche Energy versus Starting Junction Temperature



Figure 13. Thermal Response

PACKAGE DIMENSIONS

SOT−223 (TO−261)
CASE 318E−04
ISSUE N



NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCH.

	MILLIMETERS			INCHES		
DIM	MIN	NOM	MAX	MIN	NOM	MAX
A	1.50	1.63	1.75	0.060	0.064	0.068
A1	0.02	0.06	0.10	0.001	0.002	0.004
b	0.60	0.75	0.89	0.024	0.030	0.035
b1	2.90	3.06	3.20	0.115	0.121	0.126
c	0.24	0.29	0.35	0.009	0.012	0.014
D	6.30	6.50	6.70	0.249	0.256	0.263
E	3.30	3.50	3.70	0.130	0.138	0.145
e	2.20	2.30	2.40	0.087	0.091	0.094
e1	0.85	0.94	1.05	0.033	0.037	0.041
L	0.20	−−−	−−−	0.008	−−−	−−−
L1	1.50	1.75	2.00	0.060	0.069	0.078
H_E	6.70	7.00	7.30	0.264	0.276	0.287
θ		−			−	

STYLE 3:
PIN 1. GATE
2. DRAIN
3. SOURCE
4. DRAIN

	10°	0°	10°

SOLDERING FOOTPRINT*



*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative