

# 作業系統 Operating Systems

大綱-  
資料處理模式  
人腦 vs. 電腦




靜宜大學資訊傳播工程學系


劉國有 助理教授

[kyluu@pu.edu.tw](mailto:kyluu@pu.edu.tw)

## 資料處理模式



## 人腦 vs. 電腦



## 電腦之父-馮紐曼



- 1945年-世界上第一部通用電子電腦：Electronic Numerical Integrator And Computer (ENIAC, 電子數值積分計算機)
- 由賓州大學莫奇來 (Mauchly) 博士和他的學生愛克特 (Eckert) 設計以真空管為元件所設計的電腦，目的是用來計算砲彈彈道。
- 1945年-馮紐曼架構：儲存程式邏輯架構。為現代各式電腦所遵循的主要設計架構。


約翰·馮·諾伊曼  
John von Neumann



20世紀40年代的馮諾伊曼

出生	1903年12月28日 奧匈帝國布達佩斯
逝世	1957年2月8日 (53歲) 美國華盛頓沃爾特·里德陸軍醫院
居住地	美國
國籍	匈牙利人、美國人
研究領域	數學、電腦科學、經濟學
任職於	柏林大學 普林斯頓大學 普林斯頓高等研究院 洛斯阿拉莫斯國家實驗室
母校	帕茨瑪尼·彼得大學 蘇黎世聯邦理工學院
博士導師	利波特·費耶爾
博士學生	唐納德·B·吉利斯 以色列·霍爾珀林
其他著名學生	保羅·豪爾莫什 克利福德·休·克爾
獲獎	博修紀念獎 (1938) 恩里科·費米獎 (1956)

## 馮紐曼架構




## Memory Subsystem

- Memory, also called RAM (Random Access Memory),
  - Consists of many memory cells (storage units) of a fixed size. Each cell has an address associated with it: 0, 1, ...
  - All accesses to memory are to a specified address. A cell is the minimum unit of access (fetch/store a complete cell).
  - The time it takes to fetch/store a cell is the same for all cells.
- When the computer is running, both
  - Program
  - Data (variables)
 are stored in the memory.


# RAM

- Need to distinguish between
  - the address of a memory cell and the content of a memory cell
- Memory width (W):
  - How many bits is each memory cell, typically one byte (=8 bits)
- Address width (N):
  - How many bits used to represent each address, determines the maximum memory size = address space
  - If address width is N-bits, then address space is  $2^N$  ( $0, 1, \dots, 2^N-1$ )



## Structure of the Memory Subsystem

- Fetch(address)
  - Load address into MAR.
  - Decode the address in MAR.
  - Copy the content of memory cell with specified address into MDR.
- Store(address, value)
  - Load the address into MAR.
  - Load the value into MDR.
  - Decode the address in MAR
  - Copy the content of MDR into memory cell with the specified address.




## Input/Output Subsystem

- Handles devices that allow the computer system to:
  - Communicate and interact with the outside world
    - Screen, keyboard, printer, ...
  - Store information (mass-storage)
    - Hard-drives, floppies, CD, tapes, ...
- Mass-Storage Device Access Methods:
  - Direct Access Storage Devices (DASDs)
    - Hard-drives, floppy-disks, CD-ROMs, ...
  - Sequential Access Storage Devices (SASDs)
    - Tapes (for example, used as backup devices)

## I/O Controllers

- Speed of I/O devices is slow compared to RAM
  - RAM ~ 50 nsec.
  - Hard-Drive ~ 10msec. = (10,000,000 nsec)
- Solution:
  - I/O Controller, a special purpose processor:
    - Has a small memory buffer, and a control logic to control I/O device (e.g. move disk arm).
    - Sends an interrupt signal to CPU when done read/write.
  - Data transferred between RAM and memory buffer.
  - Processor free to do something else while I/O controller reads/writes data from/to device into I/O buffer.

## Structure of the I/O Subsystem




## The ALU Subsystem

- The ALU (Arithmetic/Logic Unit) performs
  - mathematical operations (+, -, x, /, ...)
  - logic operations (=, <, >, and, or, not, ...)
 in today's computers integrated into the CPU
- Consists of:
  - Circuits to do the arithmetic/logic operations.
  - Registers (fast storage units) to store intermediate computational results.
  - Bus that connects the two.

## Structure of the ALU

- Registers:
  - Very fast local memory cells, that store operands of operations and intermediate results.
  - CCR (condition code register), a special purpose register that stores the result of  $<$ ,  $=$ ,  $>$  operations
- ALU circuitry:
  - Contains an array of circuits to do mathematical/logic operations.
- Bus:
  - Data path interconnecting the registers to the ALU circuitry.



## The Control Unit

- Program is stored in memory
  - as machine language instructions, in binary
- The task of the control unit is to execute programs by repeatedly:
  - Fetch from memory the next instruction to be executed.
  - Decode it, that is, determine what is to be done.
  - Execute it by issuing the appropriate signals to the ALU, memory, and I/O subsystems.
  - Continues until the HALT instruction

## Machine Language Instructions

- A machine language instruction consists of:
  - Operation code, telling which operation to perform
  - Address field(s), telling the memory addresses of the values on which the operation works.
- Example: ADD X, Y (Add content of memory locations X and Y, and store back in memory location Y).
- Assume: opcode for ADD is 9, and addresses X=99, Y=100

Opcode (8 bits)	Address 1 (16 bits)	Address 2 (16 bits)
00001001	0000000001100011	0000000001100100

## Structure of the Control Unit

- PC (Program Counter):
  - stores the address of next instruction to fetch
- IR (Instruction Register):
  - stores the instruction fetched from memory
- Instruction Decoder:
  - Decodes instruction and activates necessary circuitry

