

Attachment 3

Report No.: 6213304.51D

IEC60335_1X ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
ATTACHMENT TO TEST REPORT IEC 60335-1 Republic of Korea NATIONAL DIFFERENCES Household and similar electrical appliances - Safety - Part 1: General requirements			
Differences according to : KC60335-1(2022-06)			
TRF template used: : IECEE OD-2020-F3, Ed. 1.1			
Attachment Form No. : KR_ND_IEC60335_1X			
Attachment Originator : KTL			
Master Attachment : Dated 2022-11-11			
Copyright © 2022 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.			
	National Differences		--
7	Marking and instructions		--
7.17 (new subclause)	For ozone generating appliances with percentage of ozone exceeding 5×10^{-6} according to clause 32, the product and instructions shall indicate the following: -P recautions to prevent the user from approaching the ozone generating parts during operation -P recautions to ventilate the room for ozone removal during or after use -P prohibition of use in a confined space -C ozone concentration (PPM) and ozone generation rate(mg / m^3) (applicable to appliances used by a trained specialist for sterilization and deodorization) Note The ozone concentration is measured according to clause 32, and the ozone concentration of 1 PPM corresponds to the amount of ozone generation rate of 2 mg / m^3. -A appliances used by trained specialists for sterilization, deodorization and other purposes should include instructions for user protection and instructions on wearing protective equipment		N/A

IEC60335_1X ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
24	Components		--
24.4 (addition)	Plugs for the connection of the apparatus to the supply main shall comply with the Korean requirement(KS C 8305).		P
32	Radiation, toxicity and similar hazards		--
(addition)	The following tests shall be applied for appliances with ozone generation function, or The relevant standard shall be applied, if the test method is specified in Part 2 (particular standard). The ozone concentration produced by ozone generating appliances shall not be excessive. Compliance is checked by the following tests. The tests are carried out in a room without openings having dimensions of 2.5 m × 3.5 m × 3.0 m, the walls being covered with polyethylene sheet. The appliance is positioned in accordance with the instructions. The appliances used on a table are placed in the center of the room approximately 750 mm above the floor. The appliance is supplied at rated voltage and operated for the following duration to allow ozone to be generated at maximum. -m maximum time allowed on appliance, if the continuous operation time is less than 1 hour or -m maximum time allowed on appliance (24 hours if exceeding 24 hours), if the continuous operation time is over 1 hour The ozone sampling tube is to be located in the air stream 50 mm from the air outlet of the appliance. The background ozone concentration measured prior to the test is subtracted from the maximum concentration measured during the tests. Appliance provided with container or so on that can be open without aid of tool, the tests also carried out with the container or so on open. The percentage of ozone in the room shall not exceed as following; -1 × 10⁻⁵ (if the continuous operation time is less		N/A

Attachment 3

Report No.: 6213304.51D

IEC60335_1X ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	than 1 hour), or -5 $\times 10^{-6}$ (if the continuous operation time is over 1 hour) This requirement is not applicable to appliances that intended to be used by trained professionals for sterilization, deodorization, etc. If the instructions of appliances state that the appliance must be installed in a space of 30 m³ or more, the size of the test room may be increased as described in the instructions. Ozone concentration and ozone generation values according to 7.17 should be within $\pm 20\%$ error range.		
	Special national conditions		--
Voltage	National supply voltages are 110 V, 220 V and 380 V.		P
Frequency	Only appliances having supply frequency of 60Hz or a frequency range including 60Hz are accepted.		P
Instruction	Instruction manuals and appliance marking related safety, including nameplate shall be in Korean		P

---END---