Paired settings: observed-positive difference and worst-case unknown bounds
These intervals are NOT confidence intervals; each setting has only 12 task identities.

Clean U

Attack U

Attack A

f16/full → q4/full
f16/truncate → q4/truncate
f16/long_summary → q4/long_summary
f16/short_summary → q4/short_summary
f16/short_summary_rag → q4/short_summary_rag
f16/full → f16/truncate
f16/full → f16/long_summary
f16/full → f16/short_summary
f16/full → f16/short_summary_rag
q4/full → q4/truncate
q4/full → q4/long_summary
q4/full → q4/short_summary
q4/full → q4/short_summary_rag
f16/short_summary → f16/short_summary_rag
q4/short_summary → q4/short_summary_rag

n12 / ?pairs 0
n12 / ?pairs 6
n12 / ?pairs 2
n12 / ?pairs 4
n12 / ?pairs 4
n12 / ?pairs 6
n12 / ?pairs 2
n12 / ?pairs 4
n12 / ?pairs 3
n12 / ?pairs 6
n12 / ?pairs 2
n12 / ?pairs 1
n12 / ?pairs 2
n12 / ?pairs 4
n12 / ?pairs 2

n24 / ?pairs 1
n24 / ?pairs 17
n24 / ?pairs 12
n24 / ?pairs 13
n24 / ?pairs 12
n24 / ?pairs 17
n24 / ?pairs 10
n24 / ?pairs 10
n24 / ?pairs 8
n24 / ?pairs 17
n24 / ?pairs 7
n24 / ?pairs 8
n24 / ?pairs 8
n24 / ?pairs 12
n24 / ?pairs 10

n24 / ?pairs 1
n24 / ?pairs 17
n24 / ?pairs 12
n24 / ?pairs 13
n24 / ?pairs 12
n24 / ?pairs 17
n24 / ?pairs 10
n24 / ?pairs 10
n24 / ?pairs 8
n24 / ?pairs 17
n24 / ?pairs 7
n24 / ?pairs 8
n24 / ?pairs 8
n24 / ?pairs 12
n24 / ?pairs 10

−100 −50 0 50 100
Variant − control (percentage points)

−100 −50 0 50 100
Variant − control (percentage points)

−100 −50 0 50 100
Variant − control (percentage points)