



Lithium bis(oxalato)borate (LiBOB)

LITHIUM ELECTROLYTE SALT

PRODUCT OVERVIEW

Lithium bis(oxalato)borate (LiBOB) is a borate-based lithium electrolyte salt used in battery research. Applications include electrolyte formulation, salt-blend evaluation, and electrode-electrolyte compatibility studies.

CAS No. 244761-29-3 | Formula C_4BLiO_8 | Abbreviation LiBOB

TECHNICAL SPECIFICATIONS

PROPERTY	SPECIFICATION	REPRESENTATIVE RESULT
Appearance	White powder	White powder
Assay (IC)	≥ 99.8 wt%	99.979 wt%
Water (Karl Fischer)	≤ 300 ppm	142.7 ppm
Acidity, as HF	≤ 100 ppm	0 ppm
Color	≤ 30 Hazen	11.6 Hazen
Chloride	≤ 10 ppm	0.75 ppm
Sulfate	≤ 10 ppm	<10.0 ppm

TRACE METALS

ELEMENT	SPEC. (ppm)	REP. RESULT (ppm)	ELEMENT	SPEC. (ppm)	REP. RESULT (ppm)
Cd	≤ 5	0	Cu	≤ 5	0
Ba	≤ 5	0.07	Fe	≤ 5	4.32
Mn	≤ 5	0	Al	≤ 5	0
Ni	≤ 5	0.39	Pb	≤ 5	0.11
Cr	≤ 5	0.73	K	≤ 5	0.22
Mg	≤ 5	0.14	Ca	≤ 5	0.49
Zn	≤ 5	0	Na	≤ 5	3.49

QUALITY / DOCUMENTATION

Lot-specific Certificate of Analysis and SDS are available upon request.