



1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether (TTE)

BATTERY SOLVENTS

PRODUCT OVERVIEW

1,1,2,2-Tetrafluoroethyl 2,2,3,3-tetrafluoropropyl ether (TTE) is used in solvent formulation, materials evaluation, and electrochemical research.

CAS No. 16627-68-2 | Formula $C_5H_4F_8O$ | Abbreviation TTE

Grade / Category: Battery material grade / Battery Solvents

TECHNICAL SPECIFICATIONS

PROPERTY	SPECIFICATION	REPRESENTATIVE RESULT
Appearance	Colorless transparent liquid; no mechanical impurities	Conforms
Purity	≥ 99.00 wt%	99.778 wt%
Water	≤ 200 ppm	22.1 ppm
Acidity, as HF	≤ 10 ppm	0.0 ppm
Color (APHA)	≤ 20	3.2
Chloride, Cl^-	≤ 5 ppm	0.69 ppm
Sulfate, SO_4^{2-}	≤ 10 ppm	<5.0 ppm

TRACE METALS

ELEMENT	SPEC. (ppm)	REP. RESULT (ppm)	ELEMENT	SPEC. (ppm)	REP. RESULT (ppm)
Na	≤ 10	0.01	Zn	≤ 10	0
K	≤ 10	0	Cr	≤ 10	0
Ca	≤ 10	0.19	Ni	≤ 10	0
Fe	≤ 10	0	Ba	≤ 10	0
Pb	≤ 10	0.01	Cd	≤ 10	ND
Cu	≤ 10	0	Mn	≤ 10	ND
Mg	≤ 10	0			

QUALITY / DOCUMENTATION

Lot-specific Certificate of Analysis and SDS are available upon request.

Supplied and technically supported by Winigen Materials.

www.winigenmaterials.com | contact@winigenmaterials.com

TTE-TDS-001

Representative analytical results are provided for technical reference and may vary by lot. The lot-specific Certificate of Analysis governs material supplied.