



# Succinonitrile (SN)

## ELECTROLYTE ADDITIVE

### PRODUCT OVERVIEW

Succinonitrile (SN) is an electrolyte additive supplied for battery-electrolyte formulation, additive screening, and electrochemical research. This sheet summarizes specification limits and representative quality-control results.

### PRODUCT INFORMATION

CAS No. 110-61-2 | Formula  $C_4H_4N_2$  | Abbreviation SN

### TECHNICAL SPECIFICATIONS

| PROPERTY                                       | SPECIFICATION                        | REPRESENTATIVE QC RESULT                    | UNIT  |
|------------------------------------------------|--------------------------------------|---------------------------------------------|-------|
| Appearance                                     | Waxy solid, no mechanical impurities | Conforms                                    | —     |
| Color                                          | ≤30                                  | 19.6                                        | Hazen |
| Water                                          | ≤100                                 | 47.5                                        | ppm   |
| Assay                                          | ≥99.90                               | 99.959                                      | wt%   |
| Acidity, as HF                                 | ≤100                                 | 0                                           | ppm   |
| Chloride                                       | ≤5                                   | 0.44                                        | ppm   |
| Sulfate                                        | ≤10                                  | <10.0                                       | ppm   |
| Trace metals: Na / Ca / K / Pb / Fe / Cu / Zn  | ≤5 each                              | 0.10 / 0.03 / 0 / 0.19 / 0.01 / 0.01 / 0.04 | ppm   |
| Trace metals: Mg / Cr / Ni / Mn / Ba / Cd / Al | ≤5 each                              | 0 / 0 / 0 / 0 / 0 / 0.01 / 0                | ppm   |

### REPRESENTATIVE QC HIGHLIGHTS

99.959 wt% assay

47.5 ppm water

0 ppm acidity

### RESEARCH APPLICATIONS

Electrolyte formulation development; additive screening; cell-material compatibility studies; and electrochemical research. Suitability should be confirmed in the intended system.

### STORAGE / SHELF LIFE

180 days

### QUALITY / DOCUMENTATION

Specification limits and representative quality-control results are provided for technical reference. Lot-specific Certificate of Analysis is available upon request.

Supplied and technically supported by Winigen Materials.

www.winigenmaterials.com | contact@winigenmaterials.com

SN-TDS-001

Specification limits and representative quality-control results are provided for technical reference. Representative results are lot-specific and are not guaranteed values. The applicable lot-specific Certificate of Analysis governs material supplied.