

ARMP Deployment — R3

Frontend (Netlify staging)

Upload the contents of `deploy/` (including `deploy/auth/`) to the Netlify staging site root. `_headers` must be at the root. **Never upload** `tests/`, `supabase/seed/`, `source/internal/`, `generators/`, or `docs/` — they contain customer-derived fixtures or internal material.

Frontend config uses only public values: `SUPABASE_URL=https://vjxdmujxnmlfvnksvpy.supabase.co` and the publishable key. The service-role key is never in frontend config.

Backend (Supabase staging) — owner-approved, CI-driven

1. Owner sets GitHub secrets (`ARMP_SUPABASE_OWNER_SETUP`, Step 2).
2. GitHub → Actions → “ARMP R3 — Staging Deploy (manual)” → type `STAGING`. Runs `supabase db push` + `supabase functions deploy` against ref `vjxdmujxnmlfvnksvpy`.
3. Bootstrap the first owner (Step 5), then unset `ARMP_BOOTSTRAP_ENABLED`.

Exact files deployed to staging (shown before any apply, per §27A)

- Migrations: `supabase/migrations/20260722000000{1..8}*.sql`, `..8a`, `..9`, `..10`, `..11` (12 files).
- Functions: all 20 directories under `supabase/functions/` + `_shared/armpt.ts`. Command target: project ref `vjxdmujxnmlfvnksvpy` (staging). Production is never targeted.

CSP / headers

`deploy/_headers` allows the Supabase origin in `connect-src` (https only), no Stripe origins, `payment=()`, `object-src none`, `base-uri/form-action restricted`, `referrer-policy set`, `nosniff`. The `_headers` HTTP response file — not a meta tag — is the primary control.

Verify

`sha256sum -c SHA256SUMS.txt`, then `npm install && npm test`. Smoke-check `/`, `/demo.html` (synthetic), `/admin.html` (console sign-in), `/auth/*` pages.