

Metaheuristic Optimization

Lab 1: TSP solution generator

Traveling Salesman Problem

The Traveling Salesman Problem (TSP) asks the following question: “Given a list of cities and the distances between each pair of cities, what is the shortest possible route that visits each city and returns to the origin city?”. It is an NP-hard problem with important practical and theoretical questions in computer science.

The input is a complete graph with weighted edges. For brevity each vertex $v \in V$ is given an x-coordinate $x(v)$ and y-coordinate $y(v)$. The weight of the edge between vertex u and vertex v is defined by,

$$w(u, v) = \text{nint} (\text{sqrt}((x(u) - x(v))^2 + (y(u) - y(v))^2))$$

Where *nint* is a function that rounds a number to the nearest integer. The objective is to find the shortest cycle in the graph where each node is visited exactly once.

TSP has obvious applications in route planning and other logistics scenarios, but also in wire routing for printed circuit boards, genome analysis, and many other domains. Because it is easy to explain but computationally challenging, it is often used as a testbed for new algorithms to solve combinatorial problems.

In this lab you need to implement the following heuristic solution for the TSP:

Nearest neighbor insertion : Start with a randomly selected city and repeatedly insert the closest unvisited city to the last city chosen into the current tour.

Alternative insertion heuristic: Start with a randomly selected city and repeatedly choose a random unvisited city and insert it after the closest city in the current tour (If there is more than one city to which it is closest, insert it after the first such city you encounter).

I/O Specification

Format: the input file contains $n+1$ lines, where n is the number of nodes in the graph, i.e., $|V|$. The first line contains an integer n , it is followed by n lines, each line corresponds to the x, y -coordinates of a node. The coordinates contain integer and decimal values

[input format]

n

$Id_0\ x_0\ y_0$

$Id_1\ x_1\ y_1$

...

$Id_{n-1}\ x_{n-1}\ y_{n-1}$

Example

4

1 823170 415922

2 793699 274913

3 981665 218777

4 878910 431320

Lab work

Write a python program to find a solution to a given TSP instance, and compare performance, implementing

1. The Nearest Neighbor Insertion heuristic.
2. The alternative heuristic
3. Randomly generate a full tour

You need to run your code using the command:

```
python tsp.py <input filename> <nRuns>
```

where nRuns is the number of times to run the algorithm. Your output should not be a file but rather just print two values and one solution, the best objective value found over the nRuns, the average of the solutions objective values found over the nRuns, and the route of the best solution found.

Note: A test dataset (TSPdata.zip) is available on Canvas.