

API Keys & Provider Credentials Handoff

Operational credential schedule for Azari Residences / Azari Luxury Properties LTD

Prepared by	Zivora Systems
Prepared for	Azari Residences / Azari Luxury Properties LTD
Assessment date	29 July 2026
Code baseline	GitHub: wbizmo/azari-residences
Audited revision	ed804957576f0136f8ec266373fc733d4f855a73
Source templates	.env.example and .env.extra
Classification	Confidential - credential names only; no secrets included

Purpose. This document tells the client, deployment team and integration owners exactly which accounts, API credentials, sender identities, endpoints and infrastructure values must be supplied before the corresponding application features can operate.

Important: This document intentionally contains no usable password, API key, token or private credential. Values must be transferred through an approved secret-sharing channel and entered directly into the production environment by an authorised person.

1. Executive handoff summary

The application is fail-closed for most external integrations: a provider remains disabled until its enable flag is set and its credentials are configured. The production team can therefore launch the core application first and activate providers individually after account approval and end-to-end testing.

Area	Provider / system	Launch status	What the client or team must supply
Application	Laravel / hosting	Required	Production domain, database access, a newly generated APP_KEY, HTTPS certificate and deployment access.
Payments	Flutterwave	Required if selected	Live public key, secret key, encryption key, webhook secret/hash and webhook registration.
Payments	Pesapal API 3.0	Required if selected	Live consumer key/secret plus registered IPN notification UUID.
Payments	InTouch	Blocked pending contract	Official merchant credentials and exact API contract from the assigned InTouch merchant account.
Messaging	Twilio SMS / WhatsApp	Required if enabled	Account SID, Auth Token, approved sender or Messaging Service; WhatsApp sender and Content SIDs if used.
Owner payouts	Stripe / PayPal	Required if enabled	Stripe secret key; PayPal client ID and secret for the appropriate environment.
Email	SMTP / SES / Postmark / Resend	Operationally required	Credentials for one real delivery provider and an authorised From address/domain.
Storage / backup	Local or S3-compatible	Choice required	If S3 is selected: access key, secret, region, bucket and optional endpoint/URL.
Bot protection	CAPTCHA	Optional	Site key and secret key from the chosen CAPTCHA provider.
Maps	Map provider	Optional	Provider name and browser/server API key as applicable.

Priority definitions

- Required: the application cannot be safely deployed without the value.
- Required if enabled: the core platform can run without it, but the named feature must remain disabled until supplied and tested.
- Generated internally: created by the deployment team, not requested from an external provider.
- Configuration, not a credential: a URL, mode, timeout, sender name or routing choice that must still be confirmed.

Never copy the APP_KEY found in .env.extra. Generate a unique production value with `php artisan key:generate` on the deployment target.

2. Core application and hosting credentials

Environment variable	Owner	Requirement / source
APP_KEY	Deployment team	Generate on the production server. Do not reuse the template value and do not share publicly.
APP_ENV	Deployment team	Set to production.
APP_DEBUG	Deployment team	Set to false in production.
APP_URL	Client / hosting team	Final canonical HTTPS URL, e.g. https://example.com.
ASSET_URL	Deployment team	Usually blank unless assets are served from a separate host/CDN.
DB_HOST / DB_PORT	Hosting team	Production MySQL endpoint and port.
DB_DATABASE	Hosting team	Dedicated production database name.
DB_USERNAME / DB_PASSWORD	Hosting team	Least-privileged production database user and password.
REDIS_HOST / REDIS_PORT / REDIS_PASSWORD	Hosting team	Only when Redis is used. Current template defaults database-backed cache/queue/session.
SESSION_DOMAIN	Deployment team	Confirm for the final host; normally null for a single host.
AZARI_* recipient emails	Client	Operational mailboxes for contact, service requests, support tickets and booking notifications.

Production conditions

- HTTPS must be active before payment, messaging or webhook integrations are enabled.
- The production .env file must not be committed to Git or included in the release ZIP.
- After adding or rotating values, run `php artisan optimize:clear` and then rebuild/cache configuration according to the deployment runbook.
- The queue worker and scheduler must run continuously for queued webhooks, notifications, reconciliation and scheduled tasks.
- Use separate sandbox/test and live credentials. Never test live payment flows with sandbox identifiers.

3. Payment provider credentials

3.1 Flutterwave Standard / API v3

Variable	Required	Where obtained / instruction
FLUTTERWAVE_PUBLIC_KEY	Yes	Flutterwave dashboard API settings for the intended test or live account.
FLUTTERWAVE_SECRET_KEY	Yes	Flutterwave dashboard API settings. Server-side secret.
FLUTTERWAVE_ENCRYPTION_KEY	Expected by template	Flutterwave dashboard encryption key for the account/environment.
FLUTTERWAVE_WEBHOOK_SECRET	Yes for webhook validation	Set/obtain the webhook secret hash in the Flutterwave dashboard and enter the identical value.
FLUTTERWAVE_PAYLOAD_HASH_ENABLED	Configuration	Enable only when the chosen Flutterwave webhook/payload contract has been validated.
FLUTTERWAVE_MODE	Configuration	test during integration; live only after production sign-off.
FLUTTERWAVE_ENABLED	Activation	Keep false until checkout, redirect, callback, webhook and server-side verification tests pass.

Register webhook URL: `${APP_URL}/payments/flutterwave/webhook`

The base URL and v3 paths are already defined by the repository; they are normally not client-supplied credentials.

3.2 Pesapal API 3.0

Variable	Required	Where obtained / instruction
PESAPAL_CONSUMER_KEY	Yes	Pesapal merchant/developer account for sandbox or production.
PESAPAL_CONSUMER_SECRET	Yes	Pesapal merchant/developer account. Treat as a server secret.
PESAPAL_NOTIFICATION_ID	Yes for IPN	UUID returned after registering the application's IPN URL with Pesapal.
PESAPAL_CALLBACK_URL	Configuration	Already designed as <code>\${APP_URL}/payments/pesapal/callback</code> .
PESAPAL_MODE	Configuration	sandbox during testing; live only with production credentials and live base URL.
PESAPAL_ENABLED	Activation	Keep false until authentication, order submission, callback, IPN and status-query tests pass.

Register IPN URL: `${APP_URL}/payments/pesapal/webhook`

Callback URL: `${APP_URL}/payments/pesapal/callback`

3.3 InTouch payment integration

The repository intentionally keeps InTouch fail-closed. It must not be enabled from assumptions or generic credentials. The assigned InTouch account manager or merchant documentation must supply the exact contract below.

Variable / item	Required information from InTouch
INTOUCH_API_PROFILE	Use custom_v1 only after the complete merchant contract is confirmed.
INTOUCH_BASE_URL	Official test/live API base URL.
INTOUCH_INITIALISE_PATH	Exact payment-initialisation endpoint path.
INTOUCH_VERIFY_PATH	Exact transaction verification/status endpoint and reference placeholder.
INTOUCH_HEALTH_PATH	Optional health/status endpoint, if provided.
INTOUCH_MERCHANT_ID	Assigned merchant identifier.
INTOUCH_USERNAME / INTOUCH_PASSWORD	Merchant API basic-auth credentials, if required by the contract.
INTOUCH_SECRET	Assigned API secret/header secret, if applicable.
INTOUCH_API_TOKEN	Assigned API token and its exact header name.
INTOUCH_AUTH_MODE and header names	Confirm whether basic auth, token headers, merchant headers or a combination is required, including exact case/spelling.
INTOUCH_WEBHOOK_SECRET	Webhook signing secret plus signature algorithm and canonical payload rules.
Response field mappings	Checkout URL, provider reference, merchant reference, status, amount and currency field names.
Status values	Definitive successful and failed status enumerations.

Callback: `${APP_URL}/payments/intouch/callback`. The client/team must also obtain the actual webhook URL requirement from InTouch because the template only defines the callback and signing contract fields.

Acceptance rule

- Do not set `INTOUCH_ENABLED=true` until Zivora Systems has mapped the official merchant documentation to the configuration and verified test transactions.
- Verify amount, currency, merchant reference and provider reference server-side before any booking is marked paid.
- Require a signed webhook contract and an independent verification/status request.

4. Messaging credentials - Twilio

Variable	Required	Client/team action
TWILIO_ACCOUNT_SID	Yes	Obtain from the Twilio Console for the relevant account/subaccount.
TWILIO_AUTH_TOKEN	Yes	Obtain from the Twilio Console; treat as a server secret and rotate after exposure.
TWILIO_MESSAGING_SERVICE_SID	One sender option	Create/select a Messaging Service and supply its SID.
TWILIO_FROM_NUMBER	Alternative sender option	Supply an approved Twilio number/sender. The app supports either this or a Messaging Service SID.
TWILIO_STATUS_CALLBACK_URL	Configuration	Use \${APP_URL}/webhooks/twilio/message-status.
TWILIO_VALIDATE_WEBHOOKS	Keep true	Requires the Auth Token and exact public callback URL for Twilio signature verification.
TWILIO_DEFAULT_COUNTRY_CODE	Confirm	234 for Nigeria unless the operational requirement changes.
TWILIO_ENABLED	Activation	Keep false until a test SMS is delivered and callback validation succeeds.

WhatsApp through Twilio (optional)

Variable	Requirement
TWILIO_WHATSAPP_FROM	Approved WhatsApp sender in the format required by Twilio, typically prefixed with whatsapp:.
TWILIO_WHATSAPP_CONTENT_BOOKING_CONFIRMED	Approved Twilio Content SID for booking confirmations.
TWILIO_WHATSAPP_CONTENT_BOOKING_REMINDER	Approved Twilio Content SID for booking reminders.
TWILIO_WHATSAPP_CONTENT_PAYMENT_CONFIRMED	Approved Twilio Content SID for payment confirmations.
TWILIO_WHATSAPP_ENABLED	Set true only after the sender and templates have been approved and tested.

Twilio signs inbound webhook requests using the account Auth Token. Production must use the final HTTPS URL; proxy/CDN URL rewriting must preserve the externally visible callback URL used for signature validation.

5. Property-owner payout credentials

These credentials are for owner withdrawals/payout operations, not guest booking checkout.

Stripe

Variable	Requirement
STRIPE_SECRET	Restricted or secret key from the Stripe account used for the implemented payout/Connect workflow. Use test key first and live key only after account activation.
STRIPE_BASE_URL	Leave at https://api.stripe.com unless Stripe explicitly directs otherwise.

Before enabling Stripe owner payouts, confirm the business account, connected-account model, supported destination countries/currencies, required onboarding, payout capability and operational reconciliation process.

PayPal

Variable	Requirement
PAYPAL_CLIENT_ID	REST application client ID from the PayPal Developer Dashboard for sandbox or live.
PAYPAL_SECRET	REST application secret from the same PayPal application/environment.
PAYPAL_MODE	sandbox during testing; live only after the live application and payout permissions are approved.
PAYPAL_BASE_URL	Sandbox: https://api-m.sandbox.paypal.com . Live: https://api-m.paypal.com .

Operational approval

- The client must confirm the legal merchant/business account that owns each payout integration.
- Payout credentials require tighter access than public checkout keys because they can initiate movement of funds.
- Use provider roles/subaccounts where available, least privilege, provider MFA, alerts, transaction limits and dual approval for production operations.
- Test success, decline, timeout, retry, duplicate request and reconciliation-required paths before live activation.

6. Email, storage, CAPTCHA and maps

Email delivery

Variable / option	What must be supplied
MAIL_MAILER	Set to smtp, ses, postmark or resend for real delivery; the template value log does not send customer email.
SMTP	MAIL_HOST, MAIL_PORT, MAIL_USERNAME, MAIL_PASSWORD, MAIL_SCHEME as required by the provider.
MAIL_FROM_ADDRESS / NAME	Verified sender address/domain and display name.
Amazon SES	AWS access key, secret and region with SES permission; verify sender/domain and production sending access.
Postmark	POSTMARK_API_KEY if selected.
Resend	RESEND_API_KEY if selected.
Operational recipients	AZARI_CONTACT_RECIPIENT_EMAIL, AZARI_SERVICE_REQUEST_EMAIL, AZARI_SUPPORT_TICKET_EMAIL and AZARI_BOOKING_NOTIFICATION_EMAIL.

Storage and backups

Variable	When needed
FILESYSTEM_DISK / BACKUP_DISK	Choose local or the production storage design.
AWS_ACCESS_KEY_ID / AWS_SECRET_ACCESS_KEY	Required for S3/S3-compatible storage or SES as applicable. Prefer separate least-privilege identities for different duties.
AWS_DEFAULT_REGION / AWS_BUCKET	Required for the selected bucket.
AWS_URL / AWS_ENDPOINT	Optional/custom for CDN or S3-compatible services; supported by config/filesystems.php even though omitted from the two environment templates.
AWS_USE_PATH_STYLE_ENDPOINT	Set according to the selected S3-compatible provider.

CAPTCHA and maps

Feature	Variables / requirement
CAPTCHA	CAPTCHA_SITE_KEY and CAPTCHA_SECRET_KEY from the chosen provider; set CAPTCHA_ENABLED=true only after domain registration and verification.
Maps	MAPS_PROVIDER and MAPS_API_KEY. Restrict the key by domain, API and quota where supported; set MAPS_ENABLED=true only when configured.

7. Secure credential collection sheet

The following can be used as the handoff checklist. Mark a row complete only after the value has been stored in the production secret store and independently tested. Do not write secrets into this PDF.

Item	Owner	Status / reference (no secret)
Final APP_URL and HTTPS active	Hosting team	_____
Fresh production APP_KEY generated	Deployment team	_____
Production database credentials	Hosting team	_____
Real email delivery credentials and verified sender	Client / IT	_____
Flutterwave live credentials + webhook registered	Finance / client	_____
Pesapal live credentials + IPN UUID	Finance / client	_____
InTouch official merchant API contract	Finance / InTouch	_____
Twilio SID/token + sender	Client / communications	_____
Twilio WhatsApp sender + Content SIDs	Client / communications	_____
Stripe payout secret/account approval	Finance / client	_____
PayPal REST app credentials/payout approval	Finance / client	_____
S3/backup credentials and restore test	Hosting / IT	_____
CAPTCHA credentials	Client / deployment	_____
Maps provider/key restrictions	Client / deployment	_____
Operational recipient mailboxes confirmed	Client	_____

Recommended transfer process

- Client creates or owns each provider account wherever commercially appropriate.
- Client grants named role-based access to an authorised integrator instead of sharing the primary account password.
- Secrets are entered directly into the hosting secret manager or production .env through an encrypted, expiring one-time secret channel.
- Recipient confirms only the variable names received, never repeats secret values in acknowledgement messages.
- After configuration, revoke temporary access and rotate any credential exposed through ordinary email, WhatsApp, tickets, Git or screenshots.

8. Activation and acceptance procedure

Stage	Acceptance evidence
1. Account ownership	Provider account legal/business owner, billing owner and technical administrators documented.
2. Environment separation	Sandbox/test and production credentials are distinct; mode and base URL match.
3. Secret installation	Values entered into production environment; .env excluded from Git and release archive.
4. Endpoint registration	Payment webhooks, callbacks, Pesapal IPN and Twilio status callback registered with final HTTPS URL.
5. Functional test	Initiation, user redirect, callback and verified final state succeed.
6. Security test	Invalid signature, wrong amount/currency/reference and replay/duplicate event are rejected or safely reconciled.
7. Failure test	Timeout, provider error, queued retry and ambiguous response do not create duplicate payment/payout states.
8. Operations	Logs, queue worker, scheduler, alerts and provider dashboard access are available to named staff.
9. Sign-off	Client and Zivora Systems record the enabled providers and test transaction references without recording secrets.

Deployment commands after credential changes

```
php artisan optimize:clear  
php artisan config:cache  
php artisan queue:restart
```

Commands must be executed by the deployment team in the correct production release directory. Queue and scheduler supervision remains a hosting responsibility.

Go-live rule

Do not activate every integration simply because a credential exists. Enable one provider at a time only after its complete workflow and failure handling have passed acceptance. Unused providers should remain disabled and their credentials should be omitted.

9. Repository evidence and limitations

Files examined

Repository file	Purpose in this handoff
.env.example	Canonical environment variable inventory and provider callback notes.
.env.extra	Secondary environment template; same provider inventory. Its embedded APP_KEY is explicitly excluded from this report and must not be reused.
config/azari.php	Flutterwave, Pesapal, InTouch and shared integration configuration mapping.
config/services.php	Twilio, Stripe, PayPal and provider-service mappings.
config/mail.php	Supported mail transports and sender configuration.
config/filesystems.php	Local/private/public and S3-compatible storage variables.
routes/web.php	Application route composition; detailed provider endpoints are referenced by the environment templates.

Limitations and disclaimer

- This is a credential requirements and implementation handoff, not a certification that any provider account is approved, funded, compliant or able to transact in a particular country or currency.
- Provider dashboards, field names, approval rules, products and availability can change. The team must verify current provider documentation and the exact merchant contract at implementation time.
- No live provider account, credential, DNS record, TLS certificate, webhook delivery or production transaction was accessed or tested for this document.
- The list is grounded in the delivered repository revision shown on the cover. Later code changes may add, remove or rename variables.
- The client remains responsible for account ownership, commercial agreements, regulatory obligations, billing, settlement details, lawful messaging consent and provider terms.
- Zivora Systems should be notified before any integration variable is changed so configuration and application expectations remain aligned.

Source references

- Azari Residences audited GitHub revision
- Flutterwave developer documentation - authentication
- Pesapal developer documentation - API 3.0
- Twilio - webhook security and signature validation
- Twilio - Messaging Services and sender configuration
- Stripe - API keys
- PayPal - REST API credentials and environments
- Laravel - environment configuration

Prepared by Zivora Systems
For Azari Residences / Azari Luxury Properties LTD
29 July 2026