

meta viewport	The element that provides instructions to the browser on how to control a webpage's dimensions and scaling
jaggies	The informal name for visual anomalies that appear in display images
call-to-action	A prompt on a website that tells the site visitor to take a specified action
breakpoints	The point where a webpage's content and design changes to adapt to a different viewport and provide the optimum user experience
border-box	CSS property that tells the browser to bundle the size of any border or padding in the values that specify a box element's height or width
viewport	The visible area of a webpage on a device's screen. The size varies by device
mobile-first	Design approach where the initial design is structured for small screen sizes first, and then scaled up through the use of media queries for larger screen sizes
universal selector	Denoted by an asterisk (*), it selects all elements on an HTML page
CSS box model	A set of rules that define different parts of a box element on a page - including margin, border, padding, and content - render on a webpage. The size of the margin, border, padding, and content are all added together to determine the total size of a box
desktop-first	Design approach where the initial design is structured for larger screens first, and then scaled down through the use of media queries for smaller screen sizes
CSS Flexbox Module (Flexbox)	CSS layout module that distributes space on a webpage in one dimension at a time -- either as a row or as a column
media queries	Enable webpage content to adapt to different screen sizes and resolutions. They are a fundamental part of responsive web design and are used to customize the appearance of websites for multiple devices
responsive design	The use of CSS and HTML to resize, hide, shrink, enlarge, or move content so that it looks good on any device with any size screen
art direction	Changing the crop or composition of an image based on device characteristics or certain breakpoints
grid-based layout	A layout structure with vertical and/or horizontal guidelines that provides a framework for organizing content

inherited property	Property values that a child element receives from its parent element
pseudo-element	A keyword that is added to a selector that styles a specific part of a selected element