

# PANDAS

# OVERVIEW

# Pandas

- Panel Data Module
- objects: series and dataframes
- series similar to a table column
- dataframe similar to a table
- designed to manage indexed data (like SQL)

# Installing Pandas

- install via *pip*

```
>> pip install pandas
```

- in Spyder install via `!pip`

```
>> !pip install pandas
```

- import both Pandas and Numpy

```
import pandas as pd  
import numpy as np
```

# Pandas Series Object

- similar to an Excel column
- "similar" to dictionary:
  1. key: column name
  2. value: list of values (all of the same type)

dict

"Weight"	list							
	0	1	2	3	4	5	6	7
	100	150	130	150	180	190	170	165

- but values could have own index

# Constructing Series

```
import pandas as pd
import numpy as np

index          = [ "x1", "x2", "x3", "x4",
                   "x5", "x6", "x7", "x8"]
Weight         = [100, 150, 130, 150,
                  180, 190, 170, 165]
weight_series  = pd.Series(Weight, index)

>> weight_series
x1      100
x2      150
x3      130
x4      150
x5      180
x6      190
x7      170
x8      165
dtype: int64
```

# Default Index

- can use default indexing

```
import pandas as pd
import numpy as np
```

```
Weight          = [100, 150, 130, 150,
                   180, 190, 170, 165]
weight_series = pd.Series(Weight)
```

```
>> weight_series
```

```
0    100
```

```
1    150
```

```
2    130
```

```
3    150
```

```
4    180
```

```
5    190
```

```
6    170
```

```
7    165
```

```
dtype: int64
```

```
dtype: int64
```

# Creating a Series from Dictionary

```
import pandas as pd
import numpy as np

new_dict = {"x1":100, "x2":150, "x3":130, "x4":150,
            "x5":180, "x6":190, "x7":170, "x8":165}

weight_series = pd.Series(new_dict)

>> weight_series
x1      100
x2      150
x3      130
x4      150
x5      180
x6      190
x7      170
x8      165
dtype: int64
```

# Accessing Data in Series

```
import pandas as pd
import numpy as np

new_dict = {"x1":100, "x2":150, "x3":130,
            "x4":150, "x5":180, "x6":190,
            "x7":170, "x8":165}

weight_series = pd.Series(new_dict)
```

- use index

```
>> print(weight_series["x3"])
130
>> print(weight_series["x5"])
180
```



# Operations on Series

```
import pandas as pd
import numpy as np

index = [ "x1", "x2", "x3", "x4",
          "x5", "x6", "x7", "x8"]
Weight = [100, 150, 130, 150,
          180, 190, 170, 165]
Foot    = [6, 8, 7, 9, 13, 11, 12, 10]

weight_series = pd.Series(Weight, index)
foot_series   = pd.Series(Foot, index)

weight_per_foot=weight_series/foot_series
```

- can do basic arithmetic (over index)

# Operations on Series

## (cont'd)

```
>> weight_per_foot
x1      16.666667
x2      18.750000
x3      18.571429
x4      16.666667
x5      13.846154
x6      17.272727
x7      14.166667
x8      16.500000
dtype: float64
```

# Broadcasting

- can perform element-wise broadcasting
- similar to numpy

```
>> weight_series * 2
```

```
x1      200
```

```
x2      300
```

```
x3      260
```

```
x4      300
```

```
x5      360
```

```
x6      380
```

```
x7      340
```

```
x8      330
```

```
dtype: int64
```

# Pandas Dataframe

- *series* contains a list with index
- *dataframe* is a collection of series with (same) index
- can create in many ways:
  1. series object
  2. reading csv/Excel file
  3. numpy array
  4. dictionary

# Dataframe from Dictionary

```
import pandas as pd
import numpy as np

df = pd.DataFrame(
    {"Weight": [100, 150, 130, 150,
               180, 190, 170, 165],
     "Foot"   : [6, 8, 7, 9, 13, 11, 12, 10]})

>> df
   Foot  Weight
0     6    100
1     8    150
2     7    130
3     9    150
4    13    180
5    11    190
6    12    170
7    10    165
```

# Custom Indexing

```
import pandas as pd
import numpy as np

df = pd.DataFrame(
    {"Weight": [100, 150, 130, 150,
               180, 190, 170, 165],
     "Foot"   : [6, 8, 7, 9, 13, 11, 12, 10]},
    index=["x1", "x2", "x3", "x4",
           "x5", "x6", "x7", "x8"])
```

```
>> df
```

	Foot	Weight
x1	6	100
x2	8	150
x3	7	130
x4	9	150
x5	13	180
x6	11	190
x7	12	170
x8	10	165

# Getting Column Values

```
>> df["Foot"]  
x1      6  
x2      8  
x3      7  
x4      9  
x5     13  
x6     11  
x7     12  
x8     10  
Name: Foot, dtype: int64
```

- alternative method

```
>> df.Foot
```

# Multiple Column Values

- pass a list of column names

```
>> df[ ["Foot", "Weight"]]
```

	Foot	Weight
x1	6	100
x2	8	150
x3	7	130
x4	9	150
x5	13	180
x6	11	190
x7	12	170
x8	10	165



# Creating a New Column

- vectorized computation

```
>> df["weight_per_foot"] = df["Weight"]/  
                                df["Foot"]
```

```
>> df
```

	Foot	Weight	weight_per_foot
x1	6	100	16.666667
x2	8	150	18.750000
x3	7	130	18.571429
x4	9	150	16.666667
x5	13	180	13.846154
x6	11	190	17.272727
x7	12	170	14.166667
x8	10	165	16.500000

# Renaming Column(s)

- rename column(s) with new name(s)

```
>> df.rename(columns={"weight_per_foot":  
                      "density"}, inplace = True)
```

```
>> df
```

	Foot	Weight	density
x1	6	100	16.666667
x2	8	150	18.750000
x3	7	130	18.571429
x4	9	150	16.666667
x5	13	180	13.846154
x6	11	190	17.272727
x7	12	170	14.166667
x8	10	165	16.500000

# Dropping Column(s)

- drop column(s) "in-place"

```
>> df.drop("density", axis=1,  
           inplace=True)
```

```
>> df
```

	Foot	Weight
x1	6	100
x2	8	150
x3	7	130
x4	9	150
x5	13	180
x6	11	190
x7	12	170
x8	10	165

# Simple Sorting

- sorting by one column
- can be done "in-place"

```
>> df_2 = df.sort_values(by=["Weight"],  
                           ascending = [False])
```

```
>> df_2
```

	Foot	Weight
x6	11	190
x5	13	180
x7	12	170
x8	10	165
x2	8	150
x4	9	150
x3	7	130
x1	6	100

# Multi-Column Sorting

- sorting by multiple columns
- can be done "in-place"

```
>> df_3 = df.sort_values(  
    by=["Weight", "Foot"],  
    ascending=[False, False])
```

```
>> df_3
```

	Foot	Weight
x6	11	190
x5	13	180
x7	12	170
x8	10	165
x4	9	150
x2	8	150
x3	7	130
x1	6	100

## *head()* and *tail()*

- *head*(n) - first *n* rows
- *tail*(n) - last *n* rows

```
>> weight_frame.head(2)
```

	Foot	Weight
x1	6	100
x2	8	150

```
>>
```

```
>> weight_frame.tail(2)
```

	Foot	Weight
x7	12	170
x8	10	165

# A Numerical Dataset

object $x_i$	Height (H)	Weight (W)	Foot (F)	Label (L)
$x_1$	5.00	100	6	green
$x_2$	5.50	150	8	green
$x_3$	5.33	130	7	green
$x_4$	5.75	150	9	green
$x_5$	6.00	180	13	red
$x_6$	5.92	190	11	red
$x_7$	5.58	170	12	red
$x_8$	5.92	165	10	red

- $N = 8$  items
- $M = 3$  (unscaled) attributes

# Code for the Dataset

```
import pandas as pd
data = pd.DataFrame(
    {"id": [ 1,2,3,4,5,6,7,8] ,
     "Label": ["green", "green", "green", "green",
               "red", "red", "red", "red"] ,
     "Height": [5, 5.5, 5.33, 5.75, 6.00, 5.92, 5.58, 5.92] ,
     "Weight": [100, 150, 130, 150, 180, 190, 170, 165] ,
     "Foot": [6, 8, 7, 9, 13, 11, 12, 10]} ,
    columns=["id", "Height", "Weight",
             "Foot", "Label"])
```

```
ipdb> data
```

	id	Height	Weight	Foot	Label
0	1	5.00	100	6	green
1	2	5.50	150	8	green
2	3	5.33	130	7	green
3	4	5.75	150	9	green
4	5	6.00	180	13	red
5	6	5.92	190	11	red
6	7	5.58	170	12	red
7	8	5.92	165	10	red




# Alternative Approach

```
data = pd.DataFrame(  
    data = [ [1, 5,      100, 6,  "green"],  
              [2, 5.5,   150, 8,  "green"],  
              [3, 5.33,  130, 7,  "green"],  
              [4, 5.75,  150, 9,  "green"],  
              [5, 6,     180, 13, "red"],  
              [6, 5.92,  190, 11, "red"],  
              [7, 5.58,  170, 12, "red"],  
              [8, 5.92,  165, 10, "red"]],  
    columns = ["id", "Height", "Weight",  
               "Foot", "Label"] )
```

```
ipdb> data
```

	id	Height	Weight	Foot	Label
0	1	5.00	100	6	green
1	2	5.50	150	8	green
2	3	5.33	130	7	green
3	4	5.75	150	9	green
4	5	6.00	180	13	red
5	6	5.92	190	11	red
6	7	5.58	170	12	red
7	8	5.92	165	10	red

# A Dataset Illustration



# Some Observations

- data in different shapes  
(dictionary, lists)
- different data types
- columns have custom names
- index can be in different  
formats

# Typical Operations

- index values

```
> data.index
```

```
RangeIndex(start=0, stop=8, step=1)
```

- column names

```
> data.columns
```

```
Index(['id', 'Height', 'Weight', 'Foot',  
      'Label'], dtype='object')
```

# Data Selection

- selection via index:

1. `.loc` by label

2. `.iloc` by position

```
> data.iloc[5]
```

```
id          6
```

```
Height      5.92
```

```
Weight      190
```

```
Foot        11
```

```
Label       red
```

```
Name: 5, dtype: object
```

# Data Selection

- selection of multiple indices

```
> data.iloc[[5,7]]
```

	id	Height	Weight	Foot	Label
5	6	5.92	190	11	red
7	8	5.92	165	10	red

- selection via index object

```
> data.iloc[data.index[1:7:2]]
```

	id	Height	Weight	Foot	Label
1	2	5.50	150	8	green
3	4	5.75	150	9	green
5	6	5.92	190	11	red

# Statistical Functions

- apply statistical functions

```
> data[['Height', 'Weight',  
        'Foot']].mean()
```

```
Height      5.625
```

```
Weight     154.375
```

```
Foot        9.500
```

```
dtype: float64
```

# Lambda Functions

- apply lambda functions

```
> data[['Height',  
        'Weight']].apply(lambda x: x**2)
```

	Height	Weight
0	25.0000	10000
1	30.2500	22500
2	28.4089	16900
3	33.0625	22500
4	36.0000	32400
5	35.0464	36100
6	31.1364	28900
7	35.0464	27225



# Adding Column(s)

```
> data['n_col']=['a','b','c','d',  
                'e','f','g','h']
```

```
> data
```

	id	Height	Weight	Foot	Label	n_col
0	1	5.00	100	6	green	a
1	2	5.50	150	8	green	b
2	3	5.33	130	7	green	c
3	4	5.75	150	9	green	d
4	5	6.00	180	13	red	e
5	6	5.92	190	11	red	f
6	7	5.58	170	12	red	g
7	8	5.92	165	10	red	h

# Dropping Column(s)

```
> data.drop(['n_col'],axis=1,inplace=True)
```

```
> data
```

	id	Height	Weight	Foot	Label
0	1	5.00	100	6	green
1	2	5.50	150	8	green
2	3	5.33	130	7	green
3	4	5.75	150	9	green
4	5	6.00	180	13	red
5	6	5.92	190	11	red
6	7	5.58	170	12	red
7	8	5.92	165	10	red

- axis: 1-columns, 0 - rows

# Dropping Duplicates

- can also drop "in-place"

```
>> data_2=data.drop_duplicates("Weight")
```

```
>> data_2
```

	id	Height	Weight	Foot	Label
0	1	5.00	100	6	green
1	2	5.50	150	8	green
2	3	5.33	130	7	green
4	5	6.00	180	13	red
5	6	5.92	190	11	red
6	7	5.58	170	12	red
7	8	5.92	165	10	red

# Desribing the Dataset

```
import pandas as pd
data = pd.DataFrame(
    {"id": [ 1,2,3,4,5,6,7,8] ,
     "Label": ["green", "green", "green", "green",
               "red", "red", "red", "red"] ,
     "Height": [5,5.5,5.33,5.75,6.00,5.92,5.58,5.92] ,
     "Weight": [100,150,130,150,180,190,170,165] ,
     "Foot": [6, 8, 7, 9, 13, 11, 12, 10]} ,
    columns=["id", "Height", "Weight",
             "Foot", "Label"])
```

```
ipdb> data.describe()
```

	id	Height	Weight	Foot
count	8.00000	8.000000	8.000000	8.00000
mean	4.50000	5.625000	154.375000	9.50000
std	2.44949	0.343428	28.962722	2.44949
min	1.00000	5.000000	100.000000	6.00000
25%	2.75000	5.457500	145.000000	7.75000
50%	4.50000	5.665000	157.500000	9.50000
75%	6.25000	5.920000	172.500000	11.25000
max	8.00000	6.000000	190.000000	13.00000

# Reversing Rows

```
> data_rev_rows = data.loc[::-1]
```

```
> data_rev_rows
```

	id	Height	Weight	Foot	Label
7	8	5.92	165	10	red
6	7	5.58	170	12	red
5	6	5.92	190	11	red
4	5	6.00	180	13	red
3	4	5.75	150	9	green
2	3	5.33	130	7	green
1	2	5.50	150	8	green
0	1	5.00	100	6	green

- similar to Python lists

# Reversing Columns

```
> data_rev_cols = data.loc[:, ::-1]
```

```
> data_rev_cols
```

	Label	Foot	Weight	Height	id
0	green	6	100	5.00	1
1	green	8	150	5.50	2
2	green	7	130	5.33	3
3	green	9	150	5.75	4
4	red	13	180	6.00	5
5	red	11	190	5.92	6
6	red	12	170	5.58	7
7	red	10	165	5.92	8

- similar to Python lists

# Filtering s DataFrame

```
> data_red = data[data["Label"]=="red"]
```

```
> data_red
```

	id	Height	Weight	Foot	Label
4	5	6.00	180	13	red
5	6	5.92	190	11	red
6	7	5.58	170	12	red
7	8	5.92	165	10	red

```
> data_s = data[data["Foot"].isin([7,9])]
```

```
> data_s
```

	id	Height	Weight	Foot	Label
2	3	5.33	130	7	green
3	4	5.75	150	9	green

# Filtering s DataFrame

## (cont'd)

```
> data_med = data[(data["Foot"] > 6)
                  & (data["Weight"] < 160)]
```

```
> data_med
```

	id	Height	Weight	Foot	Label
1	2	5.50	150	8	green
2	3	5.33	130	7	green
3	4	5.75	150	9	green

- can use multiple criteria



# Counting Values

```
> counts = data['Weight'].value_counts()
```

```
> counts
```

```
150      2
```

```
190      1
```

```
170      1
```

```
165      1
```

```
180      1
```

```
130      1
```

```
100      1
```

```
Name: Weight, dtype: int64
```

```
> counts.nlargest(1)
```

```
150      2
```

```
Name: Weight, dtype: int64
```

# Aggregating

```
> data_m = data.groupby("Label")  
                ["Weight"].mean()
```

```
> data_m
```

```
Label
```

```
green    132.50
```

```
red      176.25
```

```
Name: Weight, dtype: float64
```

```
> data_ms = data.groupby("Label")  
                ["Weight"].agg(["mean", "std"])  
                mean          std
```

```
Label
```

```
green    132.50    23.629078
```

```
red      176.25    11.086779
```

## Concepts Check:

- (a) *Series* object
- (b) broadcasting
- (c) Pandas *DataFrame*
- (d) column creation, indexing, sort
- (e) *head()* and *tail()* functions
- (f) data selection (label, position)
- (g) lambda functions
- (h) filtering, counting, aggregation