Zenith: Learning a Financial Reasoning Pipeline from Daily Experience

The Lab, Oracle and Evolve system

Will Cook*

Development report, 12 October 2026

Abstract

Zenith is a financial reasoning system built around repeated experience. A historical trading day's available feeds enter Lab, an inspectable reasoning graph that produces a thesis and dated forecasts. After the forecast horizon, Oracle compares the frozen attempt with later observations and investigates which earlier evidence could have supported a better decision. Evolve uses that comparison to propose a transferable change to the reasoning pipeline; a reviewed successor then faces later days. The learning object is the pipeline's instructions, context, skills and eventually structure. The current implementation retains the original full Lab and Oracle, source-bound agent handoffs, output contracts and versioned policies in a standalone source checkout. A pinned three-equity panel provides 291 shared daily price dates and 4,990 date-bucketed news summaries, with explicit availability assumptions. One primary-agent development episode on a separate AA slice completed all 28 Lab and 31 Oracle nodes; a separate paid-model attempt failed. The completed forecast had the correct direction but an unsupported causal explanation. A daily controller now connects preparation, native execution, explicit review of Evolve proposals and matched comparisons between generations. These results establish runnable mechanics, not learned forecasting advantage. The next empirical question is whether reviewed changes improve later reasoning and forecasts beyond an unchanged pipeline.

1 The system we want to learn

The design starts from the job a financial reasoner should repeatedly perform: inspect the available information, explain a view, make commitments, confront what happens and improve the procedure. Historical data supplies many dated instances of that job. It should preserve the shape of the intended live inputs rather than determine an unrelated research task simply because a benchmark is convenient to score.

Lab, Oracle and Evolve implement three distinct responsibilities. Lab commits using the information available at the issue time. Oracle receives both that frozen attempt and later evidence. Evolve decides whether the experience justifies a change that can be used without future information on a subsequent attempt. The investigator may be the lead agent or a worker given a fixed prompt and the same bound evidence. A scheduled chat is not required by the algorithm; it is one possible execution service.

*AI agents researched, implemented and drafted this work under Will Cook's direction. Recorded source material and execution evidence delimit its claims.

Here, learning initially means changing durable reasoning procedures and context policies, not updating the underlying language model's weights. Useful changes might make a miner recover the last comparable disclosure, require a synthesis node to confront a contrary observation, or make a forecaster disclose how it converted a qualitative view into a target price. Graph changes are a broader development option. One short skill update is the first implemented daily transition, not a permanent limit on the programme.

The central distinction is between improving a historical answer and improving the procedure that produces later answers. A hindsight explanation may expose a missed earlier signal, but it may also depend entirely on information that arrived afterward. That difference must survive into the proposed lesson.

The operator's generation analogy comes from AlphaGo Zero: experience generated by a current system informs an improved policy, which supports subsequent experience [20]. Here the policy is a reasoning procedure, and its candidate version is compared with the incumbent on the same later market situations. This is a design analogy, not an implementation of neural self-play or tree search. Market outcomes must come from external observations; replaying a historical date cannot create a new independent market realization.

2 One native graph, three stages

The standalone checkout contains the existing loader, executor, authored node JSON, contracts and policy machinery. It does not depend on the parent workspace's kernel, Task Ledger, private dossiers or interactive Station. The physical registry has 71 nodes across all retained mission families. The daily path executes the full 28-node Lab and 31-node Oracle; it does not substitute the earlier three-node price-only experiment.

Stage	Evidence and work	Persistent result
Snapshot	Completed prices and eligible news at one trading-day boundary	Immutable feeds, clocks, source hashes and missingness
Lab	Two mining passes, cross-lane synthesis, CP1 thesis, CP2 forecasts and integrity review	Frozen predictions, supporting trace and validation results
Oracle	Original attempt, original evidence and separate later observations	Reconciliation, hindsight brief, critique and ideal CP2
Evolve	Bound Lab/Oracle pair and current policy	Reviewed no-change decision or versioned candidate
Later Lab	A later snapshot and selected policy	New forecasts whose behavior can be assessed

Table 1: The daily loop. Completion of a stage and quality of its reasoning are separate facts.

The original engine assembles prompts, validates dependency order and accepts reasoning responses through its native importer. A missing response creates a pend-

ing packet; it is not successful reasoning. The daily controller advances only after the preceding mission is complete. Lab output remains fixed while Oracle examines it. Rejected responses, failed provider attempts and uncertain cost reservations remain part of the record.

The temporal handoff between versions is not a cycle inside a single forward graph. The first Lab cannot acquire Oracle's later inputs through an ordinary edge. Oracle keeps the original issue anchor and the later target time; Evolve's successor is used only on the next eligible issue. Historical replay still does not simulate the wall-clock time required to obtain and review real closing data. A live system needs a corresponding execution delay.

3 Historical feeds that fit the actual system

The longer development adapter uses three JSON files from InvestorBench [14, 15]. The pinned MSFT, HON and JNJ files share all 291 XNYS sessions from 12 March 2020 through 6 May 2021. They contain 3,636, 444 and 910 news summaries respectively. Our source audit finds no missing shared price sessions; all three symbols have news on 196 dates. These counts describe the selected files, not reproduced benchmark performance.

A snapshot contains twenty observed scalar prices per symbol and the preceding seven calendar days of complete upstream summaries. Summary date buckets lack publication and capture clocks, so the adapter assumes availability at midnight in New York on the following calendar day and excludes the current date. It excludes all filing summaries because their availability is unestablished. This is a reconstructed development stream: the lag does not prove historical availability, issuer relevance, adjustment vintage or immunity to model memory. The source repository's MIT license also does not independently establish rights to redistribute every publisher-derived item. Public code supplies the pins and adapter; downloaded text remains in local storage.

The initial adapter uses the original AA price and article files in FNSPID, pinned to source revision `4054842` [10]. For each selected XNYS session it emits the last 20 completed daily price bars and full eligible article bodies from the preceding seven calendar days. The source is a practical starting slice: two small files, approximately 8.66 MB together. It does not supply a complete multi-asset research universe.

STOCK and NEWS contain observations. ETF, MACRO, POLYMARKET, CALCULATOR and STOCKGRID retain their native artifact names but explicitly contain no supplied observations. Their absence limits support; it is not an economic event. A market article discussing macro conditions does not become an independently observed macro series. Preserving these distinctions permits the full graph to run while making the cost of sparse coverage visible.

Source admission uses original publication strings rather than blindly trusting upstream preprocessing. For example, a January article marked 17:51 EST is 22:51 UTC and must not enter that day's 21:00 UTC close snapshot. The inspected upstream converter shifted that offset in the wrong direction. Literal `Text=0` is missing text, not neutral news. Invalid or conflicting clocks are excluded and counted. The adapter retains origi-

nal body hashes and stable evidence identifiers; an AA filename does not establish that every article concerns Alcoa specifically.

The Jan16,17,18 2024 snapshots contain 1,7,7 eligible article bodies, respectively. Jan18 has no fresh article in this slice; repeated context is not new evidence. Source prices use `Close` consistently. Corporate-action vintages, original capture times and later article revisions are unverified. Filtering a publisher clock alone cannot establish complete point-in-time integrity. Modern language models may also remember historical events [11].

Other data candidates remain available for investigation. An inspected FinMultiTime article slice had body/date/URL mismatches and was not admitted to this replay; that observation does not invalidate separately sourced price or filing tables [23]. Data acquisition remains explicit. The public code does not redistribute these article bodies.

4 Oracle: outcome, explanation and earlier opportunity

Oracle first asks a mechanical question: what happened to each declared target over its declared horizon? Exact later observations score the frozen forecast. It then asks interpretive questions: which original claims were supported, which information was missed, what appeared only afterward, and which proposed causes remain uncertain? A correct direction does not validate the explanation that accompanied it.

An ideal historical answer is useful only when its earlier citations are actually available at the earlier boundary. Later reporting may direct the investigation toward a neglected earlier signal, but it cannot itself become a Lab citation. A surprising event with no earlier support should remain an unforecastable or uncertain component rather than an instruction that earlier miners ought to have discovered the future. Outcome-only and richer hindsight teachers are distinct experimental conditions, related to learning with privileged information [21].

Financial interpretation must also distinguish familiar facts from changes. For example, Salesforce's May 2023 release preserved annual revenue guidance while raising non-GAAP operating-margin guidance [18, 19]. That supports a profitability revision, not a revenue revision or an assertion about analyst surprise. Adobe's June release raised some annual targets while lowering a segment revenue range [1–3]. These supporting cases test a recurring reasoning skill; they are not the selected replacement for the daily system.

The remaining price effect is a further question. A public announcement may already be reflected in the price at which a decision could be executed. Headline-return work motivates separating observed response from later predictability [16]. Economic relationships can motivate indirect transmission [8]; shared words alone do not establish one.

5 Evolve: reviewed transitions between versions

The existing Evolve runner exports its fixed analysis instructions, original Lab CP2 and Oracle quartet with source bindings. The daily controller adds a small response contract: diagnosis, uncertainty, proposed later test, exact source quotations, and either one Lab

skill change or an explicit no-change decision. The lead agent can perform this review directly. A worker receives the same packet and returns the same shape.

Import checks the packet identity, reconstructs source bindings, resolves each quoted JSON field against its original artifact, validates the permitted node and compiles a native reasoning policy. It retains rejected attempts. An accepted candidate is a new policy file; the next day's Lab freezes that file in its execution manifest. The original policy and dossiers remain available. Repeated continuation reads recheck the decision and candidate instead of trusting a success label alone.

These checks establish provenance, structure and an explicit review decision. They cannot establish that a quoted fact supports the proposed generalization. The reviewing agent's identity is a disclosure, not authenticated expertise. No-change is a legitimate outcome when the episode supplies no convincing lesson. The transition is development adoption for later testing, not promotion to a proven live trading policy.

TextGrad and GEPA provide relevant precedents for textual feedback and reflective prompt search [4, 28]; Trace and multi-stage instruction optimization motivate inspecting intermediate computations [7, 17]. Financial agent systems provide precedents for layered memory and persistent guidance [26, 27]. Zenith uses these sources to sharpen its own explicit transition and controls. It does not claim that implementing a loop establishes a new optimization method or inherits their reported results.

6 What has actually executed

A paid full-graph development attempt using DeepSeek V4.1 Flash stopped at CP1 after 17 of 28 Lab nodes and 11 reasoning calls. Its responses confused artifact names with valid evidence identifiers, misstated numerical facts and turned missing lanes into market narrative. The attempt and its accounting remain preserved; it is not counted as a completed prediction.

A separate primary-agent attempt completed all 28 Lab nodes through 21 native reasoning imports. Its paired Oracle completed all 31 nodes through 11 accepted reasoning imports. The original forecast was down from approximately $27.87 to $27.50; the later close was approximately $27.18, producing absolute price error of $0.32. Direction was correct. Semantic review remained red because an observed trend did not establish a forward causal mechanism. This is one exposed, manually reasoned development episode, not a performance estimate for the failed paid model or the wider system.

The primary review proposed that the director distinguish the measured pattern, proposed mechanism and numerical target rule, and avoid increasing causal confidence after one directional hit. A following-day Lab was prepared with that policy but has no completed successor forecast. The newer daily controller makes the same kind of review and transition repeatable. Native hydration and synthetic transition tests establish its wiring; they do not supply additional historical forecast results. The original episode is recorded in `docs/daily-replay-receipt.json`.

Earlier A-share numerical and text controls remain useful negative development evidence [5, 12]. On 33 exposed dates, raw mean squared errors were 0.00141850 and 0.00148344 versus a zero-relative-return reference of 0.00109518. Chronological scaling produced 0.00108729 and 0.00108654. The design followed earlier aggregate inspection;

the small differences do not establish an LLM or incremental text advantage. Their retained diagnosis concerns forecast magnitude, not completion of the full daily learning loop.

7 The next useful experiment

The immediate objective is competent repeated execution with enough genuine information for the reasoning job. The newly admitted longer panel now supports this work, alongside review of missing and stale evidence and a model that consistently meets the existing contracts. Increasing the number of agents does not repair a weak source packet or an unsupported target rule.

The implemented generation adapter freezes a reviewed challenger and the exact policy that produced its teacher episode, using the existing native cohort executor and feedback evaluator. Both run the full Lab on identical later snapshots and target support with the same disclosed model identity. The selection loss is mean issue-level mean target-price relative error. Its improvement margin is declared before execution. Complete support and at least twenty issue dates are required; these are decision gates, not significance guarantees. A twenty-date two-version comparison requires 840 reasoning responses before retries, which makes base competence a practical prerequisite.

A separately reviewed retention receipt binds the comparison, selected policy and final truth cutoff. The challenger is retained only if it clears the declared margin; otherwise the incumbent remains. The next generation's first issue must follow that cutoff. Historical development remains exposed, even when these chronology and provenance checks pass. No such generation comparison has yet completed; synthetic retention tests establish the control boundary only.

Once the base works, compare an unchanged pipeline with a pipeline that receives reviewed updates, on identical later snapshots and target support. Preserve all attempts and separate source failure, invalid output, abstention, forecast error and reasoning quality. Include simple price references and a strong direct reasoner before attributing benefit to graph complexity. Numerical calibration, experience retrieval and learned procedures need separate controls. Repeated selection on the same history creates optimism [6, 9, 24]; later untouched and prospective episodes are stronger evidence than another explanation of an inspected result.

The supplied temporal forecasting paper motivates combining time-series context and text [25]; explanatory prose still needs a fidelity test. Cross-stock semantic work suggests candidate relationships to verify [13]. Financial-network forecasting motivates numerical and narrative analogs, but its targets differ from stock returns [22]. Their ideas can improve source selection and diagnostic questions without turning their benchmarks into Zenith's objective.

A trading claim would additionally require an executable entry rule, delays, positions, overlapping exposures, distributions and costs. Neither the one-day manual replay nor the supporting A-share labels establish profitability. The current deliverable is a self-contained implementation of the original learning loop and an auditable place to improve it. Whether its changes produce better later financial reasoning remains the research question.

Reproduction. Start with `README.md` and `docs/daily-replay.md`. The source checkout supports editable installation on macOS/Linux; wheel and Windows distribution are not verified. `zenith daily init` freezes the daily inputs; `zenith daily next` exposes the next actual native task; `zenith import-response` validates Lab/Oracle answers; `zenith daily review` records the reviewed Evolve decision. `zenith daily matchoff` freezes a native comparison and `zenith daily retain` records its reviewed selection; the next initializer consumes `--retention`. See `docs/generations.md`. No command in this controller purchases inference or starts a separate chat. Datasets are reacquired by pinned source identity. Historical execution custody remains local where source rights prevent bundling full inputs and transcripts. `paper/README.md` maps the evidence and limitations.

References

[1] Adobe. Adobe Reports Record Q4 and Fiscal 2022 Revenue, 2022. URL https://www.adobe.com/cc-shared/assets/investor-relations/pdfs/a2343eivfp98u.pdf. Issuer release, 2022-12-15; annual guidance tables.

[2] Adobe. Adobe Reports Record Revenue in Q2 Fiscal 2023, 2023. URL https://www.adobe.com/cc-shared/assets/investor-relations/pdfs/au5y5egrth7y.pdf. Issuer release, 2023-06-15; annual guidance tables.

[3] Adobe. Adobe Reports Record Revenue in Q1 Fiscal 2023, 2023. URL https://www.adobe.com/cc-shared/assets/investor-relations/pdfs/ayu784645yet.pdf. Issuer release, 2023-03-15; annual guidance tables.

[4] Lakshya A Agrawal, Shangyin Tan, Dilara Soylu, Noah Ziems, Rishi Khare, Krista Opsahl-Ong, Arnav Singhvi, Herumb Shandilya, Michael J Ryan, Meng Jiang, Christopher Potts, Koushik Sen, Alexandros G. Dimakis, Ion Stoica, Dan Klein, Matei Zaharia, and Omar Khattab. GEPA: Reflective Prompt Evolution Can Outperform Reinforcement Learning. arXiv:2507.19457v2, 2025. URL https://arxiv.org/abs/2507.19457v2. Version read: 2507.19457v2.

[5] ANTICH. TraderHarness A-share 5-Year Market Dataset, 2026. URL https://huggingface.co/datasets/ANTICH/traderharness-ashare-5y/tree/3bf5151ab3e94851bb09dd8ade815563c44b15a6. Dataset revision 3bf5151; original text and prices retained locally.

[6] Gavin C. Cawley and Nicola L. C. Talbot. On Over-fitting in Model Selection and Subsequent Selection Bias in Performance Evaluation. *Journal of Machine Learning Research*, 11 (70):2079–2107, 2010. URL https://www.jmlr.org/papers/v11/cawley10a.html.

[7] Ching-An Cheng, Allen Nie, and Adith Swaminathan. Trace is the Next AutoDiff: Generative Optimization with Rich Feedback, Execution Traces, and LLMs. arXiv:2406.16218v2, 2024. URL https://arxiv.org/abs/2406.16218v2. Version read: 2406.16218v2.

[8] Lauren Cohen and Andrea Frazzini. Economic Links and Predictable Returns. *The Journal of Finance*, 63(4):1977–2011, 2008. doi: 10.1111/j.1540-6261.2008.01379.x. URL https://doi.org/10.1111/j.1540-6261.2008.01379.x.

[9] Cynthia Dwork, Vitaly Feldman, Moritz Hardt, Toniann Pitassi, Omer Reingold, and Aaron Roth. Generalization in Adaptive Data Analysis and Holdout Reuse. arXiv:1506.02629v2, 2015. URL https://arxiv.org/abs/1506.02629v2. Version read: 1506.02629v2.

[10] FNSPID contributors. FNSPID original AA news and price CSV source snapshot, 2025. URL https://github.com/Zdong104/FNSPID_Financial_News_Dataset/tree/4054842ec476953b30ee874d4b7e8eea786a21fa. Commit 4054842ec476953b30ee874d4b7e8eea786a21fa; original news and stock-price files under data_processor, inspected 12 October 2026. Dataset adaptation, not reproduction of reported model scores.

[11] Paul Glasserman and Caden Lin. Assessing Look-Ahead Bias in Stock Return Predictions Generated By GPT Sentiment Analysis. arXiv:2309.17322v1, 2023. URL https://arxiv.org/abs/2309.17322v1. Version read: 2309.17322v1.

[12] HephaestLab. TraderHarness: A Contamination-Resistant Environment for Autonomous Trading Agents, 2026. URL https://github.com/HephaestLab/TraderHarness/tree/3e18369da5a2060f9c65b27c2a63f99edd93e167. Software v1.1.0, 19 July 2026; source commit 3e18369. The title is not a contamination guarantee for this study.

[13] Yikuan Huang, Zheqi Fan, Kaiqi Hu, and Yifan Ye. Cross-Stock Predictability via LLM-Augmented Semantic Networks. arXiv:2604.19476v2, 2026. URL https://arxiv.org/abs/2604.19476v2. Version 2, 26 April 2026; methodological comparison, not a reproduced result.

[14] InvestorBench contributors. INVESTOR-BENCH public data source snapshot, 2025. URL https://github.com/felis33/INVESTOR-BENCH/tree/87e0f7bc83baf7d89fbdc1a51f92458f8d4ee11a. Commit 87e0f7bc83baf7d89fbdc1a51f92458f8d4ee11a; data/msft.json, data/hon.json and data/jnj.json, inspected 12 October 2026.

[15] Haohang Li, Yupeng Cao, Yangyang Yu, Shashidhar Reddy Javaji, Zhiyang Deng, Yueru He, Yuechen Jiang, Zining Zhu, K. P. Subbalakshmi, Jimin Huang, Lingfei Qian, Xueqing Peng, Jordan W. Suchow, and Qianqian Xie. INVESTORBENCH: A benchmark for financial decision-making tasks with LLM-based agent. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics* (*Volume 1: Long Papers*), pages 2509–2525. Association for Computational Linguistics, 2025. doi: 10.18653/v1/2025.acl-long.126. URL https://aclanthology.org/2025.acl-long.126/.

[16] Alejandro Lopez-Lira and Yuehua Tang. Can ChatGPT Forecast Stock Price Movements? Return Predictability and Large Language Models. arXiv:2304.07619v6, 2023. URL https://arxiv.org/abs/2304.07619v6. Version read: 2304.07619v6; original submission 2023.

[17] Krista Opsahl-Ong, Michael J Ryan, Josh Purtell, David Broman, Christopher Potts, Matei Zaharia, and Omar Khattab. Optimizing Instructions and Demonstrations for Multi-Stage Language Model Programs. arXiv:2406.11695v2, 2024. URL https://arxiv.org/abs/2406.11695v2. Version read: 2406.11695v2.

[18] Salesforce. Salesforce Announces Strong Fourth Quarter and Full Fiscal 2023 Results, 2023. URL https://www.salesforce.com/news/press-releases/2023/03/01/q4-fy23-results-update/?bc=OTH. Issuer release, 2023-03-01; annual guidance tables.

[19] Salesforce. Salesforce Announces Strong First Quarter Fiscal 2024 Results, 2023. URL https://www.salesforce.com/news/press-releases/2023/05/31/fy24-q1-earnings/. Issuer release, 2023-05-31; annual guidance tables.

[20] David Silver and Demis Hassabis. AlphaGo Zero: Starting from Scratch, 2017. URL https://deepmind.google/blog/alphago-zero-starting-from-scratch/. DeepMind, 18 October 2017. Primary account of the self-play and policy-improvement cycle; used here as a design analogy.

[21] Vladimir Vapnik and Rauf Izmailov. Learning using privileged information: Similarity control and knowledge transfer. *Journal of Machine Learning Research*, 16(61):2023–2049, 2015. URL https://jmlr.org/papers/v16/vapnik15b.html.

[22] Mini Han Wang and Ying Yeung. Large language model-driven time-series forecasting of financial network indicators. *Frontiers in Artificial Intelligence*, 9:1722121, 2026. doi: 10.3389/frai.2026.1722121. URL https://www.frontiersin.org/journals/artificial-intelligence/articles/10.3389/frai.2026.1722121/full.

[23] Wenyan0110. Multimodal Dataset for Financial Time-Series Forecasting: S&P 500 Time Series, n.d. URL https://huggingface.co/datasets/Wenyan0110/Multimodal-Dataset-Image_Text_Table_TimeSeries-for-Financial-Time-Series-Forecasting/tree/72d4e97b9acb92651949b8efb22c55676ff633ff. Dataset snapshot 72d4e97, accessed 12 October 2026; historical OHLC adjustment vintage unverified.

[24] Halbert White. A Reality Check for Data Snooping. *Econometrica*, 68(5):1097–1126, 2000. doi: 10.1111/1468-0262.00152. URL https://bashtage.github.io/kevinsheppard.com/files/teaching/mfe/advanced-econometrics/White.pdf.

[25] Xinli Yu, Zheng Chen, Yuan Ling, Shujing Dong, Zongyi Liu, and Yanbin Lu. Temporal Data Meets LLM—Explainable Financial Time Series Forecasting. arXiv:2306.11025v1, 2023. URL https://arxiv.org/abs/2306.11025v1. Version 1, 19 June 2023; printed ACM metadata contains template placeholders.

[26] Yangyang Yu, Haohang Li, Zhi Chen, Yuechen Jiang, Yang Li, Denghui Zhang, Rong Liu, Jordan W. Suchow, and Khaldoun Khashanah. FinMem: A Performance-Enhanced LLM Trading Agent with Layered Memory and Character Design. arXiv:2311.13743v2, 2023. URL https://arxiv.org/abs/2311.13743v2.

[27] Yangyang Yu, Zhiyuan Yao, Haohang Li, Zhiyang Deng, Yupeng Cao, Zhi Chen, Jordan W. Suchow, Rong Liu, Zhenyu Cui, Zhaozhuo Xu, Denghui Zhang, Koduvayur Subbalakshmi, Guojun Xiong, Yueru He, Jimin Huang, Dong Li, and Qianqian Xie. FinCon: A Synthesized LLM Multi-Agent System with Conceptual Verbal Reinforcement for Enhanced Financial Decision Making. arXiv:2407.06567v3, 2024. URL https://arxiv.org/abs/2407.06567v3. Version read: 2407.06567v3.

[28] Mert Yuksekgonul, Federico Bianchi, Joseph Boen, Sheng Liu, Zhi Huang, Carlos Guestrin, and James Zou. TextGrad: Automatic "Differentiation" via Text. arXiv:2406.07496v1, 2024. URL https://arxiv.org/abs/2406.07496v1. Version read: 2406.07496v1.