

LLM Gateway API 串接文件

1. 服務概述

本服務提供 **OpenAI Compatible API**，可用於：

- Chatbot
- Agent
- 文件分析
- RAG
- 自動化 AI 任務

目前提供兩個模型：

模型	Route	GPU
Gemma2-9B	<code>/gemma2</code>	1 GPU
Gemma3-27B	<code>/gemma3</code>	2 GPU

2. Base URL

Gateway 入口：

```
http://<SERVER_IP>:8080
```

模型 API：

```
http://<SERVER_IP>:8080/gemma2/v1
http://<SERVER_IP>:8080/gemma3/v1
```

範例：

```
http://172.31.6.3:8080/gemma2/v1
http://172.31.6.3:8080/gemma3/v1
```

3. 模型能力

模型	Context Window	建議用途
Gemma2-9B	8K tokens	Chat / Agent
Gemma3-27B	32K tokens	長文本 / RAG

4. 查詢可用模型

Endpoint

GET /v1/models

Gemma2

curl http://172.31.6.3:8080/gemma2/v1/models

Gemma3

curl http://172.31.6.3:8080/gemma3/v1/models

Response

```
{
  "object": "list",
  "data": [
    {
      "id": "/model",
      "object": "model"
    }
  ]
}
```

```
]
}
```

⚠ 目前模型名稱為：

/model

5. Chat Completion API

Endpoint

POST /v1/chat/completions

6. Gemma2 呼叫範例

Curl

```
curl http://172.31.6.3:8080/gemma2/v1/chat/completions \
-H "Content-Type: application/json" \
-d '{
  "model": "/model",
  "messages": [
    {
      "role": "user",
      "content": "介紹一下台灣夜市文化"
    }
  ],
  "temperature": 0.7,
  "max_tokens": 512
}'
```

7. Gemma3 呼叫範例

```
curl http://172.31.6.3:8080/gemma3/v1/chat/completions \
-H "Content-Type: application/json" \
-d '{
  "model": "/model",
  "messages": [
    {
      "role": "user",
      "content": "請分析台灣夜市文化的歷史與經濟影響"
    }
  ],
  "temperature": 0.7,
  "max_tokens": 512
}'
```

8. Python 串接

安裝 SDK

```
pip install openai
```

Gemma2 Python Example

```
from openai import OpenAI

client = OpenAI(
    api_key="dummy",
    base_url="http://172.31.6.3:8080/gemma2/v1"
)

response = client.chat.completions.create(
    model="/model",
    messages=[
        {"role": "user", "content": "介紹台灣夜市文化"}
    ],
    temperature=0.7,
    max_tokens=512
)
```

```
)

print(response.choices[0].message.content)
```

Gemma3 Python Example

```
from openai import OpenAI

client = OpenAI(
    api_key="dummy",
    base_url="http://172.31.6.3:8080/gemma3/v1"
)

response = client.chat.completions.create(
    model="/model",
    messages=[
        {"role": "user", "content": "分析台灣夜市文化的經濟影響"}
    ]
)

print(response.choices[0].message.content)
```

9. Streaming 回傳

```
from openai import OpenAI

client = OpenAI(
    api_key="dummy",
    base_url="http://172.31.6.3:8080/gemma3/v1"
)

stream = client.chat.completions.create(
    model="/model",
    messages=[
        {"role": "user", "content": "寫一首關於台中的詩"}
    ],
    stream=True
)
```

```
for chunk in stream:
    if chunk.choices[0].delta.content:
        print(chunk.choices[0].delta.content, end="")
```

10. Response 格式

```
{
  "id": "chatcmpl-xxxxx",
  "object": "chat.completion",
  "choices": [
    {
      "index": 0,
      "message": {
        "role": "assistant",
        "content": "台灣夜市文化是台灣非常重要的..."
      },
      "finish_reason": "stop"
    }
  ]
}
```

11. 注意事項

1 Gemma 不支援 system role

以下寫法會錯誤：

```
{
  "role": "system"
}
```

正確：

```
{
  "role": "user"
}
```

```
}
```

2 API Key

目前 API Key **不驗證**，可填任意值：

```
dummy
```

12. 健康檢查

```
curl http://172.31.6.3:8080/gemma2/v1/models
```

若返回 JSON 即表示服務正常。