


# 消息框 Message

可任意添加文本元素，自定义图标，消息框内添加 `data-close-message` 属性的元素会触发关闭



```
<div class="message">
  <p>
    <i class="flaticon-information59 mr3"></i>We just need a little more info to create your account.
    <a href="#">link text</a>
  </p>
</div>
```

## 配色



```
<div class="message bg-gray c-white">
  <p>
    <i class="flaticon-information59 mr3"></i>We just need a little more info to create your account.
    <a href="#">link text</a>
  </p>
</div>
<div class="message bg-orange c-white">
  <p>
    <i class="flaticon-information59 mr3"></i>We just need a little more info to create your account.
    <a href="#">link text</a>
  </p>
</div>
<div class="message bg-blue c-white">
  <p>
    <i class="flaticon-information59 mr3"></i>We just need a little more info to create your account.
    <a href="#">link text</a>
  </p>
</div>
<div class="message bg-purple c-white">
  <p>
    <i class="flaticon-information59 mr3"></i>We just need a little more info to create your account.
    <a href="#">link text</a>
  </p>
</div>
```

## 弹出

为触发元素添加 `data-open-message` 属性，并用其来绑定消息框，消息框添加 `class="fade"` 会自动隐藏，消息框内添加 `data-close-dialog` 属性的元素会触发关闭



Click Button:

```
<button type="button" class="btn" data-open-message="element1">Pop up</button>
```

Message:

```
<div name="element1" class="message fade">
  <p>
    <i class="flaticon-information59 mr3"></i>We just need a little more info to create your account.
    <a href="#">link text</a>
    <button class="btn xs ml5" data-close-message>Close</button>
  </p>
</div>
```

相同 `name` 属性值的消息框将会绑定为同一个序列组

Array

Click Button:

```
<button type="button" class="btn" data-open-message="array1">Array</button>
```

Message:

```
<div name="array1" class="message fade bg-gray c-white">
  <p>
    <i class="flaticon-information59 mr3"></i>We just need a little more info to create your account.
    <a href="#">link text</a>
    <button class="btn xs ml5" data-close-message>Close</button>
  </p>
</div>
<div name="array1" class="message fade bg-orange c-white">
  ...
</div>
<div name="array1" class="message fade bg-blue c-white">
  ...
</div>
<div name="array1" class="message fade bg-purple c-white">
  ...
</div>
```

## 超时关闭

添加 `data-close-timeout` 属性设定消息框的超时关闭时间，单位是ms毫秒，可设定的最小值为 `500`

Timeout

Click Button:

```
<button type="button" class="btn" data-open-message="array2">Timeout</button>
```

Message:

```
<div name="array2" class="message fade bg-gray c-white" data-close-timeout="1000">
  <p>
    <i class="flaticon-information59 mr3"></i>We just need a little more info to create your account.
    <a href="#">link text</a>
    <button class="btn xs ml5" data-close-message>Close</button>
  </p>
</div>
<div name="array2" class="message fade bg-orange c-white" data-close-timeout="1500">
  ...
</div>
<div name="array2" class="message fade bg-blue c-white" data-close-timeout="2000">
  ...
</div>
<div name="array2" class="message fade bg-purple c-white" data-close-timeout="2500">
  ...
</div>
```

# 事件

使用 `HTMLElement.setActive()` 事件，传入参数以打开或关闭元素，参数类型为 `Boolean`

```
const message = document.querySelector('[name="element1"]');
message.setActive(true); //true || false
```