

Interferometric stabilisation of a fiber-based optical computer

Experimental study

Denis Verstraeten

ULB - Opera Photonics

April 5, 2019



ECOLE
POLYTECHNIQUE
DE BRUXELLES

Outline

- 1 Introduction
- 2 Reservoir Computing
- 3 Photonics reservoir computer with frequency-multiplexed neurons
- 4 Interferometric stabilisation of RC optical resonator
- 5 Outlooks

Context

- The need for always faster data processing devices is ever increasing
- This motivates the study of a new physical computation paradigm, the **optical computer**
- This kind of computer relies on light to process information
- Different ways to implement computing logic
- In this work, focus on **Reservoir Computing (RC)**

Outline

- 1 Introduction
- 2 Reservoir Computing
- 3 Photonics reservoir computer with frequency-multiplexed neurons
- 4 Interferometric stabilisation of RC optical resonator
- 5 Outlooks

Reservoir computing in a nutshell...

- Reservoir Computing (RC) is a *artificial neural network* scheme that allows real-time data processing
- Reservoir maps the input to a higher dimensional space
- The *neurons* are connected in a way that leads to a chaotic behaviour of the reservoir (achieved by using randomness, breaking symmetries,...)
- The input is fed into the reservoir and disturbs the intrinsic dynamics of the neurons
- Output is found by adequately combining the activation level of the neurons
- This scheme is so general that it can be implemented on physical systems
- It reaches state-of-the-art time series prediction algorithms

Mathematical model of a RC

Discrete time dynamics of a neuron [Jae01]:

$$x_i(t+1) = f_{NL} \left(W^{ij} x_j(t) + W_{in}^{ij} u_j(t) + W_{fb}^{ij} y_j(t) \right) \quad (1)$$

Discrete time output of the reservoir:

$$y_i(t) = W_{out}^{ij} x_j(t) \quad (2)$$




Figure: Principle diagram of a reservoir computer. It shows the connections between the neurons.[BFP12]

Key points on RC

- RC only requires the output weights W_{out}^{ij} to be trained
- In a first time, minimisation of the *Normalised Mean Square Error* (NMSE) during the learning phase[LJ09]:

$$\text{NMSE} = \frac{\langle ||\hat{\mathbf{y}}(t) - \mathbf{y}(t)||^2 \rangle_t}{\langle ||\hat{\mathbf{y}}(t) - \langle \hat{\mathbf{y}}(t) \rangle_t||^2 \rangle_t} \quad (3)$$

- Many numerical techniques can be used: batch learning, (stochastic) gradient descent, least mean squares, ridge regression, BackPropagation-DeCorrelation,...[Ste; Bis06; Rus10; LJS12]
- In a second time, reservoir performance are quantified on sample data

Example - NARMA 10




Figure: 50 neurons RC tested on the *Nonlinear AutoRegressive Moving Average 10* benchmark test. The NMSE is 0.1522.

Example - Nonlinear Channel Equalisation




Figure: Nonlinear Channel Equalisation task with 50 neurons. The Signal Error Rate is $3.33 \cdot 10^{-4}$ (with $\text{SNR} = 32$).

Existing optical RC

Outline

- 1 Introduction
- 2 Reservoir Computing
- 3 Photonics reservoir computer with frequency-multiplexed neurons**
- 4 Interferometric stabilisation of RC optical resonator
- 5 Outlooks




Figure: [Akr+16]

Outline

- 1 Introduction
- 2 Reservoir Computing
- 3 Photonics reservoir computer with frequency-multiplexed neurons
- 4 Interferometric stabilisation of RC optical resonator**
- 5 Outlooks

Outline

- 1 Introduction
- 2 Reservoir Computing
- 3 Photonics reservoir computer with frequency-multiplexed neurons
- 4 Interferometric stabilisation of RC optical resonator
- 5 Outlooks**

- [Akr+16] A. AkROUT et al. "Parallel photonic reservoir computing using frequency multiplexing of neurons". In: (2016).
- [BFP12] A. Bernal, S. Fok, and R. Pidaparthi. "Financial Market Time Series Prediction with Recurrent Neural Networks". In: (2012). URL: <http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.278.3606&rep=rep1&type=pdf>.
- [Bis06] Christopher Bishop. *Pattern recognition and machine learning*. New York: Springer, 2006. ISBN: 978-0387-31073-2.
- [Jae01] H. Jaeger. *The "echo state" approach to analysing and training recurrent neural networks*. 2001.

- [LJ09] M. Lukoševičius and H. Jaeger. “Reservoir computing approaches to recurrent neural network training”. In: *Computer Science Review* 3.3 (Aug. 2009), pp. 127–149. DOI: 10.1016/j.cosrev.2009.03.005. URL: <https://doi.org/10.1016/j.cosrev.2009.03.005>.
- [LJS12] M. Lukoševičius, M. Jaeger, and B. Schrauwen. “Reservoir Computing Trends”. In: *KI - Künstliche Intelligenz* 26.4 (May 2012), pp. 365–371. DOI: 10.1007/s13218-012-0204-5. URL: <https://doi.org/10.1007/s13218-012-0204-5>.
- [Rus10] Stuart Russell. *Artificial intelligence : a modern approach*. Upper Saddle River, New Jersey: Prentice Hall, 2010. ISBN: 978-0-13-604259-4.

[Ste] J.J. Steil. “Backpropagation-decorrelation: online recurrent learning with $O(N)$ complexity”. In: *2004 IEEE International Joint Conference on Neural Networks (IEEE Cat. No.04CH37541)*. IEEE. DOI: 10.1109/ijcnn.2004.1380039. URL: <https://doi.org/10.1109/ijcnn.2004.1380039>.