

# Interferometric stabilisation of a fiber-based optical computer

Experimental study

Denis Verstraeten

ULB - Opera Photonics

April 5, 2019



ECOLE  
POLYTECHNIQUE  
DE BRUXELLES

# Outline

- 1 Introduction
- 2 Reservoir Computing
- 3 Photonics reservoir computer with frequency-multiplexed neurons
- 4 Interferometric stabilisation of RC optical resonator
- 5 Outlooks

# Context

- The need for always faster data processing devices is ever increasing
- This motivates the study of a new physical computation paradigm, the **optical computer**
- This kind of computer relies on light to process information
- Different ways to implement computing logic
- In this work, focus on **Reservoir Computing (RC)**

# Outline

- 1 Introduction
- 2 Reservoir Computing
- 3 Photonics reservoir computer with frequency-multiplexed neurons
- 4 Interferometric stabilisation of RC optical resonator
- 5 Outlooks

# Reservoir Computing (RC) in a nutshell...

- Artificial Neural Network
- Real-time data processing scheme
- Can be implemented in physical systems
- State of the art performances in time series prediction

# Mathematical model of a RC

Discrete time dynamics of a neuron [Jae01]:

$$x_i(t+1) = f_{NL} \left( W^{ij} x_j(t) + W_{in}^{ij} u_j(t) + W_{fb}^{ij} y_j(t) \right) \quad (1)$$

Discrete time output of the reservoir:

$$y_i(t) = W_{out}^{ij} x_j(t) \quad (2)$$





Figure: [BFP12]


## Example - NARMA 10

- Nonlinear  
AutoRegressive  
Moving Average
- 50 neurons
- Washout : 300
- Learning : 3000
- Testing : 6000
- NMSE = 0.1439



## Example - Nonlinear Channel Equalisation

- 50 neurons
- SNR = 32 dB
- Washout : 300
- Learning : 3000
- Testing : 6000
- $SER = 3.33 \cdot 10^{-4}$





# Outline

- 1 Introduction
- 2 Reservoir Computing
- 3 Photonics reservoir computer with frequency-multiplexed neurons**
- 4 Interferometric stabilisation of RC optical resonator
- 5 Outlooks


# Motivations

- Blablabla
- Coupling of the different frequencies

## Frequency coupling - phase modulator I

Effect of a *phase modulator* :

$$Ee^{-i\omega t} \xrightarrow{\Omega} Ee^{-i\omega t} e^{im \sin \Omega t} = \sum_{k=-\infty}^{\infty} EJ_k(m) e^{-i(\omega+k\Omega)t} \quad (3)$$



- $m$  usually small ( $\leq 2$ )
- $J_k(m)$  decrease fast with  $k$
- Series can be truncated
- **Finite number of frequencies can be coupled**

## Frequency coupling - phase modulator II




Figure: Spectrum inside the cavity. 13 frequencies are usable.[Akr+16]




Figure: [Akr+16]

# Outline

- 1 Introduction
- 2 Reservoir Computing
- 3 Photonics reservoir computer with frequency-multiplexed neurons
- 4 Interferometric stabilisation of RC optical resonator**
- 5 Outlooks

# Outline

- 1 Introduction
- 2 Reservoir Computing
- 3 Photonics reservoir computer with frequency-multiplexed neurons
- 4 Interferometric stabilisation of RC optical resonator
- 5 Outlooks**

- [Akr+16] A. AkROUT et al. "Parallel photonic reservoir computing using frequency multiplexing of neurons". In: (2016).
- [BFP12] A. Bernal, S. Fok, and R. Pidaparthi. "Financial Market Time Series Prediction with Recurrent Neural Networks". In: (2012). URL: <http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.278.3606&rep=rep1&type=pdf>.
- [Jae01] H. Jaeger. *The "echo state" approach to analysing and training recurrent neural networks*. 2001.