

...or create a new repository on the command line

```
echo "# crud-spring-angular-loiane" >> README.md
git init
git add README.md
git commit -m "first commit"
git branch -M main
git remote add origin git@github.com:wdcunha/crud-spring-angular-loiane.git
git push -u origin main
```

...or push an existing repository from the command line

```
git remote add origin git@github.com:wdcunha/crud-spring-angular-loiane.git
git branch -M main
git push -u origin main
```

Quick setup — if you've done this kind of thing before

 Set up in Desktop or  HTTPS  SSH `git@github.com:wdcunha/crud-spring-angular-loiane.git`

Get started by [creating a new file](#) or [uploading an existing file](#). We recommend every repository include a [README](#), [LICENSE](#), and [.gitignore](#).

...or create a new repository on the command line

```
echo "# crud-spring-angular-loiane" >> README.md
git init
git add README.md
git commit -m "first commit"
git branch -M main
git remote add origin git@github.com:wdcunha/crud-spring-angular-loiane.git
git push -u origin main
```

...or push an existing repository from the command line

```
git remote add origin git@github.com:wdcunha/crud-spring-angular-loiane.git
git branch -M main
git push -u origin main
```

...or import code from another repository

You can initialize this repository with code from a Subversion, Mercurial, or TFS project.

 Import code

```
ssh-keygen -t ed25519 -C wdcunha@gmail.com
ls -al
ssh-add -K id_github
pbcopy < id_github.pub
```