CS544 Module 1 Assignment

© 2022, Suresh Kalathur, Boston University, All Rights Reserved.

The following document should not be disseminated outside the purview of its intended purpose.

The following sample data shows the scores of the students in an exam:

58, 46, 50, 90, 42, 52, 62, 44, 96, 92, 54, 82

Do the following using R code **with only a single expression** for each case. The solutions should be generic and work for any size data. You can assume there will be an even number of values in the given data.

Q1 (25 points)

- **a)** Assign the above data as a *vector* in the same order to the variable *scores*. Use this variable for the remaining problems.
- **b)** Using the *length* function, compute how many students took the exam? Store the expression in the variable *n*.
- **c)** Using indexing, write the expression for accessing the first two items. Store the expression in the variable *first_and_second*.
- **d)** Using indexing, write the expression for accessing the first and last items. Store the expression in the variable *first_and_last*.
- **e)** Using indexing, write the expression for accessing the middle two items. Store the expression in the variable *middle two.*

Sample output:

- [1] 12
- [1] 58 46
- [1] 58 82
- [1] 52 62

Q2 (25 points)

- a) Use *median(scores)* to compute the median of the data. Store the expression in the variable **median score**.
- **b)** Using comparison operators, write the R expression for scores less than or equal to the median of the data. Store the expression in the variable **below median**.
- **c)** Using comparison operators, write the R expression for scores greater than the median of the data. Store the expression in the variable **above median**.
- **d)** Using the **sum** function, write the R expression for the number of scores less than or equal to the median of the data. Store the expression in the variable **count below median.**
- **e)** Using the **sum** function, write the R expression for the number of scores greater than the median of the data. Store the expression in the variable **count_above_median**.

Sample output:

- [1] 56
- [1] FALSE TRUE TRUE FALSE TRUE TRUE FALSE TRUE FALSE TRUE FALSE
- [1] TRUE FALSE FALSE TRUE FALSE TRUE FALSE TRUE TRUE FALSE TRUE
- [1] 6
- [1] 6

Q3 (10 points)

- a) Using logical indexing and the results from Q2), write the R expression for all the scores that are less than or equal to the median value of the data. Store the expression in the variable scores_below_median.
- **b)** Similarly, write the R expression for all the scores that are greater than the median. Store the expression in the variable **scores above median**.

Sample output:

- [1] 46 50 42 52 44 54
- [1] 58 90 62 96 92 82

Q4 (10 points)

- **a)** Using numeric indexing, write the R expression for the odd indexed values from the scores. Store the expression in the variable **odd index values**.
- **b)** Similarly, write the R expression for the even indexed values from the scores. Store the expression in the variable **even index values**.

Use the **seq** function to generate the numeric indices for the above.

Sample output:

- [1] 58 50 42 62 96 54
- [1] 46 90 52 44 92 82

Q5 (10 points)

a) Using the **paste** function with LETTERS, write the expression for the following output. Store the expression in the variable **format scores version1**.

You can assume there are no more than 26 values.

Sample output:

```
[1] "A=58" "B=46" "C=50" "D=90" "E=42" "F=52" "G=62" "H=44" "I=96" "J=92" "K=54" "L=82"
```

b) Similarly, using the **paste** function with LETTERS, write the expression for the following output. Store the expression in the variable **format_scores_version2**.

Sample output:

```
[1] "L=58" "K=46" "J=50" "I=90" "H=42" "G=52" "F=62" "E=44" "D=96" "C=92" "B=54" "A=82"
```

Q6 (10 points)

a) Create a matrix with two rows using the **scores** data. The first half of the values belong to the first row of the matrix. Store the expression in the variable **scores_matrix**.

The code should work for any size input data.

You can assume that there are even number of values in scores.

Sample output:

```
[1,] [,2] [,3] [,4] [,5] [,6]
[1,] 58 46 50 90 42 52
[2,] 62 44 96 92 54 82
```

b) Write the expression for displaying the first and last columns of the above matrix. The code should work for any size matrix. Store the expression in the variable **first_and_last_version1**. **Sample output:**

[,1] [,2] [1,] 58 52 [2,] 62 82

Q7 (10 points)

a) Copy scores_matrix to the variable named_matrix.

Assign column names for the *named_matrix* as Student_1, Student_2,... and row names as Quiz_1, Quiz_2, ... The code should work for any size matrix, i.e., for any number of columns in the matrix and any number of rows. The code can contain multiple steps.

Sample output:

_	Student_1	Student_2	Student_3	Student_4	Student_5	Student_6
Quiz_1	58	46	50	90	42	52
Quiz_2	62	44	96	92	54	82

b) Show the result for displaying the first and last columns of the *named_matrix*. The code should work for any size matrix. Store the expression in the variable **first_and_last_version2**. **Sample output:**

	Student_1	Student_6
Quiz_1	58	52
Quiz_2	62	82

Submission:

- You must work on your assignments individually. You are not allowed to copy the answers from the others.
- Each assignment has a strict deadline. Please plan accordingly to submit on time.
- When the term *lastName* is referenced, please replace it with your last name.
- Create a folder, CS544 HW1 lastName and place the following files in this folder.
- Provide all R code in a single file, CS544_HW1_lastName.R. Clearly mark each subpart of each question.
- Provide the corresponding code and outputs from the R console in a single Word document, CS544 HW1 lastName.doc.
- Archive the folder (CS544_HW1_lastName.zip). Upload the zip file to the Assignments section of Blackboard.

Note: Only ONE submission is allowed. Please be sure that what you are submitting is your final submission.