

Data Structures and Algorithms

P and NP

Decision Problem

- Decision problem: A decision problem **P** is a set of questions each of which has a yes or no answer.
- Example: A decision problem **P_{sq}**: Determine whether an arbitrary number is a perfect square or not. This problem consists of the following questions:

p₀: Is 0 a perfect square?

p₁: Is 1 a perfect square?

...

Here, **p_i** is also called an instance of **P**.

Decision Problem

- A solution to a decision problem is an algorithm that determines the answer to every question $\mathbf{p}_i \in \mathbf{P}$.
- An algorithm that solves a decision problem should be
 - *complete* – it produces an answer, either positive or negative, to each question in the problem domain
 - *mechanistic* – it consists of a finite sequence of instructions each of which can be carried out without requiring insight, ingenuity, or guesswork
 - *deterministic* – when presented with identical input, it always produces the same result.

Decision Problem

- Decision problems:
 - *Unsolvable* (or *undecidable*)
 - *Solvable*:
 - *Tractable*: A decision problem is said to be tractable if there is at least one polynomially bounded algorithm that solves the problem. Such an algorithm is called an *efficient* algorithm.
 - *Intractable*: A decision problem is said to be intractable if there is no polynomially bounded algorithm (or no efficient algorithm) that solves the problem

Decision Problem

- An example of unsolvable problem: ***Post correspondence problem***
- Instead of formally stating the problem, we will illustrate the problem as a simple game of manipulating dominoes.
- A domino consists of two strings from a fixed alphabet, one on the top half of the domino and the other on the bottom.

<i>aba</i>
<i>bbaba</i>

Decision Problem

- We are given a finite set of different types of dominoes.
- We assume that there are an unlimited number of each type of dominoes.
- The game begins when a domino is placed on a table. Another domino is placed to the immediate right of the domino. This process is repeated making a sequence of dominoes on the table.

Decision Problem

- The *top string* is obtained by concatenating the strings in the top halves of the sequence of dominoes.
- The *bottom string* is obtained by concatenating the strings in the bottom halves of the sequence of dominoes.
- The goal of the game (or the solution to a Post correspondence problem) is to come up with a sequence of dominoes where the top string is identical to the bottom string.

Decision Problem

- Example 1. Given the following two dominoes:

<i>aaa</i>	<i>baa</i>
<i>aa</i>	<i>abaaa</i>

The following sequence of dominoes is a solution:

<i>aaa</i>	<i>baa</i>	<i>aaa</i>
<i>aa</i>	<i>abaaa</i>	<i>aa</i>

Decision Problem

- Example 2. Given the following three dominoes:


<i>ab</i>	<i>bba</i>	<i>aba</i>
<i>aba</i>	<i>aa</i>	<i>bab</i>

There is no solution.

- Theorem: There is no algorithm that determines whether an arbitrary finite set of dominoes has a solution.
- Since solvable problems are equivalent to recursive languages, *decision problems* and *languages* are used interchangeably.

Reducibility

- A decision problem \mathbf{P} is Turing reducible to a problem \mathbf{P}' if there is a Turing machine that takes any problem $\mathbf{p}_i \in \mathbf{P}$ as input and produces an associated problem $\mathbf{p}'_i \in \mathbf{P}'$ where the answer to the original problem \mathbf{p}_i can be obtained from the answer to \mathbf{p}'_i .



P and NP

- A language L is decidable in polynomial time if there is a standard (or deterministic) Turing machine M that accepts L in polynomial time, or $O(n^r)$, where r is a natural number independent of n .
- The family of languages decidable in polynomial time is denoted **P** .

P and NP

- Nondeterministic computation:
 - A deterministic machine solves a decision problem by generating a solution.
 - A nondeterministic machine needs only determine if one of possibilities is a solution.
- A language L is said to be accepted in nondeterministic polynomial time if there is a nondeterministic Turing machine that accepts L in polynomial time, or $O(n^r)$, where r is a natural number independent of n .

P and NP

- The family of languages accepted in nondeterministic polynomial time is denoted **NP**.
- Another definition: A problem is in **NP** if it is “verifiable” in polynomial time.
- What “verifiable” means is that given a possible solution (which is also called **certificate**) we can verify whether it is a solution or not in polynomial time.

P and NP

- **$P = NP$?**
- Unsolved question.
- Since every deterministic machine is also nondeterministic, **$P \subseteq NP$.**
- But it was never proved that **$NP \subseteq P$.** (If this is proved, then that proves **$P = NP$.**)

P and NP

- If Q is reducible to L in polynomial time and $L \in \mathbf{P}$, then $Q \in \mathbf{P}$.
- A language L is called ***NP-hard*** if for every $Q \in \mathbf{NP}$ Q is reducible to L in polynomial time.
- An ***NP-hard*** language that is also in \mathbf{NP} is called ***NP-complete***.
- If there is an NP-complete language that is also in \mathbf{P} , then $\mathbf{P} = \mathbf{NP}$.

P and NP

- Two examples of NP-complete problems: Hamiltonian cycle problem and traveling salesman problem.

Hamiltonian Cycle Problem

- A Hamiltonian cycle of an undirected graph $G = (V, E)$ is a simple cycle that contains each vertex in V .
- Note: A cycle is simple if a node, except the first node, is visited only once.
- A graph that contains a Hamiltonian cycle is called “Hamiltonian.”
- ***Hamiltonian Cycle Problem:*** Does a graph G have a Hamiltonian cycle?

Hamiltonian Cycle Problem


- It can be shown that the Hamiltonian cycle problem can be decidable by a Turing machine in *exponential* time, but not in *polynomial* time. This means Hamiltonian cycle problem is not in **P**.
- But, it is decidable in nondeterministic polynomial time.
- Given a cycle in a graph, we can determine whether it is Hamiltonian cycle or not in polynomial time.
- So, Hamiltonian cycle problem is in **NP**.
- In fact it is an **NP-complete** problem.

Traveling Salesman Problem

- Given a complete, non-negative weighted graph, find a Hamiltonian cycle of minimum weight.
- This problem is ***NP-complete***.
- Will briefly discuss three approximate algorithms.

Traveling Salesman Problem

- Consider the following graph:



minimum weight cycle = $1 \rightarrow 2 \rightarrow 4 \rightarrow 3 \rightarrow 1$.

total weight = $30 + 35 + 22 + 25 = 112$

Traveling Salesman Problem

- Nearest-neighbor strategy

NEAREST-TSP (G, f) /* f is a cost function, or a weight function */

select an arbitrary vertex s ;

$v = s$; $Q = \{v\}$; $S = G.V - Q$; $C = \phi$;

while $S \neq \phi$

select an edge (v, w) of minimum weight, where $w \in S$;

$C = C \cup \{(v, w)\}$;

$Q = Q \cup \{w\}$;

$S = S - \{w\}$;

$v = w$;


$C = C \cup \{(v, s)\}$;

return C ;

Running time: $O(V^2)$

Traveling Salesman Problem

- Nearest-neighbor strategy



Starting at vertex 1: (1, 3), (3, 2), (2, 4), (4, 1)

Total weight = $25 + 20 + 35 + 45 = 125$

Traveling Salesman Problem

- Shortest-link strategy

SHORTEST-LINK-TSP (G, f)

$R = G.E;$

$C = \phi;$

while $R \neq \phi$

 choose the shortest edge (v, w) from R ;

$R = R - \{(v, w)\};$

if (v, w) does not make a cycle with edges in C and (v, w) would
 not be the third edge in C incident on v or w

then

$C = C + \{(v, w)\};$


add the edge connecting the end points of the path in C ;

return C ;

Running time: $O(E \log V)$

Traveling Salesman Problem

- Shortest-link strategy



Edges added: (2, 3), (3, 4), (2, 1), (1, 4)

Total weight = $20 + 22 + 30 + 45 = 117$

Traveling Salesman Problem

- In general, we cannot establish a bound on how much the weight of an approximate algorithm differ from the weight of a minimum tour.
- If we assume the triangle inequality holds on distances among vertices, we can develop an approximate algorithm that has an upper bound on the weight.
- Triangle inequality:
$$f(u, v) \leq f(u, w) + f(w, v), \text{ for all } u, v, w \in G.V.$$
- Euclidean distance has the triangle inequality property.

Traveling Salesman Problem


- The following approximate algorithm has an upper bound on the weight: total weight of a cycle is no more than the twice that of the minimum spanning tree's weight

APPROX-TSP-TOUR (G, f)

```
select a vertex  $r \in G.V$  to be the root;  
compute MST  $T$  from  $r$  using MST-PRIM( $G, f, r$ );  
let  $H$  be a list of vertices, ordered according to when they are  
    first visited in a preorder tree walk of  $T$ ;  
return  $H$ 
```


Traveling Salesman Problem

- Example: Given the following complete graph (There are edges from each node to all other nodes though edges are not shown in the graph below).




Traveling Salesman Problem

- A minimum spanning tree T (a is the root)



Traveling Salesman Problem


- A minimum spanning tree T (a is the root)



$a \rightarrow b \rightarrow c \rightarrow h \rightarrow d \rightarrow e \rightarrow f \rightarrow g \rightarrow a$

Traveling Salesman Problem


- H returned by APPROX-TSP-TOUR is



total weight = approx. 19.074

Traveling Salesman Problem

- An optimal tour (or Hamiltonian cycle with minimum weight)



total weight = approx. 14.715

Reference

- T.A. Sudkamp, “Languages and Machines,” 1988, Addison Wesley.
- T.H. Cormen, C.E. Leiserson, R.L. Rivest, C. Stein, “Introduction to Algorithms,” 3rd Ed., 2009, MIT Press.