

Documentation for the incompressible Navier-Stokes Matlab codes

William D. Henshaw^{a,1,}

^a*Department of Mathematical Sciences, Rensselaer Polytechnic Institute, Troy, NY 12180, USA*

Abstract

Here is documentation and notes for the incompressible Navier-Stokes Matlab codes.

Contents

1	Matlab files	2
2	Introduction, governing equations, boundary conditions	2
2.1	Boundary conditions	2
3	Discrete approximations	4
4	Grid convergence tests	4
5	Numerical Results	4
5.1	Taylor Green vortex	5
5.2	Shear flow in a periodic channel	6

Email address: `henshw@rpi.edu` (William D. Henshaw)

1. Matlab files

ins.m	Main routine .
runChecks.m	Run regression tests.
runGridConvergence.m	Run a grid convergence test.
advanceAdams.m	Adams time-stepping.
advanceIM.m	IMEX time-stepping.
advancePC.m	Predictor-Corrector time-stepping.
applyBoundaryConditions.m	apply (explicit) boundary conditions
pressureEquation.m	form pressure equation and solve
evalMap.m	eval the grid mapping and derivatives
formImplicitTimeSteppingMatrix.m	form systems for implicit time-stepping
solveImplicitTimeStep.m	solve the implicit time-step equations
getInitialConditions.m	assign initial conditions
getUt.m	evaluate momentum equations
getTimeStep.m	determine the time-step Δt
plotSolution.m	plot solution contours and streamlines
plotStreamLines.m	stream line plotter

Table 1: Selected ins Matlab files.

2. Introduction, governing equations, boundary conditions

The `ins.m` Matlab code solves the incompressible Navier-Stokes equations in velocity-pressure form,

$$\partial_t \mathbf{u} + (\mathbf{u} \cdot \nabla) \mathbf{u} + \frac{1}{\rho} \nabla p = \nu \Delta \mathbf{u}, \quad \mathbf{x} \in \Omega, \quad t > 0, \quad (1a)$$

$$\frac{1}{\rho} \Delta p = -\nabla \mathbf{u} : \nabla \mathbf{u}, \quad \mathbf{x} \in \Omega, \quad t > 0, \quad (1b)$$

$$\mathbf{u}(\mathbf{x}, 0) = \mathbf{u}_0(\mathbf{x}) \quad \mathbf{x} \in \Omega, \quad (1c)$$

$$\nabla \cdot \mathbf{u}(\mathbf{x}, 0) = 0 \quad \mathbf{x} \in \partial\Omega, \quad (1d)$$

with appropriate boundary conditions as discussed below.

2.1. Boundary conditions

Let $\mathbf{n}(\mathbf{x})$ denote the outward unit normal vector to a point $\mathbf{x}$ on a boundary. Let $\mathbf{t}$ denote the corresponding unit tangent vector. Here are the physical boundary conditions. Numerically, additional compatibility conditions will be used.

No-slip wall or inflow.

$$\mathbf{u}(\mathbf{x}, t) = \mathbf{g}(\mathbf{x}, t), \quad \mathbf{x} \in \partial\Omega, \quad t > 0, \quad (2a)$$

$$\nabla \cdot \mathbf{u}(\mathbf{x}, t) = 0, \quad \mathbf{x} \in \partial\Omega, \quad t > 0. \quad (2b)$$

Slip wall.

$$\mathbf{n} \cdot \mathbf{u}(\mathbf{x}, t) = 0 \quad \mathbf{x} \in \partial\Omega, \quad t > 0, \quad (3a)$$

$$\partial_n (\mathbf{t} \cdot \mathbf{u}) = 0, \quad \mathbf{x} \in \partial\Omega, \quad t > 0, \quad (3b)$$

$$\nabla \cdot \mathbf{u}(\mathbf{x}, t) = 0 \quad \mathbf{x} \in \partial\Omega, \quad t > 0. \quad (3c)$$

Outflow.

$$a_0 p(\mathbf{x}, t) + a_1 \partial_n p(\mathbf{x}, t) = g(\mathbf{x}, t), \quad \mathbf{x} \in \partial\Omega, \quad t > 0, \quad (4a)$$

$$\partial_n^2 (\mathbf{t} \cdot \mathbf{u}) \quad \mathbf{x} \in \partial\Omega, \quad t > 0, \quad (4b)$$

$$\nabla \cdot \mathbf{u}(\mathbf{x}, t) = 0 \quad \mathbf{x} \in \partial\Omega, \quad t > 0. \quad (4c)$$

Pressure inflow.

$$p(\mathbf{x}, t) = g_1(\mathbf{x}, t), \quad \mathbf{x} \in \partial\Omega, \quad t > 0, \quad (5a)$$

$$\mathbf{t} \cdot \mathbf{u} = g_2 \quad \mathbf{x} \in \partial\Omega, \quad t > 0, \quad (5b)$$

$$\nabla \cdot \mathbf{u}(\mathbf{x}, t) = 0 \quad \mathbf{x} \in \partial\Omega, \quad t > 0. \quad (5c)$$

3. Discrete approximations

The discrete approach is based on the methods described in [1–3].

The method-of-lines approximation keeps time continuous and discretizes in space. Let $\mathbf{V}_j(t) \approx \mathbf{u}(\mathbf{x}_j, t)$, and $P_j(t) = p(\mathbf{x}_j, t)$. The discretization of the interior equations takes the form

$$\frac{d}{dt} \mathbf{V}_j + (\mathbf{V}_j \cdot \nabla_h) \mathbf{V}_j + \frac{1}{\rho} \nabla_h P_j = \nu \Delta_h \mathbf{V}_j - \mathcal{D}_h^{(2)} \mathbf{V}_j, \quad \mathbf{j} \in \Omega_h, \quad (6a)$$

$$\Delta_h P_j = \nabla_h \mathbf{V}_j : \nabla_h \mathbf{V}_j + \frac{c_d}{\Delta t} \nabla_h \cdot \mathbf{V}_j, \quad \mathbf{j} \in \Omega_h, \quad (6b)$$

where ∇_h and Δ_h denote discrete approximations to ∇ and Δ , respectively. The second-order artificial dissipation operator $\mathcal{D}_h^{(2)}$ is

$$\mathcal{D}_h^{(2)} \mathbf{V}_j \stackrel{\text{def}}{=} (a_1 + a_2 \|\nabla_h \mathbf{V}_j\|_1) \left((-\Delta x^2 D_{+x} D_{-x}) + (-\Delta y^2 D_{+y} D_{-y}) \right), \quad (6c)$$

$$\|\nabla_h \mathbf{V}_j\|_1 = |D_{0x} V_{1,j}| + |D_{0x} V_{2,j}| + |D_{0y} V_{1,j}| + |D_{0y} V_{2,j}|, \quad (6d)$$

while c_d is the coefficient of the divergence damping.

4. Grid convergence tests

The Matlab code `runGridConvergence.m` can be used to run grid convergence tests. Here is an example

```
>> runGridConvergence -ts=pc2 -tf=.25 -ms=trig -numResolutions=4
N      p-err  ratio  u-err  ratio  v-err ratio  div  ratio  cpu(s)  ratio
-----
10  4.46e-02      6.31e-03      4.17e-03      4.00e-02      1.00e-02
20  1.16e-02  3.8  4.71e-04 13.4  3.54e-04 11.8  3.28e-03 12.2  8.00e-02  8.0
40  2.92e-03  4.0  1.17e-04  4.0  6.59e-05  5.4  2.31e-04 14.2  1.35e+00 16.9
80  7.41e-04  3.9  2.92e-05  4.0  1.57e-05  4.2  1.79e-05 12.9  1.01e+01  7.5
```

5. Numerical Results

5.1. Taylor Green vortex

The Taylor Green vortex is an exact solution given by

$$u = +\alpha \sin(kx) \cos(ky) F(t) \quad (7a)$$

$$v = -\alpha \cos(kx) \sin(ky) F(t) \quad (7b)$$

$$p = \frac{\rho\alpha^2}{4} (\cos(2kx) + \cos(2ky)) F^2(t) \quad (7c)$$

$$F(t) \stackrel{\text{def}}{=} \exp(-2\nu k^2 t) \quad (7d)$$

where α is a parameter defining the initial amplitude.

Figure 1 shows some results using the command

```
ins -ts=im2 -tf=.5 -ms=none -knownSolution=TaylorGreen -idebug=1 -nu=0.1 -bcs=nnnn -N0=100 -plotOption=1
```




Figure 1: Taylor Green vortex

5.2. Shear flow in a periodic channel

Figure 2 shows the roll-up of a shear flow in periodic channel. The initial condition is perturbed shear flow

$$u(x, y, 0) = \tanh(\beta(y - y_m)), \quad (8)$$

$$v(x, y, 0) = \delta \cos(2\pi(y - y_m)) \sin(2\pi k_x x) \quad (9)$$

```
ins -ts=pc2 -tf=2.0 -tp=0.5 -ms=none -knownSolution=none -idebug=1 -nu=.0002 -ya=-.5 -yb=1.5 -xb=2
-bcs=ppnn -N0=800 -ic=shear -movieMode=1 -plotOption=3 -plotErrors=0 -kx=1 -checkTimeStep=20
-ad=1 -ad21=.1 -ad22=.1 -cfl=0.95
```

Artificial dissipation is added.




Figure 2: Rollup of a shear flow in a channel.

Here are the timings on a Mac-book pro showing that most of the time is spent in solving for the pressure.

```
----- TIMINGS pc2 Nx=800 Ny=800 Nt= 1005 -----
              cpu (s)    %
Total          5.89e+02  100.0
  setup         7.09e+01   12.0
  getUt         1.16e+02   19.7
implicit solve  0.00e+00    0.0
implicit factor 0.00e+00    0.0
pressure solve  3.75e+02   63.7
    bc          3.50e-01    0.1
plotting       2.03e+01    3.4
```

References

- [1] G. S. Chesshire, W. D. Henshaw, Composite overlapping meshes for the solution of partial differential equations 90 (1) (1990) 1–64, [publications/cgns1990.pdf](#).
- [2] W. D. Henshaw, N. A. Petersson, A split-step scheme for the incompressible Navier-Stokes equations, in: M. M. Hafez (Ed.), Numerical Simulation of Incompressible Flows, World Scientific, 2003, pp. 108–125, [publications/henshawPetersson2001.pdf](#).
- [3] F. Meng, J. W. Banks, W. D. Henshaw, D. W. Schwendeman, Fourth-order accurate fractional-step IMEX schemes for the incompressible Navier-Stokes equations on moving overlapping grids, Computer Methods in Applied Mechanics and Engineering 366 (2020) 113040, [publications/FourthOrderAccurateFractionalStepIMEXSchemeForINSOnMovingGrids_MengBanksHenshawSchwendeman2020.pdf](#).