Claude Code

Complete Reference

Skills · commands · keys · CLI · March 2026 · v1.5

● Create ● Validate ● Ship ● Non-code

SUPERPOWERS — WORKFLOW

- `/using-superpowers` Discover available skills
- `/brainstorming` Creative exploration before code
- `/writing-plans` Implementation plans from specs
- `/writing-skills` Create or edit CC skills
- `/receiving-code-review` Handle review feedback
- `/requesting-code-review` Request review of work
- `/systematic-debugging` Structured bug investigation
- `/test-driven-development` Tests before implementation
- `/verification-before-completion` Verify before claiming done
- `/dispatching-parallel-agents` Run 2+ tasks concurrently
- `/executing-plans` Execute plan task-by-task
- `/finishing-a-development-branch` Merge, PR, keep, or discard
- `/subagent-driven-development` Parallel subagent execution
- `/using-git-worktrees` Isolated worktree setup

GIT & PR

- `/code-review` Code review a PR
- `/review-pr` Multi-agent PR review
- `/clean_gone` Clean deleted remote branches
- `/commit` Git commit (conventional msg)
- `/commit-push-pr` Commit + push + open PR

CODE QUALITY

- `/feature-dev` Guided feature dev + architecture
- `/claude-md-improver` Audit CLAUDE.md quality
- `/revise-claude-md` Update CLAUDE.md from session
- `/simplify` Review code for reuse & clarity

CREATIVE & DESIGN

- `/frontend-design` Production-grade frontend UI
- `/playground` Interactive HTML explorers
- `/skill-creator` Create & benchmark skills

PROJECT-SPECIFIC

- `/cursor` Open Cursor IDE for cwd

SETUP & CONFIG

- `/claude-automation-recommender` Recommend automations
- `/keybindings-help` Customize shortcuts
- `/update-config` Edit settings.json / hooks
- `/claude-api` Build with Claude API / SDK
- `/new-sdk-app` Create Agent SDK app

AUTOMATION

- `/loop` Recurring prompt interval
- `/schedule` Cron-scheduled remote agents

SESSION & CONTEXT

- `/add-dir` Add working directory
- `/branch` Fork conversation (/fork)
- `/btw` Side question mid-response
- `/clear` Clear & start fresh
- `/compact` Summarize to free context
- `/memory` View/edit persistent memory
- `/plan` Enter plan mode
- `/rename` Name current session
- `/resume` Resume previous conversation
- `/rewind` Undo code changes

DEPRECATED

/execute-plan → /executing-plans · /write-plan → /writing-plans · /brainstorm → /brainstorming · /output-style → /config

MODEL & OUTPUT

- `/color` Prompt bar color
- `/config` Settings (/settings)
- `/copy` Copy response / code blocks
- `/effort` Thinking effort (○ ◐ ●)
- `/export` Export conversation
- `/fast` Toggle fast mode
- `/model` Switch model
- `/theme` Color theme
- `/voice` Voice input (push-to-talk)

INFO & DIAGNOSTICS

- `/cheatsheet` Generate reference PDF
- `/context` Context window breakdown
- `/cost` Session cost & tokens
- `/debug` Debug current session
- `/doctor` Config & env diagnostics
- `/feedback` Submit feedback
- `/help` Show help
- `/release-notes` View release notes
- `/stats` Personal usage stats
- `/status` System & account status
- `/usage` Plan usage limits

EXTENSIONS & INTEGRATIONS

- `/agents` List agents
- `/extra-usage` Purchase extra usage
- `/ide` IDE extension
- `/mcp` MCP servers
- `/permissions` Tool permission rules
- `/plugins` Plugin management
- `/remote-control` Bridge to claude.ai/code
- `/sandbox` Bash sandboxing
- `/skills` List skills
- `/terminal-setup` Terminal integration
- `/todos` Current todo items
- `/upgrade` Switch to Max plan

KEYBOARD SHORTCUTS

- `!` Bash mode (shell commands)
- `/` Slash commands & skills
- `@` File paths, agents, MCP resources
- `&` Send to background agent
- `Shift+↵` Insert newline in prompt
- `Tab` Autocomplete file / command
- `↑ / ↓` Cycle prompt history
- `Esc` Interrupt (2× to clear input)
- `Ctrl+U` Clear input line
- `Ctrl+K` Cut to end of line
- `Ctrl+Y` Yank (paste cut text)
- `Alt+Y` Yank-pop (cycle kill ring)
- `Shift+Tab` Toggle auto-accept edits
- `Ctrl+O` Transcript / verbose output
- `Ctrl+R` History search (bash-style)
- `Ctrl+S` Stash prompt (save for later)
- `Ctrl+G` Edit prompt in $EDITOR
- `Ctrl+X Ctrl+E` Edit in $EDITOR (alt)
- `Ctrl+L` Clear screen & redraw
- `Ctrl+Z` Suspend (fg to resume)
- `Ctrl+_` Undo prompt input
- `Alt+P` Switch model (while typing)
- `Alt+O` Toggle fast mode
- `Alt+T` Toggle thinking mode
- `Ctrl+V` Paste images from clipboard
- `Ctrl+B` Background running task
- `Ctrl+X Ctrl+K` Kill all background agents
- `Shift+↓` Expand teammate pane
- `Space` Push-to-talk (voice mode)

CLI — CLAUDE [OPTIONS] [PROMPT]

- `-p, --print` Non-interactive output (pipes)
- `-c, --continue` Continue last conversation
- `-r, --resume [id]` Resume by session ID
- `-w, --worktree [name]` Isolated git worktree
- `-n, --name <name>` Session display name
- `--session-id <uuid>` Fixed session UUID
- `--from-pr [pr]` Resume PR-linked session
- `--fork-session` New ID when resuming
- `--model <model>` opus / sonnet / haiku
- `--effort <level>` low / med / high / max
- `--agent <agent>` Use specific agent
- `--agents <json>` Custom agent definitions
- `--fallback-model <m>` Overload fallback (--print)
- `--brief` Agent-to-user messaging
- `--[no-]chrome` Chrome integration on/off
- `--add-dir <dirs>` Additional directories
- `--file <specs>` Fetch file resources
- `--system-prompt <text>` Override system prompt
- `--append-system-prompt` Append to system prompt
- `--settings <file|json>` Load settings
- `--setting-sources <s>` user / project / local
- `--mcp-config <files>` MCP server configs
- `--strict-mcp-config` Only --mcp-config MCPs
- `--plugin-dir <path>` Plugins from directory
- `--tools <tools>` Restrict available tools
- `--allowed-tools <t>` Whitelist specific tools
- `--disallowed-tools <t>` Deny specific tools
- `--disable-slash-commands` Disable all skills
- `--permission-mode <m>` default / plan / auto / …
- `--dangerously-skip-permissions` Bypass checks
- `--allow-dangerously-skip-permissions` Enable bypass option
- `--bare` Minimal mode (no hooks/LSP)
- `--output-format <fmt>` text / json / stream-json
- `--input-format <fmt>` text / stream-json
- `--json-schema <schema>` Structured output
- `--include-partial-messages` Partial stream chunks
- `--replay-user-messages` Echo user input on stdout
- `--verbose` Verbose mode override
- `--max-budget-usd <$>` Spending cap
- `--no-session-persistence` Ephemeral session (--print)
- `--tmux` tmux session (with -w)
- `-d, --debug [filter]` Debug mode
- `--debug-file <path>` Debug log to file
- `--betas <betas>` Beta API headers
- `-v, --version` Show version

- `claude auth` login / status / logout
- `claude agents` List configured agents
- `claude auto-mode` Auto mode classifier
- `claude doctor` Health check
- `claude mcp` add / remove / list servers
- `claude plugin` install / enable / disable
- `claude install` Install native build
- `claude setup-token` Long-lived auth token
- `claude update` Check & install updates