



Central Valley Regional Water Quality Control Board

20 February 2020

WDID: 5A520105001

Mike Murphy
Gerber-Las Flores CSD
331 San Benito Avenue
Gerber, CA 96035

CERTIFIED MAIL:
7018 1130 0001 8556 4668

AMENDED MONITORING AND REPORTING PROGRAM, GERBER-LAS FLORES WASTEWATER TREATMENT FACILITY, WASTE DISCHARGE REQUIREMENTS ORDER 93-033, TEHAMA COUNTY

The Gerber-Las Flores Wastewater Treatment Facility (Facility) is owned and operated by Gerber-Las Flores Community Services District (Discharger). The Central Valley Regional Water Quality Control Board (Central Valley Water Board) regulates wastewater discharges from the Facility under Waste Discharge Requirements (WDRs) Order 93-033, adopted on 26 February 1993.

The Central Valley Water Board issued a permit continuance of Order 93-033 on 15 May 2019 and has been scheduled to be reviewed for renewal or update on 15 May 2029. Additionally, Central Valley Water Board Staff notified the Discharger that Monitoring and Reporting Program Order 93-033 would be amended to maintain consistency with current monitoring requirements.

Please see the enclosed Amended Monitoring and Reporting Program Order 93-033.

If you have any questions, please contact me by mail, at the footer address at the bottom of this notice, by phone at (530) 224-6130, or by email at Valerie.Rasmussen@waterboards.ca.gov.

Valerie Rasmussen
Water Resource Control Engineer
WDR Unit

VMR: ch

Enclosure: Amended Monitoring and Reporting Program Order 93-033

KARL E. LONGLEY ScD, P.E., CHAIR | PATRICK PULUPA, ESQ., EXECUTIVE OFFICER

364 Knollcrest Drive, Suite 205, Redding, CA 96002 | www.waterboards.ca.gov/centralvalley

**CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD
CENTRAL VALLEY REGION**

**AMENDED MONITORING AND REPORTING PROGRAM ORDER 93-033
FOR
GERBER-LAS FLORES CSD
GERBER-LAS FLORES WASTEWATER TREATMENT FACILITY
TEHAMA COUNTY**

Separately issued pursuant to Water Code section 13267, subdivision (b)(1), this Order establishes a Monitoring and Reporting Program (MRP) for waste discharges regulated under Waste Discharge Requirements Order 93-033 (WDRs Order). Each of the Findings set forth in the WDRs Order, including those pertaining to the need for submission of reports, are hereby incorporated as part of this MRP Order.

This MRP is issued pursuant to Water Code section 13267. The Discharger shall not implement any changes to this MRP unless and until the Central Valley Water Board adopts, or the Executive Officer issues, a revised MRP.

This MRP Order may be separately revised by the Executive Officer, in accordance with their delegated authority under Water Code section 13223.

A. General Monitoring Requirements

Flow Monitoring

Hydraulic flow rates shall be measured at the monitoring points specified in this MRP. Central Valley Water Board staff shall approve any proposed changes to flow monitoring locations prior to implementation of the change. All flow monitoring systems shall be appropriate for the conveyance system (i.e., open channel flow or pressure pipeline) and liquid type. Unless otherwise specified, each flow meter shall be equipped with a flow totalizer to allow reporting of cumulative volume as well as instantaneous flow rate. Flow meters shall be calibrated at the frequency recommended by the manufacturer; typically, at least once per year and records of calibration shall be maintained for review upon request.

Monitoring and Sampling Locations

Samples shall be obtained at the monitoring points specified in this MRP. Central Valley Water Board staff shall approve any proposed changes to sampling locations prior to implementation of the change.

The Discharger shall monitor the following locations to demonstrate compliance with the requirements of this Order:

Table 1 - Monitoring Locations

Monitoring Location Name	Monitoring Location Description
INF	Location where a representative sample of wastewater entering the Facility can be obtained
EFF	Location where a representative sample of wastewater leaving the Facility can be obtained
PND-1 AND PND-2	Two storage ponds
LAA	Land application area

Sampling and Sample Analysis

All samples shall be representative of the volume and nature of the discharge or matrix of material sampled. Except as specified otherwise in this MRP, grab samples will be considered representative of water, wastewater, soil, solids/sludges and groundwater.

The time, date, and location of each sample shall be recorded on the sample chain of custody form. All analyses shall be performed in accordance with the *Standard Provisions and Reporting Requirements for Waste Discharge Requirements*, dated 1 March 1991 (Standard Provisions).

Field test instruments (such as those used to measure pH, electrical conductivity, dissolved oxygen, wind speed, and precipitation) may be used provided that:

- The operator is trained in proper use and maintenance of the instruments;
- The instruments are field calibrated at the frequency recommended by the manufacturer;
- The instruments are serviced and/or calibrated by the manufacturer at the recommended frequency; and
- Field calibration reports are submitted as described in the "Reporting" section of this MRP.

Laboratory analytical procedures shall comply with the methods and holding times specified in the following (as applicable to the medium to be analyzed):

- *Methods for Organic Chemical Analysis of Municipal and Industrial Wastewater* (EPA);

- *Test Methods for Evaluating Solid Waste* (EPA);
- *Methods for Chemical Analysis of Water and Wastes* (EPA);
- *Methods for Determination of Inorganic Substances in Environmental Samples* (EPA);
- *Standard Methods for the Examination of Water and Wastewater* (APHA/AWWA/WEF); and
- *Soil, Plant and Water Reference Methods for the Western Region* (WREP 125).

Approved editions shall be those that are approved for use by the United States Environmental Protection Agency or the California Department of Public Health's Environmental Laboratory Accreditation Program (ELAP). The Discharger may propose alternative methods for approval. Where technically feasible, laboratory reporting limits shall be lower than the applicable water quality objectives for the constituents to be analyzed.

If monitoring consistently shows no significant variation in a constituent concentration or parameter after at least 12 months of monitoring, the Discharger may request this MRP be revised to reduce monitoring frequency. The proposal must include adequate technical justification for reduction in monitoring frequency. This monitoring program shall remain in effect unless and until a revised MRP is issued.

B. Specific Monitoring Requirements

Influent Monitoring

Influent flow rates shall be monitored, and influent samples shall be collected upstream of the treatment system. At a minimum, influent shall be monitored as specified below:

Table 2 - Influent Monitoring

Constituent	Units	Sample Type	Monitoring Frequency	Reporting Frequency
Flow	million gallons per day	Meter Reading	Continuous	Quarterly
BOD	milligrams per liter	Grab	Monthly	Quarterly

Constituent	Units	Sample Type	Monitoring Frequency	Reporting Frequency
Total Suspended Solids	milligrams per liter	Grab	Monthly	Quarterly
Total Nitrogen	milligrams per liter	Grab	Monthly	Quarterly
Total Dissolved Solids	milligram per liter	Grab	Monthly	Quarterly

Effluent Monitoring

Effluent samples shall be collected upstream of the point of discharge to the effluent storage ponds on the same day as influent samples. At a minimum, effluent shall be monitored as specified below:

Table 3 - Effluent Monitoring

Constituent	Units	Sample Type	Monitoring Frequency	Reporting Frequency
BOD	milligrams per liter	Grab	Monthly	Quarterly
Total Suspended Solids	milligrams per liter	Grab	Monthly	Quarterly
Total Dissolved Solids	milligrams per liter	Grab	Monthly	Quarterly
Total Nitrogen	milligrams per liter	Grab	Monthly	Quarterly
pH	standard units	Grab	Monthly	Quarterly
Nitrate as N	milligrams per liter	Grab	Monthly	Quarterly
Electrical Conductivity	microsiemens per centimeter	Grab	Monthly	Quarterly
Standard Minerals	milligrams per liter	Grab	Annually	Annually

Pond Monitoring

Ponds used for treatment, storage, or disposal of wastewater shall be monitored as specified below. Dissolved oxygen monitoring applies to any pond containing more than two feet of standing water:

Table 4 - Pond Monitoring

Constituent	Units	Sample Type	Monitoring Frequency	Reporting Frequency
Dissolved Oxygen	milligrams per liter	Grab	Weekly	Quarterly
Freeboard	0.1 feet	Measurement	Weekly	Quarterly
pH	standard unit	Grab	Weekly	Quarterly
Odors	--	Observation	Weekly	Quarterly
Berm Condition	--	Observation	Weekly	Quarterly
Liner Condition	--	Observation	Weekly	Quarterly

Land Application Area Monitoring

The Discharger shall inspect the LAAs at least once daily prior to and during irrigation events, and observations from those inspections shall be documented for inclusion in the quarterly monitoring reports. The following items shall be documented for each check or field to be irrigated that day:

- a. Evidence of erosion;
- b. Containment berm condition;
- c. Condition of above-ground pipes, flow control valves, sprinklers, and/or drip emitters (as applicable);
- d. Proper use of valves;
- e. Soil saturation;
- f. Ponding;
- g. Irrigation supply and tailwater ditch condition and potential for runoff to off-site areas;
- h. Potential and actual discharge of waste to surface water;
- i. Odors that have the potential to be objectionable at or beyond the property boundary; and
- j. Insects (e.g., flies, mosquitoes).

- k. Any corrective actions taken based on observations made.

A copy of entries made in the log during each month shall be submitted as part of the Quarterly Monitoring Report. If no irrigation with wastewater takes place during a given month, then the monitoring report shall so state.

Sludge/Biosolids Monitoring

Sludge and/or biosolids monitoring shall be conducted as required in Title 40 of the Code of Federal Regulations (40 CFR), Part 503.8(b)(4) at the following frequency, depending on volume of sludge and removed from the wastewater treatment system for disposal or treated for beneficial reuse as biosolids:

Table 5 - Sludge/Biosolids Monitoring

Disposal Volume (dry metric tons/year)	Monitoring Frequency	Reporting Frequency
0 to 290	Annually	Annually
290 to 1,500	Quarterly	Monthly
1,500 to 15,000	Bimonthly	Monthly
Greater than 15,000	Monthly	Monthly

At a minimum, sludge/biosolids samples shall be analyzed to determine the total concentration in milligram per kilogram (mg/Kg) for arsenic, lead, nickel, cadmium, mercury, selenium, copper, molybdenum, zinc, total nitrogen, and total solids.

Sludge and/or biosolids monitoring records shall be retained for a minimum of five years in accordance with 40 CFR, Part 503.17. A log shall be kept of sludge quantities generated and of handling, application, and disposal activities. The frequency of entries is discretionary; however, the log should be complete enough to serve as a basis to report sludge monitoring.

The Discharger shall demonstrate that treated sludge (i.e., biosolids) meets Class A or Class B pathogen reduction levels by one of the methods listed in 40 CFR, Part 503.32, and shall maintain records of the operational parameters used to comply with the Vector Attraction Reduction requirements in 40 CFR, Part 503.33(b), as well as records of offsite disposal (quantity, date, disposal site).

Residual Solids Monitoring

The Discharger shall monitor the residual solids generated and disposed of on a monthly basis. The following shall be monitored and reported:

1. Volume of Solids Generated. Solids may include pomace, seeds, stems, screenings, pond solids, and sump solids, or other material.
2. Volume Disposed of off-site. Describe the disposal method (e.g. animal feed, land application, off-site composting, landfill, etc.); the amount disposed (tons); and the name of the hauling company.
3. Volume Disposed of On-site. Describe the amount disposed (tons); location of on-site disposal (e.g. land application area field); method of application, spreading, and incorporation; application rate (tons/acre), and weekly grab sample analysis for total nitrogen.

Reporting Requirements

All monitoring reports should be converted to a searchable Portable Document Format (PDF) and submitted electronically. Documents that are less than 50MB should be emailed to: centralvalleyredding@waterboards.ca.gov.

Documents that are 50 MB or larger should be transferred to a CD, DVD, or flash drive and mailed to the following address:

Central Valley Regional Water Quality Control Board
ECM Mailroom
364 Knollcrest Drive, Suite 205
Redding, California 96002

To ensure that your submittal is routed to the appropriate staff person, the following information should be included in the body of the email or transmittal sheet:

Gerber-Las Flores Wastewater Treatment Facility
Tehama County
Place ID: 227080

A transmittal letter shall accompany each monitoring report. The letter shall include a discussion of all violations of the WDRs and this MRP during the reporting period and actions taken or planned for correcting each violation. If the Discharger has previously submitted a report describing corrective actions taken and/or a time schedule for implementing the corrective actions, reference to the previous correspondence will be satisfactory. Pursuant to Section B.3 of the Standard Provisions and General Reporting Requirements, the transmittal letter shall contain a statement by the Discharger or the

Discharger's authorized agent certifying under penalty of perjury that the report is true, accurate and complete to the best of the signer's knowledge.

In reporting monitoring data, the Discharger shall arrange the data in tabular form so that the date, sample type (e.g., effluent, pond, etc.), and reported analytical result for each sample are readily discernible. The data shall be summarized in such a manner to clearly illustrate compliance with waste discharge requirements and spatial or temporal trends, as applicable. The results of any monitoring done more frequently than required at the locations specified in the Monitoring and Reporting Program shall be reported in the next scheduled monitoring report.

Laboratory analysis reports do not need to be included in the monitoring reports; however, all laboratory reports must be retained for a minimum of three years in accordance with Standard Provision C.3. For a Discharger conducting any of its own analyses, reports must also be signed and certified by the chief of the laboratory.

In addition to the requirements of Standard Provision C.3, monitoring information shall include the method detection limit (MDL) and the Reporting limit (RL) or practical quantitation limit (PQL). If the regulatory limit for a given constituent is less than the RL (or PQL), then any analytical results for that constituent that are below the RL (or PQL) but above the MDL shall be reported and flagged as estimated.

All monitoring reports that involve planning, investigation, evaluation or design, or other work requiring interpretation and proper application of engineering or geologic sciences, shall be prepared by or under the direction of persons registered to practice in California pursuant to California Business and Professions Code sections 6735, 7835, and 7835.1.

In the future, the State Water Board or Central Valley Regional Water Board may require electronic submittal of monitoring reports using the [State Water Board's California Integrated Water Quality System \(CIWQS\) Program Web site](http://www.waterboards.ca.gov/ciwqs/index.html) (<http://www.waterboards.ca.gov/ciwqs/index.html>) or similar system. Electronic submittal to CIWQS, when implemented, will meet the requirements of our Paperless Office System.

Quarterly Monitoring Reports

Quarterly monitoring reports shall be submitted to the Board by the first day of the second month after the quarter (i.e. the January-March quarterly report is due by May 1st). Each Quarterly Monitoring Report shall include the following:

1. Results of Influent Monitoring, including calculated values for total flow and average daily flow for each month, and total annual flow to date

2. Results of Effluent Monitoring
3. Results of Pond Monitoring
4. Results of any Sludge/Biosolids Monitoring completed during the quarter, and (if applicable) verification of classification of biosolids as nonhazardous per 22 CCR, Article 11, Criteria for Identification of Hazardous and Extremely Hazardous Waste (California Assessment Manual procedures).
5. Results of Residual Solids Monitoring
6. A comparison of monitoring data to the effluent limitations and discharge specifications and an explanation of any violation of those requirements.
7. Land area application monitoring results
8. A copy of inspection log page(s) documenting inspections completed during the quarter.
9. A copy of calibration log page(s) verifying calibration of all hand-held monitoring instruments performed during the quarter.

The Fourth Quarterly Monitoring Report will serve as an Annual Monitoring Report. The Fourth Quarterly Monitoring Report for each calendar year shall include the following in addition to the items listed above.

1. Total annual influent flow, average monthly flows for each month of the year, and the average dry weather flow compared to the flow limitations of the WDRs.
2. Results of any Sludge/Biosolids Monitoring completed during the year, and (if applicable) verification of classification of biosolids as nonhazardous per 22 CCR, Article 11, Criteria for Identification of Hazardous and Extremely Hazardous Waste (California Assessment Manual procedures).
3. For each discrete LAA, a chronological log of dates of fertilizer application, irrigation, precipitation, and runoff control operations.

Sludge/Biosolids monitoring results, if sludge or biosolids were removed for off-site disposal during the year.

4. A summary of all biosolids/sludge analytical data and verification of compliance with the biosolids/sludge monitoring requirements.

5. A summary of information on the disposal of sludge and/or solid waste during the calendar year.

Other Standard Reporting Requirements

6. An evaluation of the performance of the WWTF, including discussion of capacity issues, infiltration and inflow rates, nuisance conditions, and a forecast of the flows anticipated in the next year, as described in Standard Provision E.4
7. A discussion of compliance and the corrective actions taken, as well as any planned or proposed actions needed to bring the discharge into full compliance with the waste discharge requirements.
8. A copy of the certification for each certified wastewater treatment plant operator working at the facility and a statement about whether the Discharger is in compliance with Title 23, CCR, Division 3, Chapter 26.
9. Monitoring equipment maintenance and calibration records, as described in Standard Provision C.4.
10. A statement of when the wastewater treatment system Operation and Maintenance Manual was last reviewed for adequacy and a description of any changes made during the year.
11. A discussion of any data gaps and potential deficiencies or redundancies in the monitoring system or reporting program.

A letter transmitting the self-monitoring reports shall accompany each report. The letter shall clearly indicate the submitting Discharger's name, facility or site name, county, monitoring period, and type of report (i.e., monthly, quarterly, or annual). The letter shall include a discussion of any requirement violations during the reporting period and actions taken or planned for correcting noted violations, such as operation or facility modifications. If the discharger has previously submitted a report describing corrective actions and/or a time schedule for implementing the corrective actions, reference to the previous correspondence will be satisfactory. Pursuant to the Standard Provisions and Reporting Requirements, the transmittal letter shall contain a statement by the Discharger or its authorized agent, under penalty of perjury, that to the best of the signer's knowledge, the report is true, accurate, and complete.

The Discharger shall implement the above monitoring program as of the date of this Order.

If, in the opinion of the Executive Officer, the Discharger fails to comply with the provisions of this Order, the Executive Officer may refer this matter to the Attorney General for judicial enforcement, may issue a complaint for administrative civil liability, or may take other enforcement actions. Failure to comply with this Order may result in the assessment of Administrative Civil Liability of up to \$10,000 per violation, per day, depending on the violation, pursuant to the Water Code, including sections 13268, 13350 and 13385. The Central Valley Water Board reserves its right to take any enforcement actions authorized by law.

Any person aggrieved by this Central Valley Water Board action may petition the State Water Board for review in accordance with Water Code section 13320 and California Code of Regulations, title 23, section 2050 et seq. The State Water Board must receive the petition by 5:00 p.m. on the 30th day after the date of this Order; if the 30th day falls on a Saturday, Sunday, or state holiday, the petition must be received by the State Water Board by 5:00 p.m. on the next business day. Copies of the law and regulations applicable to filing petitions are available on the [Internet](http://www.waterboards.ca.gov/public_notices/petitions/water_quality) (http://www.waterboards.ca.gov/public_notices/petitions/water_quality), and will be provided upon request.

The Discharger shall implement the above monitoring program as of the date of this MRP.

Ordered by:



PATRICK PULUPA, Executive Officer
2/11/2020

(Date)