

Central Valley Regional Water Quality Control Board

5 May 2016

Stephen Jackson, President
Rawhide Investment Corporation
PO Box 859
Jamestown, CA 95327

CERTIFIED MAIL
7015 1730 0000 9937 4053

MONITORING AND REPORTING PROGRAM REVISION, RAWHIDE INVESTMENT CORPORATION, RAWHIDE MOBILE HOME PARK, RM 394368, TUOLUMNE COUNTY

Central Valley Water Board staff received a 24 May 2015 request from Don Nessler, the Rawhide Mobile Home Park (MHP) Wastewater Treatment System operator for changes to the monitoring and reporting schedule. Monitoring and reporting requirements for the facility are specified in Monitoring and Reporting Program (MRP) for Waste Discharge Requirements Order 97-10-DWQ, as applied by the Notice of Applicability issued on 13 February 2014.

The requested changes in the MRP for the facility are summarized below:

For aerated pond influent monitoring and sampling, the operator requests that monthly monitoring for total suspended solids and 20°C BOD₅ be replaced with weekly dissolved oxygen grab samples.

For effluent monitoring and sampling, the operator requests that flow to the storage ponds be sampled monthly for BOD₅ and total suspended solids, and requests that the sampling frequency for nitrate and total nitrogen be reduced from monthly to quarterly. Since disinfection of the effluent is not required, the operator also requests discontinuation of total coliform sampling.

Staff review of the request, as described in the enclosed Staff Memorandum, finds that changes to the MRP are appropriate. Pursuant to California Water Code section 13267, the monitoring and reporting requirements associated with the 13 February 2014 Notice of Applicability are modified as follows:

1. Under Aerated Pond Systems Monitoring, Influent Monitoring, monthly BOD and total suspended solids sampling is replaced by weekly dissolved oxygen sample results.
2. The Aerated Pond Systems Monitoring, Effluent Monitoring, is hereby deleted.
3. Under Disposal Monitoring, Pond/Basin Monitoring, the table has been modified to include monthly BOD₅ and total suspended solids monitoring, and the sampling frequency for nitrate and total nitrogen has been reduced from monthly to quarterly. The text has been modified to require sample collection after all waste streams are combined, or at the inlet side of the disposal ponds.

These changes are shown in Attachment A. For your convenience, Attachment B shows the additions and deletions made to the MRP. Additions are shown in bold, and deletions in strike out. Except as modified herein, all terms and conditions of the 13 February 2014 Notice of Applicability remain in effect.

If you have questions regarding this letter, please contact Omar Mostafa at Omar.Mostafa@waterboards.ca.gov or at (559) 445-5197.



- for -

Pamela C. Creedon
Executive Officer

Attachment A – Revised Monitoring and Reporting Program for 97-10-DWQ-R5139
Attachment B – Modifications to Monitoring and Reporting Program for 97-10-DWQ-R5139

Enclosure: Staff Memorandum

cc: Don Nessler, 8400 Old Melones Rd., Jamestown, CA, 95327
Tuolumne County Environmental Health Department, Sonora

Rawhide MHP WWTF

Revised Monitoring and Reporting Program for 97-10-DWQ-R5139

Septic Tank Monitoring

No Modifications

Activated Sludge Systems Monitoring

Not Applicable

Aerated Pond Systems Monitoring**Influent Monitoring**

Monitoring of Aerated Pond Systems influent shall consist of the following:

<u>Parameter</u>	<u>Units</u>	<u>Type of Sample</u>	<u>Sampling Frequency</u>
Daily Flow	Gals/day	n/a	Daily
Dissolved Oxygen	mg/l	Grab	Weekly

Effluent Monitoring

Effluent monitoring requirements for Aerated Pond Systems deleted.

Disposal Monitoring**Pond/Basin Monitoring**

Samples should be representative of the volume and nature of the discharge. Time of collection of grab samples shall be recorded. Samples shall be collected from each pond/basin after all waste streams are combined or at the inlet side of the disposal ponds. Samples shall be collected between 0800 and 0900 hours. The following shall constitute UNLINED pond/basin monitoring:

<u>Parameter</u>	<u>Units</u>	<u>Type of Sample</u>	<u>Sampling Frequency</u>
pH	pH Units	Grab	Monthly
*Dissolved Oxygen	mg/l	Grab	Monthly
Nitrate as NO ₃ -N	mg/l	Grab	Quarterly
Total Nitrogen	mg/l	Grab	Quarterly
Pond Freeboard	feet	Measurement	Monthly
20°C BOD5	mg/l	Grab	Monthly
Total Suspended Solids	mg/l	Grab	Monthly

*Dissolved Oxygen Monitoring may be omitted when pond depth is less than 1-foot

pH monitoring shall be conducted using field measurement devices, or by grab sample delivered to an analytical laboratory.

Rawhide MHP WWTF

Revised Monitoring and Reporting Program for 97-10-DWQ-R5139

Recreational Vehicle (RV) Waste Monitoring

No Modifications

Reporting

No Modifications

Rawhide MHP WWTF

Modifications to Monitoring and Reporting Program for 97-10-DWQ-R5139

Septic Tank Monitoring

No Modifications

Activated Sludge Systems Monitoring

Not Applicable

Aerated Pond Systems Monitoring**Influent Monitoring**

Monitoring of Aerated Pond Systems influent shall consist of the following:

<u>Parameter</u>	<u>Units</u>	<u>Type of Sample</u>	<u>Sampling Frequency</u>
Daily Flow	Gals/day	n/a	Daily
Dissolved Oxygen	mg/l	Grab	Weekly
20°C BOD5	mg/l	Grab	Monthly
Total Suspended Solids	mg/l	Grab	Monthly

Effluent Monitoring

Effluent monitoring requirements for Aerated Pond Systems deleted.

Disposal Monitoring**Pond/Basin Monitoring**

Samples should be representative of the volume and nature of the discharge. Time of collection of grab samples shall be recorded. Samples shall be collected ~~at a depth of one foot from each pond/basin~~ **after all waste streams are combined or at the inlet side of the disposal ponds opposite the inlet.** Samples shall be collected between 0800 and 0900 hours. The following shall constitute UNLINED pond/basin monitoring:

<u>Parameter</u>	<u>Units</u>	<u>Type of Sample</u>	<u>Sampling Frequency</u>
pH	pH Units	Grab	Monthly
*Dissolved Oxygen	mg/l	Grab	Monthly
Nitrate as NO ₃ -N	mg/l	Grab	Monthly Quarterly
Total Nitrogen	mg/l	Grab	Monthly Quarterly
Pond Freeboard	feet	Measurement	Monthly
20°C BOD5	mg/l	Grab	Monthly
Total Suspended Solids	mg/l	Grab	Monthly

*Dissolved Oxygen Monitoring may be omitted when pond depth is less than 1-foot

pH monitoring shall be conducted using field measurement devices, or by grab sample delivered to an analytical laboratory.

Rawhide MHP WWTF

Modifications to Monitoring and Reporting Program for 97-10-DWQ-R5139

Recreational Vehicle (RV) Waste Monitoring

No Modifications

Reporting

No Modifications

Central Valley Regional Water Quality Control Board

TO: Clay Rodgers
Assistant Executive Officer
RB5F

Dale Harvey
Supervising WRC Engineer
RB5F

FROM: Warren W. Gross, CEG 1528, CHG 681
Senior Engineering Geologist
RB5F

DATE: 5 May 2016

SUBJECT: **MONITORING AND REPORTING PROGRAM REVISION, RAWHIDE
INVESTMENT CORPORATION, RAWHIDE MOBILE HOME PARK, RM
394368, TUOLUMNE COUNTY**

Rawhide Mobile Home Park (Discharger) is requesting a reduction in the monitoring and reporting schedule through its wastewater treatment system operator Don Nessler, a Grade III operator. The system was designed by Frank Walter and Associates and was intended to be a simplistic pond system, with an active aeration pond, settling tanks, and two disposal ponds. A sampling protocol was developed to assign the lines entering the ballast pond as influent and the pumped water to the two disposal ponds as effluent.

The Discharger has reported that the current monitoring schedule and associated cost makes it difficult to do anything other than sampling and reporting. They are planning to launch a study into alternatives to their system which would improve overall efficiency and effluent quality. Presently, approximately 10% of the sanitary sewer flow bypasses the aeration pond due to a topographic divide in the collection system that mimics site topography and would require a lift station (not in place) to pump those flows to the aeration pond. The existing effluent sample collection protocol may not characterize this 10% contribution, which flows intermittently into the disposal ponds.

For aerated pond influent monitoring and sampling, the operator recommends continuation of daily monitoring of the aerated pond system influent, elimination of total suspended solids and 20°C BOD₅ sampling, and replacement of those eliminated measurements with weekly dissolved oxygen grab samples.

For effluent monitoring and sampling, the operator recommends that flow to the storage ponds be sampled monthly for BOD₅ and total suspended solids, quarterly for nitrate and total nitrogen (as opposed to the current weekly sampling for all the specified parameters), and that coliform sampling be suspended.

A review of 2015 monitoring data, with average monthly flow of up to 0.016 mgd, is supportive of the requested revision of the monitoring and reporting program. The facility has low flows, oversized ponds, no history of complaints, and does not require disinfection (there is no use or recycling of disposal pond effluent, no spray fields, and the soil profile appears to be adequate for pathogen mitigation). However, the effluent monitoring point should be moved to a location that will provide a representative sample of the total effluent flow to the ponds. This can be accomplished by replacing the present effluent sampling point with disposal pond sampling on the influent side of the pond.