

CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD
CENTRAL COAST REGION
1102-A Laurel Lane
San Luis Obispo, California 93401

ORDER NO. 89-76

WASTE DISCHARGE REQUIREMENTS
FOR
SAN LUCAS COUNTY WATER DISTRICT
COMMUNITY WASTEWATER FACILITIES
MONTEREY COUNTY

The California Regional Water Quality Control Board, Central Coast Region, (hereafter Board), finds:

1. San Lucas County Water District filed a Report of Waste Discharge on February 21, 1989, in accordance with Section 13260 of the California Water Code. The report was filed requesting authorization to discharge domestic wastewater within the Salinas River sub-basin. The information supports a request allowing discharge of domestic wastewater.
2. San Lucas County Water District (hereafter Discharger), proposes to own and operate domestic wastewater treatment and disposal facilities located one mile north of the community of San Lucas, north of the intersection of Highway 198 and Freeman Flat Road. The facilities are as shown on Attachment "A" of this order.
3. Up to 34,000 gallons-per-day ($129 \text{ m}^3/\text{day}$) of treated wastewater are discharged at this facility. The treatment facility consists of a mechanically aerated pond and an oxidation pond. Wastewater is discharged to a seven-acre spray disposal area. Capacity of the wastewater treatment and disposal system is at least 34,000 gallons-per-day. An effluent storage pond to provide wet weather storage is also provided.
4. The wastewater facility is located on slightly sloping topography consisting of sandy silt soils to a depth of 12 feet. Depth to ground water is estimated to be greater than 60 feet. There are no ground water wells at the site.
5. The Salinas River is located 1 1/2 miles southwest of the facility and flows in a northwesterly direction to the Pacific Ocean.

6. The Water Quality Control Plan, Central Coastal Basin, (Basin Plan) was adopted by the Board on March 14, 1975, and approved by the State Water Resources Control Board on March 20, 1975. The Basin Plan incorporates statewide plans and policies by reference and contains a strategy for protecting beneficial uses of State waters.
7. Present and anticipated beneficial uses of groundwater in the vicinity of the discharge include:
 - a. Municipal and Domestic Supply; and,
 - b. Agricultural Supply.
8. Present and anticipated beneficial uses of the Salinas River that could be affected by the discharge include:
 - a. Municipal and domestic supply;
 - b. Water contact recreation;
 - c. Non-contact water recreation;
 - d. Industrial service supply;
 - e. Ground water recharge;
 - f. Agricultural supply; and,
 - g. Wildlife habitat.
9. The County of Monterey certified a final Environmental Impact Report in accordance with the California Environmental Quality Act (Public Resources Code, Section 21000, et seq.) and the California Code of Regulations.
10. Discharge of waste is a privilege, not a right, and authorization to discharge is conditional upon the discharge complying with provisions of Division 7 of the California Water Code and any more stringent effluent limitations necessary to implement water quality control plans, to protect beneficial uses, and to prevent nuisance. Compliance with this Order should assure this and mitigate any potential adverse changes in water quality due to the discharge.
11. On March 23, 1989, the Board notified the Discharger and interested agencies and persons of its intent to adopt waste discharge requirements for the discharge and has provided them with a copy of the proposed order and an opportunity to submit written views and comments.
12. After considering all comments pertaining to this discharge during a public hearing on June 9, 1989, this Order was found consistent with the above findings.

IT IS HEREBY ORDERED, pursuant to authority in Section 13263 of the California Water Code, San Lucas County Water District, its agents, successors, and assigns, may discharge waste at wastewater treatment facilities, providing compliance is maintained with the following:

(Note: other prohibitions and conditions, definitions, and the method of determining compliance are contained in the attached "Standard Provisions and Reporting Requirements for Waste Discharge Requirements" dated January, 1984. Applicable paragraphs are referenced in paragraph D.3. of this Order.)

A. Prohibitions

1. Discharge to areas other than the designated wastewater disposal area shown in Attachment "A," is prohibited.
2. Discharge of any wastes, including wind-blown spray, to adjacent drainageways or adjacent properties, is prohibited.
3. Bypass of the treatment facility and discharge of untreated or partially treated wastes directly to spray disposal areas is prohibited.

B. Discharge Specifications

1. Daily flow averaged over each month shall not exceed 34,000 gallons (129 m³).
2. Effluent discharged to the designated wastewater disposal area shall not contain a total dissolved solids concentration excess of 1,500 mg/l.
3. Effluent discharged to the designated wastewater disposal area shall not have a pH less than 6.5 or greater than 8.4.
4. Surface drainage shall be excluded from the designated wastewater disposal areas.
5. Freeboard shall exceed two feet in all wastewater ponds.
6. The spray disposal area shall be operated in a regular alternating-type sequence.
7. Discharge shall not occur during rainfall.


C. Ground Water Limitations

1. The discharge shall not cause a significant increase of mineral constituent concentrations in underlying groundwaters, as determined by comparison of samples collected from wells located upgradient and downgradient of the disposal area.
2. The discharge shall not cause concentrations of chemicals and radionuclides in groundwater to exceed limits set forth in Title 22, Chapter 15, Articles 4 and 5 of the California Code of Regulations.

D. Provisions

1. Wastewater facilities shall be designed to retain wastewater flows during a 100-year rainfall season.
2. Discharger shall comply with "Monitoring and Reporting Program No. 89-76," as specified by the Executive Officer.
3. Discharger shall comply with all items of the attached "Standard Provisions and Reporting Requirements for Waste Discharge Requirements" dated January, 1984.
4. An all-weather access diked-path shall be constructed around the perimeter of the spray disposal area as necessary to prevent effluent runoff offsite and permit inspection.
5. Personnel involved in wastewater operations shall be informed of possible health hazards that may result from contact with undisinfected wastewater.
6. Pursuant to Title 23, Chapter 3, Subchapter 9, of the California Code of Regulations, the Discharger must submit a written report to the Executive Officer not later than January 1, 1994, addressing:
 - a. Whether there will be changes in the continuity, character, location, or volume of the discharge; and,
 - b. Whether, in their opinion, there is any portion of the Order that is incorrect, obsolete, or otherwise in need of revision.

I, WILLIAM R. LEONARD, Executive Officer, do hereby certify the foregoing is a full, true, and correct copy of an Order adopted by the California Regional Water Quality Control Board, Central Coast Region, on June 9, 1989.


Executive Officer

sm5:89-76.WDR