

The Presentation of Entities and Relations and its Application in Inference

Weidi Xu

Peking University, Computational Intelligence Laboratory

June 9, 2015

Overview

- Knowledge Graph: a directed graph with entities and relations
- Knowledge Inference: link prediction in knowledge graph
- Representation: efficient and scalable inference methods

Table of Contents

- 1 Background
 - Knowledge Graph
 - Knowledge Inference
 - Methods


- 2 Representation learning for knowledge graph
 - Framework
 - Methods based on reconstruction error
 - Methods based on ranking loss
 - Pros and Cons

Table

- 1 Background
 - Knowledge Graph
 - Knowledge Inference
 - Methods
- 2 Representation learning for knowledge graph
 - Framework
 - Methods based on reconstruction error
 - Methods based on ranking loss
 - Pros and Cons

Knowledge Graph

- Knowledge graph is a directed graph comprised by entities and relations.



- (John, athletePlaysForTeam, 76ers)
 - (Bob, athletePlaysForTeam, 76ers)
 - (Tom, athleteMates, Tom)
 - (Tom, athletePlaysInLeague, NBA)
 - (76ers, teamPlaysInLeague, NBA)
- However the knowledge graph is incomplete: it only covers small part of facts.

Knowledge Inference

- Knowledge inference: link prediction in knowledge graph.



- (John, teamMates, Bob)
- (Bob, athletePlaysInLeague, NBA)
- ...

- Inference in Knowledge Graph can increase the coverage.

Methods

- Inference based on representation learning.
 - ① Collective Matrix Factoriation (Nickel et al., 2011)
 - ② Neural Tensor Networks (Socher et al., 2013)
 - ③ Translating Embeddings (Bordes et al., 2013)
- Inference based on markov random field.
 - ① Markov Logic Networks (Richardson and Domingos, 2006)
 - ② Probabilistic Soft Logic (Brocheler et al., 2012)
- Inference based on random walk.
 - ① Path Ranking (Lao et al., 2011)

Table

- 1 Background
 - Knowledge Graph
 - Knowledge Inference
 - Methods
- 2 Representation learning for knowledge graph
 - Framework
 - Methods based on reconstruction error
 - Methods based on ranking loss
 - Pros and Cons

Framework

- Hidden variable model: modeling data in hidden variable space.

Learning

- Learning entity and relation embeddings in hidden vector spaces.
- Define an fitness function to determine the certainty of entity-relation-entity pairs.
- Define an objective function to determine the certainty of entity-relation-entity pairs.

Prediction

- Using the model and objective function to inference.

Framework

- Hidden variable model: modeling data in hidden variable space.

Learning

- Learning entity and relation embeddings in hidden vector spaces.
- Define an fitness funtion to determine the certainty of entity-relation-entity pairs.
- Define an objective funtion and use the facts dataset to learn the model parameters.

Objective function

- Reconstruction error
- Ranking loss

RESCAL: reconstruction error

- Representation in hidden vector/matrix space and the corresponding fitness function:

$$f(e_i, r_k, e_j) = \mathbf{e}_i^T \mathbf{R}_k \mathbf{e}_j$$

$$f_{ij}^{(k)} = \text{green bar} \times \text{grey square} \times \text{orange bar}$$

projection

- Learn based on reconstruction error:


$$\min_{\mathbf{e}_i, \mathbf{R}_k} \sum_k \sum_i \sum_j (y_{i,j}^k - f(e_i, r_k, e_j))^2 + \lambda R \quad (1)$$

assumption

It is assumed that all pairs not contained in dataset are negative.

NTN: ranking loss

- Representation in hidden vector/matrix space and the corresponding fitness function:



$$f(e_i, r_k, e_j) = U_k^T g(e_i^T W_k^{[1:K]} e_j + V_k[e_i : e_j] + b_k) \quad (2)$$

- Learn based on reconstruction error:

$$\min_{e_i, R_k} \sum_{t^+ \in O} \sum_{t^- \in D} (\lambda + f(e_i, r_k, e_j) - f(e'_i, r_k, e'_j)) \quad (3)$$

assumption

It is assumed that all pairs not contained in dataset are negative.

TransE: ranking loss

- Representation in hidden vector space and the corresponding fitness function:

$$f(e_i, r_k, e_j) = \|\mathbf{e}_i + \mathbf{r}_k - \mathbf{e}_j\|_1$$

translation

- Learn based on ranking loss:

$$\min_{e_i, R_k} \sum_{t^+ \in O} \sum_{t^- \in D} (\lambda + f(e_i, r_k, e_j) - f(e'_i, r_k, e'_j)) \quad (4)$$

assumption

It is assumed that pairs not contained in dataset are partially negative.

Prons and Cons

- Pros
 - ① Hidden space model can capture the complex concepts.
 - ② It is computationally efficient.
- Cons
 - ① It is not logical: we can capture the co-occurrence information but not logical properties of relation.
 - ② It is not precise: data-driven methods will be noisy-prone.

- Bordes, A., Usunier, N., Garcia-Duran, A., Weston, J., and Yakhnenko, O. (2013). Translating embeddings for modeling multi-relational data. In *Advances in Neural Information Processing Systems*, pages 2787–2795.
- Brocheler, M., Mihalkova, L., and Getoor, L. (2012). Probabilistic similarity logic. *arXiv preprint arXiv:1203.3469*.
- Lao, N., Mitchell, T., and Cohen, W. W. (2011). Random walk inference and learning in a large scale knowledge base. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pages 529–539. Association for Computational Linguistics.
- Nickel, M., Tresp, V., and Kriegel, H.-P. (2011). A three-way model for collective learning on multi-relational data. In *Proceedings of the 28th international conference on machine learning (ICML-11)*, pages 809–816.
- Richardson, M. and Domingos, P. (2006). Markov logic networks. *Machine learning*, 62(1-2):107–136.
- Socher, R., Chen, D., Manning, C. D., and Ng, A. (2013). Reasoning with neural tensor networks for knowledge base completion. In *Advances in Neural Information Processing Systems*, pages 926–934.