

The Presentation of Entities and Relations and its Application in Inference

Weidi Xu

Peking University, Computational Intelligence Laboratory

June 10, 2015

Overview

- Knowledge Graph: a directed graph with entiites and relations
- Knowledge Inference: link prediction in knowledge graph
- Representation: efficient and scalable inference methods

Table of Contents


- 1 Background
 - Knowledge Graph
 - Knowledge Inference
 - Methods
- 2 Representation Learning for Knowledge Graph
 - Framework
 - Methods based on Reconstruction Error
 - Methods based on Ranking Loss
- 3 Recent Advance
 - Consider Long-Range Interaction
- 4 Pros and Cons

Table of Contents

- 1 Background
 - Knowledge Graph
 - Knowledge Inference
 - Methods
- 2 Representation Learning for Knowledge Graph
 - Framework
 - Methods based on Reconstruction Error
 - Methods based on Ranking Loss
- 3 Recent Advance
 - Consider Long-Range Interaction
- 4 Pros and Cons

Knowledge Graph

- Knowledge graph is a directed graph comprised by entities and relations.




- (John, athletePlaysForTeam, 76ers)
- (Bob, athletePlaysForTeam, 76ers)
- (Tom, athleteMates, Tom)
- (Tom, athletePlaysInLeague, NBA)
- (76ers, teamPlaysInLeague, NBA)

- However the knowledge graph is incomplete: it only covers small part of facts.

Knowledge Inference

- Knowledge inference: link prediction in knowledge graph.



- (John, teamMates, Bob)
- (Bob, athletePlaysInLeague, NBA)
-

- Inference in Knowledge Graph can increase the coverage.

Methods

- Inference based on representation learning.
 - ① Collective Matrix Factoriation (Nickel et al., 2011)
 - ② Neural Tensor Networks (Socher et al., 2013)
 - ③ Translating Embeddings (Bordes et al., 2013)
- Inference based on markov random field.
 - ① Markov Logic Networks (Richardson and Domingos, 2006)
 - ② Probabilistic Soft Logic (Brocheler et al., 2012)
- Inference based on random walk.
 - ① Path Ranking (Lao et al., 2011)

Table of Contents

- 1 Background
 - Knowledge Graph
 - Knowledge Inference
 - Methods
- 2 Representation Learning for Knowledge Graph
 - Framework
 - Methods based on Reconstruction Error
 - Methods based on Ranking Loss
- 3 Recent Advance
 - Consider Long-Range Interaction
- 4 Pros and Cons

Framework

- Hidden variable model: modeling data in hidden variable space.

Learning

- Learning entity and relation embeddings in hidden vector spaces.
- Define a fitness function to determine the certainty of entity-relation-entity pairs.
- Define an objective function and use the facts dataset to learn the model parameters.

Prediction

- Using the model and objective function to inference.

Framework

- Hidden variable model: modeling data in hidden variable space.

Learning

- Learning entity and relation embeddings in hidden vector spaces.
- Define a fitness function to determine the certainty of entity-relation-entity pairs.
- Define an objective function and use the facts dataset to learn the model parameters.

Objective function

- Reconstruction error
- Ranking loss

RESCAL: reconstruction error

- Representation in hidden vector/matrix space and the corresponding fitness function:

$$f(e_i, r_k, e_j) = \mathbf{e}_i^T \mathbf{R}_k \mathbf{e}_j$$

$$f_{ij}^{(k)} = \text{green bar} \times \text{projection} \times \text{yellow bar}$$

- Learn based on reconstruction error:


$$\min_{\mathbf{e}_i, \mathbf{R}_k} \sum_k \sum_i \sum_j (y_{i,j}^k - f(e_i, r_k, e_j))^2 + \lambda R$$

assumption

It is assumed that all pairs not contained in dataset are negative.

Neural Tensor Network: ranking loss

- Representation in hidden vector/matrix space and the corresponding fitness function:



$$f(e_i, r_k, e_j) = U_k^T g(e_i^T W_k^{[1:K]} e_j + V_k[e_i : e_j] + b_k)$$

- Learn based on ranking loss:

$$\min_{e_i, R_k} \sum_{t^+ \in O} \sum_{t^- \in D} (\lambda + f(e_i, r_k, e_j) - f(e'_i, r_k, e'_j))$$

assumption

It is assumed that all pairs not contained in dataset are negative.

TransE: ranking loss

- Representation in hidden vector space and the corresponding fitness function:

$$f(e_i, r_k, e_j) = \|e_i + r_k - e_j\|_1$$

$$f_{ij}^{(k)} = \text{translation}$$

- Learn based on ranking loss:

$$\min_{e_i, R_k} \sum_{t^+ \in O} \sum_{t^- \in D} (\lambda + f(e_i, r_k, e_j) - f(e'_i, r_k, e'_j))$$

assumption

It is assumed that pairs not contained in dataset are partially negative.

Table of Contents

- 1 Background
 - Knowledge Graph
 - Knowledge Inference
 - Methods
- 2 Representation Learning for Knowledge Graph
 - Framework
 - Methods based on Reconstruction Error
 - Methods based on Ranking Loss
- 3 Recent Advance
 - Consider Long-Range Interaction
- 4 Pros and Cons


Recent Advance: Consider Long-range Interaction

Previous approaches only consider triples information, it's better to take long-range information into consideration.

- Relation between Relations (Bowman et al., 2014)
- Combining Long-Range Interaction (Wu et al., 2015)

Relation between Relations (Bowman et al., 2014)

- This model leaves out the representation of entities and concern the relation between relations.



- It tries to minimize the difference between the inferred relation $v_r(\pi)$ (w.r.t. path π) and the single relation r .


$$v_r(\pi) = RNN(\pi)$$

$$f(\pi_r, r) = \text{sigmoid}(v_r(\pi), r)$$

- And negative samples are used to maximize the margin.

Combining Long-Range Interaction (Wu et al., 2015)

- This paper jointly utilizes the triple information and long-range interaction in knowledge base.



- Ranking loss for triples:

$$\min_{e_i, R_k} \sum_{t^+ \in O} \sum_{t^- \in D} (\lambda + f(e_i, r_k, e_j) - f(e'_i, r_k, e'_j))$$

- And long-range loss:

$$f(\pi_r, r) = L(v_r(\pi), r)$$

Table of Contents

- 1 Background
 - Knowledge Graph
 - Knowledge Inference
 - Methods
- 2 Representation Learning for Knowledge Graph
 - Framework
 - Methods based on Reconstruction Error
 - Methods based on Ranking Loss
- 3 Recent Advance
 - Consider Long-Range Interaction
- 4 Pros and Cons

Prons and Cons

- Pros

- 1 Hidden space model can capture the complex concepts.
- 2 It is computationally efficient.

- Cons

- 1 It is not logical: we can capture the co-occurrence information but not logical properties of relation, e.g. transitivity, reflexivity..
- 2 It is not precise: data-driven methods will be noisy-prone.

References I

- Bordes, A., Usunier, N., Garcia-Duran, A., Weston, J., and Yakhnenko, O. (2013). Translating embeddings for modeling multi-relational data. In *Advances in Neural Information Processing Systems*, pages 2787–2795.
- Bowman, S. R., Potts, C., and Manning, C. D. (2014). Recursive neural networks for learning logical semantics. *arXiv preprint arXiv:1406.1827*.
- Brocheler, M., Mihalkova, L., and Getoor, L. (2012). Probabilistic similarity logic. *arXiv preprint arXiv:1203.3469*.
- Lao, N., Mitchell, T., and Cohen, W. W. (2011). Random walk inference and learning in a large scale knowledge base. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pages 529–539. Association for Computational Linguistics.
- Nickel, M., Tresp, V., and Kriegel, H.-P. (2011). A three-way model for collective learning on multi-relational data. In *Proceedings of the 28th international conference on machine learning (ICML-11)*, pages 809–816.

References II

- Richardson, M. and Domingos, P. (2006). Markov logic networks. *Machine learning*, 62(1-2):107–136.
- Socher, R., Chen, D., Manning, C. D., and Ng, A. (2013). Reasoning with neural tensor networks for knowledge base completion. In *Advances in Neural Information Processing Systems*, pages 926–934.
- Wu, F., Song, J., Yang, Y., Li, X., Zhang, Z., and Zhuang, Y. (2015). Structured embedding via pairwise relations and long-range interactions in knowledge base. In *Twenty-Ninth AAAI Conference on Artificial Intelligence*.

Thanks

Question & Answer?