

Performance without compromise

FASM
Rotary screw Air Compressors
with permanent magnate motor

firstAir
Compressors! No compromises.

FASM Permanent Magnetic Variable Speed Screw Air Compressors

Advanced Variable Speed Technology for Lower Operating Costs.



High-efficiency airend for superior performance.

IE4 permanent magnet motor for maximum energy savings.

7-inch touchscreen with smart monitoring & easy operation.

Intelligent inverter ensures precise pressure control.

Remote control for convenient system management.



High-efficiency permanent magnet motors

It is driven by a super IE4 high-efficiency permanent magnet motor, made of neodymium magnet, which makes the frequency adjustment more precise and does not demagnetize at the extreme temperature of the air compressor operation, and has a long service life to ensure reliable energy-saving.

Technical Data

Parameter	Unit	FASM08A-*	FASM11A-*	FASM15A-*	FASM18A-*	FASM22A-*	FASM30A-*	FASM37A-*
Discharge Pressure 5 bar(g)	CFM	17 ~ 44	28~ 69	40 ~ 101	52 ~ 131	62 ~ 155	85 ~ 212	105 ~ 263
Discharge Pressure 7 bar(g)	CFM	16~39	25~62	36~90	47~117	56~141	76~191	95~237
Discharge Pressure 8 bar(g)	CFM	15~36	23~58	34~85	42~106	54~134	73~184	89~223
Discharge Pressure 10 bar(g)	CFM	14~34	21~53	29~73	36~90	48~120	65~163	81~203
Discharge Pressure 12 bar(g)	CFM	12~29	20~49	26~65	33~81	42~106	57~143	71~178
Discharge Pressure 13 bar(g)	CFM	11~27	18~ 46	24~ 61	30~ 76	40 ~ 99	53 ~ 133	66 ~ 166
Discharge Pressure 16 bar(g)	CFM	11~ 21	18~ 35	26 ~ 51	30~ 60	39 ~ 78	53 ~ 106	67 ~ 134
Power	kW	7.5	11	15	18.5	22	30	37
Starting Method	Type			Inverter(VFD)				
Voltage/Frequency	V/Hz			400V/50Hz				
Rear cooler outlet temperature	℃			≤Ambient temperature+15℃				
Transmission Method				Coaxial Direct Transmission				
Discharge Pipe Diameter	in.	G3/4	G3/4	G3/4	G1	G1	G1-1/4	G1-1/4
Length	mm	680	680	680	780	780	920	920
Width	mm	680	680	680	780	780	840	840
Height	mm	1220	1240	1240	1300	1300	1422	1422
Weight	kg	245	260	270	300	320	425	450


Remarks:
1) The symbol "*" in the model means different discharge pressure, such as 5/7/8/10/12/13/16 bar(g).
2) Specific voltage (380V/415V) and specific frequency (60Hz) can be customized.

Smart Features for Superior Performance




Intelligent Color Screen Control System

Intelligent color screen design, including the current monitoring data display of the main motor and fan motor, and other multi–point control mode, easy to control, with a good human–com–puter interaction interface experience.



Variable Frequency Starting

Variable frequency starting, smooth linear operation, no high current of traditional direct start or star triangle start. Reduce the impact on the line and electrical, greatly extend the service life of the electromagnetic contactor, motor and airend.



Constant Pressure Air Supply

Frequency converting control can instantly reflect the change of air volume,the fluctuation of air supply pressure is stable below 0.1kgf/cm2, and there is no required setting of 1–2kgf/cm2 pressure difference between empyt and load, can greatly save electricity.

Energy Efficiency:	Permanent Magnet (PM) motor with Variable Frequency Drive (VFD) for maximum energy savings.
Compact Design:	Space-saving footprint with easy installation.
User-Friendly:	7-inch full-color touchscreen with an intelligent control system.
High Reliability:	Durable, high-quality components ensure dependable, trouble-free operation.
Remote Control:	Convenient and flexible operation from a remote location.

---

1. Advanced Technology
Powered by a Permanent Magnet (PM) motor and Variable Speed Drive (VSD), the FASM Series delivers outstanding performance with maximum energy efficiency.

2. Compact & Efficient
Its compact design saves floor space and simplifies installation and maintenance. The integrated VSD automatically adjusts output to match air demand, reducing energy consumption.

3. Smart Control System
A 7-inch color touchscreen provides intuitive operation, real-time energy monitoring, automatic airflow adjustment, maintenance alerts, and fault diagnostics—ensuring reliable performance with minimal downtime.

4. Reliable Performance
An optimized airend, premium components, high-precision bearings, and quality shaft seals ensure smooth operation, long service life, and dependable performance.





High-Efficiency Airend
The optimized airend minimizes internal air losses for maximum efficiency. Its large rotor and low-speed design reduce vibration and noise while extending service life. High-precision bearings and premium seals ensure reliable, leak-free performance with a bearing life of up to 60,000 hours.

firstAir

Compressors! No compromises.

Contact Us
FS Compressors India Pvt. Ltd.
PAP Plot No. S-3, Chakan MIDC Industrial Area,Phase II,
Savardari, Taluka- Khed, Dist- Pune, Maharashtra – 410501
Contact : (+91) 7420056998 • Email : Info@fscurtis.in
Web : www.firstair.co.in

Distributor

Leaflet_firstAir_EN_07/26