

# Zelig Styler SDK — iOS Integration Guide

This guide covers embedding the Zelig Styler widget into a third-party iOS app. Shoppers build looks, try on outfits, and add items to cart; your app handles dismissal and cart operations through a small delegate / closure bridge.

The SDK ships as a **pre-built closed-source binary** (ZeligStylerSDK.xcframework) — no source code is included.

## Prerequisites

- iOS 13.0+
- Xcode 14+ (Xcode 15+ requires one extra build setting for CocoaPods — see Option B, step 4)
- Swift 5.7+
- Your **storeId** and **storeKey** — provided by your Zelig solutions engineer

## Release artifacts

**Current version: 1.0.5** — the URLs below are pinned to it. When Zelig publishes a newer native SDK, bump these version strings (see Step 10).

| Artifact                      | URL                                                                                                                                                                                                           |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| XCFramework zip (Option A)    | <a href="https://storage.googleapis.com/ios-widget-sdk-zelig-prod/ZeligStylerSDK-1.0.5.xcframework.zip">https://storage.googleapis.com/ios-widget-sdk-zelig-prod/ZeligStylerSDK-1.0.5.xcframework.zip</a>     |
| CocoaPods podspec (Option B)  | <a href="https://raw.githubusercontent.com/wearezelig/ZeligStylerSDK-binary/1.0.5/ZeligStylerSDK.podspec">https://raw.githubusercontent.com/wearezelig/ZeligStylerSDK-binary/1.0.5/ZeligStylerSDK.podspec</a> |
| SPM binary package (Option C) | repo <a href="https://github.com/wearezelig/ZeligStylerSDK-binary.git">https://github.com/wearezelig/ZeligStylerSDK-binary.git</a> — pin by <b>version/tag (1.0.5)</b>                                        |

All three channels download the **same** prod XCFramework from GCS. Prefer pinning a **tag / version** (shown above), not **main**, so your app store build stays reproducible.

## Step 1 — Install the SDK (pick one)

All three options deliver the same pre-built binary.

**Use only one at a time.** Before switching, fully remove the previous integration (dragged-in framework, pod entries, or SPM package), otherwise you'll see `Missing package product` or `duplicate-module` errors.

### Option A — Direct XCFramework (simplest, no tooling required)

1. Download and unzip:

```
https://storage.googleapis.com/ios-widget-sdk-zelig-prod/  
ZeligStylerSDK-1.0.5.xcframework.zip
```

2. Drag `ZeligStylerSDK.xcframework` into your Xcode project. In the dialog that appears, make sure your **app target** is checked. Either “Reference files in place” or “Copy” works.
3. In your target's **General** → **Frameworks, Libraries, and Embedded Content**, set `ZeligStylerSDK.xcframework` to **Embed & Sign**. (Xcode may default to “Do Not Embed” — you must change it.)

That's it — no package manager involved.

This option has no automatic version management or checksum verification. Upgrading means downloading the **new versioned zip URL** and swapping the file. For SHA-256-verified pinned installs, prefer Option B or C.

**Upgrading (example → 1.0.5):** download .../  
`ZeligStylerSDK-1.0.5.xcframework.zip` → remove the old  
`ZeligStylerSDK.xcframework` from the project navigator → drag in the new one  
→ confirm **Embed & Sign** → rebuild and ship.

Option A — Direct XCFramework  
Option A — Direct XCFramework

### Option B — CocoaPods

1. Add one line to your Podfile:

```
platform :ios, '13.0'  
use_frameworks!  
  
target 'YourApp' do  
  # Pin a tagged release (recommended – keep builds  
  # reproducible):  
  pod 'ZeligStylerSDK', :podspec => 'https://  
    raw.githubusercontent.com/wearezelig/ZeligStylerSDK-  
    binary/1.0.5/ZeligStylerSDK.podspec'  
end
```

CocoaPods fetches the podspec from the binary repo tag (GitHub raw); the podspec downloads the pre-built zip from GCS and verifies SHA-256.

2. Run:

```
pod install
```

A successful install prints Installing ZeligStylerSDK (1.0.5).

3. **Always open YourApp.xcworkspace from this point on, not .xcodeproj.**

Opening the wrong file causes “no such module ‘ZeligStylerSDK’” at compile time.

4. **Required on Xcode 15+:** target → Build Settings → search User Script Sandboxing → set to **No** (both Debug and Release). Skipping this causes Command PhaseScriptExecution failed with a nonzero exit code — Xcode 15’s sandbox blocks CocoaPods’ framework-embed script on every pod-based project.

**Upgrading (example → 1.0.5):** change the tag in the Podfile URL, then reinstall:

```
pod 'ZeligStylerSDK', :podspec => 'https://
  raw.githubusercontent.com/wearezelig/ZeligStylerSDK-
  binary/1.0.5/ZeligStylerSDK.podspec'
```

```
rm -rf Pods Podfile.lock
pod install
```

Installing ZeligStylerSDK (1.0.5) in the output confirms success. Rebuild and ship.

Changing only Podfile.lock / re-running pod install **without** bumping the tag URL will keep you on the version you were already using.

Option B — CocoaPods  
Option B — CocoaPods

## Option C — Swift Package Manager

The SDK ships as a binary Swift package. Pin it by **version**, not branch.

1. Xcode: **File** → **Add Package Dependencies...**

2. Paste the **git repo URL** — not the zip URL. (Pasting a zip URL prompts for a username/password; Xcode downloads and SHA-256-verifies the zip automatically based on the package’s declaration.)

```
https://github.com/wearezelig/ZeligStylerSDK-binary.git
```

3. Set the **Dependency Rule** to **Up to Next Major Version**, starting at 1.0.5.

That locks you to the 1.x line (safe under semver) without picking up a breaking 1.0.5 automatically.

Use **Exact Version 1.0.5** only if your release process requires freezing a single binary until an explicit bump.

4. **Add to Project** → select your app project → **Add Package**. In the sheet that appears, **Add to Target** → select your app target → **Add**.
5. Verify: the Project Navigator shows **zeligstylersdk-binary**, and your target's **General** → **Frameworks, Libraries, and Embedded Content** lists ZeligStylerSDK.

**Upgrading within 1.x** (recommended rule = Up to Next Major):

1. Zelig tags a new release on ZeligStylerSDK-binary (e.g. 1.0.5) and publishes a new GCS zip.
2. Xcode → **File** → **Packages** → **Update to Latest Package Versions** (or **Resolve Package Versions**). If Xcode won't refresh: **File** → **Packages** → **Reset Package Caches**, then update again.
3. Confirm the resolved version in the Project navigator / Package.resolved is the new tag.
4. Rebuild and ship.

**Upgrading if you used Exact Version:** change the rule to the new tag (e.g. 1.0.5), resolve packages, rebuild, and ship.

Option C — Swift Package Manager  
Option C — Swift Package Manager

## Step 2 — Import

```
import ZeligStylerSDK
```

If this compiles, the installation succeeded. If you see `Unable to resolve module`: Option A — check target membership and the Embed setting; Option B — make sure you opened the `.xcworkspace`.

## Step 3 — Store credentials

Your Zelig solutions engineer will provide your **storeId** and **storeKey**.

**Security:** treat `storeKey` like a password. Do not commit it to source control or embed it as a string literal in your binary. Load it from a secrets manager, a remote config endpoint, or your app's secure configuration layer.

Code examples in this guide use a placeholder store; substitute your own credentials.

## Step 4 — Basic integration

**Integration Note:** The examples below show adding ZeligStyler to a product page, but you can integrate it anywhere in your app — product detail pages, cart, home recommendations, or a dedicated “Stylist” entry point. Replace class/view names with your actual implementation.

## SwiftUI (recommended)

```
import SwiftUI
import ZeligStylerSDK

// Example: Add a "Build a Look" button to your existing view
struct ProductDetailView: View {
    let productCode: String // The product SKU/code to open on –
                           // passed from your product page
    let userId: String?     // Current logged-in user ID from
                           // your auth system, or nil for guests
    @State private var showStyler = false

    var body: some View {
        Button("Build a Look") { showStyler = true }
            .sheet(isPresented: $showStyler) {
                ZeligStylerView(
                    config: ZeligStylerConfig(
                        storeId: "YOUR_STORE_ID", //
                        // Replace with your storeId from Zelig
                        storeKey: "YOUR_STORE_KEY", //
                        // Replace with your storeKey from Zelig
                        productCode: productCode,
                        userId: userId
                    ),
                    onAddToCart: handleAddToCart, // Revolve's
                    // method (see Step 5)
                    onClose: { showStyler = false },
                    onError: { error in
                        print("Zelig error: \(error)")
                    },
                    onOpenProductLink: handleProductLink // see
                    // "Product links"
                )
                .ignoresSafeArea()
            }
    }

    // Revolve's own method – the SDK calls it through the
    // `onAddToCart` hook so
    // Revolve can add the item to its cart and run any logging /
    // analytics it needs.
    // Revolve owns the body; full version in Step 5.
    private func handleAddToCart(item: ZeligCartItem,
                                completion: @escaping (Bool) ->
                                Void) { /* see Step 5 */ }
}
```

## UIKit

```
import UIKit
import ZeligStylerSDK
```

```

// Example: Add a "Build a Look" button to your existing view
controller
final class ProductViewController: UIViewController,
    ZeligStylerDelegate {
    private var styler: ZeligStyler?

    func showStyler(productCode: String, userId: String? = nil) {
        let config = ZeligStylerConfig(
            storeId: "YOUR_STORE_ID",           // Replace with your
            // storeId from Zelig
            storeKey: "YOUR_STORE_KEY",        // Replace with your
            // storeKey from Zelig
            productCode: productCode,
            userId: userId                      // Pass logged-in
            // user ID, or nil for guests
        )
        let styler = ZeligStyler(config: config, delegate: self)
        self.styler = styler                  // retain the reference
        styler.present(from: self)
    }

    // Required delegate method – the SDK calls this when the
    // shopper taps Add to
    // Bag, so Revolve can add the item to its cart and run any
    // logging / analytics
    // it needs. Revolve owns the body; full version in Step 5.
    func zeligStyler(_ styler: ZeligStyler,
        didRequestAddToCart item: ZeligCartItem,
        completion: @escaping (Bool) -> Void) {
        // ... your cart call, then completion(true) /
        // completion(false) – see Step 5
    }

    // Optional – defaults to dismissing the styler.
    func zeligStylerDidRequestClose(_ styler: ZeligStyler) {
        styler.dismiss(animated: true)
    }

    // Optional – called on load or initialization failures.
    func zeligStyler(_ styler: ZeligStyler, didFailWith error:
        ZeligStylerError) {
        print("Zelig error: \(error)")
    }

    // The shopper tapped a link inside the widget – route to the
    // host's own
    // screen. Body in "Product links" below.
    func zeligStyler(_ styler: ZeligStyler,
        didRequestOpenProductLink link: ZeligProductLink) {
        // ... route to the host's product or listing screen
    }
}

```

## Presentation style: sheet (card) or full screen

The widget places no restriction on how it's presented. The examples above use a **sheet (card style, `.sheet`)**; **full-screen presentation** is equally supported — the SDK handles both, so pick whichever fits the product.

**SwiftUI** — the two styles are almost identical; the only difference is `.sheet(isPresented:)` [\[?\]](#) `.fullScreenCover(isPresented:)` (config below is the same `ZeligStylerConfig` as in the example above):

```
// Style 1: sheet (card, half-height, with the system's built-in
// swipe-to-dismiss)
.sheet(isPresented: $showStyler) {
    ZeligStylerView(
        config: config,
        onAddToCart: handleAddToCart,
        onClose: { showStyler = false },
        onError: { error in print("Zelig error: \(error)") }
    )
    .ignoresSafeArea()
}

// Style 2: full screen – the only difference from above is .sheet
// → .fullScreenCover
.fullScreenCover(isPresented: $showStyler) {
    ZeligStylerView(
        config: config,
        onAddToCart: handleAddToCart,
        onClose: { showStyler = false },
        onError: { error in print("Zelig error: \(error)") }
    )
    .ignoresSafeArea()
}
```

**UIKit** — `ZeligStyler.present(from:)` currently supports full screen only; there is no card (sheet) mode.

## CTA visibility — gate it on whether the product has a Look

The SDK only opens the widget once invoked; it **does not control the visibility of the Build a Look CTA on the product detail page**. Whether the CTA is shown is decided by the host app, based on whether the product has a Look.

After switching products within the detail page, re-evaluate the CTA visibility against the new SKU.

Reference implementation: `ZeligWebViewDemo/TestApp/TestApp/ProductDetail.swift`.

```
private struct ColorVariant: Identifiable, Hashable {
    let code: String        // the SKU for this color
    let label: String
    let swatch: Color
    let hasLook: Bool       // whether this SKU has a Look
}
```

```

    var id: String { code }
}

struct ProductDetailView: View {
    let product: Product

    /// The SKU currently shown on the detail page. Update it when
    the product changes in place.
    @State private var selectedCode: String
    @State private var showStyler = false

    /// Demo sample data – only one product is given color
    variants; every other product returns nil.
    /// `hasLook` is hardcoded here; a real integration replaces
    it with the host's own result.
    private var colorVariants: [ColorVariant]? {
        guard product.productCode == "ASTR-WD190" else { return
            nil }
        return [
            .init(code: "ASTR-WD190", label: "Coral Multi",
                swatch: Color(red: 0.96, green: 0.90, blue:
                    0.86), hasLook: true),
            .init(code: "ASTR-WD660", label: "Navy Polka Dot",
                swatch: Color(red: 0.10, green: 0.12, blue:
                    0.22), hasLook: false)
        ]
    }

    /// CTA visibility – takes the result for the current SKU;
    products without variant data always show it.
    /// This is the demo's simplified form: it reads the hardcoded
    sample data above.
    /// A real integration should read the current SKU's result
    from the actual eligibility source.
    private var showsBuildALook: Bool {
        if let variants = colorVariants {
            return variants.first { $0.code ==
                selectedCode }?.hasLook ?? false
        }
        return true
    }

    var body: some View {
        ScrollView {
            // ... product image, title, price, details
        }
        .safeAreaInset(edge: .bottom) {
            HStack(spacing: 12) {
                Button("Build a Look") { showStyler = true }
                    .opacity(showsBuildALook ? 1 :
                        0) // opacity rather than removal, so the bottom bar
                    doesn't jump
                    .disabled(!showsBuildALook) //
                    transparent is still tappable – disable it too
            }
        }
    }
}

```

```

        Button("Add to Bag") { /* the host's own add-to-
            cart */ }
    }
}
.sheet(isPresented: $showStyler) {
    // Present ZeligStylerView with productCode:
    // selectedCode – see Basic integration above
}
}
}

```

## Preheating

The first open requires a full load (a few seconds). Call `prepare()` to preheat the widget asynchronously in the background — e.g. when the home screen appears; once preheating completes, the user can open Build a Look with no wait.

```

// SwiftUI – warm when the home view appears, and re-warm if the
// user changes
// Full reference: ZeligWebViewDemo/TestApp/TestApp/
// ContentView.swift
.task(id: userId) {
    ZeligStyler(config: ZeligStylerConfig(
        storeId: "YOUR_STORE_ID",
        storeKey: "YOUR_STORE_KEY",
        productCode:
            "", // any value – the shared widget is warmed
            regardless
        userId: userId
    )).prepare()
}

// UIKit – warm ahead of the open (e.g. on viewDidLoad)
let styler = ZeligStyler(config: ZeligStylerConfig(
    storeId: "YOUR_STORE_ID",
    storeKey: "YOUR_STORE_KEY",
    productCode: "",
    userId: userId
), delegate: self)
styler.prepare()
// ... later, when the user opens:
styler.present(from: self)

```

`prepare()` is scoped to the identity (`storeId + userId`): calling it again for the **same** identity is a no-op, but a **new** `userId` re-injects the cookie and reloads. So when `userId` can change at runtime (login, logout, account switch), preheat again under the new identity — otherwise the preheat done under the old identity no longer applies and the first open after a switch pays the full load again. In SwiftUI, keying the `.task` on `userId` (as above) does this automatically; in UIKit, call `prepare()` again with the new `userId` after the identity changes.

## Step 5 — The add-to-cart bridge

When a shopper taps **Add to Bag** in the widget, the SDK calls **handleAddToCart**, a **function Revolve provides**, to add the item to the cart — the same role `window.addToBagWithData` plays in the web integration.

The example below shows `handleAddToCart` in full (pseudocode), including how `fromZelig` drives add-source attribution. `revolveCustomCartService` and `revolveCustomAnalyticsService` are pseudocode placeholders for Revolve's existing cart and tracking modules; the `insertPageTrackWithData` method is named after the web integration's own call, so the two sides line up.

**SwiftUI** — the `handleAddToCart` method you passed to `onAddToCart` in Step 4:

```
private func handleAddToCart(item: ZeligCartItem,
                             completion: @escaping (Bool) ->
                                Void) {
    // `revolveCustomCartService` is Revolve's own cart layer –
    // not part of the SDK.
    revolveCustomCartService.add(
        sku: item.sku,
        size: item.size,
        quantity: item.quantity ?? 1,
        fromZelig: item.fromZelig ?? true
    ) { didSucceed in
        // After the add, report the source with Revolve's own
        // tracking. The
        // name/fields here just mirror web for easy comparison –
        // what matters
        // is passing `fromZelig` through as the source flag.
        revolveCustomAnalyticsService.insertPageTrackWithData(
            addToCartFlag: true,
            productCode: item.sku,
            isZeligAddToBag: item.fromZelig ?? true // web's
            fromZelig
        )
        completion(didSucceed) // true = added · false = failed
    }
}
```

**Reference (SwiftUI):** a runnable version ships in the sample app — `handleStylerAddToCart` in `ZeligWebViewDemo/TestApp/TestApp/ProductDetail.swift:206`. It's a SwiftUI implementation, so it maps to the SwiftUI code above (not the UIKit delegate below).

**Real-world example (Revolve's production app).** The same `onAddToCart` hook wired into a real cart layer. `RShopManager` / `RShoppingBag` are Revolve's own types — not part of the SDK — so this does not compile in the sample as-is (it's kept there as a comment); it shows the real shape:

```
private func handleAddToCart(_ item: ZeligCartItem, completion:
    @escaping (Bool) -> Void) {
    guard let shopManager = RShopManager.sharedInstance() else {
        completion(false)
    }
```

```

        return
    }

    let quantity = String(item.quantity ?? 1)

    shopManager.updateShoppingCart(
        forEmail: "",
        action: "add",
        code: item.sku,
        numSku: "1",
        prevSize: nil,
        qty: quantity,
        newSize: item.size,
        newCode: nil,
        itemDepartment: "",
        department: nil,
        pageType: "PDP",
        additionalQueryForURL: nil,
        success: { responseObject in
            DispatchQueue.main.async {
                guard let shoppingBag = responseObject as?
                    RShoppingBag else {
                    completion(false)
                    return
                }

                if shoppingBag.success {
                    shopManager.bagBadgeCount =
                        shoppingBag.numItems
                    NotificationCenter.default.post(name:
                        NSNotification.Name.bagBadgeUpdated, object: nil)
                    completion(true)
                } else {
                    completion(false)
                }
            }
        },
        failure: { _ in
            DispatchQueue.main.async {
                completion(false)
            }
        }
    )

    // Add-source attribution fires on *intent*: a tap in the
    // widget counts as a
    // Zelig-originated add, even if the cart write above fails.
    // Report it after
    // kicking off the cart call – decoupled from the success/
    // failure branches.
    revolveCustomAnalyticsService.insertPageTrackWithData(
        addToCartFlag: true,
        productCode: item.sku,
        isZeligAddToBag: item.fromZelig ?? true
    )

```

```
)
}
```

**UIKit** — the `ZeligStylerDelegate` method (the empty one from Step 4, now filled in).

As above, `revolveCustomCartService`, `revolveCustomAnalyticsService`, and `insertPageTrackWithData` are pseudocode placeholders — **replace them with the real definitions in your host app**.

```
func zeligStyler(_ styler: ZeligStyler,
                didRequestAddToCart item: ZeligCartItem,
                completion: @escaping (Bool) -> Void) {
    // `revolveCustomCartService` is Revolve's own cart layer –
    // not part of the SDK.
    revolveCustomCartService.add(
        sku: item.sku,
        size: item.size,
        quantity: item.quantity ?? 1,
        fromZelig: item.fromZelig ?? true
    ) { didSucceed in
        // After the add, report the source with Revolve's own
        // tracking. The
        // name/fields here just mirror web for easy comparison –
        // what matters
        // is passing `fromZelig` through as the source flag.
        revolveCustomAnalyticsService.insertPageTrackWithData(
            addToCartFlag: true,
            productCode: item.sku,
            isZeligAddToBag: item.fromZelig ?? true // web's
            fromZelig
        )
        completion(didSucceed) // true = added · false = failed
    }
}
```

**What fromZelig is for — add-source attribution.** `insertPageTrackWithData` uses it to decide whether to tag the call as Zelig-originated, exactly as on web. The whole Zelig-specific difference is one line inside it:

```
// web (pseudocode): inside insertPageTrackWithData
if (isZeligAddToBag) u += "&navsrc=zeligplp"; // tag the source
only when it came from Zelig
```

If your cart API reports success differently — say it returns a `Result` or throws — map that to the boolean: `completion(true)` on the success path, `completion(false)` on the failure path.

The item carries these fields:

| Field | Description                                                                  |
|-------|------------------------------------------------------------------------------|
| sku   | Normalized product SKU (from the widget's code / <code>productCode</code> ). |
| size  | Selected size string ("all" for one-size items).                             |

| Field     | Description                                                                         |
|-----------|-------------------------------------------------------------------------------------|
| quantity  | Quantity if the widget supplied one; otherwise nil.                                 |
| fromZelig | true when the widget flagged this as a Zelig-originated add-to-cart; nil if absent. |

**The contract:** you only need to call `completion` once — `true` if the item made it into the cart, `false` if not. The widget drives its in-modal UI from that signal and falls back to a ~2–4 s timeout; if the timeout fires first, its displayed state can drift from the cart, so respond promptly.

## Product links — routing to the host’s own screens

Product names inside the widget link to that product’s page, and the widget’s **View All** button links to the store’s listing page. On the web both open in the browser; a `WKWebView` has no browser to open them in, so the SDK cancels those navigations and reports the link instead. The host routes to its own screen.

Without this callback the links are inert: tapping a product name does nothing.

The shape matches add-to-cart: Revolve writes its own method and the SDK calls it through the callback. `revolveCustomRouter` below is a placeholder for Revolve’s existing navigation layer — not part of the SDK.

```
private func handleProductLink(_ link: ZeligProductLink) {
    // SwiftUI: showStyler = false · UIKit:
    //   styler?.dismiss(animated: true)
    showStyler = false //
    // suggested: close the Styler first

    if link.isShopMore {
        revolveCustomRouter.openListingPage(url: link.url,
        navsrc: link.navsrc)
    } else if let code = link.productCode {
        revolveCustomRouter.openProductDetail(code: code, navsrc:
        link.navsrc)
    } else {
        print("Zelig link without a product code: \(link.url)")
    }
}
```

Wire it as `onOpenProductLink` on `ZeligStylerView` (SwiftUI) or `zeligStyler(_:didRequestOpenProductLink:)` on `ZeligStylerDelegate` (UIKit) — both are shown in Step 4.

The link carries four fields:

| Field       | Description                                                                                                                                                                               |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| productCode | Product code parsed out of the URL path: <code>.../dp/LOVF-WK1189</code> → <code>"LOVF-WK1189"</code> . nil when the URL doesn’t follow that pattern — route on <code>url</code> instead. |

| Field      | Description                                                                                                                                                                                                                                                                                                   |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| navsrc     | The link's navsrc attribution tag; product links inside the widget carry "zeligplp". Pass it into the tracking the destination screen fires: on the web it stays in the URL and PageTrack attributes the later add-to-cart from it, but routing to a native screen drops the URL and the attribution with it. |
| isShopMore | true when the tap was the widget's <b>View All</b> button rather than a product. It points at a listing page (productCode is nil for it), so route to the host's own listing screen.                                                                                                                          |
| url        | The full link, exactly as the widget built it.                                                                                                                                                                                                                                                                |

**The contract:** the callback fires once per tap, on the main thread. The SDK reports the link and does nothing else — it does not navigate, and it does not dismiss the Styler; closing it is the host's call.

## Step 6 — Configuration reference

| Parameter   | Type             | Required               | Default        | Description                                          |
|-------------|------------------|------------------------|----------------|------------------------------------------------------|
| storeId     | String           | Yes                    | —              | Your Zelig store identifier.                         |
| storeKey    | String           | Yes                    | —              | Your store API secret, paired with storeId.          |
| productCode | String           | Yes for .productDetail | —              | Hero SKU to open on. Pass "" for .buildALook /.myClo |
| userId      | String?          | No                     | nil            | Your app's logged-in user ID. See Step 7.            |
| entry       | ZeligStylerEntry | No                     | .productDetail | Which experience to open. See “Entry modes” below.   |

## Entry modes

```
public enum ZeligStylerEntry { case productDetail, buildALook, myCloset }
```

Two ways the styler is launched:

**CTA launch** — **.productDetail** (*default*) Opened from a product's Style-It CTA, on a specific product. productCode must be non-empty.

**Banner launch — .buildALook / .myCloset** Opened from a banner entry point with no host-provided product (pass `productCode: ""`):

- **.buildALook** — opens the Build a Look experience. The widget picks the hero product itself (the shopper's last look, else the store's default recommendation).
- **.myCloset** — same as **.buildALook**, but lands directly on the My Closet tab.

SwiftUI landing: see `ZeligWebViewDemo/TestApp/TestApp/ContentView.swift` — `editorialBanner` renders the block and `.sheet(item:)` presents the styler.

Banner launch — Build a Look / My Closet  
Banner launch — Build a Look / My Closet

*// Open on a specific product (e.g. from a PDP):*

```
ZeligStylerConfig(  
    storeId: "YOUR_STORE_ID",  
    storeKey: "YOUR_STORE_KEY",  
    productCode: "PRODUCT_123"  
)
```

*// Entry points with no specific product:*

```
ZeligStylerConfig(  
    storeId: "YOUR_STORE_ID",  
    storeKey: "YOUR_STORE_KEY",  
    productCode: "",  
    entry: .buildALook  
)
```

```
ZeligStylerConfig(  
    storeId: "YOUR_STORE_ID",  
    storeKey: "YOUR_STORE_KEY",  
    productCode: "",  
    userId: "USER_123", // Pass user ID for authenticated users  
    entry: .myCloset  
)
```

## Step 7 — Shopper identity & closet

`userId` tells the Zelig backend how to scope the shopper's closet:

- **Non-nil (signed in)** — the closet is tied to this user and syncs across devices. An anonymous closet is automatically inherited on first sign-in.
- **nil (guest)** — a device-local anonymous closet is used instead.

```
let config = ZeligStylerConfig(  
    storeId: "YOUR_STORE_ID", // Replace with your storeId  
    from Zelig  
    storeKey: "YOUR_STORE_KEY", // Replace with your storeKey  
    from Zelig  
    productCode: productCode,
```

```

        userId: userId // Pass your logged-in user ID,
                        or nil for guests
    )

```

## Step 8 — Error handling

When the widget fails to load or initialize, the SDK hands you a `ZeligStylerError` through the optional error callback — the `onError` closure in SwiftUI, the `zeligStyler(_:didFailWith:)` method in UIKit (both wired up in Step 4). Implementing it is optional but recommended, so you can show the shopper a graceful fallback instead of a stuck screen.

All cases occur during load / initialization — they do not interrupt an already-open session:

| Case                                               | What it means                                                                     |
|----------------------------------------------------|-----------------------------------------------------------------------------------|
| <code>.loaderLoadFailed(URL)</code>                | The widget loader couldn't be fetched from the CDN (the failing URL is attached). |
| <code>.widgetInitTimeout</code>                    | The widget didn't finish initializing within the timeout.                         |
| <code>.modalMountTimeout</code>                    | The widget's modal UI didn't mount in time.                                       |
| <code>.webViewNavigationFailed(underlying:)</code> | The underlying WKWebView navigation failed (the underlying Error is attached).    |
| <code>.hostPageUnavailable</code>                  | The page hosting the widget couldn't be reached.                                  |

This error callback is separate from the add-to-cart completion contract (which must fire on both success and failure) — see Step 5 for that.

## Step 9 — Testing & debugging

Use the test SKUs your Zelig solutions engineer provides for your store.

Your main signal for diagnosing problems is the **error callback** (SwiftUI `onError` / UIKit `didFailWith`): handle the `ZeligStylerError` cases there, and add your own logging in that callback and in `onAddToCart` to trace behaviour.

## Step 10 — SDK versions & updates (how Revolve / hosts upgrade)

Two layers update independently:

| Layer              | What it is                   | How it updates |
|--------------------|------------------------------|----------------|
| <b>Widget (JS)</b> | Styler UI, looks, algorithms |                |

| Layer      | What it is                           | How it updates                                                                                                                                                              |
|------------|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Native SDK | ZeligStylerSDK.xcframework<br>bridge | Loaded at runtime from Zelig's CDN. <b>No app store release required</b> — shoppers get the latest widget the next time they open the styler.                               |
|            |                                      | Version-pinned in your Xcode project. You only bump it when Zelig ships a new <b>native</b> release (bridge / public API). Your solutions engineer notifies you in advance. |

Pinning 1.0.5 is intentional: your App Store binary stays reproducible until you choose to upgrade the native SDK.

## When Zelig publishes a new native version (e.g. 1.0.5 → 1.0.5)

Zelig will:

1. Upload ZeligStylerSDK-1.0.5.xcframework.zip to GCS (ios-widget-sdk-zelig-prod).
2. Tag <https://github.com/wearezelig/ZeligStylerSDK-binary> as 1.0.5 (Package.swift + podspec updated with the new URL + SHA-256).
3. Tell you the new version number.

Then upgrade with **your** install method only:

| Your install                  | What to do                                                                                                                                                                                                                                                                                                 |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>A — Direct XCFramework</b> | Download the new versioned zip (.../ZeligStylerSDK-1.0.5.xcframework.zip) → remove the old framework → drag in the new one → Embed & Sign → rebuild → ship                                                                                                                                                 |
| <b>B — CocoaPods</b>          | Bump the <b>tag in the Podfile URL</b> (.../ZeligStylerSDK-binary/1.0.5/ZeligStylerSDK.podspec) → <code>rm -rf Pods Podfile.lock &amp;&amp; pod install</code> → confirm Installing ZeligStylerSDK (1.0.5) → rebuild → ship                                                                                |
| <b>C — SPM</b>                | <ul style="list-style-type: none"> <li>• <b>Up to Next Major rule:</b> <b>File</b> → <b>Packages</b> → <b>Update to Latest Package Versions</b> → confirm the resolved version → rebuild → ship.</li> <li>• <b>Exact Version rule:</b> change it to 1.0.5 first, then resolve → rebuild → ship.</li> </ul> |

Previous version zips remain online — old app builds keep resolving.

The SDK follows semantic versioning. Any **1.x** update is backward-compatible with your existing integration code. A future **2.x** would be a breaking change and would be called out explicitly (SPM’s “Up to Next Major” would not auto-adopt it).

## Step 11 — Release checklist

- ☐ Your `storeId` / `storeKey` are correct.
- ☐ `storeKey` not committed to source control.
- ☐ `productCode` passed and present in your store’s catalog.
- ☐ Add-to-cart callback implemented; `completion` called on both success and failure.
- ☐ Logged-in `userId` passed for authenticated shoppers (`nil` only for guests).
- ☐ Tested on multiple device sizes (phone and tablet).

## Troubleshooting

| Symptom                                         | Fix                                                                                                                                                      |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Missing package product 'ZeligStylerSDK'        | A previous install method wasn't fully removed.<br>Check Package Dependencies, the Frameworks list, and the Podfile — keep exactly one.                  |
| Command PhaseScriptExecution failed (CocoaPods) | Xcode 15+ sandbox restriction. Build Settings → User Script Sandboxing → <b>No</b> (see Option B, step 4).                                               |
| Unable to resolve module 'ZeligStylerSDK'       | Option B: you opened <code>.xcodproj</code> — open <code>.xcworkspace</code> instead.<br>Option A: check target membership and the Embed & Sign setting. |
| Widget blank or not loading                     | Check network connectivity; verify <code>storeId</code> / <code>storeKey</code> ; open Safari Web Inspector and filter for [Zelig iOS] logs.             |

| Symptom                                      | Fix                                                                                                                  |
|----------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Add to cart hangs or never resolves          | Confirm your onAddToCart / delegate method is wired up and that completion(true/false) is called on every code path. |
| Wrong product opens                          | Verify productCode is correct and exists in your store's catalog.                                                    |
| Touches not registering on a physical device | Contact your Zelig solutions engineer — this is typically a host-app layout configuration issue.                     |

## API reference

```
public enum ZeligStylerEntry { case productDetail, buildALook, myCloset }
```

```
public struct ZeligStylerConfig {
    public let storeId: String
    public let storeKey: String
    public let productCode: String
    public let userId: String?
    public let entry: ZeligStylerEntry

    public init(
        storeId: String,
        storeKey: String,
        productCode: String,
        userId: String? = nil,
        entry: ZeligStylerEntry = .productDetail
    )
}
```

```
public struct ZeligCartItem {
    public let sku: String
    public let size: String
    public let quantity: Int?
    public let fromZelig: Bool?
}
```

```
public struct ZeligProductLink {
    public let url: URL
    public let productCode: String?
    public let navsrc: String?
    public let isShopMore: Bool
}
```

```

public enum ZeligStylerError: Error {
    case loaderLoadFailed(URL)
    case widgetInitTimeout
    case modalMountTimeout
    case webViewNavigationFailed(underlying: Error)
    case hostPageUnavailable
}

public protocol ZeligStylerDelegate: AnyObject {
    // Required:
    func zeligStyler(_ styler: ZeligStyler,
                     didRequestAddToCart item: ZeligCartItem,
                     completion: @escaping (Bool) -> Void)

    // Optional:
    func zeligStylerDidRequestClose(_ styler: ZeligStyler)
    func zeligStyler(_ styler: ZeligStyler, didFailWith error:
        ZeligStylerError)
    func zeligStyler(_ styler: ZeligStyler,
                     didRequestOpenProductLink link: ZeligProductLink)
}

public final class ZeligStyler {
    public init(config: ZeligStylerConfig, delegate:
        ZeligStylerDelegate? = nil)

    /** Whether the widget has finished warming (true after
        prepare() / first open). */
    public var isReady: Bool { get }

    /** Fires when warming completes (main thread). May fire again
        on a reload. */
    public var onReady: (() -> Void)?

    /** Warm the widget in the background ahead of time.
        Idempotent – a no-op if
        already warmed for the same identity. Call early for an
        instant first open. */
    public func prepare()

    /** Present and open on the given product/entry. Near-instant
        if already warmed. */
    public func open(productCode: String = "", entry:
        ZeligStylerEntry = .productDetail,
                     from presenter: UIViewController, animated:
        Bool = true)

    public func present(from presenter: UIViewController,
                       animated: Bool = true)
    public func dismiss(animated: Bool = true)
}

public struct ZeligStylerView: UIViewControllerRepresentable {
    public init(
        config: ZeligStylerConfig,

```

```
onAddToCart: @escaping (ZeligCartItem, @escaping (Bool)
-> Void) -> Void,
onClose: (() -> Void)? = nil,
onError: ((ZeligStylerError) -> Void)? = nil,
onOpenProductLink: ((ZeligProductLink) -> Void)? = nil
)
}
```

## Support

Contact your Zelig solutions engineer for store credentials, environment configuration, and any merchant-specific setup.

---

**Version:** 1.0.5 · **Last updated:** August 2026